



Reading the contacts

Dr. Charles Yu

- Demo1:
 - ContactsPhoneNumber
 - It still needs user's providing access rights in the run time


ContactsPhone Number

- Let's see what I have in the emulator.
 - The contacts are randomly input into the emulator
 - Click the 1st contact, then we can see the detail




ContactsPhoneNumber

- Run the App and let's see how it looks like?




ContactsPhoneNumber

- If we go back to the “Phone app” → Contacts
- Add a new contact



ContactsPhoneNumber

- Go back to the ContactsPhone Number App
- You will see one more contact is read into the app



ContactsPhoneNumber

- Let's see our AndroidManifest.xml
- Nothing is special
 - Just one Activity!
- Watch out!
 - **android.permission.READ_CONTACTS**
- Let's see MainActivity.java

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <manifest xmlns:android="http://schemas.android.com/apk/res/android"
3   xmlns:tools="http://schemas.android.com/tools">
4   <uses-permission android:name="android.permission.READ_CONTACTS" />
5   <application
6     android:allowBackup="true"
7     android:dataExtractionRules="@xml/data_extraction_rules"
8     android:fullBackupContent="@xml/backup_rules"
9     android:icon="@mipmap/ic_launcher"
10    android:label="ContactsPhoneNumber"
11    android:supportsRtl="true"
12    android:theme="@style/Theme.ContactsPhoneNumber"
13    tools:targetApi="31">
14     <activity
15       android:name=".MainActivity"
16       android:exported="true">
17       <intent-filter>
18         <action android:name="android.intent.action.MAIN" />
19
20         <category android:name="android.intent.category.LAUNCHER" />
21       </intent-filter>
22     </activity>
23   </application>
24
25 </manifest>
```

ContactsPhoneNumber

- This is our onCreate() looks like
- Let's see our activity_main.
- You will know how the contact list is shown over there

```
2 usages
public class MainActivity extends AppCompatActivity {
    1 usage
    private static final int MY_PERMISSIONS_REQUEST_READ_CONTACTS = 0; // This is request code 0
    3 usages
    String phoneNumber;
    2 usages
    ListView lv;
    2 usages
    ArrayList<String> ContactNumbersList = new ArrayList<String>();


    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        grantReadContacts();

        lv = (ListView) findViewById(R.id.lv);
        getPhoneNumber(this.getContentResolver());
    }
}
```


ContactsPhoneNumber

- I use the ListView as my UI component.
- I will show you how to use the **instance (object) of ListView** to bind with an **adapter**
- The **adapter** is populated with the **data** from the **return of a query**.
- Query for contacts in this phone
- The id is called “lv”, we will use that later



```
1 <?xml version="1.0" encoding="utf-8"?>
2 <androidx.constraintlayout.widget.ConstraintLayout xmlns:android="http://schemas.android.com/apk/res/android"
3     xmlns:app="http://schemas.android.com/apk/res-auto"
4     xmlns:tools="http://schemas.android.com/tools"
5     android:layout_width="match_parent"
6     android:layout_height="match_parent"
7     tools:context=".MainActivity">
8     |
9     <ListView
10         android:layout_width="match_parent"
11         android:layout_height="fill_parent"
12         android:id="@+id/lv"
13         tools:ignore="MissingConstraints" />
14
15 </androidx.constraintlayout.widget.ConstraintLayout>
```

ContactsPhoneNumber

- Grant the access rights
- We instantiate the “lv”
- Then, get the phone number, and form a list

```
2 usages
public class MainActivity extends AppCompatActivity {
    1 usage
    private static final int MY_PERMISSIONS_REQUEST_READ_CONTACTS = 0; // This is request code 0
    3 usages
    String phoneNumber;
    2 usages
    ListView lv;
    2 usages
    ArrayList<String> ContactNumbersList = new ArrayList<String>();

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        grantReadContacts();

        lv = (ListView) findViewById(R.id.lv);
        getPhoneNumber(this.getContentResolver());
    }
}
```

ContactsPhoneNumber

- This permission has to be the same as the one we specified in the AndroidManifest.xml
- The way to request the run-time permission from the end user is the same as we had seen earlier (This is still old style, around 2018~2022)
- (If we have enough time left, I can talk about the latest approach to request multiple access rights in one time)



```
1 usage
36 public void grantReadContacts() {
37     System.out.println("grantReadContacts");
38     if (ActivityCompat.checkSelfPermission(context: this, Manifest.permission.READ_CONTACTS)
39         != PackageManager.PERMISSION_GRANTED) {
40         ActivityCompat.requestPermissions(activity: this, new String[]{Manifest.permission.READ_CONTACTS},
41             MY_PERMISSIONS_REQUEST_READ_CONTACTS);
42     }
43 }
44
```

ContactsPhoneNumber

- Finally, our getPhoneNumber()...

```
1 usage
45 @SuppressWarnings("Range")
46 @ public void getPhoneNumber(ContentResolver cr) {
47     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
48     while (records.moveToNext()) {
49
50         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51
52         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
53
54
55         System.out.println(name + " : " + phoneNumber);
56
57         ContactNumbersList.add(name + " : " + phoneNumber);
58
59     }
60
61     records.close();
62
63     ArrayAdapter<String> adapter = new ArrayAdapter<String>(context: this,
64         android.R.layout.simple_list_item_1,
65         ContactNumbersList);
66
67     lv.setAdapter(adapter);
68
69 }
70
71 }
```

ContactsPhoneNumber

- The 1st thing, `@SuppressWarnings("Range")`
 - The **lint** tool is used in the Android Studio. It checks the Android project source files for potential bugs and optimization improvements for correctness, security, performance, usability, accessibility, and internationalization.
 - If you are interested, go to check this page
 - <https://developer.android.com/studio/write/lint#:~:text=The%20lint%20tool%20checks%20your,when%20you%20build%20your%20app.>
 - The reason I want to do this, is...
 - I want to suppress some “warning” message during the compilation.

ContactsPhoneNumber

- Cursor? What is this? (Contacts data is a kind of internal database...)
 - When we are performing a database query, the cursor is used to access the result set which is returned from the query
 - The cursor can be seen as a pointer, **which is pointing to the result set**. Or, we can say it is a kind of interface.
 - <https://developer.android.com/reference/android/database/Cursor>

```
Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
while (records.moveToNext()) {

    String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));

    phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));

    System.out.println(name + " : " + phoneNumber);

    ContactNumbersList.add(name + " : " + phoneNumber);


}

records.close();
```

ContactsPhoneNumber

We use “this.getContentResolver()” in the onCreate() to get the “cr”


- Inside of the getPhoneNumber()
 - We need the ContentResolver (cr) to execute the query



```
1 usage
45 @SuppressWarnings("Range")
46 @ public void getPhoneNumber(ContentResolver cr) {
47     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
48     while (records.moveToNext()) {
49
50         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51
52         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
53
54
55         System.out.println(name + " : " + phoneNumber);
56
57         ContactNumbersList.add(name + " : " + phoneNumber);
58
59     }
60
61     records.close();
62
63     ArrayAdapter<String> adapter = new ArrayAdapter<String>(context: this,
64         android.R.layout.simple_list_item_1,
65         ContactNumbersList);
66
67     lv.setAdapter(adapter);
68
69 }
70
71 }
```

ContactsPhoneNumber


- The while loop means, I'm going to read everything to the end of the cursor "records" can point to



```
1 usage
45 @SuppressWarnings("Range")
46 @ public void getPhoneNumber(ContentResolver cr) {
47     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
48     while (records.moveToNext()) {
49
50         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51
52         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
53
54
55         System.out.println(name + " : " + phoneNumber);
56
57         ContactNumbersList.add(name + " : " + phoneNumber);
58     }
59
60     records.close();
61
62     ArrayAdapter<String> adapter = new ArrayAdapter<String>( context: this,
63         android.R.layout.simple_list_item_1,
64         ContactNumbersList);
65
66     lv.setAdapter(adapter);
67
68 }
69
70
71 }
```


ContactsPhoneNumber


- We can use “ContactsContract” to index the “**name**” and the “**phone number**” as **indices** of **columns** we want to retrieve.

A screenshot of a code editor showing Java code. Two orange arrows originate from the text in the first bullet point. One arrow points from the word "name" to the line `String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));`. The other arrow points from the words "phone number" to the line `phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));`.

```
1 usage
45 @SuppressWarnings("Range")
46 @ public void getPhoneNumber(ContentResolver cr) {
47     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
48     while (records.moveToNext()) {
49
50         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51
52         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
53
54
55         System.out.println(name + " : " + phoneNumber);
56
57         ContactNumbersList.add(name + " : " + phoneNumber);
58
59     }
60
61     records.close();
62
63     ArrayAdapter<String> adapter = new ArrayAdapter<String>( context: this,
64         android.R.layout.simple_list_item_1,
65         ContactNumbersList);
66
67     lv.setAdapter(adapter);
68
69 }
70
71 }
```

ContactsPhoneNumber


- Finally, we use the “ContactNumberList”, which is an array list of string to collect the name + phone numbers



```
45  @SuppressWarnings("Range")
46  @
47  public void getPhoneNumber(ContentResolver cr) {
48      Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
49      while (records.moveToNext()) {
50          String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51          phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
52
53          System.out.println(name + " : " + phoneNumber);
54          ContactNumbersList.add(name + " : " + phoneNumber);
55      }
56
57      records.close();
58
59      ArrayAdapter<String> adapter = new ArrayAdapter<String>(context: this,
60          android.R.layout.simple_list_item_1,
61          ContactNumbersList);
62
63      lv.setAdapter(adapter);
64  }
65  }
```

ContactsPhoneNumber

- We need to close the cursor, in case to introduce unnecessary memory leaks




```
1 usage
45 @SuppressWarnings("Range")
46 @
47 public void getPhoneNumber(ContentResolver cr) {
48     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
49     while (records.moveToNext()) {
50
51         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
52
53         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
54
55         System.out.println(name + " : " + phoneNumber);
56
57         ContactNumbersList.add(name + " : " + phoneNumber);
58     }
59
60     records.close();
61
62     ArrayAdapter<String> adapter = new ArrayAdapter<String>(context: this,
63         android.R.layout.simple_list_item_1,
64         ContactNumbersList);
65
66     lv.setAdapter(adapter);
67
68 }
69
70
71 }
```

ContactsPhoneNumber

- In order to show something onto the UI, we need a ListView (lv)
- “lv” needs to reflect the changes from the query we just made.
- “lv” needs an “adapter”

```
1 usage
45 @SuppressWarnings("Range")
46 @
47 public void getPhoneNumber(ContentResolver cr) {
48     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
49     while (records.moveToNext()) {
50         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
52
53         System.out.println(name + " : " + phoneNumber);
54         ContactNumbersList.add(name + " : " + phoneNumber);
55     }
56     records.close();
57     ArrayAdapter<String> adapter = new ArrayAdapter<String>(context: this,
58         android.R.layout.simple_list_item_1,
59         ContactNumbersList);
60     lv.setAdapter(adapter);
61 }
62 }
```



ContactsPhoneNumber

- The adapter is set by using an “ArrayAdapter” of “String”.
 - We need to specify the style
 - We need to specify the data resource, for the construction of adapter

```
1 usage
@SuppressLint("Range")
45 @
46 public void getPhoneNumber(ContentResolver cr) {
47     Cursor records = cr.query(ContactsContract.CommonDataKinds.Phone.CONTENT_URI, projection: null, selection: null, selectionArgs: null, sortOrder: null);
48     while (records.moveToNext()) {
49
50         String name = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.DISPLAY_NAME_PRIMARY));
51
52         phoneNumber = records.getString(records.getColumnIndex(ContactsContract.CommonDataKinds.Phone.NUMBER));
53
54
55         System.out.println(name + " : " + phoneNumber);
56
57         ContactNumbersList.add(name + " : " + phoneNumber);
58
59     }
60
61     records.close();
62
63     ArrayAdapter<String> adapter = new ArrayAdapter<String>(context: this,
64         android.R.layout.simple_list_item_1,
65         ContactNumbersList);
66
67     lv.setAdapter(adapter);
68
69 }
70
71 }
```