

# ASCII Table

## Introduction

I adapted this information from a [web site](#) and I have made it available locally.

ASCII stands for American Standard Code for Information Interchange. Below is the ASCII character table, including descriptions of the first 32 characters. ASCII was originally designed for use with teletypes, and so the descriptions are somewhat obscure and their use is frequently not as intended.

Java actually uses Unicode, which includes ASCII and other characters from languages around the world.

## ASCII Table

Dec = Decimal Value  
Char = Character

'5' has the int value 53  
if we write '5'-'0' it evaluates to 53-48, or the int 5  
if we write char c = 'B'+32; then c stores 'b'

Dec	Char	Dec	Char	Dec	Char	Dec	Char
0	NUL (null)	32	SPACE	64	@	96	`
1	SOH (start of heading)	33	!	65	A	97	a
2	STX (start of text)	34	"	66	B	98	b
3	ETX (end of text)	35	#	67	C	99	c
4	EOT (end of transmission)	36	\$	68	D	100	d
5	ENQ (enquiry)	37	%	69	E	101	e
6	ACK (acknowledge)	38	&	70	F	102	f
7	BEL (bell)	39	'	71	G	103	g
8	BS (backspace)	40	(	72	H	104	h
9	TAB (horizontal tab)	41	)	73	I	105	i
10	LF (NL line feed, new line)	42	*	74	J	106	j
11	VT (vertical tab)	43	+	75	K	107	k
12	FF (NP form feed, new page)	44	,	76	L	108	l
13	CR (carriage return)	45	-	77	M	109	m
14	SO (shift out)	46	.	78	N	110	n
15	SI (shift in)	47	/	79	O	111	o
16	DLE (data link escape)	48	0	80	P	112	p
17	DC1 (device control 1)	49	1	81	Q	113	q
18	DC2 (device control 2)	50	2	82	R	114	r
19	DC3 (device control 3)	51	3	83	S	115	s
20	DC4 (device control 4)	52	4	84	T	116	t
21	NAK (negative acknowledge)	53	5	85	U	117	u
22	SYN (synchronous idle)	54	6	86	V	118	v
23	ETB (end of trans. block)	55	7	87	W	119	w
24	CAN (cancel)	56	8	88	X	120	x
25	EM (end of medium)	57	9	89	Y	121	y
26	SUB (substitute)	58	:	90	Z	122	z
27	ESC (escape)	59	;	91	[	123	{
28	FS (file separator)	60	<	92	\	124	
29	GS (group separator)	61	=	93	]	125	}
30	RS (record separator)	62	>	94	^	126	~
31	US (unit separator)	63	?	95	_	127	DEL