

| DIMENSION VARIATION | | | | | | | | |
|---------------------|------|------|------|------|------|------|-------|--|
| PKG. | | D2 | | | L | | | |
| CODES | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. | ±0.10 | |
| T1655-2 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T1655-2C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T1655-3 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T1655-3C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T1655-4 | 2.19 | 2.29 | 2.39 | 2.19 | 2.29 | 2.39 | | |
| T1655-4C | 2.19 | 2.29 | 2.39 | 2.19 | 2.29 | 2.39 | | |
| T1655N-1 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T2055-3 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T2055M-3 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T2055-4 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T2055-4C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T2055-5 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2055-5C | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2055MN-5 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2055-6C | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2855-3 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | | |
| T2855-3C | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | | |
| T2855-4 | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855-4C | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855-5 | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855-5C | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855M-5 | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855-6 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | | |
| T2855-6A | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | | |
| T2855-6C | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | | |
| T2855-7 | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855-7C | 2.60 | 2.70 | 2.80 | 2.60 | 2.70 | 2.80 | | |
| T2855-8 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2855-8C | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2855MK-8 | 3.15 | 3,25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |
| T2855N-1 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | | |
| T2855-13 | 3.15 | 3.25 | 3.35 | 3.15 | 3.25 | 3.35 | 0.40 | |

| COMMON DIMENSIONS | | | | | | | | | | | | | | | |
|-------------------|------------|-------------------|---------|------------|-------------|-----------|-----------|----------|-----------|------|-----------|------|------|------|------|
| PKG. | 16L 5×5 20 | | 20L 5×5 | | 28L 5×5 | | | 32L 5×5 | | | 40L 5×5 | | | | |
| SYMBOL | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. |
| Α | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 |
| A1 | 0 | 0.02 | 0.05 | 0 | 0.02 | 0.05 | 0 | 0.02 | 0.05 | 0 | 0.02 | 0.05 | 0 | 0.02 | 0.05 |
| A2 | 0.2 | 20 REF. 0.20 REF. | | 0.20 REF. | | 0.20 REF. | | | 0.20 REF. | | | | | | |
| b | 0.25 | 0.30 | 0.35 | 0.25 | 0.30 | 0.35 | 0.20 | 0.25 | 0.30 | 0.20 | 0.25 | 0.30 | 0.15 | 0.20 | 0.25 |
| D | 5. | .00 B | SC | C 5.00 BSC | | 5.00 BSC | | 5.00 BSC | | | 5.00 BSC | | | | |
| Е | 5 | .00 B | SC | 5.00 BSC | | 5.00 BSC | | 5.00 BSC | | | 5.00 BSC | | | | |
| e | 0. | 80 BS | SC. | 0. | 65 B | SC. | 0.50 BSC. | | 0.50 BSC. | | 0.40 BSC. | | | | |
| k | 0.25 | _ | - | 0.25 | _ | _ | 0.25 | _ | _ | 0.25 | - | - | 0.25 | _ | - |
| L | 0.30 | 0.40 | 0.50 | 0.45 | 0.55 | 0.65 | 0.45 | 0.55 | 0.65 | 0.30 | 0.40 | 0.50 | 0.30 | 0.40 | 0.50 |
| N | | 16 | | 20 | | 28 | | 32 | | 40 | | | | | |
| ND | | 4 | | 5 | | 7 | | 8 | | 10 | | | | | |
| NE | | 4 | | 5 | | 7 | | 8 | | | 10 | | | | |
| JEDEC | \ | √HHB | | \ | WHHC WHHD-1 | | | -1 | WHHD-2 | | | | | | |



PACKAGE DUTLINE, 16,20,28,32,40L
THIN QFN, 5×5×0.75mm

APPROVAL DOCUMENT CONTROL NO. RE
21-0140 A

REV. 2/4

| DIMENSION VARIATION | | | | | | | | |
|---------------------|------|------|------|------|------|------|-------|--|
| PKG. | | D2 | | | L | | | |
| CODES | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. | ±0.10 | |
| T3255-3 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-3C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-4 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-4C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255M-4 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-5 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-5C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-6 | 2.00 | 2.10 | 2.20 | 2.00 | 2.10 | 2.20 | | |
| T3255-6C | 2.00 | 2.10 | 2.20 | 2.00 | 2.10 | 2,20 | | |
| T3255-7 | 3.00 | 3.10 | 3,20 | 3.00 | 3.10 | 3.20 | | |
| T3255-7C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-8 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-8C | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255-9 | 3.30 | 3.40 | 3.50 | 3.30 | 3.40 | 3.50 | | |
| T3255M-5 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255MK-1 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255MK-2 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255N-1 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T3255MN-1 | 3.00 | 3.10 | 3.20 | 3.00 | 3.10 | 3.20 | | |
| T4055-1 | 3.40 | 3.50 | 3.60 | 3.40 | 3.50 | 3.60 | | |
| T4055-1C | 3.40 | 3.50 | 3.60 | 3.40 | 3.50 | 3.60 | | |
| T4055-2 | 3.40 | 3.50 | 3.60 | 3.40 | 3.50 | 3.60 | | |
| T4055-2C | 3.40 | 3.50 | 3.60 | 3.40 | 3.50 | 3.60 | | |

| C⊡RNER LEAD CHAMFER ∨ARIATI⊡N | | | | | | | | |
|----------------------------------|-----------------|----------|--|--|--|--|--|--|
| PKG. CODES | С | L4 | | | | | | |
| T3255-3 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-3C | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-4 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-4C | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-5 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-5C | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-6 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-6C | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-7 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-7C | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-8 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-8C | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255-9 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255M-4 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255M-5 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255MK-1 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255MK-2 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255N-1 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T3255MN-1 | 0.120 X 45° REF | 0.31 REF | | | | | | |
| T4055-1 | 0.160 X 45° REF | 0.28 REF | | | | | | |
| T4055-1C | 0.160 X 45° REF | 0.28 REF | | | | | | |
| T4055-2 | 0.160 X 45° REF | 0.28 REF | | | | | | |
| T4055-2C | 0.160 X 45° REF | 0.28 REF | | | | | | |
| T4055MN-1 | 0.160 X 45° REF | 0.28 REF | | | | | | |
| T4055N-1 | 0.160 X 45° REF | 0.28 REF | | | | | | |

| DIMENSION VARIATION | | | | | | | | | |
|---------------------|------|------|------|------|------|------|-------|--|--|
| PKG. | | D2 | | | L | | | | |
| CODES | MIN. | N□M. | MAX. | MIN. | N□M. | MAX. | ±0.10 | | |
| T4055N-1 | 3.40 | 3.50 | 3.60 | 3.40 | 3.50 | 3.60 | | | |
| T4055MN-1 | 3.40 | 3.50 | 3.60 | 3.40 | 3.50 | 3.60 | | | |



THE:
PACKAGE DUTLINE, 16,20,28,32,40L
THIN QFN, 5×5×0.75mm

APPROVAL DOCUMENT CONTROL NO. RE:
21-0140 A

REV. 3/4

NOTES:

- 1. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 2. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
- 3. N IS THE TOTAL NUMBER OF TERMINALS.
- THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- DIMENSION 6 APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25 mm AND 0.30 mm FROM TERMINAL TIP.
- 6. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE RESPECTIVELY.
- 7. DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
- DRAWING CONFORMS TO JEDEC MO220, EXCEPT EXPOSED PAD DIMENSION FOR T2855-3, T2855-6, T4055-1 AND T4055-2.
- ✓9.\ WARPAGE SHALL N□T EXCEED 0.10 mm.
- 10 MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- $\cancel{\Delta\Omega}$ REFER TO DIMENSION VARIATION TABLE FOR LEAD LENGTH VARIATION
- APPLICABLE ONLY FOR PACKAGES WITH TIGHT CORNER LEADS METAL TO METAL CLEARANCE.
- 13. NUMBER OF LEADS SHOWN ARE FOR REFERENCE ONLY.
- 14. LEAD CENTERLINES TO BE AT TRUE POSITION AS DEFINED BY BASIC DIMENSION "e", ±0.05.
- 15. MATERIAL MUST BE COMPLIANT WITH MAXIM SPECIFICATION 10-0131 FOR SUBSTANCE CONTENT, MUST BE EU ROHS COMPLIANT WITHOUT EXEMPTION AND PB-FREE.
- 16. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PbFREE (+) PKG. CODES.



TITLE:

PACKAGE DUTLINE, 16,20,28,32,40L THIN QFN, 5×5×0.75mm

APPROVAL

DOCUMENT CONTROL NO. 21-0140

REV. 4