

GitHub Codespaces GUI Setup — Flow

Single-script workflow for XFCE + TigerVNC + noVNC. No Chrome, Open Video Downloader, or other application installation is included.

1. Put the script in your Codespace

Create the file and paste the supplied setup-gui.sh script into it:

```
nano ~/setup-gui.sh
```

Save with Ctrl+O, Enter, then Ctrl+X.

2. Make it executable

```
chmod +x ~/setup-gui.sh
```

3. Run the single script

```
~/setup-gui.sh
```

4. Select what you need

- 1) Fresh GUI setup
Installs XFCE + TigerVNC + noVNC and starts the GUI.
- 2) GUI already installed - start GUI only
Skips installation and starts VNC + noVNC.
- 3) GUI already installed - configure auto-start
Skips installation and configures GUI auto-start.
- 4) GUI already installed - start GUI + configure auto-start
Skips installation, starts the GUI, and configures auto-start.
- 5) Exit
Closes the script.

5. First-time setup

Choose option 1 if the GUI components are not installed yet. The script installs only the GUI infrastructure: XFCE, xfce4-goodies, dbus-x11, xterm, TigerVNC, noVNC, and Websockify.

6. If GUI setup is already complete

Choose option 2, 3, or 4. The script will not reinstall the GUI packages.

7. Open the browser GUI

After the GUI starts, open the Codespaces PORTS panel, find port 6080, open it in your browser, and click Connect. Use the VNC password created during setup.

8. Ports and display

```
XFCE      → desktop session
TigerVNC  → display :1 / port 5901
noVNC     → port 6080
Browser   → forwarded Codespaces port 6080
```

9. Auto-start behavior

Option 3 or 4 adds a startup entry to `~/.bashrc`. This is shell-start auto-start, not a `systemd` boot service. A new Codespaces shell can therefore start the GUI services automatically.

10. If something fails

Stop and inspect the exact terminal error. Do not install unrelated applications to fix the GUI setup.