

SECURITY ASSESSMENT

Vulnerability Assessment Report

Target System: Metasploitable 2 (192.168.128.2)

Assessment type:	Internal Vulnerability Assessment & Web Application Test
Prepared by:	Numan Khalid Bhat
Credentials:	CompTIA Security+ (SY0-701)
Date:	31 July 2026
Environment:	Isolated home lab (UTM / Kali Linux)
Classification:	Confidential

This document is for demonstration and portfolio purposes. All testing was conducted against an intentionally vulnerable system owned and operated by the author within an isolated laboratory network.

Table of Contents

1	Executive Summary
2	Scope & Objectives
3	Methodology
4	Risk Rating Definitions
5	Summary of Findings
6	Detailed Findings: Infrastructure
7	Detailed Findings: Web Application (DVWA)
8	Remediation Roadmap
9	Conclusion
A	Appendix: Reconnaissance Output

1. Executive Summary

This assessment looked at the host **192.168.128.2** (Metasploitable 2) to find security weaknesses in the network services it runs and the web application it hosts. Automated scanning was used to map the attack surface, and the key issues were then verified by hand to confirm what an attacker could actually do with them.

The host is in a very poor security state. It has **23 open TCP ports**, and every service running on them is years past its supported life. Several of the findings are severe on their own. One port gives an **unauthenticated root shell** to anyone who connects. Several services carry **known remote code execution vulnerabilities**. The web application is open to the common **OWASP Top 10** injection and access control flaws. Any attacker who can reach this host over the network could take full control of it in a matter of minutes.

The table below summarises the issues identified, grouped by severity:

Severity	Count	Representative issues
CRITICAL	7	Root bind shell (1524), vsftpd 2.3.4 backdoor, Samba usermap_script RCE, UnrealIRCd backdoor, OS command injection, SQL injection, unrestricted file upload
HIGH	8	SMB NULL sessions, absent password policy, cleartext protocols, end-of-life web stack, blind SQLi, local file inclusion, stored XSS, credential brute force
MEDIUM	4	Anonymous FTP, exposed phpMyAdmin/phpinfo, reflected XSS, CSRF

Overall risk rating: CRITICAL. This system should never be placed on an untrusted network. On a real production host, the right response would be to take it offline straight away and rebuild it on a current, hardened platform.

2. Scope & Objectives

In-scope target: 192.168.128.2 (Metasploitable 2), all TCP services and the hosted DVWA web application.

Out of scope: the host operating system's underlying hypervisor, the attacker workstation, and any system outside the isolated lab network.

Objective: enumerate the attack surface, identify vulnerabilities, and confirm exploitability to determine business impact, then provide prioritised remediation guidance.

Rules of engagement: testing was authorised and performed by the system owner in an isolated lab. Denial-of-service testing was excluded.

3. Methodology

The assessment followed a standard vulnerability-assessment workflow aligned with the reconnaissance and exploitation phases of common industry frameworks (PTES / OWASP Testing Guide):

Phase	Activity	Tools
Discovery	Host and port discovery, service version detection	Nmap
Enumeration	Web technology fingerprinting, web server scanning, SMB user/ share enumeration	WhatWeb, Nikto, enum4linux
Vulnerability analysis	Mapping service versions to known CVEs; identifying misconfigurations	Manual analysis, CVE/ NVD
Exploitation / verification	Manual confirmation of web application flaws to prove impact	Browser, manual payloads
Reporting	Risk rating, business impact, remediation guidance	n/a


4. Risk Rating Definitions

Rating	CVSS band	Definition
CRITICAL	9.0 – 10.0	Trivially exploitable; leads directly to full system or data compromise. Remediate immediately.
HIGH	7.0 – 8.9	Serious impact on confidentiality, integrity, or availability. Remediate urgently.
MEDIUM	4.0 – 6.9	Meaningful risk, often requiring specific conditions or user interaction. Remediate in planned cycle.
LOW	0.1 – 3.9	Limited impact; typically information disclosure or defence-in-depth.

5. Summary of Findings

ID	Finding	Category	Severity
INF-01	Unauthenticated root bind shell (port 1524)	Infrastructure	CRITICAL
INF-02	vsftpd 2.3.4 backdoor (CVE-2011-2523)	Infrastructure	CRITICAL
INF-03	Samba usermap_script RCE (CVE-2007-2447)	Infrastructure	CRITICAL
INF-04	UnrealIRCd backdoor (CVE-2010-2075)	Infrastructure	CRITICAL
INF-05	SMB NULL sessions (anonymous enumeration)	Infrastructure	HIGH
INF-06	Absent password policy (no complexity/lockout)	Infrastructure	HIGH
INF-07	Cleartext protocols (Telnet, r-services, FTP)	Infrastructure	HIGH
INF-08	End-of-life web stack (Apache 2.2.8 / PHP 5.2.4)	Infrastructure	HIGH
INF-09	Anonymous FTP access enabled	Infrastructure	MEDIUM
INF-10	Exposed phpMyAdmin, phpinfoc & directory indexing	Infrastructure	MEDIUM
WEB-01	OS Command Injection	Web application	CRITICAL
WEB-02	SQL Injection	Web application	CRITICAL
WEB-03	Unrestricted File Upload	Web application	CRITICAL
WEB-04	Local File Inclusion	Web application	HIGH
WEB-05	Stored Cross-Site Scripting	Web application	HIGH
WEB-06	Blind SQL Injection	Web application	HIGH
WEB-07	Credential Brute Force (weak auth)	Web application	HIGH
WEB-08	Reflected Cross-Site Scripting	Web application	MEDIUM
WEB-09	Cross-Site Request Forgery	Web application	MEDIUM

6. Detailed Findings: Infrastructure



```
kali@kali: ~  
Session Actions Edit View Help  
(kali@kali)-[~]  
$ nmap -sV 192.168.128.2  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-31 14:37 -0400  
Nmap scan report for 192.168.128.2  
Host is up (0.032s latency).  
Not shown: 977 closed tcp ports (reset)  
PORT      STATE SERVICE      VERSION  
21/tcp    open  ftp          vsftpd 2.3.4  
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)  
23/tcp    open  telnet       Linux telnetd  
25/tcp    open  smtp         Postfix smtpd  
53/tcp    open  domain       ISC BIND 9.4.2  
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)  
111/tcp   open  rpcbind      2 (RPC #100000)  
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)  
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)  
512/tcp   open  exec         netkit-rsh rexecd  
513/tcp   open  login          
514/tcp   open  shell        Netkit rshd  
1099/tcp  open  java-rmi     GNU Classpath grmiregistry  
1524/tcp  open  bindshell    Metasploitable root shell  
2049/tcp  open  nfs          2-4 (RPC #100003)  
2121/tcp  open  ftp          ProFTPD 1.3.1  
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5  
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7  
5900/tcp  open  vnc          VNC (protocol 3.3)  
6000/tcp  open  X11          (access denied)  
6667/tcp  open  irc          UnrealIRCd  
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)  
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1  
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 16.53 seconds  
  
(kali@kali)-[~]  
$
```

Figure 1. Nmap service scan of 192.168.128.2 showing 23 open ports and their versions.

INF-01: Unauthenticated Root Bind Shell (port 1524) **CRITICAL**

Service: 1524/tcp (bindshell) • **CVSS v3.1:** 10.0

Port 1524 hosts a bind shell that grants an interactive **root** command prompt to anyone who connects, with no authentication whatsoever. This is the single most severe issue on the host.

Impact: instant, complete compromise. An attacker simply connects (e.g. `nc 192.168.128.2 1524`) and receives a root shell.

Remediation: the service is a backdoor and must not exist on any real system. Rebuild the host from a trusted image and audit for unauthorised listeners.

INF-02: vsftpd 2.3.4 Backdoor (CVE-2011-2523) **CRITICAL**

Service: 21/tcp (vsftpd 2.3.4) • **CVSS v3.1:** 9.8

The FTP service runs vsftpd 2.3.4, a version that shipped with a malicious backdoor: supplying a username ending in `:)` opens a root shell on port 6200.

Impact: remote root code execution by an unauthenticated attacker.

Remediation: remove this compromised build; deploy a current, vendor-supported FTP server or replace FTP with SFTP.

INF-03: Samba usermap_script Command Execution (CVE-2007-2447) **CRITICAL**

Service: 139/445 (Samba 3.0.20-Debian) • **CVSS v3.1:** 9.8

Samba 3.0.20 is vulnerable to shell metacharacter injection via the username field, allowing arbitrary command execution as root without valid credentials.

Impact: unauthenticated remote root code execution.

Remediation: upgrade Samba to a supported release; never pass client-supplied values to a shell.

INF-04: UnrealIRCd Backdoor (CVE-2010-2075) **CRITICAL**

Service: 6667/tcp (UnrealIRCd) • **CVSS v3.1:** 9.8

The IRC daemon is a backdoored build of UnrealIRCd that executes any command sent after a special `AB;` sequence.

Impact: unauthenticated remote command execution.

Remediation: remove the compromised binary and reinstall from a verified source with checksum validation.

INF-05: SMB NULL Sessions Permit Anonymous Enumeration **HIGH**

Service: 139/445 (Samba) • **CVSS v3.1:** 7.5

The SMB service permits NULL (anonymous) sessions. Without any credentials, an attacker retrieved the complete list of **35 local user accounts** (including `root` and `msfadmin`), the share list, and the domain SID, and confirmed the `tmp` share is anonymously readable.

```
kali@kali: ~  
Session Actions Edit View Help  
[+] Got domain/workgroup name: WORKGROUP  
  
===== ( Nbtstat Information for 192.168.128.2 ) =====  
Looking up status of 192.168.128.2  
METASPLOITABLE <00> - B <ACTIVE> Workstation Service  
METASPLOITABLE <03> - B <ACTIVE> Messenger Service  
METASPLOITABLE <20> - B <ACTIVE> File Server Service  
.._MSBROWSE_.. <01> - <GROUP> B <ACTIVE> Master Browser  
WORKGROUP <00> - <GROUP> B <ACTIVE> Domain/Workgroup Name  
WORKGROUP <1d> - B <ACTIVE> Master Browser  
WORKGROUP <1e> - <GROUP> B <ACTIVE> Browser Service Elections  
  
MAC Address = 00-00-00-00-00-00  
  
===== ( Session Check on 192.168.128.2 ) =====  
[+] Server 192.168.128.2 allows sessions using username '', password ''  
  
===== ( Getting domain SID for 192.168.128.2 ) =====  
Domain Name: WORKGROUP  
Domain Sid: (NULL SID)  
[+] Can't determine if host is part of domain or part of a workgroup  
  
===== ( OS information on 192.168.128.2 ) =====
```

Figure 2. enum4linux confirming an anonymous SMB session ("allows sessions using username ", password "").

Impact: the disclosed usernames provide a ready-made target list for the brute-force attack in WEB-07; information disclosure significantly lowers the effort required for further attacks.

Remediation: disable NULL sessions (`restrict anonymous`), require authentication for share access, and restrict SMB to trusted hosts.

INF-06: Absent Password Policy HIGH

Source: enum4linux password policy • **CVSS v3.1:** 7.0

The domain password policy has **no complexity requirement, no account lockout threshold, no minimum length, and no maximum password age**. This removes all friction from online password-guessing attacks.

Impact: directly enables credential brute forcing (see WEB-07). Weak or guessable passwords will never be rejected and repeated guessing is never locked out.

Remediation: enforce a strong password policy: minimum length, complexity, history, and an account lockout threshold with a reset window.

INF-07: Cleartext Protocols Enabled HIGH

Services: 23 (Telnet), 512/513/514 (r-services), 21 (FTP) • **CVSS v3.1:** 7.4

Multiple legacy services transmit credentials and data in cleartext, including Telnet and the Berkeley r-services (rexec/rlogin/rsh).

Impact: an attacker positioned on the network can capture credentials and hijack sessions via man-in-the-middle.

Remediation: disable Telnet and r-services entirely; use SSH. Replace plain FTP with SFTP/FTPS.

INF-08: End-of-Life Web Stack (Apache 2.2.8 / PHP 5.2.4) HIGH

Service: 80/tcp • **CVSS v3.1:** 7.5

The web server runs Apache 2.2.8 with PHP 5.2.4, both many years past end-of-life and affected by numerous public CVEs. The `X-Powered-By` header discloses the exact PHP version, and WebDAV (DAV/2) is enabled.

Impact: large known-vulnerability surface; version disclosure aids targeted exploitation.

Remediation: upgrade to supported Apache/PHP releases, suppress version headers, and disable WebDAV if not required.

INF-09: Anonymous FTP Access Enabled MEDIUM

Service: 21/tcp • **CVSS v3.1:** 5.3

The FTP service allows anonymous login (`ftp-anon: Anonymous FTP login allowed`).

Impact: unauthenticated access to any files exposed over FTP; potential information disclosure or upload abuse.

Remediation: disable anonymous FTP unless explicitly required; if required, tightly restrict its directory and permissions.

INF-10: Exposed phpMyAdmin, phpinfo & Directory Indexing MEDIUM

Source: Nikto • **CVSS v3.1:** 6.5

The web server exposes an unprotected `phpMyAdmin` instance, a `phpinfo.php` page leaking full system/configuration detail (CWE-552), the HTTP TRACE method (XST), and directory indexing on `/icons/` , `/doc/` , and `/test/` .

Impact: information disclosure and a direct management path to the MySQL database.

Remediation: remove phpinfo pages, restrict phpMyAdmin to authorised hosts behind authentication, disable TRACE and directory indexing.

7. Detailed Findings: Web Application (DVWA)

The following findings were confirmed by manual exploitation of the hosted DVWA application at security level **Low**. Each is evidenced with a screenshot captured during testing.

WEB-01: OS Command Injection **CRITICAL**

CWE-78 • OWASP A03:2021 Injection • CVSS v3.1: 9.8

The "ping" function passes user input directly to a system shell. Appending `; whoami` to a valid IP executed the injected command and returned the web-server user.

Payload: `127.0.0.1; whoami`

Result: command output returned `www-data`.




Figure 3. Injected `whoami` executed by the server, returning `www-data`.

Impact: arbitrary command execution as the web-server user; a foothold for reverse shells, data theft, and lateral movement.

Remediation: never pass user input to a shell; use safe parameterised APIs and strict input allowlisting (validate that input is a well-formed IP address).

WEB-02: SQL Injection **CRITICAL**

CWE-89 • OWASP A03:2021 Injection • CVSS v3.1: 9.8

The User ID field concatenates input directly into a SQL query. A tautology payload returned every record in the users table rather than a single match.

Payload: `' OR '1'='1`

Result: full user table disclosed (admin, Gordon Brown, Hack Me, Pablo Picasso, Bob Smith).

Vulnerability: SQL Injection

User ID:

Submit

ID: 1' OR '1' = '1
First name: admin
Surname: admin

ID: 1' OR '1' = '1
First name: Gordon
Surname: Brown

ID: 1' OR '1' = '1
First name: Hack
Surname: Me

ID: 1' OR '1' = '1
First name: Pablo
Surname: Picasso

ID: 1' OR '1' = '1
First name: Bob
Surname: Smith

Figure 4. The tautology payload returns all database users, confirming SQL injection.

Impact: full database disclosure (including credentials/PII), authentication bypass, and potential data modification.

Remediation: use parameterised queries/prepared statements exclusively; apply least-privilege database accounts and input validation.

WEB-03: Unrestricted File Upload **CRITICAL**

CWE-434 • OWASP A04:2021 Insecure Design • CVSS v3.1: 9.8

The upload function accepts a PHP file with no type or content validation and stores it in a web-accessible, script-executing directory. The uploaded file executed when requested.

File: `shell.php` containing `<?php echo "Upload test"; ?>`

Result: reachable at `/dvwa/hackable/uploads/shell.php` and executed by the server.




Figure 5. The uploaded PHP file executes server-side, returning "Upload test".

Impact: in a real attack this would be a web shell, granting remote code execution and interactive server control.

Remediation: validate uploads against an allowlist of extensions/MIME types, rename files, store them outside the web root, and disable script execution in the upload directory.

WEB-04: Local File Inclusion HIGH

CWE-98 • OWASP A01:2021 Broken Access Control • CVSS v3.1: 7.5

The `page` parameter is passed to an include statement without validation. Supplying an absolute path returned the contents of a sensitive system file.

Payload: `?page=/etc/passwd`

Result: full contents of `/etc/passwd` disclosed in the browser.




Figure 6. `/etc/passwd` disclosed via the unvalidated `page` parameter.

Impact: disclosure of sensitive files (system accounts, configuration, credentials); can escalate to RCE when combined with log poisoning or an upload vector.

Remediation: map user choices to a fixed server-side allowlist; never build include paths from user input; disable `allow_url_include`.

WEB-05: Stored Cross-Site Scripting HIGH

CWE-79 • OWASP A03:2021 Injection • CVSS v3.1: 7.4

Input to the guestbook message field is stored and rendered to every visitor without output encoding. The injected script executed automatically on page load.

Payload: `<script>alert('XSS')</script>`




Figure 7. Stored payload executes automatically when the page loads.

Impact: the script runs for every visitor with no interaction needed, so it can be used for mass session hijacking, credential theft, and page defacement. It is more dangerous than reflected XSS because the payload persists on the page and reaches everyone who views it.

Remediation: apply context-aware output encoding at render time, sanitise stored input, deploy a Content Security Policy, and set `HttpOnly` on session cookies.

WEB-06: Blind SQL Injection HIGH

CWE-89 • OWASP A03:2021 Injection • CVSS v3.1: 8.6

The application is injectable even where results are not directly displayed. Logically equivalent inputs produce different application responses (true vs false), confirming the query can be manipulated and data inferred bit by bit.

Payloads: `1' AND '1'='1` (true) vs `1' AND '1'='2` (false)

Impact: full data extraction via boolean/time-based inference, typically automated; equivalent end-impact to classic SQLi.

Remediation: parameterised queries (identical fix to WEB-02), generic responses that do not leak query state, and least-privilege database accounts.

WEB-07: Credential Brute Force / Weak Authentication HIGH

CWE-307 • OWASP A07:2021 Auth Failures • CVSS v3.1: 8.1

The login function applies no rate limiting, no CAPTCHA, and no account lockout, and stores passwords using unsalted **MD5**. Combined with the disclosed usernames (INF-05) and absent password policy (INF-06), this makes automated credential guessing highly effective.

Method: automated wordlist attack (e.g. Hydra) against the login form.

Impact: account takeover; any dumped MD5 hashes are cracked almost instantly offline.

Remediation: hash with bcrypt/Argon2, enforce rate limiting and account lockout, add MFA, and monitor for brute-force patterns.

WEB-08: Reflected Cross-Site Scripting MEDIUM

CWE-79 • OWASP A03:2021 Injection • CVSS v3.1: 6.1

User input is reflected into the response without output encoding. The injected script executed immediately in the browser.

Payload: `<script>alert('XSS')</script>`

Vulnerability: Reflected Cross Site Scripting (XSS)

What's your name?

More info

<http://hacker.org/xss.html>

http://en.wikipedia.org/wiki/Cross-site_scripting

<http://www.cgisecurity.com/xss-faq.html>

🌐 192.168.128.2

XSS

Figure 8. Reflected payload executes in the victim's browser.

Impact: when delivered via a crafted link, enables session theft, phishing, and actions performed as the victim.


Remediation: context-aware output encoding, input validation, Content Security Policy, and `HttpOnly` cookies.

WEB-09: Cross-Site Request Forgery MEDIUM

CWE-352 • OWASP A01:2021 Broken Access Control • CVSS v3.1: 6.5

The password-change function performs a sensitive state change with no anti-CSRF token, authenticated only by the ambient session cookie. The password was changed via a simple crafted request.

Request: `/vulnerabilities/csrf/?password_new=...&password_conf=...&Change=Change`



http://192.168.128.2/dvwa/vulnerabilities/csrf/?password_new=hacked123&password_conf=hacked123

Kali Forums Kali NetHunter Exploit-DB Google Hacking DB

DVWA

Vulnerability: Cross Site Request Forgery (CSRF)

Change your admin password:

New password:
Confirm new password:

Change

Password Changed

More info

http://www.owasp.org/index.php/Cross-Site_Request_Forgery
<http://www.cgisecurity.com/csrf-faq.html>
http://en.wikipedia.org/wiki/Cross-site_request_forgery

Figure 9. Password changed with no anti-CSRF token or re-authentication.

Impact: an attacker can force a logged-in victim to change their password (account takeover) or perform other sensitive actions by getting them to load a malicious page.

Remediation: implement per-request anti-CSRF tokens, set `SameSite` on session cookies, and require re-authentication for sensitive actions.

8. Remediation Roadmap

Remediation is prioritised by risk. The critical items remove the fastest paths to full compromise and should be addressed first.

Priority	Action	Addresses
IMMEDIATE	Isolate the host from untrusted networks; remove backdoor services (bind shell, vsftpd 2.3.4, UnrealIRCd); patch Samba	INF-01 – INF-04
IMMEDIATE	Rewrite web application data access to parameterised queries; remove shell calls; fix file-upload validation	WEB-01, WEB-02, WEB-03, WEB-06
URGENT	Disable SMB NULL sessions; enforce a password policy with lockout; disable cleartext protocols (Telnet, r-services)	INF-05, INF-06, INF-07
URGENT	Upgrade Apache/PHP to supported versions; add output encoding and CSP; implement anti-CSRF tokens; add allowlist for file inclusion	INF-08, WEB-04, WEB-05, WEB-08, WEB-09
PLANNED	Disable anonymous FTP; remove phpinfo; restrict phpMyAdmin; disable directory indexing and TRACE; strengthen authentication (bcrypt, MFA)	INF-09, INF-10, WEB-07

9. Conclusion

The assessed host is comprehensively insecure at both the infrastructure and application layers. Nineteen distinct findings were identified, seven of them critical, several of which independently permit full, unauthenticated compromise of the system. The web application separately exhibits the complete range of common OWASP Top 10 injection and access-control flaws, each confirmed by manual exploitation.

The weaknesses run right through the system, from backdoored services and unpatched software to missing hardening and insecure application code. Because the problems are this deep, fixing them one at a time will not make the host safe. On a real production system the correct response is to isolate it immediately and rebuild it on a current, supported, and hardened platform, then re-test to confirm the issues are gone. The prioritised roadmap in Section 8 sets out the order to work through.

Appendix A: Reconnaissance Output

A.1 Nmap service scan (`nmap -sV 192.168.128.2`)

PORT	STATE	SERVICE	VERSION
21/tcp	open	ftp	vsftpd 2.3.4
22/tcp	open	ssh	OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp	open	telnet	Linux telnetd
25/tcp	open	smtp	Postfix smtpd
53/tcp	open	domain	ISC BIND 9.4.2
80/tcp	open	http	Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp	open	rpcbind	2 (RPC #100000)
139/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp	open	netbios-ssn	Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)
512/tcp	open	exec	netkit-rsh rexecd
513/tcp	open	login	
514/tcp	open	shell	Netkit rshd
1099/tcp	open	java-rmi	GNU Classpath grmiregistry
1524/tcp	open	bindshell	Metasploitable root shell
2049/tcp	open	nfs	2-4 (RPC #100003)
2121/tcp	open	ftp	ProFTPD 1.3.1
3306/tcp	open	mysql	MySQL 5.0.51a-3ubuntu5
5432/tcp	open	postgresql	PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp	open	vnc	VNC (protocol 3.3)
6000/tcp	open	X11	(access denied)
6667/tcp	open	irc	UnrealIRCd
8009/tcp	open	ajp13	Apache Jserv (Protocol v1.3)
8180/tcp	open	http	Apache Tomcat/Coyote JSP engine 1.1

A.2 Web fingerprint (WhatWeb)

```
http://192.168.128.2 [200 OK] Apache[2.2.8], HTTPServer[Ubuntu Linux][Apache/2.2.8 (Ubuntu) DAV/2], PHP[5.2.4-2ubuntu5.10], Title[Metasploitable2 - Linux], WebDAV[2], X-Powered-By[PHP/5.2.4-2ubuntu5.10]
```

A.3 SMB enumeration (enum4linux), key results

```
[+] Server 192.168.128.2 allows sessions using username '', password '' (NULL session permitted)
[+] Enumerated 35 local accounts including root, msfadmin, www-data, postgres, mysql
[+] Share 'tmp' Mapping: OK Listing: OK (anonymously accessible)
[+] Password policy: Minimum length 0 | Complexity Disabled | Account Lockout Threshold: None
```

End of report