CRT ADAPTER



ASSEMBLY WITH WIRES - 527-045-9-001 NYLON RECEPTACLE 779 -004 - 9-001 PINS (SPECIFY QTY.) 765-006-9-001 19 [! **•** 104

WIRING SCHEME		
CRT SOCKET PIN	WIRE COLOR	NYLON RECEP- TACLE
1	BŁK	1
2	YEL/RED	10
3	RED	4
4	WHT/RED	7
5	WHT/GRN	9
6	YEL/GRN	6
7	GRN	3
8	keyway	_
9	WHT	12
10	keyway	
11	YEL/BLU	5
12	เลา	8
13	WHT/BLU	11
14	BRN	2
]	!	

FITS CRT DIMENSIONS:

- A = pin circle diameter
- a = angular pin spacing
- B = post diameter
- C = keyway width
- C keyway widii
- D = keyway depth
- E = keyway width
- R1= outer keyway radius
- $= 20.32 \text{ mm}/0.800^{\circ} \text{ nom.}$
- = 25-5/7°
- = 11.5 mm/0.455" max.
- $= 3.4 \text{ mm}/0.135^{\circ} \text{ max}.$
- $= 1.77 \text{ mm/0.070}^{\circ} \text{ max.}$
- = 1.83 mm/0.072" max.
- $= 26.24 \text{ mm}/1.033^{\circ} \text{ min.}$



B & K-Precision, Factory Service Department Maxing International Corporation 6470 West Conflord Street Chicago, Illinois 60635 Telephones (312) 339-1443

481-167-9-019B