

```


freqNum = 3000; % number of frequencies to plot
medianAmpSpectrumMat = zeros(freqNum, 10); % matrix to store the median
amplitude spectrum of each digit
Q25AmpSpectrumMat = zeros(freqNum, 10); % matrix to store the 25th
percentile amplitude spectrum of each digit
Q75AmpSpectrumMat = zeros(freqNum, 10); % matrix to store the 75th
percentile amplitude spectrum of each digit
meanAmpSpectrumMat = zeros(freqNum, 10); % matrix to store the mean
amplitude spectrum of each digit
everyAmpSpectrumMat = cell(10, 1); % matrix to store the amplitude spectrum
of each digit

audioSignals = cell(50, 1); % Each one of the 50 samples will contain the
audio signals of each one of the digits
for i = 1:50
    audioSignals{i} = preProcess(i-1); % get the audio signals of each one
of the digits from the sample
end

[medianAmpSpectrumMat, Q25AmpSpectrumMat, Q75AmpSpectrumMat,
meanAmpSpectrumMat, everyAmpSpectrumMat] = digitsAmpSpectrums(audioSignals,
'default');

```

Median, Q25 and Q75 Amplitude Spectrum of each digit, with window




```

digitsAmpSpectrums(audioSignals, 'hamming');


```

Median, Q25 and Q75 Amplitude Spectrum of each digit, with window




```
digitsAmpSpectrums(audioSignals, 'hann');
```

Median, Q25 and Q75 Amplitude Spectrum of each digit, with window



```
digitsAmpSpectrums(audioSignals, 'blackman');
```

Median, Q25 and Q75 Amplitude Spectrum of each digit, with window



```
spectralFeatures = containers.Map(); % Hashmap containing the spectral
features of each digit
```

```
% These arrays will store the spectral features of each sample of each digit
```

```
spectralMean = cell(10, 1);
```

```
spectralFlux = cell(10, 1);
```

```
spectralSpread = cell(10, 1);
```

```
spectralPeaksMedian = cell(10, 1);
```

```
spectralFlatness = cell(10, 1);
```

```
spectralVariance = cell(10, 1);
```

```
% These arrays will store the spectral features of each sample of the
current digit
```

```
% So each index of the previous arrays will contain one of these arrays,
forming a 50x10 matrix
```

```
curSampleSpectralMean = cell(50, 1);
```

```
curSampleSpectralFlux = cell(50, 1);
```

```
curSampleSpectralSpread = cell(50, 1);
```

```
curSampleSpectralPeaksMedian = cell(50, 1);
```

```
curSampleSpectralFlatness = cell(50, 1);
```

```
curSampleSpectralVariance = cell(50, 1);
```

```
% Iterate through every digit
```

```

for digit = 1:10
    % Iterate through every sample of the current digit
    for sample = 1:50
        % Calculate the diferent spectral features of the current sample of
the current digit
        curSampleSpectralMean{sample} = mean(everyAmpSpectrumMat{digit}(:,
sample), 1);
        curSampleSpectralFlux{sample} =
sum(abs(diff(everyAmpSpectrumMat{digit}(:, sample))), 1);
        curSampleSpectralSpread{sample} = std(everyAmpSpectrumMat{digit}(:,
sample), 1);
        curSampleSpectralPeaksMedian{sample} =
median(findpeaks(everyAmpSpectrumMat{digit}(:, sample)), 1);
        curSampleSpectralFlatness{sample} =
geomean(everyAmpSpectrumMat{digit}(:, sample)) /
mean(everyAmpSpectrumMat{digit}(:, sample));
        curSampleSpectralVariance{sample} = var(everyAmpSpectrumMat{digit}
(:, sample), 1);
    end
    % Store the spectral features of the current digit after iterating
through all the samples
    spectralMean{digit} = curSampleSpectralMean;
    spectralFlux{digit} = curSampleSpectralFlux;
    spectralSpread{digit} = curSampleSpectralSpread;
    spectralPeaksMedian{digit} = curSampleSpectralPeaksMedian;
    spectralFlatness{digit} = curSampleSpectralFlatness;
    spectralVariance{digit} = curSampleSpectralVariance;
end

% Store the 50x10 matrix of spectral features in an hashmap for easy access
spectralFeatures('Spectral Mean') = spectralMean;
spectralFeatures('Spectral Flux') = spectralFlux;
spectralFeatures('Spectral Spread') = spectralSpread;
spectralFeatures('Spectral Peaks Median') = spectralPeaksMedian;
spectralFeatures('Spectral Variance') = spectralVariance;
spectralFeatures('Spectral Flatness') = spectralFlatness;

spectralFeaturesStrings = {'Spectral Mean', 'Spectral Flux', 'Spectral
Spread', 'Spectral Peaks Median', 'Spectral Variance', 'Spectral Flatness'};


% Scatterplot every feature
figure;
annotation('textbox', [0 0.9 1 0.1], 'String', ['Extracted spectral
features'], 'EdgeColor', 'none', 'HorizontalAlignment', 'center',
'FontSize', 15);
for i = 1:6
    % Create a scatter plot
    subplot(2, 3, i);

```

```

scatterplotFeature(spectralFeatures(spectralFeaturesStrings{i}),
spectralFeaturesStrings{i}, strcat(spectralFeaturesStrings{i}, ' for Each
Digit'));
end

```



```

spectralBestFeaturesStrings = {'Spectral Peaks Median', 'Spectral Flux',
'Spectral Flatness'};
% Boxplot the 3 beast features
figure;
annotation('textbox', [0 0.9 1 0.1], 'String', ['Best spectral features
for digit differentiation'], 'EdgeColor', 'none', 'HorizontalAlignment',
'center', 'FontSize', 15);
for i = 1:3
    % Make a boxplot of the spectral mean of each digit
    subplot(1, 3, i);
    boxplotFeature(spectralFeatures(spectralBestFeaturesStrings{i}),
spectralBestFeaturesStrings{i}, strcat(spectralBestFeaturesStrings{i}, ' for
Each Digit'));
end

```

Best spectral features for digit differentiation

Spectral Peaks Median for Each Digit Spectral Flux for Each Digit Spectral Flatness for Each Digit

