
PROJ coordinate transformation software library

Release 5.0.1

PROJ contributors

May 26, 2018

CONTENTS

1	About	1
1.1	Citation	1
1.2	License	1
2	Download	3
2.1	Current Release	3
2.2	Past Releases	3
3	Installation	5
3.1	Installation from package management systems	5
3.1.1	Cross platform	5
3.1.2	Windows	5
3.1.3	Linux	6
3.1.4	Mac OS X	6
3.2	Compilation and installation from source code	7
3.2.1	Autotools	7
3.2.2	CMake	7
4	Using PROJ	9
4.1	Quick start	9
4.2	Cartographic projection	10
4.2.1	Units	10
4.2.2	False Easting/Northing	11
4.2.3	Longitude Wrapping	11
4.2.4	Prime Meridian	11
4.2.5	Axis orientation	12
4.3	Geodetic transformation	12
4.3.1	Transformation pipelines	13
4.3.2	cs2cs paradigm	14
4.3.3	Grid Based Datum Adjustments	15
4.4	Environment variables	17
4.5	Known differences between versions	17
4.5.1	Version 5.0.0	17
5	Applications	19
5.1	proj	19
5.1.1	Synopsis	19
5.1.2	Description	19
5.1.3	Example	21
5.2	cct	21

5.2.1	Synopsis	21
5.2.2	Description	21
5.2.3	Examples	22
5.2.4	Background	23
5.3	cs2cs	23
5.3.1	Synopsis	23
5.3.2	Description	23
5.3.3	Example	25
5.4	geod	25
5.4.1	Synopsis	25
5.4.2	Description	25
5.4.3	Examples	27
5.4.4	Further reading	27
5.5	gie	27
5.5.1	Synopsis	27
5.5.2	Description	27
5.5.3	Examples	28
5.5.4	gie command language	29
5.5.5	Background	31
6	Coordinate operations	33
6.1	Projections	33
6.1.1	Albers Equal Area	33
6.1.2	Azimuthal Equidistant	35
6.1.3	Airy	36
6.1.4	Aitoff	37
6.1.5	Modified Stererographics of Alaska	38
6.1.6	Apian Globular I	39
6.1.7	August Epicycloidal	41
6.1.8	Bacon Globular	41
6.1.9	Bipolar conic of western hemisphere	42
6.1.10	Boggs Eumorphic	42
6.1.11	Bonne (Werner lat_1=90)	43
6.1.12	Cal Coop Ocean Fish Invest Lines/Stations	43
6.1.13	Cassini (Cassini-Soldner)	45
6.1.14	Central Cylindrical	48
6.1.15	Central Conic	48
6.1.16	Equal Area Cylindrical	51
6.1.17	Chamberlin Trimetric	51
6.1.18	Collignon	52
6.1.19	Craster Parabolic (Putnins P4)	52
6.1.20	Denoyer Semi-Elliptical	53
6.1.21	Eckert I	53
6.1.22	Eckert II	54
6.1.23	Eckert III	54
6.1.24	Eckert IV	55
6.1.25	Eckert V	55
6.1.26	Eckert VI	56
6.1.27	Equidistant Cylindrical (Plate Carrée)	56
6.1.28	Equidistant Conic	59
6.1.29	Euler	59
6.1.30	Extended Transverse Mercator	60
6.1.31	Fahey	60
6.1.32	Foucaut	61

6.1.33	Foucaut Sinusoidal	61
6.1.34	Gall (Gall Stereographic)	62
6.1.35	Geostationary Satellite View	64
6.1.36	Ginsburg VIII (TsNIIGAiK)	66
6.1.37	General Sinusoidal Series	67
6.1.38	Gnomonic	67
6.1.39	Goode Homolosine	68
6.1.40	Mod. Stererographics of 48 U.S.	68
6.1.41	Mod. Stererographics of 50 U.S.	69
6.1.42	Hammer & Eckert-Greifendorff	69
6.1.43	Hatano Asymmetrical Equal Area	70
6.1.44	HEALPix	71
6.1.45	rHEALPix	73
6.1.46	Interrupted Goode Homolosine	75
6.1.47	International Map of the World Polyconic	76
6.1.48	Icosahedral Snyder Equal Area	76
6.1.49	Kavraisky V	77
6.1.50	Kavraisky VII	77
6.1.51	Krovak	78
6.1.52	Laborde	78
6.1.53	Lambert Azimuthal Equal Area	79
6.1.54	Lagrange	79
6.1.55	Larrivee	80
6.1.56	Laskowski	80
6.1.57	Lambert Conformal Conic	81
6.1.58	Lambert Conformal Conic Alternative	81
6.1.59	Lambert Equal Area Conic	82
6.1.60	Lee Oblated Stereographic	82
6.1.61	Loximuthal	83
6.1.62	Space oblique for LANDSAT	83
6.1.63	McBryde-Thomas Flat-Polar Sine (No. 1)	84
6.1.64	McBryde-Thomas Flat-Pole Sine (No. 2)	84
6.1.65	McBride-Thomas Flat-Polar Parabolic	85
6.1.66	McBryde-Thomas Flat-Polar Quartic	85
6.1.67	McBryde-Thomas Flat-Polar Sinusoidal	86
6.1.68	Mercator	86
6.1.69	Miller Oblated Stereographic	89
6.1.70	Miller Cylindrical	89
6.1.71	Mollweide	91
6.1.72	Murdoch I	92
6.1.73	Murdoch II	92
6.1.74	Murdoch III	93
6.1.75	Natural Earth	93
6.1.76	Nell	95
6.1.77	Nell-Hammer	95
6.1.78	Nicolosi Globular	96
6.1.79	Near-sided perspective	96
6.1.80	New Zealand Map Grid	97
6.1.81	General Oblique Transformation	98
6.1.82	Oblique Cylindrical Equal Area	98
6.1.83	Oblated Equal Area	99
6.1.84	Oblique Mercator	99
6.1.85	Ortelius Oval	100
6.1.86	Orthographic	100

6.1.87	Perspective Conic	101
6.1.88	Polyconic (American)	102
6.1.89	Putnins P1	102
6.1.90	Putnins P2	103
6.1.91	Putnins P3	103
6.1.92	Putnins P3'	104
6.1.93	Putnins P4'	104
6.1.94	Putnins P5	105
6.1.95	Putnins P5'	105
6.1.96	Putnins P6	106
6.1.97	Putnins P6'	106
6.1.98	Quartic Authalic	107
6.1.99	Quadrilateralized Spherical Cube	107
6.1.100	Robinson	111
6.1.101	Rousselhe Stereographic	111
6.1.102	Rectangular Polyconic	112
6.1.103	Sinusoidal (Sanson-Flamsteed)	112
6.1.104	Swiss. Obl. Mercator	113
6.1.105	Stereographic	113
6.1.106	Oblique Stereographic Alternative	114
6.1.107	Gauss-Schreiber Transverse Mercator (aka Gauss-Laborde Reunion)	114
6.1.108	Transverse Central Cylindrical	115
6.1.109	Transverse Cylindrical Equal Area	115
6.1.110	Tissot	116
6.1.111	Transverse Mercator	116
6.1.112	Two Point Equidistant	120
6.1.113	Tilted perspective	121
6.1.114	Universal Polar Stereographic	122
6.1.115	Urmaev V	123
6.1.116	Urmaev Flat-Polar Sinusoidal	123
6.1.117	Universal Transverse Mercator (UTM)	124
6.1.118	van der Grinten (I)	124
6.1.119	van der Grinten II	125
6.1.120	van der Grinten III	125
6.1.121	van der Grinten IV	126
6.1.122	Vitkovsky I	126
6.1.123	Wagner I (Kavraisky VI)	127
6.1.124	Wagner II	127
6.1.125	Wagner III	128
6.1.126	Wagner IV	128
6.1.127	Wagner V	129
6.1.128	Wagner VI	129
6.1.129	Wagner VII	130
6.1.130	Web Mercator / Pseudo Mercator	130
6.1.131	Werenskiold I	132
6.1.132	Winkel I	132
6.1.133	Winkel II	133
6.1.134	Winkel Tripel	133
6.2	Conversions	133
6.2.1	Axis swap	133
6.2.2	Cartesian to geodetic conversion	134
6.2.3	Lat/long (Geodetic alias)	135
6.2.4	Unit conversion	135
6.3	Transformations	137

6.3.1	Kinematic datum shifting utilizing a deformation model	137
6.3.2	Helmert transform	139
6.3.3	Molodensky transform	143
6.3.4	Horizontal grid shift	144
6.3.5	Vertical grid shift	146
6.4	The pipeline operator	148
6.4.1	Rules for pipelines	148
6.4.2	Parameters	149
7	Resource files	151
7.1	External resources	151
7.2	Transformation grids	151
7.2.1	Free grids	152
7.2.2	Non-Free Grids	152
7.2.3	HARN	153
7.2.4	HTDP	154
7.3	Init files	156
7.4	The defaults file	157
8	Geodesic calculations	159
8.1	Introduction	159
8.2	Solution of geodesic problems	159
8.3	Additional properties	159
8.4	Multiple shortest geodesics	160
8.5	Background	160
9	Development	163
9.1	Quick start	163
9.2	Transformations	165
9.3	Error handling	165
9.4	Threads	165
9.4.1	Key Thread Safety Issues	165
9.4.2	projCtx	165
9.4.3	src/multistresstest.c	166
9.5	Reference	166
9.5.1	Data types	166
9.5.2	Functions	175
9.5.3	Deprecated API	184
9.6	Using PROJ in CMake projects	188
9.7	Language bindings	189
9.7.1	Python	189
9.7.2	Ruby	189
9.7.3	TCL	189
9.7.4	MySQL	189
9.7.5	Excel	189
9.7.6	Visual Basic	189
9.8	Version 4 to 5 API Migration	189
9.8.1	Background	190
9.8.2	Code example	190
9.8.3	Function mapping from old to new API	192
10	Community	193
10.1	Communication channels	193
10.1.1	Mailing list	193
10.1.2	GitHub	193

10.2	Contributing	193
10.2.1	Help a fellow PROJ user	194
10.2.2	Adding bug reports	194
10.2.3	Feature requests	194
10.2.4	Write documentation	194
10.2.5	Code contributions	195
10.2.6	Additional Resources	195
10.2.7	Acknowledgements	196
10.3	Guidelines for PROJ code contributors	196
10.3.1	Code contributions.	196
10.3.2	Tools	197
11	FAQ	199
11.1	Where can I find the list of projections and their arguments?	199
11.2	How do I build/configure PROJ to support datum shifting?	199
11.3	How do I debug problems with NAD27/NAD83 datum shifting?	200
11.4	How do I use EPSG coordinate system codes with PROJ?	200
11.5	How do I use 3 parameter and 7 parameter datum shifting	201
11.6	Does PROJ work in different international numeric locales?	201
11.7	Changing Ellipsoid / Why can't I convert from WGS84 to Google Earth / Virtual Globe Mercator?	201
11.8	Why do I get different results with 4.5.0 and 4.6.0?	202
11.9	How do I calculate distances/directions on the surface of the earth?	202
11.10	What is the HEALPix projection and how can I use it?	202
11.11	What is the rHEALPix projection and how can I use it?	203
11.12	What options does PROJ allow for the shape of the Earth (geodesy)?	203
11.13	What if I want a spherical Earth?	204
11.14	How do I change the radius of the Earth? How do I use PROJ for work on Mars?	204
11.15	How do I do False Eastings and False Northings?	204
12	Glossary	205
Bibliography		207
Index		209

CHAPTER ONE

ABOUT

PROJ is a generic coordinate transformation software, that transforms geospatial coordinates from one coordinate reference system (CRS) to another. This includes cartographic projections as well as geodetic transformations.

PROJ includes *command line applications* for easy conversion of coordinates from text files or directly from user input. In addition to the command line utilities PROJ also exposes an *application programming interface*, or API in short. The API let developers use the functionality of PROJ in their own software without having to implement similar functionality themselves.

PROJ started purely as a cartography application letting users convert geodetic coordinates into projected coordinates using a number of different cartographic projections. Over the years, as the need has become apparent, support for datum shifts has slowly worked it's way into PROJ as well. Today PROJ support more than a hundred different map projections and can transform coordinates between datums using all but the most obscure geodetic techniques.

1.1 Citation

To cite PROJ in publications use:

PROJ contributors (2018). PROJ coordinate transformation software library. Open Source Geospatial Foundation. URL <http://proj4.org/>.

A BibTeX entry for LaTeX users is

```
@Manual{,  
    title = {{PROJ} coordinate transformation software library},  
    author = {{PROJ contributors}},  
    organization = {Open Source Geospatial Foundation},  
    year = {2018},  
    url = {http://proj4.org/},  
}
```

1.2 License

PROJ uses the MIT license. The software was initially released by the USGS in the public domain. When Frank Warmerdam took over the development of PROJ it was moved under the MIT license. The license is as follows:

Copyright (c) 2000, Frank Warmerdam

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the

Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

DOWNLOAD

Here you can download current and previous releases of PROJ. We only supply a distribution of the source code and various resource files archives. See [Installation](#) for information on how to get pre-built packages of PROJ.

2.1 Current Release

- [2018-04-01](#) proj-5.0.1.tar.gz (md5)
- [2018-03-01](#) proj-datumgrid-1.7.zip
- [2018-03-01](#) proj-datumgrid-europe-1.0.zip
- [2018-03-01](#) proj-datumgrid-north-america-1.0.zip
- [2018-03-01](#) proj-datumgrid-oceania-1.0.zip
- **PDF Manual** proj.pdf

2.2 Past Releases

- [2018-03-01](#) proj-5.0.0.tar.gz
- [2016-09-02](#) proj-4.9.3.tar.gz
- [2015-09-13](#) proj-4.9.2.tar.gz
- [2015-03-04](#) proj-4.9.1.tar.gz
- [2016-09-11](#) proj-datumgrid-1.6.zip

INSTALLATION

These pages describe how to install PROJ on your computer without compiling it yourself. Below are guides for installing on Windows, Linux and Mac OS X. This is a good place to get started if this is your first time using PROJ. More advanced users may want to compile the software themselves.

3.1 Installation from package management systems

3.1.1 Cross platform

PROJ is also available via cross platform package managers.

Conda

The conda package manager includes several PROJ packages. We recommend installing from the `conda-forge` channel:

```
conda install -c conda-forge proj4
```

Docker

A Docker image with just PROJ binaries and a full compliment of grid shift files is available on DockerHub. Get the package with:

```
docker pull osgeo/proj.4
```

3.1.2 Windows

The simplest way to install PROJ on Windows is to use the [OSGeo4W](#) software distribution. OSGeo4W provides easy access to many popular open source geospatial software packages. After installation you can use PROJ from the OSGeo4W shell. To install PROJ do the following:

Note: If you have already installed software via OSGeo4W on your computer it is likely that PROJ is already installed.

1. Download either the [32 bit](#) or [64 bit](#) installer.
2. Run the OSGeo4W setup program.

3. Select “Advanced Install” and press Next.
4. Select “Install from Internet” and press Next.
5. Select a installation directory. The default suggestion is fine in most cases. Press Next.
6. Select “Local packacke directory”. The suggestions is fine in most cases. Press Next.
7. Select “Direct connection” and press Next.
8. Choose the download.osgeo.org and press Next.
9. Find “proj” under “Commandline_Utilitys” and click the package in the “New” column until the version you want to install appears.
10. Press next to install PROJ.

You should now have a “OSGeo” menu in your start menu. Within that menu you can find the “OSGeo4W Shell” where you have access to all the OSGeo4W applications, including proj.

For those who are more inclined to the command line, steps 2–10 above can be accomplished by executing the following command:

```
C:\temp\osgeo4w-setup-x86-64.exe -q -k -r -A -s http://download.osgeo.org/osgeo4w/ -a_x86_64 -P proj
```

3.1.3 Linux

How to install PROJ on Linux depends on which distribution you are using. Below is a few examples for some of the more common Linux distributions:

Debian

On Debian and similar systems (e.g. Ubuntu) the APT package manager is used:

```
sudo apt-get install proj-bin
```

Red Hat

On Red Hat based system packages are installed with yum:

```
sudo yum install proj
```

3.1.4 Mac OS X

On OS X PROJ can be installed via the Homebrew package manager:

```
brew install proj
```

PROJ is also available from the MacPorts system:

```
sudo ports install proj
```

3.2 Compilation and installation from source code

The classical way of installing PROJ is via the source code distribution. The most recent version is available from the [download page](#). You will need that and at least the standard *proj-datumgrid* package for a successful installation. The following guides show how to compile and install the software using the Autotools and CMake build systems.

3.2.1 Autotools

FSF's configuration procedure is used to ease installation of the PROJ system.

Note: The Autotools build system is only available on UNIX-like systems. Follow the CMake installation guide if you are not using a UNIX-like operating system.

The default destination path prefix for installed files is `/usr/local`. Results from the installation script will be placed into subdirectories `bin`, `include`, `lib`, `man/man1` and `man/man3`. If this default path prefix is proper, then execute:

```
./configure
```

If another path prefix is required, then execute:

```
./configure --prefix=/my/path
```

In either case, the directory of the prefix path must exist and be writable by the installer.

Before proceeding with the installation we need to add the datum grids. Unzip the contents of the *proj-datumgrid* package into `nad/`:

```
unzip proj-datumgrid-1.7.zip -d proj-5.0.1/nad/
```

The installation will automatically move the grid files to the correct location. Alternatively the grids can be installed manually in the directory pointed to by the `PROJ_LIB` environment variable. The default location is `/usr/local/share/proj`.

With the grid files in place we can now build and install PROJ:

```
make  
make install
```

The install target will create, if necessary, all required sub-directories.

Tests are run with:

```
make check
```

The test suite requires that the *proj-datumgrid* package is installed in `PROJ_LIB`.

3.2.2 CMake

With the CMake build system you can compile and install PROJ on more or less any platform. After unpacking the source distribution archive step into the source- tree:

```
cd proj-5.0.1
```

Create a build directory and step into it:

```
mkdir build  
cd build
```

From the build directory you can now configure CMake and build the binaries:

```
cmake ..  
cmake --build .
```

On Windows, one may need to specify generator:

```
cmake -G "Visual Studio 15 2017" ..
```

Tests are run with:

```
ctest
```

The test suite requires that the proj-datumgrid package is installed in *PROJ_LIB*.

CHAPTER FOUR

USING PROJ

The main purpose of PROJ is to transform coordinates from one coordinate reference system to another. This can be achieved either with the included command line applications or the C API that is a part of the software package.

4.1 Quick start

Coordinate transformations are defined by, what in PROJ terminology is known as, “proj-strings”. A proj-string describes any transformation regardless of how simple or complicated it might be. The simplest case is projection of geodetic coordinates. This section focuses on the simpler cases and introduces the basic anatomy of the proj-string. The complex cases are discussed in *Geodetic transformation*.

A proj-strings holds the parameters of a given coordinate transformation, e.g.

```
+proj=merc +lat_ts=56.5 +ellps=GRS80
```

I.e. a proj-string consists of a projection specifier, `+proj`, a number of parameters that applies to the projection and, if needed, a description of a datum shift. In the example above geodetic coordinates are transformed to projected space with the *Mercator projection* with the latitude of true scale at 56.5 degrees north on the GRS80 ellipsoid. Every projection in PROJ is identified by a shorthand such as `merc` in the above example.

By using the above projection definition as parameters for the command line utility `proj` we can convert the geodetic coordinates to projected space:

```
$ proj +proj=merc +lat_ts=56.5 +ellps=GRS80
```

If called as above `proj` will be in interactive mode, letting you type the input data manually and getting a response presented on screen. `proj` works as any UNIX filter though, which means that you can also pipe data to the utility, for instance by using the `echo` command:

```
$ echo 55.2 12.2 | proj +proj=merc +lat_ts=56.5 +ellps=GRS80
3399483.80      752085.60
```

PROJ also comes bundled with the `cs2cs` utility which is used to transform from one coordinate reference system to another. Say we want to convert the above Mercator coordinates to UTM, we can do that with `cs2cs`:

```
$ echo 3399483.80 752085.60 | cs2cs +proj=merc +lat_ts=56.5 +ellps=GRS80 +to_
+proj=utm +zone=32
6103992.36      1924052.47 0.00
```

Notice the `+to` parameter that separates the source and destination projection definitions.

If you happen to know the EPSG identifiers for the two coordinates reference systems you are transforming between you can use those with `cs2cs`:

```
$ echo 56 12 | cs2cs +init=epsg:4326 +to +init=epsg:25832  
231950.54      1920310.71 0.00
```

In the above example we transform geodetic coordinates in the WGS84 reference frame to UTM zone 32N coordinates in the ETRS89 reference frame. UTM coordinates

4.2 Cartographic projection

The foundation of PROJ is the large number of *projections* available in the library. This section is devoted to the generic parameters that can be used on any projection in the PROJ library.

Below is a list of PROJ parameters which can be applied to most coordinate system definitions. This table does not attempt to describe the parameters particular to particular projection types. These can be found on the pages documenting the individual *projections*.

Parameter	Description
+a	Semimajor radius of the ellipsoid axis
+axis	Axis orientation
+b	Seminor radius of the ellipsoid axis
+ellps	Ellipsoid name (see <code>proj -le</code>)
+k	Scaling factor (deprecated)
+k_0	Scaling factor
+lat_0	Latitude of origin
+lon_0	Central meridian
+lon_wrap	Center longitude to use for wrapping (see below)
+no_defs	Don't use the /usr/share/proj/proj_def.dat defaults file
+over	Allow longitude output outside -180 to 180 range, disables wrapping (see below)
+pm	Alternate prime meridian (typically a city name, see below)
+proj	Projection name (see <code>proj -l</code>)
+units	meters, US survey feet, etc.
+vunits	vertical units.
+x_0	False easting
+y_0	False northing

In the sections below most of the parameters are explained in details.

4.2.1 Units

Horizontal units can be specified using the `+units` keyword with a symbolic name for a unit (ie. `us-ft`). Alternatively the translation to meters can be specified with the `+to_meter` keyword (ie. `0.304800609601219` for US feet). The `-lu` argument to `cs2cs` or `proj` can be used to list symbolic unit names. The default unit for projected coordinates is the meter. A few special projections deviate from this behaviour, most notably the latlong pseudo-projection that returns degrees.

Vertical (Z) units can be specified using the `+vunits` keyword with a symbolic name for a unit (ie. `us-ft`). Alternatively the translation to meters can be specified with the `+vto_meter` keyword (ie. `0.304800609601219` for US feet). The `-lu` argument to `cs2cs` or `proj` can be used to list symbolic unit names. If no vertical units are specified, the vertical units will default to be the same as the horizontal coordinates.

Note: `proj` do not handle vertical units at all and hence the `+vto_meter` argument will be ignored.

Scaling of output units can be done by applying the `+k_0` argument. The returned coordinates are scaled by the value assigned with the `+k_0` parameter.

4.2.2 False Easting/Northing

Virtually all coordinate systems allow for the presence of a false easting (`+x_0`) and northing (`+y_0`). Note that these values are always expressed in meters even if the coordinate system is some other units. Some coordinate systems (such as UTM) have implicit false easting and northing values.

4.2.3 Longitude Wrapping

By default PROJ wraps output longitudes in the range -180 to 180. The `+over` switch can be used to disable the default wrapping which is done at a low level in `pj_inv()`. This is particularly useful with projections like the *equidistant cylindrical* where it would be desirable for X values past -20000000 (roughly) to continue past -180 instead of wrapping to +180.

The `+lon_wrap` option can be used to provide an alternative means of doing longitude wrapping within `pj_transform()`. The argument to this option is a center longitude. So `+lon_wrap=180` means wrap longitudes in the range 0 to 360. Note that `+over` does **not** disable `+lon_wrap`.

4.2.4 Prime Meridian

A prime meridian may be declared indicating the offset between the prime meridian of the declared coordinate system and that of greenwich. A prime meridian is declared using the “pm” parameter, and may be assigned a symbolic name, or the longitude of the alternative prime meridian relative to greenwich.

Currently prime meridian declarations are only utilized by the `pj_transform()` API call, not the `pj_inv()` and `pj_fwd()` calls. Consequently the user utility `cs2cs` does honour prime meridians but the `proj` user utility ignores them.

The following predeclared prime meridian names are supported. These can be listed using with `cs2cs -lm`.

Meridian	Longitude
greenwich	0dE
lisbon	9d07'54.862"W
paris	2d20'14.025"E
bogota	74d04'51.3"E
madrid	3d41'16.48"W
rome	12d27'8.4"E
bern	7d26'22.5"E
jakarta	106d48'27.79"E
ferro	17d40'W
brussels	4d22'4.71"E
stockholm	18d3'29.8"E
athens	23d42'58.815"E
oslo	10d43'22.5"E

Example of use. The location `long=0, lat=0` in the greenwich based lat/long coordinates is translated to lat/long coordinates with Madrid as the prime meridian.

```
cs2cs +proj=latlong +datum=WGS84 +to +proj=latlong +datum=WGS84 +pm=madrid
0 0
3d41'16.48"E    0dN 0.000
```

4.2.5 Axis orientation

Starting in PROJ 4.8.0, the `+axis` argument can be used to control the axis orientation of the coordinate system. The default orientation is “easting, northing, up” but directions can be flipped, or axes flipped using combinations of the axes in the `+axis` switch. The values are:

- “e” - Easting
- “w” - Westing
- “n” - Northing
- “s” - Southing
- “u” - Up
- “d” - Down

They can be combined in `+axis` in forms like:

- `+axis=enu` - the default easting, northing, elevation.
- `+axis=neu` - northing, easting, up - useful for “lat/long” geographic coordinates, or south orientated transverse mercator.
- `+axis=wnu` - westing, northing, up - some planetary coordinate systems have “west positive” coordinate systems

Note: The `+axis` argument does not work with the `proj` command line utility.

4.3 Geodetic transformation

PROJ can do everything from the most simple projection to very complex transformations across many reference frames. While originally developed as a tool for cartographic projections, PROJ has over time evolved into a powerful generic coordinate transformation engine that makes it possible to do both large scale cartographic projections as well as coordinate transformation at a geodetic high precision level. This chapter delves into the details of how geodetic transformations of varying complexity can be performed.

In PROJ, two frameworks for geodetic transformations exists, the `cs2cs` framework and the *transformation pipelines* framework. The first is the original, and limited, framework for doing geodetic transforms in PROJ. The latter is a newer addition that aims to be a more complete transformation framework. Both are described in the sections below. Large portions of the text are based on [\[EversKnudsen2017\]](#).

Before describing the details of the two frameworks, let us first remark that most cases of geodetic transformations can be expressed as a series of elementary operations, the output of one operation being the input of the next. E.g. when going from UTM zone 32, datum ED50, to UTM zone 32, datum ETRS89, one must, in the simplest case, go through 5 steps:

1. Back-project the UTM coordinates to geographic coordinates
2. Convert the geographic coordinates to 3D cartesian geocentric coordinates
3. Apply a Helmert transformation from ED50 to ETRS89

4. Convert back from cartesian to geographic coordinates
5. Finally project the geographic coordinates to UTM zone 32 planar coordinates.

4.3.1 Transformation pipelines

The homology between the above steps and a Unix shell style pipeline is evident. It is there the main architectural inspiration behind the transformation pipeline framework. The pipeline framework is realized by utilizing a special “projection”, that takes as its user supplied arguments, a series of elementary operations, which it strings together in order to implement the full transformation needed. Additionally, a number of elementary geodetic operations, including Helmert transformations, general high order polynomial shifts and the Molodensky transformation are available as part of the pipeline framework. In anticipation of upcoming support for full time-varying transformations, we also introduce a 4D spatiotemporal data type, and a programming interface (API) for handling this.

The Molodensky transformation converts directly from geodetic coordinates in one datum, to geodetic coordinates in another datum, while the (typically more accurate) Helmert transformation converts from 3D cartesian to 3D cartesian coordinates. So when using the Helmert transformation one typically needs to do an initial conversion from geodetic to cartesian coordinates, and a final conversion the other way round, to arrive at the desired result. Fortunately, this three-step compound transformation has the attractive characteristic that each step depends only on the output of the immediately preceding step. Hence, we can build a geodetic-to-geodetic Helmert transformation by tying together the outputs and inputs of 3 steps (geodetic-to-cartesian → Helmert → cartesian-to-geodetic), pipeline style. The pipeline driver, makes this kind of chained transformations possible. The implementation is compact, consisting of just one pseudo-projection, called `pipeline`, which takes as its arguments strings of elementary projections (note: “projection” is the, slightly misleading, PROJ term used for any kind of transformation). The pipeline pseudo projection is supplemented by a number of elementary transformations, all in all providing a framework for building high accuracy solutions for a wide spectrum of geodetic tasks.

As a first example, let us take a look at the iconic *geodetic* → *Cartesian* → *Helmert* → *geodetic* case (steps 2 to 4 in the example in the introduction). In PROJ it can be implemented as

```
proj=pipeline
step proj=cart ellps=intl
step proj=helmert
    x=-81.0703  y=-89.3603  z=-115.7526
    rx=-0.48488 ry=-0.02436 rz=-0.41321  s=-0.540645
step proj=cart inv ellps=GRS80
```

The pipeline can be expanded at both ends to accommodate whatever coordinate type is needed for input and output: In the example below, we transform from the deprecated Danish System 45, a 2D system with some tension in the original defining network, to UTM zone 33, ETRS89. The tension is reduced using a polynomial transformation (the `init=./s45b...` step, `s45b.pol` is a file containing the polynomial coefficients), taking the S45 coordinates to a technical coordinate system (TC32), defined to represent “UTM zone 32 coordinates, as they would look if the Helmert transformation between ED50 and ETRS89 was perfect”. The TC32 coordinates are then converted back to geodetic(ED50) coordinates, using an inverse UTM projection, further to cartesian(ED50), then to cartesian(ETRS89), using the relevant Helmert transformation, and back to geodetic(ETRS89), before finally being projected onto the UTM zone 33, ETRS89 system. All in all a 6 step pipeline, implementing a transformation with centimeter level accuracy from a deprecated system with decimeter level tensions.

```
proj=pipeline
step init=./s45b.pol:s45b_tc32
step proj=utm inv ellps=intl zone=32
step proj=cart ellps=intl
step proj=helmert
    x=-81.0703  y=-89.3603  z=-115.7526
    rx=-0.48488 ry=-0.02436 rz=-0.41321  s=-0.540645
```

(continues on next page)

(continued from previous page)

```
step proj=cart inv ellps=GRS80
step proj=utm ellps=GRS80 zone=33
```

With the pipeline framework spatiotemporal transformation is possible. This is possible by leveraging the time dimension in PROJ that enables 4D coordinates (three spatial components and one temporal component) to be passed through a transformation pipeline. In the example below a transformation from ITRF93 to ITRF2000 is defined. The temporal component is given as GPS weeks in the input data, but the 14-parameter Helmert transform expects temporal units in decimalyears. Hence the first step in the pipeline is the unitconvert pseudo-projection that makes sure the correct units are passed along to the Helmert transform. Most parameters of the Helmert transform are taken from [AltamimiEtAl2002], except the epoch which is the epoch of the transformation. The default setting is to use “coordinate frame” convention of the Helmert transform, but “position vector” convention can also be used. The last step in the pipeline is converting the coordinate timestamps back to GPS weeks.

```
proj=pipeline
step proj=unitconvert t_in=gps_week t_out=decimalyear
step proj=helmert
    x=0.0127 y=0.0065 z=-0.0209 s=0.00195
    rx=0.00039 ry=-0.00080 rz=0.00114
    dx=-0.0029 dy=-0.0002 dz=-0.0006 ds=0.00001
    drx=0.00011 dry=0.00019 drz=-0.00007
    t_epoch=1988.0
step proj=unitconvert t_in=decimalyear t_out=gps_week
```

4.3.2 cs2cs paradigm

Parameter	Description
+datum	Datum name (see <code>proj -ld</code>)
+geoidgrids	Filename of GTX grid file to use for vertical datum transforms
+nadgrids	Filename of NTV2 grid file to use for datum transforms
+towgs84	3 or 7 term datum transform parameters
+to_meter	Multiplier to convert map units to 1.0m
+vto_meter	Vertical conversion to meters

The *cs2cs* framework delivers a subset of the geodetic transformations available with the *pipeline* framework. Coordinate transformations done in this framework are transformed in a two-step process with WGS84 as a pivot datum. That is, the input coordinates are transformed to WGS84 geodetic coordinates and then transformed from WGS84 coordinates to the specified output coordinate reference system, by utilizing either the Helmert transform, datum shift grids or a combination of both. Datum shifts can be described in a proj-string with the parameters `+towgs84`, `+nadgrids` and `+geoidgrids`. An inverse transform exists for all three and is applied if specified in the input proj-string. The most common is `+towgs84`, which is used to define a 3- or 7-parameter Helmert shift from the input reference frame to WGS84. Exactly which realization of WGS84 is not specified, hence a fair amount of uncertainty is introduced in this step of the transformation. With the `+nadgrids` parameter a non-linear planar correction derived from interpolation in a correction grid can be applied. Originally this was implemented as a means to transform coordinates between the North American datums NAD27 and NAD83, but corrections can be applied for any datum for which a correction grid exists. The inverse transform for the horizontal grid shift is “dumb”, in the sense that the correction grid is applied verbatim without taking into account that the inverse operation is non-linear. Similar to the horizontal grid correction, `+geoidgrids` can be used to perform grid corrections in the vertical component. Both grid correction methods allow inclusion of more than one grid in the same transformation.

In contrast to the *transformation pipeline* framework, transformations with the *cs2cs* framework are expressed as two separate proj-strings. One proj-string *to* WGS84 and one *from* WGS84. Together they form the mapping from the

source coordinate reference system to the destination coordinate reference system. When used with the `cs2cs` the source and destination CRS's are separated by the special `+to` parameter.

The following example demonstrates converting from the Greek GGRS87 datum to WGS84 with the `+towgs84` parameter.

```
cs2cs +proj=latlong +ellps=GRS80 +towgs84=-199.87,74.79,246.62
      +to +proj=latlong +datum=WGS84
20 35
20d0'5.467"E    35d0'9.575"N 8.570
```

The EPSG database provides this example for transforming from WGS72 to WGS84 using an approximated 7 parameter transformation.

```
cs2cs +proj=latlong +ellps=WGS72 +towgs84=0,0,4.5,0,0,0.554,0.219 \
      +to +proj=latlong +datum=WGS84
4 55
4d0'0.554"E      55d0'0.09"N 3.223
```

4.3.3 Grid Based Datum Adjustments

In many places (notably North America and Australia) national geodetic organizations provide grid shift files for converting between different datums, such as NAD27 to NAD83. These grid shift files include a shift to be applied at each grid location. Actually grid shifts are normally computed based on an interpolation between the containing four grid points.

PROJ supports use of grid files for shifting between various reference frames. The grid shift table formats are ctble (the binary format produced by the PROJ `nad2bin` program), NTv1 (the old Canadian format), and NTv2 (.gsb - the new Canadian and Australian format).

The text in this section is based on the `cs2cs` framework. Gridshifting is off course also possible with the *pipeline* framework. The major difference between the two is that the `cs2cs` framework is limited to grid mappings to WGS84, whereas with *transformation pipelines* it is possible to perform grid shifts between any two reference frames, as long as a grid exists.

Use of grid shifts with `cs2cs` is specified using the `+nadgrids` keyword in a coordinate system definition. For example:

```
% cs2cs +proj=latlong +ellps=clrk66 +nadgrids=ntv1_can.dat \
      +to +proj=latlong +ellps=GRS80 +datum=NAD83 << EOF
-111 50
EOF
111d0'2.952"W   50d0'0.111"N 0.000
```

In this case the `/usr/local/share/proj/ntv1_can.dat` grid shift file was loaded, and used to get a grid shift value for the selected point.

It is possible to list multiple grid shift files, in which case each will be tried in turn till one is found that contains the point being transformed.

```
cs2cs +proj=latlong +ellps=clrk66 \
      +nadgrids=conus,alaska,hawaii,stgeorge,stlrnc,stpaul \
      +to +proj=latlong +ellps=GRS80 +datum=NAD83 << EOF
-111 44
EOF
111d0'2.788"W   43d59'59.725"N 0.000
```

Skipping Missing Grids

The special prefix @ may be prefixed to a grid to make it optional. If it not found, the search will continue to the next grid. Normally any grid not found will cause an error. For instance, the following would use the `ntv2_0.gsb` file if available (see [Non-Free Grids](#)), otherwise it would fallback to using the `ntv1_can.dat` file.

```
cs2cs +proj=latlong +ellps=clrk66 +nadgrids=@ntv2_0.gsb,ntv1_can.dat \
+to +proj=latlong +ellps=GRS80 +datum=NAD83 << EOF
-111 50
EOF
111d0'3.006"W 50d0'0.103"N 0.000
```

The null Grid

A special `null` grid shift file is shift with releases after 4.4.6 (not inclusive). This file provides a zero shift for the whole world. It may be listed at the end of a `nadgrids` file list if you want a zero shift to be applied to points outside the valid region of all the other grids. Normally if no grid is found that contains the point to be transformed an error will occur.

```
cs2cs +proj=latlong +ellps=clrk66 +nadgrids=conus,null \
+to +proj=latlong +ellps=GRS80 +datum=NAD83 << EOF
-111 45
EOF
111d0'3.006"W 50d0'0.103"N 0.000

cs2cs +proj=latlong +ellps=clrk66 +nadgrids=conus,null \
+to +proj=latlong +ellps=GRS80 +datum=NAD83 << EOF
-111 44
-111 55
EOF
111d0'2.788"W 43d59'59.725"N 0.000
111dW 55dN 0.000
```

For more information see the chapter on [Transformation grids](#).

Caveats

- Where grids overlap (such as `conus` and `ntv1_can.dat` for instance) the first found for a point will be used regardless of whether it is appropriate or not. So, for instance, `+nadgrids=ntv1_can.dat,conus` would result in the Canadian data being used for some areas in the northern United States even though the `conus` data is the approved data to use for the area. Careful selection of files and file order is necessary. In some cases border spanning datasets may need to be pre-segmented into Canadian and American points so they can be properly grid shifted
- There are additional grids for shifting between NAD83 and various HPGN versions of the NAD83 datum. Use of these haven't been tried recently so you may encounter problems. The `FL.lla`, `WO.lla`, `MD.lla`, `TN.lla` and `WI.lla` are examples of high precision grid shifts. Take care!
- Additional detail on the grid shift being applied can be found by setting the `PROJ_DEBUG` environment variable to a value. This will result in output to `stderr` on what grid is used to shift points, the bounds of the various grids loaded and so forth
- The `cs2cs` framework always assumes that grids contain a shift to NAD83 (essentially WGS84). Other types of grids can be used with the `pipeline` framework.

4.4 Environment variables

PROJ can be controlled by setting environment variables. Most users will have a use for the [PROJ_LIB](#).

On UNIX systems environment variables can be set for a shell-session with:

```
$ export VAR="some variable"
```

or it can be set for just one command line call:

```
$ VAR="some variable" ./cmd
```

Environment variables on UNIX are usually removed with the `unset` command:

```
$ unset VAR
```

On windows systems environment variables can be set in the command line with:

```
> set VAR="some variable"
```

`VAR will be available for the entire session, unless it is unset. This is done by setting the variable with no content:

```
> set VAR=
```

PROJ_LIB

The location of PROJ [resource files](#). It is only possible to specify a single library in [PROJ_LIB](#); e.g. it does not behave like PATH. PROJ is hardcoded to look for resource files in other locations as well, amongst those are the users home directory, `/usr/share/proj` and the current folder.

PROJ_DEBUG

Set the debug level of PROJ. The default debug level is zero, which results in no debug output when using PROJ. A number from 1-3, with 3 being the most verbose setting.

4.5 Known differences between versions

Once in a while, a new version of PROJ causes changes in the existing behaviour. In this section we track deliberate changes to PROJ that break from previous behaviour. Most times that will be caused by a bug fix. Unfortunately, some bugs have existed for so long that their faulty behaviour is relied upon by software that uses PROJ.

Behavioural changes caused by new bugs are not tracked here, as they should be fixed in later versions of PROJ.

4.5.1 Version 5.0.0

Longitude wrapping when using custom central meridian

By default PROJ wraps output longitudes in the range -180 to 180. Previous to PROJ 5, this was handled incorrectly when a custom central meridian was set with `+lon`. This caused a change in sign on the resulting easting as seen below:

```
$ proj +proj=merc +lon_0=110
-70 0
-20037508.34    0.00
290 0
20037508.34    0.00
```

From PROJ 5 on onwards, the same input now results in same coordinates, as seen from the example below where PROJ 5 is used:

```
$ proj +proj=merc +lon_0=110  
-70 0  
-20037508.34 0.00  
290 0  
-20037508.34 0.00
```

The change is made on the basis that $\lambda = 290^\circ$ is a full rotation of the circle larger than $\lambda = -70^\circ$ and hence should return the same output for both.

Adding the `+over` flag to the projection definition provides the old behaviour.

APPLICATIONS

Bundled with PROJ comes a set of small command line utilities. The `proj` program is limited to converting between geographic and projection coordinates within one datum. The `cs2cs` program operates similarly, but allows translation between any pair of definable coordinate systems, including support for basic datum translation. The `geod` program provides the ability to do geodesic (great circle) computations. `gief` is the program used for regression tests in PROJ.

5.1 proj

5.1.1 Synopsis

```
proj [ -beEfIImorsStTvVwW ] [ args ] [ +args ] file[s]  
invproj [ -beEfIImorsStTvVwW ] [ args ] [ +args ] file[s]
```

5.1.2 Description

`proj` and `invproj` perform respective forward and inverse transformation of cartographic data to or from cartesian data with a wide range of selectable projection functions.

`invproj` may not be available on all platforms; in this case use `proj -I` instead.

The following control parameters can appear in any order

-b

Special option for binary coordinate data input and output through standard input and standard output. Data is assumed to be in system type double floating point words. This option is to be used when `proj` is a child process and allows bypassing formatting operations.

-i

Selects binary input only (see `-b`).

-I

Alternate method to specify inverse projection. Redundant when used with `invproj`.

-o

Selects binary output only (see `-b`).

-t<a>

Where *a* specifies a character employed as the first character to denote a control line to be passed through without processing. This option applicable to ASCII input only. (# is the default value).

-e <string>

Where *string* is an arbitrary string to be output if an error is detected during data transformations. The default value is a three character string: * \t *. Note that if the [-b](#), [-i](#) or [-o](#) options are employed, an error is returned as `HUGE_VAL` value for both return values.

-E

Causes the input coordinates to be copied to the output line prior to printing the converted values.

-l<[=id]>

List projection identifiers that can be selected with `+proj`. `proj -l=id` gives expanded description of projection *id*, e.g. `proj -l=merc`.

-lp

List of all projection id that can be used with the `+proj` parameter. Equivalent to `proj -l`.

-lp

Expanded description of all projections that can be used with the `+proj` parameter.

-le

List of all ellipsoids that can be selected with the `+ellps` parameters.

-lu

List of all distance units that can be selected with the `+units` parameter.

-ld

List of datums that can be selected with the `+datum` parameter.

-r

This options reverses the order of the expected input from longitude-latitude or x-y to latitude-longitude or y-x.

-s

This options reverses the order of the output from x-y or longitude-latitude to y-x or latitude-longitude.

-s

Causes estimation of meridional and parallel scale factors, area scale factor and angular distortion, and maximum and minimum scale factors to be listed between `<>` for each input point. For conformal projections meridional and parallel scales factors will be equal and angular distortion zero. Equal area projections will have an area factor of 1.

-m <mult>

The cartesian data may be scaled by the *mult* parameter. When processing data in a forward projection mode the cartesian output values are multiplied by *mult* otherwise the input cartesian values are divided by *mult* before inverse projection. If the first two characters of *mult* are 1/ or 1: then the reciprocal value of *mult* is employed.

-f <format>

Where *format* is a printf format string to control the form of the output values. For inverse projections, the output will be in degrees when this option is employed. The default format is "% .2f" for forward projection and DMS for inverse.

-w<n>

Where *n* is the number of significant fractional digits to employ for seconds output (when the option is not specified, -w3 is assumed).

-W<n>

Where *n* is the number of significant fractional digits to employ for seconds output. When -W is employed the fields will be constant width with leading zeroes.

-v

Causes a listing of cartographic control parameters tested for and used by the program to be printed prior to input data. Should not be used with the [-T](#) option.

-v

This option causes an expanded annotated listing of the characteristics of the projected point. `-v` is implied with this option.

-T <ulow,uh,i,vlow,vhi,res[,umax,vmax]>

This option creates a set of bivariate Chebyshev polynomial coefficients that approximate the selected cartographic projection on stdout. The values *low* and *hi* denote the range of the input where the *u* or *v* prefixes apply to respective longitude-x or latitude-y depending upon whether a forward or inverse projection is selected. The integer *res* is a number specifying the power of 10 precision of the approximation. For example, a *res* of -3 specifies an approximation with an accuracy better than 0.001. Optional *umax*, and *vmax* specify maximum degree of the polynomials (default: 15).

The `+args` run-line arguments are associated with cartographic parameters. Additional projection control parameters may be contained in two auxiliary control files: the first is optionally referenced with the `+init=file:id` and the second is always processed after the name of the projection has been established from either the run-line or the contents of `+init` file. The environment parameter `PROJ_LIB` establishes the default directory for a file reference without an absolute path. This is also used for supporting files like datum shift files.

One or more files (processed in left to right order) specify the source of data to be transformed. A `-` will specify the location of processing standard input. If no files are specified, the input is assumed to be from stdin. For ASCII input data the two data values must be in the first two white space separated fields and when both input and output are ASCII all trailing portions of the input line are appended to the output line.

Input geographic data (longitude and latitude) must be in DMS format and input cartesian data must be in units consistent with the ellipsoid major axis or sphere radius units. Output geographic coordinates will be in DMS (if the `-w` switch is not employed) and precise to 0.001" with trailing, zero-valued minute-second fields deleted.

5.1.3 Example

The following script

```
proj +proj=utm +lon_0=112w +ellps=clrk66 -r <<EOF
45d15'33.1" 111.5W
45d15.551666667N -111d30
+45.25919444444 111d30'000w
EOF
```

will perform UTM forward projection with a standard UTM central meridian nearest longitude 112W. The geographic values of this example are equivalent and meant as examples of various forms of DMS input. The x-y output data will appear as three lines of:

460769.27	5011648.45
-----------	------------

5.2 cct

5.2.1 Synopsis

`cct [-cIostvz [args]] +opts[=arg] file[s]`

5.2.2 Description

`cct` a 4D equivalent to the `proj` projection program, performs transformation coordinate systems on a set of input points. The coordinate system transformation can include translation between projected and geographic coordinates

as well as the application of datum shifts.

The following control parameters can appear in any order:

-c <x,y,z,t>

Specify input columns for (up to) 4 input parameters. Defaults to 1,2,3,4.

-I

Do the inverse transformation.

-o <output file name>, --output=<output file name>

Specify the name of the output file.

-t <time>, --time=<time>

Specify a fixed observation *time* to be used for all input data.

-z <height>, --height=<height>

Specify a fixed observation *height* to be used for all input data.

-s <n>, --skip-lines=<n>

New in version 5.1.0.

Skip the first *n* lines of input. This applies to any kind of input, whether it comes from STDIN, a file or interactive user input.

-v, --verbose

Write non-essential, but potentially useful, information to stderr. Repeat for additional information (-vv, -vvv, etc.)

--version

Print version number.

The +*args* arguments are associated with coordinate operation parameters. Usage varies with operation.

cct is an acronym meaning *Coordinate Conversion and Transformation*.

The acronym refers to definitions given in the OGC 08-015r2/ISO-19111 standard “Geographical Information – Spatial Referencing by Coordinates”, which defines two different classes of *coordinate operations*:

Coordinate Conversions, which are coordinate operations where input and output datum are identical (e.g. conversion from geographical to cartesian coordinates) and

Coordinate Transformations, which are coordinate operations where input and output datums differ (e.g. change of reference frame).

5.2.3 Examples

1. The operator specs describe the action to be performed by **cct**. So the following script

```
echo 12 55 0 0 | cct +proj=utm +zone=32 +ellps=GRS80
```

will transform the input geographic coordinates into UTM zone 32 coordinates. Hence, the command

```
echo 12 55 | cct -z0 -t0 +proj=utm +zone=32 +ellps=GRS80
```

Should give results comparable to the classic **proj** command

```
echo 12 55 | proj +proj=utm +zone=32 +ellps=GRS80
```

2. Convert geographical input to UTM zone 32 on the GRS80 ellipsoid:

```
cct +proj=utm +ellps=GRS80 +zone=32
```

3. Roundtrip accuracy check for the case above:

```
cct +proj=pipeline +proj=utm +ellps=GRS80 +zone=32 +step +step +inv
```

4. As (2) but specify input columns for longitude, latitude, height and time:

```
cct -c 5,2,1,4 +proj=utm +ellps=GRS80 +zone=32
```

5. As (2) but specify fixed height and time, hence needing only 2 cols in input:

```
cct -t 0 -z 0 +proj=utm +ellps=GRS80 +zone=32
```

5.2.4 Background

cct also refers to Carl Christian Tscherning (1942–2014), professor of Geodesy at the University of Copenhagen, mentor and advisor for a generation of Danish geodesists, colleague and collaborator for two generations of global geodesists, Secretary General for the International Association of Geodesy, IAG (1995–2007), fellow of the American Geophysical Union (1991), recipient of the IAG Levallois Medal (2007), the European Geosciences Union Vening Meinesz Medal (2008), and of numerous other honours.

cct, or Christian, as he was known to most of us, was recognized for his good mood, his sharp wit, his tireless work, and his great commitment to the development of geodesy – both through his scientific contributions, comprising more than 250 publications, and by his mentoring and teaching of the next generations of geodesists.

As Christian was an avid Fortran programmer, and a keen Unix connoisseur, he would have enjoyed to know that his initials would be used to name a modest Unix style transformation filter, hinting at the tireless aspect of his personality, which was certainly one of the reasons he accomplished so much, and meant so much to so many people.

Hence, in honour of *cct* (the geodesist) this is **cct** (the program).

5.3 cs2cs

5.3.1 Synopsis

```
cs2cs [ -eEfIlrstvwW [ args ] ] [ +opts[=arg] ] [ +to [+opts[=arg]] ] file[s]
```

5.3.2 Description

cs2cs performs transformation between the source and destination cartographic coordinate system on a set of input points. The coordinate system transformation can include translation between projected and geographic coordinates as well as the application of datum shifts.

The following control parameters can appear in any order:

-I

Method to specify inverse translation, convert from *+to* coordinate system to the primary coordinate system defined.

-t <a>

Where *a* specifies a character employed as the first character to denote a control line to be passed through without processing. This option applicable to ASCII input only. (# is the default value).

-e <string>

Where *string* is an arbitrary string to be output if an error is detected during data transformations. The default value is a three character string: *\t*.

-E

Causes the input coordinates to be copied to the output line prior to printing the converted values.

-l<[=id]>

List projection identifiers that can be selected with *+proj*. `cs2cs -l=id` gives expanded description of projection *id*, e.g. `cs2cs -l=merc`.

-lp

List of all projection id that can be used with the *+proj* parameter. Equivalent to `cs2cs -l`.

-lp

Expanded description of all projections that can be used with the *+proj* parameter.

-le

List of all ellipsoids that can be selected with the *+ellps* parameters.

-lu

List of all distance units that can be selected with the *+units* parameter.

-ld

List of datums that can be selected with the *+datum* parameter.

-r

This options reverses the order of the expected input from longitude-latitude or x-y to latitude-longitude or y-x.

-s

This options reverses the order of the output from x-y or longitude-latitude to y-x or latitude-longitude.

-f <format>

Where *format* is a printf format string to control the form of the output values. For inverse projections, the output will be in degrees when this option is employed. If a format is specified for inverse projection the output data will be in decimal degrees. The default format is "% .2f" for forward projection and DMS for inverse.

-w<n>

Where *n* is the number of significant fractional digits to employ for seconds output (when the option is not specified, -w3 is assumed).

-W<n>

Where *n* is the number of significant fractional digits to employ for seconds output. When -W is employed the fields will be constant width with leading zeroes.

-v

Causes a listing of cartographic control parameters tested for and used by the program to be printed prior to input data.

The **cs2cs** program requires two coordinate system definitions. The first (or primary) is defined based on all projection parameters not appearing after the *+to* argument. All projection parameters appearing after the *+to* argument are considered the definition of the second coordinate system. If there is no second coordinate system defined, a geographic coordinate system based on the datum and ellipsoid of the source coordinate system is assumed. Note that the source and destination coordinate system can both be projections, both be geographic, or one of each and may have the same or different datums.

Additional projection control parameters may be contained in two auxiliary control files: the first is optionally referenced with the *+init=file:id* and the second is always processed after the name of the projection has been established from either the run-line or the contents of *+init* file. The environment parameter **PROJ_LIB** establishes the default directory for a file reference without an absolute path. This is also used for supporting files like datum shift files.

One or more files (processed in left to right order) specify the source of data to be transformed. A `-` will specify the location of processing standard input. If no files are specified, the input is assumed to be from stdin. For input data the two data values must be in the first two white space separated fields and when both input and output are ASCII all trailing portions of the input line are appended to the output line.

Input geographic data (longitude and latitude) must be in DMS or decimal degrees format and input cartesian data must be in units consistent with the ellipsoid major axis or sphere radius units. Output geographic coordinates will normally be in DMS format (use `-f %.12f` for decimal degrees with 12 decimal places), while projected (cartesian) coordinates will be in linear (meter, feet) units.

5.3.3 Example

The following script

```
cs2cs +proj=latlong +datum=NAD83 +to +proj=utm +zone=10 +datum=NAD27 -r <<EOF
45d15'33.1" 111.5W
45d15.551666667N -111d30
+45.25919444444 111d30'000W
EOF
```

will transform the input NAD83 geographic coordinates into NAD27 coordinates in the UTM projection with zone 10 selected. The geographic values of this example are equivalent and meant as examples of various forms of DMS input. The x-y output data will appear as three lines of:

1402285.99	5076292.42	0.000
------------	------------	-------

5.4 geod

5.4.1 Synopsis

```
geod +ellps=<ellipse> [ -affIptwW [ args ] ] [ +args ] file[s]
invgeod +ellps=<ellipse> [ -affIptwW [ args ] ] [ +args ] file[s]
```

5.4.2 Description

geod (direct) and **invgeod** (inverse) perform geodesic (Great Circle) computations for determining latitude, longitude and back azimuth of a terminus point given a initial point latitude, longitude, azimuth and distance (direct) or the forward and back azimuths and distance between an initial and terminus point latitudes and longitudes (inverse). The results are accurate to round off for $|f| < 1/50$, where f is flattening.

invgeod may not be available on all platforms; in this case use `geod -I` instead.

The following command-line options can appear in any order:

-I

Specifies that the inverse geodesic computation is to be performed. May be used with execution of **geod** as an alternative to **invgeod** execution.

-a

Latitude and longitudes of the initial and terminal points, forward and back azimuths and distance are output.

-t<a>

Where *a* specifies a character employed as the first character to denote a control line to be passed through without processing.

-1e

Gives a listing of all the ellipsoids that may be selected with the *+ellps*= option.

-1u

Gives a listing of all the units that may be selected with the *+units*= option.

-f <format>

Where *format* is a printf format string to control the output form of the geographic coordinate values. The default mode is DMS for geographic coordinates and "% .3f" for distance.

-F <format>

Where *format* is a printf format string to control the output form of the distance value (-F). The default mode is DMS for geographic coordinates and "% .3f" for distance.

-w<n>

Where *n* is the number of significant fractional digits to employ for seconds output (when the option is not specified, -w3 is assumed).

-W<n>

Where *n* is the number of significant fractional digits to employ for seconds output. When -W is employed the fields will be constant width with leading zeroes.

-p

This option causes the azimuthal values to be output as unsigned DMS numbers between 0 and 360 degrees. Also note [-f](#).

The +args command-line options are associated with geodetic parameters for specifying the ellipsoidal or sphere to use. controls. The options are processed in left to right order from the command line. Reentry of an option is ignored with the first occurrence assumed to be the desired value.

One or more files (processed in left to right order) specify the source of data to be transformed. A - will specify the location of processing standard input. If no files are specified, the input is assumed to be from stdin.

For direct determinations input data must be in latitude, longitude, azimuth and distance order and output will be latitude, longitude and back azimuth of the terminus point. Latitude, longitude of the initial and terminus point are input for the inverse mode and respective forward and back azimuth from the initial and terminus points are output along with the distance between the points.

Input geographic coordinates (latitude and longitude) and azimuthal data must be in decimal degrees or DMS format and input distance data must be in units consistent with the ellipsoid major axis or sphere radius units. The latitude must lie in the range [-90d,90d]. Output geographic coordinates will be in DMS (if the [-f](#) switch is not employed) to 0.001" with trailing, zero-valued minute-second fields deleted. Output distance data will be in the same units as the ellipsoid or sphere radius.

The Earth's ellipsoidal figure may be selected in the same manner as program **proj** by using *+ellps*=, *+a*=, *+es*=, etc.

geod may also be used to determine intermediate points along either a geodesic line between two points or along an arc of specified distance from a geographic point. In both cases an initial point must be specified with *+lat_1=lat* and *+lon_1=lon* parameters and either a terminus point *+lat_2=lat* and *+lon_2=lon* or a distance and azimuth from the initial point with *+S=distance* and *+A=azimuth* must be specified.

If points along a geodesic are to be determined then either *+n_S=integer* specifying the number of intermediate points and/or *+del_S=distance* specifying the incremental distance between points must be specified.

To determine points along an arc equidistant from the initial point both *+del_A=angle* and *+n_A=integer* must be specified which determine the respective angular increments and number of points to be determined.

5.4.3 Examples

The following script determines the geodesic azimuths and distance in U.S. statute miles from Boston, MA, to Portland, OR:

```
geod +ellps=clrk66 <<EOF -I +units=us-mi  
42d15'N 71d07'W 45d31'N 123d41'W  
EOF
```

which gives the results:

```
-66d31'50.141" 75d39'13.083" 2587.504
```

where the first two values are the azimuth from Boston to Portland, the back azimuth from Portland to Boston followed by the distance.

An example of forward geodesic use is to use the Boston location and determine Portland's location by azimuth and distance:

```
geod +ellps=clrk66 <<EOF +units=us-mi  
42d15'N 71d07'W -66d31'50.141" 2587.504  
EOF
```

which gives:

```
45d31'0.003"N 123d40'59.985"W 75d39'13.094"
```

Note: Lack of precision in the distance value compromises the precision of the Portland location.

5.4.4 Further reading

1. [GeographicLib](#).
2. C. F. F. Karney, [Algorithms for Geodesics](#), J. Geodesy **87**(1), 43–55 (2013); [addenda](#).
3. [A geodesic bibliography](#).

5.5 gie

5.5.1 Synopsis

```
gie [ -hovql [ args ] ] file[s]
```

5.5.2 Description

gie, the Geospatial Integrity Investigation Environment, is a regression testing environment for the PROJ transformation library. Its primary design goal is to be able to perform regression testing of code that are a part of PROJ, while not requiring any other kind of tooling than the same C compiler already employed for compiling the library.

-h, --help

Print usage information

```
-o <file>, --output <file>
    Specify output file name

-v, --verbose
    Verbose: Provide non-essential informational output. Repeat -v for more verbosity (e.g. -vv)

-q, --quiet
    Quiet: Opposite of verbose. In quiet mode not even errors are reported. Only interaction is through the return
    code (0 on success, non-zero indicates number of FAILED tests)

-l, --list
    List the PROJ internal system error codes

--version
    Print version number
```

Tests for **gie** are defined in simple text files. Usually having the extension .**gie**. Test for **gie** are written in the purpose-build command language for gie. The basic functionality of the gie command language is implemented through just 3 command verbs: *operation*, which defines the PROJ operation to test, *accept*, which defines the input coordinate to read, and *expect*, which defines the result to expect.

A sample test file for **gie** that uses the three above basic commands looks like:

```
<gie>

-----
Test output of the UTM projection
-----
operation +proj=utm +zone=32 +ellps=GRS80
-----
accept    12 55
expect    691_875.632_14    6_098_907.825_05
</gie>
```

Parsing of a **gie** file starts at **<gie>** and ends when **</gie>** is reached. Anything before **<gie>** and after **</gie>** is not considered. Test cases are created by defining an *operation* which *accept* an input coordinate and *expect* an output coordinate.

Because **gie** tests are wrapped in the **<gie>/</gie>** tags it is also possible to add test cases to custom made *init files*. The tests will be ignore by PROJ when reading the init file with **+init** and **gie** ignores anything not wrapped in **<gie>/</gie>**.

gie tests are defined by a set of commands like *operation*, *accept* and *expect* in the example above. Together the commands make out the **gie** command language. Any line in a **gie** file that does not start with a command is ignored. In the example above it is seen how this can be used to add comments and styling to **gie** test files in order to make them more readable as well as documenting what the purpose of the various tests are.

Below the *gie command language* is explained in details.

5.5.3 Examples

1. Run all tests in a file with all debug information turned on

```
gie -vvvv corner-cases.gie
```

2. Run all tests in several files

```
gie foo bar
```

5.5.4 gie command language

operation <+args>

Define a PROJ operation to test. Example:

```
operation proj=utm zone=32 ellps=GRS80
# test 4D function
accept    12 55 0 0
expect   691875.63214 6098907.82501 0 0

# test 2D function
accept    12 56
expect   687071.4391 6210141.3267
```

accept <x y [z [t]]>

Define the input coordinate to read. Takes test coordinate. The coordinate can be defined by either 2, 3 or 4 values, where the first two values are the x- and y-components, the 3rd is the z-component and the 4th is the time component. The number of components in the coordinate determines which version of the operation is tested (2D, 3D or 4D). Many coordinates can be accepted for one *operation*. For each *accept* an accompanying *expect* is needed.

Note that **gie** accepts the underscore (_) as a thousands separator. It is not required (in fact, it is entirely ignored by the input routine), but it significantly improves the readability of the very long strings of numbers typically required in projected coordinates.

See *operation* for an example.

expect <x y [z [t]]> | <error code>

Define the expected coordinate that will be returned from accepted coordinate passed through an operation. The expected coordinate can be defined by either 2, 3 or 4 components, similarly to *accept*. Many coordinates can be expected for one *operation*. For each *expect* an accompanying *accept* is needed.

See *operation* for an example.

In addition to expecting a coordinate it is also possible to expect a PROJ error code in case an operation can't be created. This is useful when testing that errors are caught and handled correctly. Below is an example of that tests that the pipeline operator fails correctly when a non-invertible pipeline is constructed.

```
operation proj=pipeline step
proj=urm5 n=0.5 inv
expect failure pjd_err_malformed_pipeline
```

See *gie -l* for a list of error codes that can be expected.

tolerance <tolerance>

The *tolerance* command controls how much accepted coordinates can deviate from the expected coordinate. This is handy to test that an operation meets a certain numerical tolerance threshold. Some operations are expected to be accurate within millimeters where others might only be accurate within a few meters. *tolerance* should

```
operation proj=merc
# test coordinate as returned by ```echo 12 55 | proj +proj=merc```
tolerance 1 cm
accept    12 55
```

(continues on next page)

(continued from previous page)

```
expect      1335833.89 7326837.72

# test that the same coordinate with a 50 m false easting as determined
# by ``echo 12 55 |proj +proj=merc +x_0=50`` is still within a 100 m
# tolerance of the unaltered coordinate from proj=merc
tolerance   100 m
accept      12 55
expect      1335883.89 7326837.72
```

The default tolerance is 0.5 mm. See [proj -lu](#) for a list of possible units.

roundtrip <n> <tolerance>

Do a roundtrip test of an operation. [roundtrip](#) needs a [operation](#) and a [accept](#) command to function. The accepted coordinate is passed to the operation first in it's forward mode, then the output from the forward operation is passed back to the inverse operation. This procedure is done n times. If the resulting coordinate is within the set tolerance of the initial coordinate, the test is passed.

Example with the default 100 iterations and the default tolerance:

```
operation   proj=merc
accept     12 55
roundtrip
```

Example with count and default tolerance:

```
operation   proj=merc
accept     12 55
roundtrip  10000
```

Example with count and tolerance:

```
operation   proj=merc
accept     12 55
roundtrip  10000 5 mm
```

direction <direction>

The [direction](#) command specifies in which direction an operation is performed. This can either be [forward](#) or [inverse](#). An example of this is seen below where it is tested that a symmetrical transformation pipeline returns the same results in both directions.

```
operation proj=pipeline zone=32 step
          proj=utm ellps=GRS80 step
          proj=utm ellps=GRS80 inv
tolerance 0.1 mm

accept 12 55 0 0
expect 12 55 0 0

# Now the inverse direction (still same result: the pipeline is symmetrical)

direction inverse
expect 12 55 0 0
```

The default direction is “forward”.

ignore <error code>

This is especially useful in test cases that rely on a grid that is not guaranteed to be available. Below is an example of that situation.

```
operation proj=hgridshift +grids=nzgd2kgrid0005.gsb ellps=GRS80
tolerance 1 mm
ignore    pjd_err_failed_to_load_grid
accept    172.999892181021551 -45.001620431954613
expect    173                 -45
```

See `gie -l` for a list of error codes that can be ignored.

`echo <text>`

Add user defined text to the output stream. See the example below.

```
<gie>
echo ** Mercator projection tests **
operation +proj=merc
accept 0 0
expect 0 0
</gie>
```

which returns

```
-----
Reading file 'test.gie'
** Mercator projection test **

-----
```

total: 1 tests succeeded, 0 tests skipped, 0 tests failed.

`skip`

Skip any test after the first occurrence of `skip`. In the example below only the first test will be performed. The second test is skipped. This feature is mostly relevant for debugging when writing new test cases.

```
<gie>
operation proj=merc
accept 0 0
expect 0 0
skip
accept 0 1
expect 0 110579.9
</gie>
```

5.5.5 Background

More importantly than being an acronym for “Geospatial Integrity Investigation Environment”, gie were also the initials, user id, and USGS email address of Gerald Ian Evenden (1935–2016), the geospatial visionary, who, already in the 1980s, started what was to become the PROJ of today.

Gerald’s clear vision was that map projections are *just special functions*. Some of them rather complex, most of them of two variables, but all of them *just special functions*, and not particularly more special than the `sin()`, `cos()`, `tan()`, and `hypot()` already available in the C standard library.

And hence, according to Gerald, *they should not be particularly much harder to use*, for a programmer, than the `sin()`’s, `tan()`’s and `hypot()`’s so readily available.

Gerald’s ingenuity also showed in the implementation of the vision, where he devised a comprehensive, yet simple, system of key-value pairs for parameterising a map projection, and the highly flexible `PJ` struct, storing run-time compiled versions of those key-value pairs, hence making a map projection function call, `pj_fwd(PJ, point)`, as easy as a traditional function call like `hypot(x, y)`.

While today, we may have more formally well defined metadata systems (most prominent the OGC WKT2 representation), nothing comes close being as easily readable (“human compatible”) as Gerald’s key-value system. This system in particular, and the PROJ system in general, was Gerald’s great gift to anyone using and/or communicating about geodata.

It is only reasonable to name a program, keeping an eye on the integrity of the PROJ system, in honour of Gerald.

So in honour, and hopefully also in the spirit, of Gerald Ian Evenden (1935–2016), this is the Geospatial Integrity Investigation Environment.

CHAPTER
SIX

COORDINATE OPERATIONS

Coordinate operations in PROJ are divided into three groups: Projections, conversions and transformations. Projections are purely cartographic mappings of the sphere onto the plane. Technically projections are conversions (according to ISO standards), though in PROJ projections are distinguished from conversions. Conversions are coordinate operations that do not exert a change in reference frame. Operations that do exert a change in reference frame are called transformations.

6.1 Projections

Projections are coordinate operations that are technically conversions but since projections are so fundamental to PROJ we differentiate them from conversions.

Projections map the spherical 3D space to a flat 2D space.

6.1.1 Albers Equal Area

Classification	Conic
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Global
Alias	aea
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



Options

Note: All options are optional for the Albers Equal Area projection.

+lat_1=<value>

First standard parallel.

Defaults to 0.0.

+lat_2=<value>

Second standard parallel.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+ellps=<value>

See [proj -le](#) for a list of available ellipsoids.

Defaults to "WGS84".

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>


False northing.

Defaults to 0.0.

6.1.2 Azimuthal Equidistant

Classification	Azimuthal
Available forms	Forward and inverse, spherical and elliptical projection
Alias	aeqd
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=aeqd



Options

Note: All options are optional for the Azimuthal Equidistant projection.

+guam

Use Guam elliptical formulas. Only accurate near the Island of Guam ($\lambda \approx 144.5^\circ$, $\phi \approx 13.5^\circ$)

+k_0=<value>

Scale factor. Determines scale factor used in the projection.

Defaults to 1.0.

+lat_ts=<value>

Latitude of true scale. Defines the latitude where scale is not distorted. Takes precedence over **+k_0** if both options are used together.

Defaults to 0.0.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

+ellps=<value>

See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>


Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

6.1.3 Airy

The Airy projection is an azimuthal minimum error projection for the region within the small or great circle defined by an angular distance, ϕ_b , from the tangency point of the plane (λ_0, ϕ_0).

Classification	Azimuthal
Available forms	Forward spherical projection
Defined area	Global
Alias	airy
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=airy



Options

+lat_b

Angular distance from tangency point of the plane (λ_0, ϕ_0) where the error is kept at minimum.

Defaults to 90° (suitable for hemispherical maps).

+no_cut

Do not cut at hemisphere limit

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.


Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

6.1.4 Aitoff

Classification	Miscellaneous
Available forms	Forward and inverse spherical projection
Defined area	Global
Alias	aitoff
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

6.1.5 Modified Stereographics of Alaska

Classification	Modified azimuthal
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Alaska
Alsk	alsk
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



Options

Note: All options are optional for the projection.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with `+ellps` `+R` takes precedence.

6.1.6 Apian Globular I

Classification	Miscellaneous
Available forms	Forward spherical projection
Defined area	Global
Alias	apian
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



Options

Note: All options are optional for the Apian Globular projection.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

6.1.7 August Epicycloidal

+proj=august



6.1.8 Bacon Globular

+proj=bacon



6.1.9 Bipolar conic of western hemisphere

+proj=bipc +ns



6.1.10 Boggs Eumorphic

+proj=boggs



6.1.11 Bonne (Werner lat_1=90)


`+proj=bonne +lat_1=90`



6.1.12 Cal Coop Ocean Fish Invest Lines/Stations

The CalCOFI pseudo-projection is the line and station coordinate system of the California Cooperative Oceanic Fisheries Investigations program, known as CalCOFI, for sampling offshore of the west coast of the U.S. and Mexico.

Classification	Conformal cylindrical
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Only valid for the west coast of USA and Mexico
Alias	calcofi
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



The coordinate system is based on the Mercator projection with units rotated -30 degrees from the meridian so that they are oriented with the coastline of the Southern California Bight and Baja California. Lines increase from Northwest

to Southeast. A unit of line is 12 nautical miles. Stations increase from inshore to offshore. A unit of station is equal to 4 nautical miles. The rotation point is located at line 80, station 60, or 34.15 degrees N, -121.15 degrees W, and is depicted by the red dot in the figure. By convention, the ellipsoid of Clarke 1866 is used to calculate CalCOFI coordinates.

The CalCOFI program is a joint research effort by the U.S. National Oceanic and Atmospheric Administration, University of California Scripps Oceanographic Institute, and California Department of Fish and Game. Surveys have been conducted for the CalCOFI program since 1951, creating one of the oldest and most scientifically valuable joint oceanographic and fisheries data sets in the world. The CalCOFI line and station coordinate system is now used by several other programs including the Investigaciones Mexicanas de la Corriente de California (IMECOCAL) program offshore of Baja California. The figure depicts some commonly sampled locations from line 40 to line 156.7 and offshore to station 120. Blue numbers indicate line (bottom) or station (left) numbers along the grid. Note that lines spaced at approximate 3-1/3 intervals are commonly sampled, e.g., lines 43.3 and 46.7.

Usage

A typical forward CalCOFI projection would be from lon/lat coordinates on the Clark 1866 ellipsoid. For example:

```
proj +proj=calcofi +ellps=clrk66 -E <<EOF  
-121.15 34.15  
EOF
```

Output of the above command:

```
-121.15 34.15    80.00    60.00
```

The reverse projection from line/station coordinates to lon/lat would be entered as:

```
proj +proj=calcofi +ellps=clrk66 -I -E -f "%.\.2f" <<EOF  
80.0 60.0  
EOF
```

Output of the above command:

```
80.0 60.0    -121.15 34.15
```

Options

Note: All options are optional for the CalCOFI projection.

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with `+ellps +R` takes precedence.

Mathematical definition

The algorithm used to make conversions is described in [\[EberHewitt1979\]](#) with a few corrections reported in [\[WeberMoore2013\]](#).

Further reading

1. General information about the CalCOFI program
2. The Investigaciones Mexicanas de la Corriente de California

6.1.13 Cassini (Cassini-Soldner)

Although the Cassini projection has been largely replaced by the Transverse Mercator, it is still in limited use outside the United States and was one of the major topographic mapping projections until the early 20th century.

Classification	Transverse and oblique cylindrical
Available forms	Forward and inverse, Spherical and Elliptical
Defined area	Global, but best used near the central meridian with long, narrow areas
Alias	cass
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=cass



Usage

There has been little usage of the spherical version of the Cassini, but the ellipsoidal Cassini-Soldner version was adopted by the Ordnance Survey for the official survey of Great Britain during the second half of the 19th century [[Steers1970](#)]. Many of these maps were prepared at a scale of 1:2,500. The Cassini-Soldner was also used for the detailed mapping of many German states during the same period.

Example using EPSG 30200 (Trinidad 1903, units in clarke's links):

```
$ echo 0.17453293 -1.08210414 | proj +proj=cass +lat_0=10.44166666666667 +lon_0=-61.  
↪333333333333334 +x_0=86501.46392051999 +y_0=65379.0134283 +a=6378293.645208759  
↪+b=6356617.987679838 +to_meter=0.201166195164 +no_defs  
66644.94     82536.22
```

Example using EPSG 3068 (Soldner Berlin):

```
$ echo 13.5 52.4 | proj +proj=cass +lat_0=52.4186482777778 +lon_0=13.627203666666667 ↵+x_0=40000 +y_0=10000 +ellps=bessel +datum=potsdam +units=m +no_defs
31343.05      7932.76
```

Options

Note: All options are optional for the Cassini projection.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

+ellps=<value>

See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

Mathematical definition

The formulas describing the Cassini projection are taken from Snyder’s [\[Snyder1987\]](#).

ϕ_0 is the latitude of origin that match the center of the map (default to 0). It can be set with +lat_0.

Spherical form

Forward projection

$$x = \arcsin(\cos(\phi) \sin(\lambda))$$

$$y = \arctan 2(\tan(\phi), \cos(\lambda)) - \phi_0$$

Inverse projection

$$\phi = \arcsin(\sin(y + \phi_0) \cos(x))$$

$$\lambda = \arctan 2(\tan(x), \cos(y + \phi_0))$$

Elliptical form**Forward projection**

$$N = (1 - e^2 \sin^2(\phi))^{-1/2}$$

$$T = \tan^2(\phi)$$

$$A = \lambda \cos(\phi)$$

$$C = \frac{e^2}{1 - e^2} \cos^2(\phi)$$

$$x = N(A - T \frac{A^3}{6} - (8 - T + 8C)T \frac{A^5}{120})$$

$$y = M(\phi) - M(\phi_0) + N \tan(\phi) (\frac{A^2}{2} + (5 - T + 6C) \frac{A^4}{24})$$

and M() is the meridional distance function.

Inverse projection

$$\phi' = M^{-1}(M(\phi_0) + y)$$

if $\phi' = \frac{\pi}{2}$ then $\phi = \phi'$ and $\lambda = 0$

otherwise evaluate T and N above using ϕ' and

$$R = (1 - e^2)(1 - e^2 \sin^2 \phi')^{-3/2}$$

$$D = x/N$$

$$\phi = \phi' - \tan \phi' \frac{N}{R} (\frac{D^2}{2} - (1 + 3T) \frac{D^4}{24})$$

$$\lambda = \frac{(D - T \frac{D^3}{3} + (1 + 3T)T \frac{D^5}{15})}{\cos \phi'}$$

Further reading

1. Wikipedia
2. [Snyder1987]
3. EPSG, POSC literature pertaining to Coordinate Conversions and Transformations including Formulas

6.1.14 Central Cylindrical

+proj=cc



6.1.15 Central Conic

New in version 5.0.0.

This is central (centrographic) projection on cone tangent at :option:`lat_1` latitude, identical with `conic()` projection from `mapproj` R package.

Classification	Conic
Available forms	Forward and inverse, spherical projection
Defined area	Global, but best used near the standard parallel
Alias	ccon
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=ccon +lat_1=52 +lon_0=19



Usage

This simple projection is rarely used, as it is not equidistant, equal-area, nor conformal.

An example of usage (and the main reason to implement this projection in proj4) is the ATPOL geobotanical grid of Poland, developed in Institute of Botany, Jagiellonian University, Krakow, Poland in 1970s [[Zajac 1978](#)]. The grid was originally handwritten on paper maps and further copied by hand. The projection (together with strange Earth radius) was chosen by its creators as the compromise fit to existing maps during first software development in DOS era. Many years later it is still de facto standard grid in Polish geobotanical research.

The ATPOL coordinates can be achieved with the following parameters:

```
+proj=ccon +lat_1=52 +lon_0=19 +axis=esu +a=6390000 +x_0=330000 +y_0=-350000
```

For more information see [[Komsta 2016](#)] and [[Verey 2017](#)].

Parameters

Required

+lat_1=<value>

Standard parallel of projection.

Optional

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

Mathematical definition

Forward projection

$$r = \cot \phi_0 - \tan(\phi - \phi_0)$$

$$x = r \sin(\lambda \sin \phi_0)$$

$$y = \cot \phi_0 - r \cos(\lambda \sin \phi_0)$$

Inverse projection

$$y = \cot \phi_0 - y$$

$$\phi = \phi_0 - \tan^{-1}(\sqrt{x^2 + y^2} - \cot \phi_0)$$

$$\lambda = \frac{\tan^{-1} \sqrt{x^2 + y^2}}{\sin \phi_0}$$

Reference values

For ATPOL to WGS84 test, run the following script:

```
#!/bin/bash
cat << EOF | src/cs2cs -v -f "%E" +proj=ccon +lat_1=52 +lat_0=52 +lon_0=19 +axis=esu_
↪+a=6390000 +x_0=330000 +y_0=-350000 +to +proj=longlat +datum=WGS84 +no_defs
0 0
0 700000
700000 0
700000 700000
330000 350000
EOF
```

It should result with

```
1.384023E+01 5.503040E+01 0.000000E+00
1.451445E+01 4.877385E+01 0.000000E+00
2.478271E+01 5.500352E+01 0.000000E+00
2.402761E+01 4.875048E+01 0.000000E+00
1.900000E+01 5.200000E+01 0.000000E+00
```

Analogous script can be run for reverse test:


```
cat << EOF | src/cs2cs -v -f "%E" +proj=longlat +datum=WGS84 +no_defs +to +proj=ccon_
↪+lat_1=52 +lat_0=52 +lon_0=19 +axis=esu +a=6390000 +x_0=330000 +y_0=-350000
24 55
15 49
24 49
19 52
EOF
```

and it should give the following results:

```
6.500315E+05 4.106162E+03 0.000000E+00
3.707419E+04 6.768262E+05 0.000000E+00
6.960534E+05 6.722946E+05 0.000000E+00
3.300000E+05 3.500000E+05 0.000000E+00
```


6.1.16 Equal Area Cylindrical

+proj=cea




6.1.17 Chamberlin Trimetric

+proj=chamb +lat_1=10 +lon_1=30 +lon_2=40



6.1.18 Collignon

+proj=collg



6.1.19 Craster Parabolic (Putnins P4)

+proj=crast




6.1.20 Denoyer Semi-Elliptical

`+proj=denoy`



6.1.21 Eckert I


`+proj=eckl`



$$\begin{aligned}x &= 2\sqrt{2/3\pi}\lambda(1 - |\phi|/\pi) \\y &= 2\sqrt{2/3\pi}\phi\end{aligned}$$


6.1.22 Eckert II

+proj=eck2




6.1.23 Eckert III

+proj=eck3



6.1.24 Eckert IV

+proj=eck4




$$x = \lambda(1 + \cos\phi)/\sqrt{2 + \pi}$$

$$y = 2\phi/\sqrt{2 + \pi}$$


6.1.25 Eckert V

+proj=eck5



6.1.26 Eckert VI

+proj=eck6




6.1.27 Equidistant Cylindrical (Plate Carrée)

The simplest of all projections. Standard parallels (0° when omitted) may be specified that determine latitude of true scale ($k=h=1$).

Classification	Conformal cylindrical
Available forms	Forward and inverse
Defined area	Global, but best used near the equator
Alias	eqc
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=eqc



Usage

Because of the distortions introduced by this projection, it has little use in navigation or cadastral mapping and finds its main use in thematic mapping. In particular, the plate carrée has become a standard for global raster datasets, such as Celestia and NASA World Wind, because of the particularly simple relationship between the position of an image pixel on the map and its corresponding geographic location on Earth.

The following table gives special cases of the cylindrical equidistant projection.

Projection Name	(lat ts=) ϕ_0
Plain/Plane Chart	0°
Simple Cylindrical	0°
Plate Carrée	0°
Ronald Miller—minimum overall scale distortion	37°30'
E.Graffarend and A.Niermann	42°
Ronald Miller—minimum continental scale distortion	43°30'
Gall Isographic	45°
Ronald Miller Equirectangular	50°30'
E.Graffarend and A.Niermann minimum linear distortion	61°7'

Example using EPSG 32662 (WGS84 Plate Carrée):

```
$ echo 2 47 | proj +proj=eqc +lat_ts=0 +lat_0=0 +lon_0=0 +x_0=0 +y_0=0 +ellps=WGS84
↪+datum=WGS84 +units=m +no_defs
222638.98      5232016.07
```

Example using Plate Carrée projection with true scale at latitude 30° and central meridian 90°W:

```
$ echo -88 30 | proj +proj=eqc +lat_ts=30 +lon_0=90w
192811.01      3339584.72
```

Parameters

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+lat_ts=<value>

Latitude of true scale. Defines the latitude where scale is not distorted. Takes precedence over +k_0 if both options are used together.

Defaults to 0.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

+ellps=<value>

See [`proj -le`](#) for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with `+ellps +R` takes precedence.

Mathematical definition

The formulas describing the Equidistant Cylindrical projection are all taken from Snyder’s [[Snyder1987](#)].

ϕ_{ts} is the latitude of true scale, that mean the standard parallels where the scale of the projection is true. It can be set with `+lat_ts`.

ϕ_0 is the latitude of origin that match the center of the map. It can be set with `+lat_0`.

Forward projection

$$x = \lambda \cos \phi_{ts}$$

$$y = \phi - \phi_0$$

Inverse projection

$$\lambda = x / \cos \phi_{ts}$$

$$\phi = y + \phi_0$$

Further reading

1. [Wikipedia](#)
2. [Wolfram Mathworld](#)

6.1.28 Equidistant Conic

+proj=eqdc +lat_1=55 +lat_2=60




6.1.29 Euler

+proj=euler +lat_1=67 +lat_2=75




6.1.30 Extended Transverse Mercator

+proj=etmerc




6.1.31 Fahey


+proj=fahey



6.1.32 Foucaut



6.1.33 Foucaut Sinusoidal



The y -axis is based upon a weighted mean of the cylindrical equal-area and the sinusoidal projections. Parameter $n = n$ is the weighting factor where $0 \leq n \leq 1$.

$$\begin{aligned}x &= \lambda \cos \phi / (n + (1 - n) \cos \phi) \\y &= n\phi + (1 - n) \sin \phi\end{aligned}$$

For the inverse, the Newton-Raphson method can be used to determine ϕ from the equation for y above. As $n \rightarrow 0$ and $\phi \rightarrow \pi/2$, convergence is slow but for $n = 0$, $\phi = \sin^{-1} y$

6.1.34 Gall (Gall Stereographic)

The Gall stereographic projection, presented by James Gall in 1855, is a cylindrical projection. It is neither equal-area nor conformal but instead tries to balance the distortion inherent in any projection.

Classification	Transverse and oblique cylindrical
Available forms	Forward and inverse, Spherical
Defined area	Global
Alias	gall
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=gall



Usage

The need for a world map which avoids some of the scale exaggeration of the Mercator projection has led to some commonly used cylindrical modifications, as well as to other modifications which are not cylindrical. The earliest common cylindrical example was developed by James Gall of Edinburgh about 1855 (Gall, 1885, p. 119-123). His meridians are equally spaced, but the parallels are spaced at increasing intervals away from the Equator. The parallels of latitude are actually projected onto a cylinder wrapped about the sphere, but cutting it at lats. 45° N. and S., the point of perspective being a point on the Equator opposite the meridian being projected. It is used in several British atlases, but seldom in the United States. The Gall projection is neither conformal nor equal-area, but has a blend of various features. Unlike the Mercator, the Gall shows the poles as lines running across the top and bottom of the map.

Example using Gall Stereographical

```
$ echo 9 51 | proj +proj=gall +lon_0=0 +x_0=0 +y_0=0 +ellps=WGS84 +datum=WGS84
↪+units=m +no_defs
708432.90    5193386.36
```

Example using Gall Stereographical (Central meridian 90°W)

```
$ echo 9 51 | proj +proj=gall +lon_0=90w +x_0=0 +y_0=0 +ellps=WGS84 +datum=WGS84
↪+units=m +no_defs
7792761.91 5193386.36
```

Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

+ellps=<value>

See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

Mathematical definition

The formulas describing the Gall Stereographical are all taken from Snyder’s [[Snyder1993](#)].

Spherical form

Forward projection

$$x = \frac{\lambda}{\sqrt{2}}$$

$$y = \left(1 + \frac{\sqrt{2}}{2}\right) \tan(\phi/2)$$

Inverse projection

$$\phi = 2 \arctan\left(\frac{y}{1 + \frac{\sqrt{2}}{2}}\right)$$

$$\lambda = \sqrt{2}x$$

Further reading

1. [Wikipedia](#)
2. [Cartographic Projection Procedures for the UNIX Environment-A User's Manual](#)

6.1.35 Geostationary Satellite View

The geos projection pictures how a geostationary satellite scans the earth at regular scanning angle intervals.

Classification	Azimuthal
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Global
Alias	geos
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=geos +h=35785831.0 +lon_0=-60 +sweep=y



Usage

In order to project using the geos projection you can do the following:

```
proj +proj=geos +h=35785831.0
```

The required argument h is the viewing point (satellite position) height above the earth.

The projection coordinate relate to the scanning angle by the following simple relation:

```
scanning_angle (radians) = projection_coordinate / h
```

Note on sweep angle

The viewing instrument on-board geostationary satellites described by this projection have a two-axis gimbal viewing geometry. This means that the different scanning positions are obtained by rotating the gimbal along a N/S axis (or y) and a E/W axis (or x).



In the image above, the outer-gimbal axis, or sweep-angle axis, is the N/S axis (y) while the inner-gimbal axis, or fixed-angle axis, is the E/W axis (x).

This example represents the scanning geometry of the Meteosat series satellite. However, the GOES satellite series use the opposite scanning geometry, with the E/W axis (x) as the sweep-angle axis, and the N/S (y) as the fixed-angle axis.

The sweep argument is used to tell PROJ which on which axis the outer-gimbal is rotating. The possible values are x or y, y being the default. Thus, the scanning geometry of the Meteosat series satellite should take sweep as x, and GOES should take sweep as y.

Parameters

Required

+h=<value>

Height of the view point above the Earth and must be in the same units as the radius of the sphere or semimajor axis of the ellipsoid.

Optional

+sweep=<axis>

Sweep angle axis of the viewing instrument. Valid options are “x” and “y”.

Defaults to “y”.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+ellps=<value>

See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

6.1.36 Ginsburg VIII (TsNIIGAiK)

+proj=gins8



6.1.37 General Sinusoidal Series

+proj=gn_sinu +m=2 +n=3



6.1.38 Gnomonic

+proj=gnom +lat_0=90 +lon_0=-50



6.1.39 Goode Homolosine

+proj=goode



6.1.40 Mod. Stereographics of 48 U.S.

+proj=gs48




6.1.41 Mod. Stereographics of 50 U.S.

+proj=gs50



6.1.42 Hammer & Eckert-Greifendorff


+proj=hammer



6.1.43 Hatano Asymmetrical Equal Area

Classification	<i>Pseudocylindrical Projection</i>
Available forms	Forward and inverse, spherical projection
Defined area	Global
Alias	hatano
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=hatano



Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

Mathematical Definition

Forward

$$x = 0.85\lambda \cos \theta$$

$$y = C_y \sin \theta$$

$$P(\theta) = 2\theta + \sin 2\theta - C_p \sin \phi$$

$$P'(\theta) = 2(1 + \cos 2\theta)$$

$$\theta_0 = 2\phi$$

Condition	C_y	C_p
For $\phi > 0$	1.75859	2.67595
For $\phi < 0$	1.93052	2.43763

For $\phi = 0$, $y \leftarrow 0$, and $x \leftarrow 0.85\lambda$.

Further reading

1. [Compare Map Projections](#)
2. [Mathworks](#)

6.1.44 HEALPix

Classification	Miscellaneous
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Global
Alias	healpix
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



The HEALPix projection is area preserving and can be used with a spherical and ellipsoidal model. It was initially developed for mapping cosmic background microwave radiation. The image below is the graphical representation of the mapping and consists of eight isomorphic triangular interrupted map graticules. The north and south contains four in which straight meridians converge polewards to a point and unequally spaced horizontal parallels. HEALPix provides a mapping in which points of equal latitude and equally spaced longitude are mapped to points of equal latitude and equally spaced longitude with the module of the polar interruptions.

Usage

To run a forward HEALPix projection on a unit sphere model, use the following command:

```
proj +proj=healpix +lon_0=0 +a=1 -E <<EOF
0 0
EOF
# output
0 0 0.00 0.00
```

Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>
False northing.

Defaults to 0.0.

+ellps=<value>
See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>
Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

Further reading

1. [NASA](#)
2. [Wikipedia](#)

6.1.45 rHEALPix

Classification	Miscellaneous
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Global
Alias	rhealpix
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates



rHEALPix is a projection based on the HEALPix projection. The implementation of rHEALPix uses the HEALPix projection. The rHEALPix combines the peaks of the HEALPix into a square. The square's position can be translated and rotated across the x-axis which is a novel approach for the rHEALPix projection. The initial intention of using rHEALPix in the Spatial Computation Engine Science Collaboration Environment (SCENZGrid).

Usage

To run a rHEALPix projection on a WGS84 ellipsoidal model, use the following command:

```
proj +proj=rhealpix -f '%.2f' +ellps=WGS84 +south_square=0 +north_square=2 -E << EOF
> 55 12
> EOF
55 12    6115727.86  1553840.13
```

Parameters

Note: All parameters for the projection are optional.

+north_square

Position of the north polar square. Valid inputs are 0–3.

Defaults to 0.0.

+south_square

Position of the south polar square. Valid inputs are 0–3.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to “WGS84”.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.


Defaults to 0.0.

Further reading

1. [NASA](#)
2. [Wikipedia](#)

6.1.46 Interrupted Goode Homolosine

`+proj=igh`



6.1.47 International Map of the World Polyconic

+proj=imw_p +lat_1=30 +lat_2=-40




6.1.48 Icosahedral Snyder Equal Area

+proj=isea




6.1.49 Kavraisky V

+proj=kav5



6.1.50 Kavraisky VII

+proj=kav7




6.1.51 Krovak

+proj=krovak




6.1.52 Laborde

+proj=labrd +lon_0=40 +lat_0=-10




6.1.53 Lambert Azimuthal Equal Area

+proj=laea



6.1.54 Lagrange

+proj=lagrng



6.1.55 Larrivee

+proj=larr



6.1.56 Laskowski

+proj=task



6.1.57 Lambert Conformal Conic

+proj=lcc +lon_0=-90




6.1.58 Lambert Conformal Conic Alternative

+proj=lcc+a+lat_0=35




6.1.59 Lambert Equal Area Conic

+proj=leac




6.1.60 Lee Oblated Stereographic

+proj=lee_os



6.1.61 Loximuthal

+proj=loxim



6.1.62 Space oblique for LANDSAT

+proj=lsat +path=2 +lsat=1


6.1.63 McBryde-Thomas Flat-Polar Sine (No. 1)

+proj=mbt_s



6.1.64 McBryde-Thomas Flat-Pole Sine (No. 2)

+proj=mbt_fps




6.1.65 McBride-Thomas Flat-Polar Parabolic

+proj=mbtfpp



6.1.66 McBryde-Thomas Flat-Polar Quartic

+proj=mbtfpq



6.1.67 McBryde-Thomas Flat-Polar Sinusoidal

+proj=mbtfps




6.1.68 Mercator

The Mercator projection is a cylindrical map projection that originates from the 15th century. It is widely recognized as the first regularly used map projection. The projection is conformal which makes it suitable for navigational purposes.

Classification	Conformal cylindrical
Available forms	Forward and inverse, spherical and elliptical projection
Defined area	Global, but best used near the equator
Alias	merc
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=merc



Usage

Applications should be limited to equatorial regions, but is frequently used for navigational charts with latitude of true scale (`+lat_ts`) specified within or near chart's boundaries. Often inappropriately used for world maps since the regions near the poles cannot be shown [[Evenden1995](#)].

Example using latitude of true scale:

```
$ echo 56.35 12.32 | proj +proj=merc +lat_ts=56.5  
3470306.37    759599.90
```

Example using scaling factor:

```
echo 56.35 12.32 | proj +proj=merc +k_0=2  
12545706.61    2746073.80
```

Note that `+lat_ts` and `+k_0` are mutually exclusive. If used together, `+lat_ts` takes precedence over `+k_0`.

Parameters

Note: All parameters for the projection are optional.

+lat_ts=<value>

Latitude of true scale. Defines the latitude where scale is not distorted. Takes precedence over `+k_0` if both options are used together.

Defaults to 0.0.

+k_0=<value>

Scale factor. Determines scale factor used in the projection.

Defaults to 1.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to "WGS84".

+R=<value>

Radius of the sphere given in meters. If used in conjunction with `+ellps` `+R` takes precedence.

Mathematical definition

The formulas describing the Mercator projection are all taken from G. Evenden's libproj manuals [*Evenden2005*].

Spherical form

For the spherical form of the projection we introduce the scaling factor:

$$k_0 = \cos \phi_{ts}$$

Forward projection

$$x = k_0 \lambda$$

$$y = k_0 \ln \left[\tan \left(\frac{\pi}{4} + \frac{\phi}{2} \right) \right]$$

Inverse projection

$$\lambda = \frac{x}{k_0}$$

$$\phi = \frac{\pi}{2} - 2 \arctan \left[e^{-y/k_0} \right]$$

Elliptical form

For the elliptical form of the projection we introduce the scaling factor:

$$k_0 = m(\phi_{ts})$$

where $m(\phi)$ is the parallel radius at latitude ϕ .

We also use the Isometric Latitude kernel function $t()$.

Note: $m()$ and $t()$ should be described properly on a separate page about the theory of projections on the ellipsoid.

Forward projection

$$x = k_0 \lambda$$

$$y = k_0 \ln t(\phi)$$

Inverse projection

$$\lambda = \frac{x}{k_0}$$

$$\phi = t^{-1} \left[e^{-y/k_0} \right]$$

Further reading

1. [Wikipedia](#)
2. [Wolfram Mathworld](#)

6.1.69 Miller Oblated Stereographic



6.1.70 Miller Cylindrical

The Miller cylindrical projection is a modified Mercator projection, proposed by Osborn Maitland Miller in 1942. The latitude is scaled by a factor of $\frac{4}{5}$, projected according to Mercator, and then the result is multiplied by $\frac{5}{4}$ to retain scale along the equator.

Classification	Neither conformal nor equal area cylindrical
Available forms	Forward and inverse spherical
Defined area	Global, but best used near the equator
Alias	mill
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=mill



Usage

The Miller Cylindrical projection is used for world maps and in several atlases, including the National Atlas of the United States (USGS, 1970, p. 330-331) [[Snyder1987](#)].

Example using Central meridian 90°W:

```
$ echo -100 35 | proj +proj=mill +lon_0=90w  
-1113194.91      4061217.24
```

Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

Mathematical definition

The formulas describing the Miller projection are all taken from Snyder's manuals [[Snyder1987](#)].

Forward projection

$$x = \lambda$$

$$y = 1.25 * \ln \left[\tan \left(\frac{\pi}{4} + 0.4 * \phi \right) \right]$$

Inverse projection

$$\lambda = x$$


$$\phi = 2.5 * (\arctan [e^{0.8*y}] - \frac{\pi}{4})$$

Further reading

1. [Wikipedia](#)

6.1.71 Mollweide

+proj=moll




6.1.72 Murdoch I

+proj=murd1 +lat_1=30 +lat_2=50



6.1.73 Murdoch II

+proj=murd2 +lat_1=30 +lat_2=50



6.1.74 Murdoch III


`+proj=murd3 +lat_1=30 +lat_2=50`



6.1.75 Natural Earth

Classification	Pseudo cylindrical
Available forms	Forward and inverse, spherical projection
Defined area	Global
Alias	natearth
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

`+proj=natearth`



The Natural Earth projection is intended for making world maps. A distinguishing trait is its slightly rounded corners fashioned to emulate the spherical shape of Earth. The meridians (except for the central meridian) bend acutely inward

as they approach the pole lines, giving the projection a hint of three-dimensionality. This bending also suggests that the meridians converge at the poles instead of truncating at the top and bottom edges. The distortion characteristics of the Natural Earth projection compare favorably to other world map projections.

Usage

The Natural Earth projection has no special options so usage is simple. Here is an example of an inverse projection on a sphere with a radius of 7500 m:

```
$ echo 3500 -8000 | proj -I +proj=natearth +a=7500  
37d54'6.091"E 61d23'4.582"S
```

Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.


Defaults to 0.0.

Further reading

1. [Wikipedia](#)


6.1.76 Nell

+proj=nell



6.1.77 Nell-Hammer

+proj=nell_h



6.1.78 Nicolosi Globular

+proj=nicol



6.1.79 Near-sided perspective

The near-sided perspective projection simulates a view from a height h similar to how a satellite in orbit would see it.

Classification	Azimuthal. Neither conformal nor equal area.
Available forms	Forward and inverse spherical projection
Defined area	Global, although for one hemisphere at a time.
Alias	nsper
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=nsper +h=3000000 +lat_0=-20 +lon_0=145



Parameters

Required

+h=<value>

Height of the view point above the Earth and must be in the same units as the radius of the sphere or semimajor axis of the ellipsoid.

Optional

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.


+y_0=<value>

False northing.

Defaults to 0.0.


6.1.80 New Zealand Map Grid

+proj=nzmg




6.1.81 General Oblique Transformation

+proj=ob_tran +o_proj=mill +o_lon_p=40 +o_lat_p=50 +lon_0=60




6.1.82 Oblique Cylindrical Equal Area

+proj=ocea




6.1.83 Oblated Equal Area

+proj=oea +m=1 +n=2




6.1.84 Oblique Mercator

+proj=omerc +lat_1=45 +lat_2=55



6.1.85 Ortelius Oval

`+proj=ortel`




6.1.86 Orthographic

The orthographic projection is a perspective azimuthal projection centered around a given latitude and longitude.

Classification	Azimuthal
Available forms	Forward and inverse, spherical projection
Defined area	Global, although only one hemisphere can be seen at a time
Alias	ortho
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

`+proj=ortho`



Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.


+y_0=<value>

False northing.

Defaults to 0.0.

6.1.87 Perspective Conic

+proj=pconic +lat_1=25 +lat_2=75



6.1.88 Polyconic (American)

+proj=poly




6.1.89 Putnins P1

+proj=putp1



6.1.90 Putnins P2

+proj=putp2




6.1.91 Putnins P3

+proj=putp3




6.1.92 Putnins P3'

+proj=putp3p




6.1.93 Putnins P4'

+proj=putp4p



6.1.94 Putnins P5

+proj=putp5



6.1.95 Putnins P5'

+proj=putp5p



6.1.96 Putnins P6

+proj=putp6



6.1.97 Putnins P6'

+proj=putp6p



6.1.98 Quartic Authalic

+proj=qua_au



6.1.99 Quadrilaterized Spherical Cube

Classification	Azimuthal
Available forms	Forward and inverse, elliptical projection
Defined area	Global
Alias	qsc
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

The purpose of the Quadrilaterized Spherical Cube (QSC) projection is to project a sphere surface onto the six sides of a cube:



For this purpose, other alternatives can be used, notably [Gnomonic](#) or [HEALPix](#). However, QSC projection has the following favorable properties:

It is an equal-area projection, and at the same time introduces only limited angular distortions. It treats all cube sides equally, i.e. it does not use different projections for polar areas and equatorial areas. These properties make QSC projection a good choice for planetary-scale terrain rendering. Map data can be organized in quadtree structures for each cube side. See [\[LambersKolb2012\]](#) for an example.

The QSC projection was introduced by [\[ONeilLaubscher1976\]](#), building on previous work by [\[ChanONeil1975\]](#). For clarity: The earlier QSC variant described in [\[ChanONeil1975\]](#) became known as the COBE QSC since it was used by the NASA Cosmic Background Explorer (COBE) project; it is an approximately equal-area projection and is not the same as the QSC projection.

See also [\[CalabrettaGreisen2002\]](#) Sec. 5.6.2 and 5.6.3 for a description of both and some analysis.

In this implementation, the QSC projection projects onto one side of a circumscribed cube. The cube side is selected by choosing one of the following six projection centers:

+lat_0=0 +lon_0=0	front cube side
+lat_0=0 +lon_0=90	right cube side
+lat_0=0 +lon_0=180	back cube side
+lat_0=0 +lon_0=-90	left cube side
+lat_0=90	top cube side
+lat_0=-90	bottom cube side

Furthermore, this implementation allows the projection to be applied to ellipsoids. A preceding shift to a sphere is performed automatically; see [\[LambersKolb2012\]](#) for details.

Usage

The following example uses QSC projection via GDAL to create the six cube side maps from a world map for the WGS84 ellipsoid:

```
gdalwarp -t_srs "+wktext +proj=qsc +units=m +ellps=WGS84 +lat_0=0 +lon_0=0" \
    -wo SOURCE_EXTRA=100 -wo SAMPLE_GRID=YES -te -6378137 -6378137 6378137 6378137 \
    worldmap.tif frontside.tif

gdalwarp -t_srs "+wktext +proj=qsc +units=m +ellps=WGS84 +lat_0=0 +lon_0=90" \
    -wo SOURCE_EXTRA=100 -wo SAMPLE_GRID=YES -te -6378137 -6378137 6378137 6378137 \
    worldmap.tif rightside.tif

gdalwarp -t_srs "+wktext +proj=qsc +units=m +ellps=WGS84 +lat_0=0 +lon_0=180" \
    -wo SOURCE_EXTRA=100 -wo SAMPLE_GRID=YES -te -6378137 -6378137 6378137 6378137 \
    worldmap.tif backside.tif

gdalwarp -t_srs "+wktext +proj=qsc +units=m +ellps=WGS84 +lat_0=0 +lon_0=-90" \
    -wo SOURCE_EXTRA=100 -wo SAMPLE_GRID=YES -te -6378137 -6378137 6378137 6378137 \
    worldmap.tif leftside.tif

gdalwarp -t_srs "+wktext +proj=qsc +units=m +ellps=WGS84 +lat_0=90 +lon_0=0" \
    -wo SOURCE_EXTRA=100 -wo SAMPLE_GRID=YES -te -6378137 -6378137 6378137 6378137 \
    worldmap.tif topside.tif

gdalwarp -t_srs "+wktext +proj=qsc +units=m +ellps=WGS84 +lat_0=-90 +lon_0=0" \
    -wo SOURCE_EXTRA=100 -wo SAMPLE_GRID=YES -te -6378137 -6378137 6378137 6378137 \
    worldmap.tif bottomside.tif
```

Explanation:

- QSC projection is selected with `+wktext +proj=qsc`.
- The WGS84 ellipsoid is specified with `+ellps=WGS84`.
- The cube side is selected with `+lat_0=... +lon_0=....`
- The `-wo` options are necessary for GDAL to avoid holes in the output maps.
- The `-te` option limits the extends of the output map to the major axis diameter (from `-radius` to `+radius` in both x and y direction). These are the dimensions of one side of the circumscribing cube.

The resulting images can be laid out in a grid like below.



Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+ellps=<value>

See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.


Defaults to 0.0.

Further reading

1. [Wikipedia](#)
2. [NASA](#)


6.1.100 Robinson

+proj=robin




6.1.101 Roussilhe Stereographic

+proj=rouss




6.1.102 Rectangular Polyconic

+proj=rpoly



6.1.103 Sinusoidal (Sanson-Flamsteed)

+proj=sinu



MacBryde and Thomas developed generalized formulas for several of the pseudocylindricals with sinusoidal meridians:

$$x = C\lambda(m + \cos\theta)/(m + 1)$$

$$y = C\theta$$

$$C = \sqrt{(m + 1)/n}$$


6.1.104 Swiss. Obl. Mercator

+proj=somerc




6.1.105 Stereographic

+proj=stere +lat_0=90 +lat_ts=75




6.1.106 Oblique Stereographic Alternative

+proj=sterea +lat_0=90




6.1.107 Gauss-Schreiber Transverse Mercator (aka Gauss-Laborde Reunion)


+proj=gstmerc



6.1.108 Transverse Central Cylindrical



6.1.109 Transverse Cylindrical Equal Area



6.1.110 Tissot

+proj=tissot +lat_1=60 +lat_2=65



6.1.111 Transverse Mercator

The transverse Mercator projection in its various forms is the most widely used projected coordinate system for world topographical and offshore mapping.

Classification	Transverse and oblique cylindrical
Available forms	Forward and inverse, Spherical and Elliptical
Defined area	Global, but reasonably accurate only within 15 degrees of the central meridian
Alias	tmerc
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=tmerc



Usage

Prior to the development of the Universal Transverse Mercator coordinate system, several European nations demonstrated the utility of grid-based conformal maps by mapping their territory during the interwar period. Calculating the distance between two points on these maps could be performed more easily in the field (using the Pythagorean theorem) than was possible using the trigonometric formulas required under the graticule-based system of latitude and longitude. In the post-war years, these concepts were extended into the Universal Transverse Mercator/Universal Polar Stereographic (UTM/UPS) coordinate system, which is a global (or universal) system of grid-based maps.

The following table gives special cases of the Transverse Mercator projection.

Projection Name	Areas	Central meridian	Zone width	Scale Factor
Transverse Mercator	World wide	Various	less than 6°	Vari-ous
Transverse Mercator south oriented	Southern Africa	2° intervals E of 11°E	2°	1.000
UTM North hemisphere	World wide equator to 84°N	6° intervals E & W of 3° E & W	Always 6°	0.9996
UTM South hemisphere	World wide north of 80°S to equator	6° intervals E & W of 3° E & W	Always 6°	0.9996
Gauss-Kruger	Former USSR, Yugoslavia, Germany, S. America, China	Various, according to area	Usually less than 6°, often less than 4°	1.0000
Gauss Boaga	Italy	Various, according to area	6°	0.9996

Example using Gauss-Kruger on Germany area (aka EPSG:31467)

```
$ echo 9 51 | proj +proj=tmerc +lat_0=0 +lon_0=9 +k=1 +x_0=3500000 +y_0=0 ↵
+ellps=bessel +datum=potsdam +units=m +no_defs
3500000.00 5651505.56
```

Example using Gauss Boaga on Italy area (EPSG:3004)

```
$ echo 15 42 | proj +proj=tmerc +lat_0=0 +lon_0=15 +k=0.9996 +x_0=2520000 +y_0=0 ↵
+ellps=intl +units=m +no_defs
2520000.00 4649858.60
```

Parameters

Note: All parameters for the projection are optional.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to “WGS84”.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+k_0=<value>

Scale factor. Determines scale factor used in the projection.

Defaults to 1.0.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

Mathematical definition

The formulas describing the Transverse Mercator are all taken from Evenden’s [[Evenden2005](#)].

ϕ_0 is the latitude of origin that match the center of the map. It can be set with +lat_0.

k_0 is the scale factor at the natural origin (on the central meridian). It can be set with +k_0.

$M(\phi)$ is the meridional distance.

Spherical form

Forward projection

$$B = \cos \phi \sin \lambda$$

$$x = \frac{k_0}{2} \ln\left(\frac{1+B}{1-B}\right)$$

$$y = k_0 \left(\arctan\left(\frac{\tan(\phi)}{\cos \lambda}\right) - \phi_0 \right)$$

Inverse projection

$$D = \frac{y}{k_0} + \phi_0$$

$$x' = \frac{x}{k_0}$$

$$\phi = \arcsin\left(\frac{\sin D}{\cosh x'}\right)$$

$$\lambda = \arctan\left(\frac{\sinh x'}{\cos D}\right)$$

Elliptical form

Forward projection

$$\begin{aligned}
 N &= \frac{k_0}{(1 - e^2 \sin^2 \phi)^{1/2}} \\
 R &= \frac{k_0(1 - e^2)}{(1 - e^2 \sin^2 \phi)^{3/2}} \\
 t &= \tan(\phi) \\
 \eta &= \frac{e^2}{1 - e^2} \cos^2 \phi \\
 x &= k_0 \lambda \cos \phi \\
 &\quad + \frac{k_0 \lambda^3 \cos^3 \phi}{3!} (1 - t^2 + \eta^2) \\
 &\quad + \frac{k_0 \lambda^5 \cos^5 \phi}{5!} (5 - 18t^2 + t^4 + 14\eta^2 - 58t^2\eta^2) \\
 &\quad + \frac{k_0 \lambda^7 \cos^7 \phi}{7!} (61 - 479t^2 + 179t^4 - t^6) \\
 y &= M(\phi) \\
 &\quad + \frac{k_0 \lambda^2 \sin(\phi) \cos \phi}{2!} \\
 &\quad + \frac{k_0 \lambda^4 \sin(\phi) \cos^3 \phi}{4!} (5 - t^2 + 9\eta^2 + 4\eta^4) \\
 &\quad + \frac{k_0 \lambda^6 \sin(\phi) \cos^5 \phi}{6!} (61 - 58t^2 + t^4 + 270\eta^2 - 330t^2\eta^2) \\
 &\quad + \frac{k_0 \lambda^8 \sin(\phi) \cos^7 \phi}{8!} (1385 - 3111t^2 + 543t^4 - t^6)
 \end{aligned}$$

Inverse projection

$$\phi_1 = M^{-1}(y)$$

$$\begin{aligned}
 N_1 &= \frac{k_0}{(1 - e^2 \sin^2 \phi_1)^{1/2}} \\
 R_1 &= \frac{k_0(1 - e^2)}{(1 - e^2 \sin^2 \phi_1)^{3/2}} \\
 t_1 &= \tan(\phi_1) \\
 \eta_1 &= \frac{e^2}{1 - e^2} \cos^2 \phi_1
 \end{aligned}$$

$$\begin{aligned}\phi &= \phi_1 \\ &\quad - \frac{t_1 x^2}{2! R_1 N_1} \\ &\quad + \frac{t_1 x^4}{4! R_1 N_1^3} (5 + 3t_1^2 + \eta_1^2 - 4\eta_1^4 - 9\eta_1^2 t_1^2) \\ &\quad - \frac{t_1 x^6}{6! R_1 N_1^5} (61 + 90t_1^2 + 46\eta_1^2 + 45t_1^4 - 252t_1^2\eta_1^2) \\ &\quad + \frac{t_1 x^8}{8! R_1 N_1^7} (1385 + 3633t_1^2 + 4095t_1^4 + 1575t_1^6) \\ \lambda &= \frac{x}{\cos \phi N_1} \\ &\quad - \frac{x^3}{3! \cos \phi N_1^3} (1 + 2t_1^2 + \eta_1^2) \\ &\quad + \frac{x^5}{5! \cos \phi N_1^5} (5 + 6\eta_1^2 + 28t_1^2 - 3\eta_1^2 + 8t_1^2\eta_1^2) \\ &\quad - \frac{x^7}{7! \cos \phi N_1^7} (61 + 662t_1^2 + 1320t_1^4 + 720t_1^6)\end{aligned}$$

Further reading

1. [Wikipedia](#)
2. EPSG, POSC literature pertaining to Coordinate Conversions and Transformations including Formulas

6.1.112 Two Point Equidistant

+proj=tpeqd +lat_1=60 +lat_2=65



6.1.113 Tilted perspective

Classification	Azimuthal
Available forms	Forward and inverse, spherical projection
Defined area	Global
Alias	tpers
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

+proj=tpers +h=5500000 +lat_0=40



Tilted Perspective is similar to [Near-sided perspective](#) (`nsper`) in that it simulates a perspective view from a height. Where `nsper` projects onto a plane tangent to the surface, Tilted Perspective orients the plane towards the direction of the view. Thus, extra parameters specifying azimuth and tilt are required beyond `nsper`'s `h`. As with `nsper`, `lat_0` & `lon_0` are also required for satellite position.

Parameters

Required

+h=<value>

Height of the view point above the Earth and must be in the same units as the radius of the sphere or semimajor axis of the ellipsoid.

Optional

+azimuth=<value>

Bearing in degrees away from north.

Defaults to 0.0.

+tilt=<value>

Angle in degrees away from nadir.

Defaults to 0.0.

+lon_0=<value>

Longitude of projection center.

Defaults to 0.0.

+lat_0=<value>

Latitude of projection center.

Defaults to 0.0.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

6.1.114 Universal Polar Stereographic

+proj=ups



6.1.115 Urmaev V

+proj=urm5 +n=0.9 +alpha=2 +q=4




6.1.116 Urmaev Flat-Polar Sinusoidal

+proj=urmfps +n=0.5




6.1.117 Universal Transverse Mercator (UTM)

+proj=utm



6.1.118 van der Grinten (I)

+proj=vandg




6.1.119 van der Grinten II

+proj=vandg2




6.1.120 van der Grinten III

+proj=vandg3



6.1.121 van der Grinten IV

+proj=vandg4




6.1.122 Vitkovsky I

+proj=vitk1 +lat_1=45 +lat_2=55




6.1.123 Wagner I (Kavraisky VI)

+proj=wag1



6.1.124 Wagner II

+proj=wag2




$$x = 0.92483\lambda \cos \theta$$

$$y = 1.38725\theta$$

$$\sin \theta = 0.88022 \sin(0.8855\phi)$$

6.1.125 Wagner III

+proj=wag3




$$x = [\cos \phi_{ts} / \cos(2\phi_{ts}/3)]\lambda \cos(2\phi/3)$$

$$y = \phi$$


6.1.126 Wagner IV

+proj=wag4




6.1.127 Wagner V

+proj=wag5




6.1.128 Wagner VI

+proj=wag6



6.1.129 Wagner VII

+proj=wag7



6.1.130 Web Mercator / Pseudo Mercator

New in version 5.1.0.

The Web Mercator / Pseudo Mercator projection is a cylindrical map projection. This is a variant of the regular *Mercator* projection, except that the computation is done on a sphere, using the semi-major axis of the ellipsoid.

From [Wikipedia](#):

This projection is widely used by the Web Mercator, Google Web Mercator, Spherical Mercator, WGS 84 Web Mercator[1] or WGS 84/Pseudo-Mercator is a variant of the Mercator projection and is the de facto standard for Web mapping applications. [...] It is used by virtually all major online map providers [...] Its official EPSG identifier is EPSG:3857, although others have been used historically.

Classification	Cylindrical (non conformant if used with ellipsoid)
Available forms	Forward and inverse, spherical projection
Defined area	Global, but best used near the equator
Alias	webmerc
Domain	2D
Input type	Geodetic coordinates
Output type	Projected coordinates

Usage

Example:

```
$ echo 2 49 | proj +proj=webmerc +datum=WGS84  
222638.98      6274861.39
```

Parameters

Note: All parameters for the projection are optional.

+R=<value>

Radius of the sphere given in meters. If used in conjunction with +ellps +R takes precedence.

+x_0=<value>

False easting.

Defaults to 0.0.

+y_0=<value>

False northing.

Defaults to 0.0.

Mathematical definition

The formulas describing the Mercator projection are all taken from G. Evenden's libproj manuals [[Evenden2005](#)].

Forward projection

$$x = \lambda$$

$$y = \ln \left[\tan \left(\frac{\pi}{4} + \frac{\phi}{2} \right) \right]$$

Inverse projection

$$\lambda = x$$


$$\phi = \frac{\pi}{2} - 2 \arctan [e^{-y}]$$

Further reading

1. [Wikipedia](#)


6.1.131 Werenskiold I

+proj=weren




6.1.132 Winkel I

+proj=winkel




6.1.133 Winkel II

+proj=wink2



6.1.134 Winkel Tripel

+proj=wintri



6.2 Conversions

Conversions are coordinate operations in which both coordinate reference systems are based on the same datum. In PROJ projections are differentiated from conversions.

6.2.1 Axis swap

New in version 5.0.0.

Change the order and sign of 2,3 or 4 axes.

Alias	axisswap
Domain	2D, 3D or 4D
Input type	Any
Output type	Any

Each of the possible four axes are numbered with 1–4, such that the first input axis is 1, the second is 2 and so on. The output ordering is controlled by a list of the input axes re-ordered to the new mapping.

Usage

Reversing the order of the axes:

```
+proj=axisswap +order=4,3,2,1
```

Swapping the first two axes (x and y):

```
+proj=axisswap +order=2,1,3,4
```

The direction, or sign, of an axis can be changed by adding a minus in front of the axis-number:

```
+proj=axisswap +order=1,-2,3,4
```

It is only necessary to specify the axes that are affected by the swap operation:

```
+proj=axisswap +order=2,1
```

Parameters

+order=<list>

Ordered comma-separated list of axis, e.g. `+order=2,1,3,4`. Adding a minus in front of an axis number results in a change of direction for that axis, e.g. southward instead of northward.

Required.

6.2.2 Cartesian to geodetic conversion

New in version 5.0.0.

Convert geodetic coordinates to cartesian coordinates.

Alias	cart
Domain	3D
Input type	Cartesian coordinates
Output type	Cartesian coordinates

Parameters

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to “WGS84”.

6.2.3 Lat/long (Geodetic alias)

Passes geodetic coordinates through unchanged.

Aliases	latlon, latlong, lonlat, longlat
Domain	2D
Input type	Geodetic coordinates
Output type	Geodetic coordinates

Note: Can not be used with the `proj` application.

Parameters

No parameters will affect the output of the operation if used on its own. However, the parameters below can be used in a declarative manner when used with `cs2cs` or in a *transformation pipeline*.

+ellps=<value>

See `proj -le` for a list of available ellipsoids.

Defaults to “WGS84”.

+datum=<value>

Declare the datum used with the coordinates. See `cs2cs -l` for a list of available datums.

+towgs84=<list>

A list of three or seven *Helmer* parameters that maps the input coordinates to the WGS84 datum.

6.2.4 Unit conversion

New in version 5.0.0.

Convert between various distance and time units.

Alias	unitconvert
Domain	2D, 3D or 4D
Input type	Any
Output type	Any

There are many examples of coordinate reference systems that are expressed in other units than the meter. There are also many cases where temporal data has to be translated to different units. The *unitconvert* operation takes care of that.

Many North American systems are defined with coordinates in feet. For example in Vermont:

```
+proj=pipeline
+step +proj=tmerc +lat_0=42.5 +lon_0=-72.5 +k=0.999964286 +x_0=500000.00001016 +y_0=0
+step +proj=unitconvert +xy_in=m +xy_out=us-ft
```

Often when working with GNSS data the timestamps are presented in GPS-weeks, but when the data transformed with the *helmert* operation timestamps are expected to be in units of decimalyears. This can be fixed with *unitconvert*:

```
+proj=pipeline
+step +proj=unitconvert +t_in=gpsweek +t_out=decimalyear
+step +proj=helmert +epoch=2000.0 +t_obs=2017.5 ...
```

Parameters

+xy_in=<unit>

Horizontal input units. See [Distance units](#) for a list of available units.

+xy_out=<unit>

Horizontal output units. See [Distance units](#) for a list of available units.

+z_in=<unit>

Vertical output units. See [Distance units](#) for a list of available units.

+z_out=<unit>

Vertical output units. See [Distance units](#) for a list of available units.

+t_in=<unit>

Temporal input units. See [Time units](#) for a list of available units.

+t_out=<unit>

Temporal output units. See [Time units](#) for a list of available units.

Distance units

In the table below all distance units supported by PROJ is listed. The same list can also be produced on the command line with **proj** or **cs2cs**, by adding the **-lu** flag when calling the utility.

Label	Name
km	Kilometer
m	Meter
dm	Decimeter
cm	Centimeter
mm	Millimeter
kmi	International Nautical Mile
in	International Inch
ft	International Foot
yd	International Yard
mi	International Statute Mile
fath	International Fathom
ch	International Chain
link	International Link
us-in	U.S. Surveyor's Inch
us-ft	U.S. Surveyor's Foot
us-yd	U.S. Surveyor's Yard
us-ch	U.S. Surveyor's Chain
us-mi	U.S. Surveyor's Statute Mile
ind-yd	Indian Yard
ind-ft	Indian Foot
ind-ch	Indian Chain

Time units

In the table below all time units supported by PROJ is listed.

label	Name
mjd	Modified Julian date
decimalyear	Decimal year
gps_week	GPS Week
yyyymmdd	Date in yyyymmdd format

6.3 Transformations

Transformations coordinate operation in which the two coordinate reference systems are based on different datums.

6.3.1 Kinematic datum shifting utilizing a deformation model

New in version 5.0.0.

Perform datum shifts means of a deformation/velocity model.

Input type	Cartesian coordinates (spatial), decimalyears (temporal).
Output type	Cartesian coordinates (spatial), decimalyears (temporal).
Domain	4D
Input type	Geodetic coordinates
Output type	Geodetic coordinates

The deformation operation is used to adjust coordinates for intraplate deformations. Usually the transformation parameters for regional plate-fixed reference frames such as the ETRS89 does not take intraplate deformation into account. It is assumed that tectonic plate of the region is rigid. Often times this is true, but near the plate boundary and in areas with post-glacial uplift the assumption breaks. Intraplate deformations can be modelled and then applied to the coordinates so that they represent the physical world better. In PROJ this is done with the deformation operation.

The horizontal grid is stored in CTable2 format and the vertical grid is stored in the GTX format. Both grids are expected to contain grid-values in units of mm/year. Details about the formats can be found in the GDAL documentation. GDAL both reads and writes both file formats. Using GDAL for construction of new grids is recommended.

Example

In [Häkli2016] coordinate transformation including a deformation model is described. The paper describes how coordinates from the global ITRFxx frames are transformed to the local Nordic realisations of ETRS89. Scandinavia is an area with significant post-glacial rebound. The deformations from the post-glacial uplift is not accounted for in the official ETRS89 transformations so in order to get accurate transformations in the Nordic countries it is necessary to apply the deformation model. The transformation from ITRF2008 to the Danish realisation of ETRS89 is in PROJ described as:

```
proj = pipeline ellps = GRS80
      # ITRF2008@t_obs -> ITRF2000@t_obs
step   init = ITRF2008:ITRF2000
      # ITRF2000@t_obs -> ETRF2000@t_obs
step   proj=helmert t_epoch = 2000.0 transpose
```

(continues on next page)

(continued from previous page)

```

x = 0.054 rx = 0.000891 drx = 8.1e-05
y = 0.051 ry = 0.00539 dry = 0.00049
z = -0.048 rz = -0.008712 drz = -0.000792
# ETRF2000@t_obs -> NKG_ETRF00@2000.0
step proj = deformation t_epoch = 2000.0
xy_grids = ./nkgrf03vel_realigned_xy.ct2
z_grids = ./nkgrf03vel_realigned_z.gtx
# NKG_ETRF@2000.0 -> ETRF92@2000.0
step proj=helmert transpose s = -0.009420e
x = 0.03863 rx = 0.00617753
y = 0.147 ry = 5.064e-05
z = 0.02776 rz = 4.729e-05
# ETRF92@2000.0 -> ETRF92@1994.704
step proj = deformation t_epoch = 1994.704 t_obs = 2000.0
xy_grids = ./nkgrf03vel_realigned_xy.ct2
z_grids = ./nkgrf03vel_realigned_z.gtx

```

From this we can see that the transformation from ITRF2008 to the Danish realisation of ETRS89 is a combination of Helmert transformations and adjustments with a deformation model. The first use of the deformation operation is:

```

proj = deformation t_epoch = 2000.0
xy_grids = ./nkgrf03vel_realigned_xy.ct2
z_grids = ./nkgrf03vel_realigned_z.gtx

```

Here we set the central epoch of the transformation, 2000.0. The observation epoch is expected as part of the input coordinate tuple. The deformation model is described by two grids, specified with `+xy_grids` and `+z_grids`. The first is the horizontal part of the model and the second is the vertical component.

Parameters

Required

+xy_grids=<list>

Comma-separated list of grids to load. If a grid is prefixed by an @ the grid is considered optional and PROJ will not complain if the grid is not available.

Grids for the horizontal component of a deformation model is expected to be in CTABLE2 format.

+z_grids=<list>

Comma-separated list of grids to load. If a grid is prefixed by an @ the grid is considered optional and PROJ will not complain if the grid is not available.

Grids for the vertical component of a deformation model is expected to be in either GTX format.

+t_epoch=<value>

Central epoch of transformation given in decimal years.

Optional

+t_obs=<value>

Observation time of coordinate(s) given in decimal years. If not specified, the observation time from the temporal component of 4D input points is used.

Mathematical description

Mathematically speaking, application of a deformation model is simple. The deformation model is represented as a grid of velocities in three dimensions. Coordinate corrections are applied in cartesian space. For a given coordinate, (X, Y, Z) , velocities (V_X, V_Y, V_Z) can be interpolated from the gridded model. The time span between t_c and t_{obs} determine the magnitude of the coordinate correcton as seen in eq. (6.1) below.

$$\begin{pmatrix} X \\ Y \\ Z \end{pmatrix}_B = \begin{pmatrix} X \\ Y \\ Z \end{pmatrix}_A + (t_c - t_{obs}) \begin{pmatrix} V_X \\ V_Y \\ V_Z \end{pmatrix} \quad (6.1)$$

Corrections are done in cartesian space.

Coordinates of the gridded model are in ENU (east, north, up) space because it would otherwise require an enormous 3 dimensional grid to handle the corrections in cartesian space. Keeping the correction in lat/long space reduces the complexity of the grid significantly. Consequently though, the input coordinates needs to be converted to lat/long space when searching for corrections in the grid. This is done with the *cart* operation. The converted grid corrections can then be applied to the input coordinates in cartesian space. The conversion from ENU space to cartesian space is done in the following way:

$$\begin{pmatrix} X \\ Y \\ Z \end{pmatrix} = \begin{pmatrix} -\sin \phi \cos \lambda N - \sin \lambda E + \cos \phi \cos \lambda U \\ -\sin \phi \sin \lambda N + \sin \lambda E + \cos \phi \sin \lambda U \\ \cos \phi N + \sin \phi U \end{pmatrix} \quad (6.1)$$

where ϕ and λ are the latitude and longitude of the coordinate that is searched for in the grid. (E, N, U) are the grid values in ENU-space and (X, Y, Z) are the corrections converted to cartesian space.

6.3.2 Helmert transform

New in version 5.0.0.

The Helmert transformation changes coordinates from one reference frame to another by means of 3-, 4-and 7-parameter shifts, or one of their 6-, 8- and 14-parameter kinematic counterparts.

Alias	helmert
Domain	2D, 3D and 4D
Input type	Cartesian coordinates (spatial), decimalyears (temporal).
Output type	Cartesian coordinates (spatial), decimalyears (temporal).
Input type	Cartesian coordinates
Output type	Cartesian coordinates

The Helmert transform, in all it's various incarnations, is used to perform reference frame shifts. The transformation operates in cartesian space. It can be used to transform planar coordinates from one datum to another, transform 3D cartesian coordinates from one static reference frame to another or it can be used to do fully kinematic transformations from global reference frames to local static frames.

All of the parameters described in the table above are marked as optional. This is true as long as at least one parameter is defined in the setup of the transformation. The behaviour of the transformation depends on which parameters are used in the setup. For instance, if a rate of change parameter is specified a kinematic version of the transformation is used.

The kinematic transformations require an observation time of the coordinate, as well as a central epoch for the transformation. The latter is usually documented alongside the rest of the transformation parameters for a given transformation. The central epoch is controlled with the parameter *t_epoch*. The observation time can either be stated as part of the coordinate when using PROJ's 4D-functionality or it can be controlled in the transformation setup by the parameter *t_obs*. When *t_obs* is specified, all transformed coordinates are treated as if they have the same observation time.

Examples

Transforming coordinates from NAD72 to NAD83 using the 4 parameter 2D Helmert:

```
proj=helmert ellps=GRS80 x=-9597.3572 y=.6112  
s=0.304794780637 theta=-1.244048
```

Simplified transformations from ITRF2008/IGS08 to ETRS89 using 7 parameters:

```
proj=helmert ellps=GRS80 x=0.67678     y=0.65495     z=-0.52827  
rx=-0.022742 ry=0.012667 rz=0.022704 s=-0.01070
```

Transformation from *ITRF2000@2017.0* to *ITRF93@2017.0* using 15 parameters:

```
proj=helmert ellps=GRS80  
x=0.0127      y=0.0065      z=-0.0209    s=0.00195  
dx=-0.0029    dy=-0.0002    dz=-0.0006   ds=0.00001  
rx=-0.00039   ry=0.00080   rz=-0.00114  
drx=-0.00011  dry=-0.00019 drz=0.00007  
t_epoch=1988.0 t_obs=2017.0 transpose
```

Parameters

Note: All parameters are optional but at least one should be used, otherwise the operation will return the coordinates unchanged.

+x=<value>

Translation of the x-axis given in meters.

+y=<value>

Translation of the x-axis given in meters.

+z=<value>

Translation of the z-axis given in meters.

+s=<value>

Scale factor given in ppm.

+rx=<value>

X-axis rotation in the 3D Helmert given arc seconds.

+ry=<value>

Y-axis rotation in the 3D Helmert given in arc seconds.

+rz=<value>

Z-axis rotation in the 3D Helmert given in arc seconds.

+theta=<value>

Rotation angle in the 2D Helmert given in arc seconds.

+dx=<value>

Translation rate of the x-axis given in m/year.

+dy=<value>

Translation rate of the y-axis given in m/year.

+dz=<value>

Translation rate of the z-axis given in m/year.

+ds=<value>

Scale rate factor given in ppm/year.

+drx=<value>

Rotation rate of the x-axis given in arc seconds/year.

+dry=<value>

Rotation rate of the y-axis given in arc seconds/year.

+drz=<value>

Rotation rate of the z-axis given in arc seconds/year.

+t_epoch=<value>

Central epoch of transformation given in decimalyear. Only used spatiotemporal transformations.

+t_obs=<value>

Observation time of coordinate(s) given in decimalyear. Mostly useful in 2D and 3D transformations where the observation time is not passed as part of the input coordinate. Can be used to override the observation time from the input coordinate.

+exact

Use exact transformation equations.

See (6.6)

+transposeTranspose rotation matrix and follow the **Coordinate Frame** rotation convention. If **+transpose** is not added the **Position Vector** rotation convention is used.

Mathematical description

In the notation used below, \hat{P} is the rate of change of a given transformation parameter P . \dot{P} is the kinematically adjusted version of P , described by

$$\dot{P} = P + \hat{P} (t - t_{central}) \quad (6.1)$$

where t is the observation time of the coordinate and $t_{central}$ is the central epoch of the transformation. Equation (6.1) can be used to propagate all transformation parameters in time.

Superscripts of vectors denote the reference frame the coordinates in the vector belong to.

2D Helmert

The simplest version of the Helmert transform is the 2D case. In the 2-dimensional case only the horizontal coordinates are changed. The coordinates can be translated, rotated and scaled. Translation is controlled with the x and y parameters. The rotation is determined by *theta* and the scale is controlled with the s parameters.

Note: The scaling parameter s is unitless for the 2D Helmert, as opposed to the 3D version where the scaling parameter is given in units of ppm.

Mathematically the 2D Helmert is described as:

$$\begin{bmatrix} X \\ Y \end{bmatrix}^B = \begin{bmatrix} T_x \\ T_y \end{bmatrix} + s \begin{bmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} X \\ Y \end{bmatrix}^A \quad (6.2)$$

(6.2) can be extended to a time-varying kinematic version by adjusting the parameters with (6.1) to (6.2), which yields the kinematic 2D Helmert transform:

$$\begin{bmatrix} X \\ Y \end{bmatrix}^B = \begin{bmatrix} \dot{T}_x \\ \dot{T}_y \end{bmatrix} + s(t) \begin{bmatrix} \cos \dot{\theta} & \sin \dot{\theta} \\ -\sin \dot{\theta} & \cos \dot{\theta} \end{bmatrix} \begin{bmatrix} X \\ Y \end{bmatrix}^A \quad (6.2)$$

All parameters in (6.2) are determined by the use of (6.1), which applies the rate of change to each individual parameter for a given timespan between t and $t_{central}$.

3D Helmert

The general form of the 3D Helmert is

$$V^B = T + (1 + s \times 10^{-6}) \mathbf{R} V^A \quad (6.2)$$

Where T is a vector consisting of the three translation parameters, s is the scaling factor and \mathbf{R} is a rotation matrix. V^A and V^B are coordinate vectors, with V^A being the input coordinate and V^B is the output coordinate.

The rotation matrix is composed of three rotation matrices, one for each axis:

$$\mathbf{R}_X = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \phi & -\sin \phi \\ 0 & \sin \phi & \cos \phi \end{bmatrix} \quad (6.2)$$

$$\mathbf{R}_Y = \begin{bmatrix} \cos \theta & 0 & \sin \theta \\ 0 & 1 & 0 \\ -\sin \theta & 0 & \cos \theta \end{bmatrix} \quad (6.3)$$

$$\mathbf{R}_Z = \begin{bmatrix} \cos \psi & -\sin \psi & 0 \\ \sin \psi & \cos \psi & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad (6.4)$$

The three rotation matrices can be combined in one:

$$\mathbf{R} = \mathbf{R}_X \mathbf{R}_Y \mathbf{R}_Z \quad (6.5)$$

For \mathbf{R} , this yields:

$$\begin{bmatrix} \cos \theta \cos \psi & -\cos \phi \sin \psi + \sin \phi \sin \theta \cos \psi & \sin \phi \sin \psi + \cos \phi \sin \theta \cos \psi \\ \cos \theta \sin \psi & \cos \phi \cos \psi + \sin \phi \sin \theta \sin \psi & -\sin \phi \cos \psi + \cos \phi \sin \theta \sin \psi \\ -\sin \theta & \sin \phi \cos \theta & \cos \phi \cos \theta \end{bmatrix} \quad (6.6)$$

Using the small angle approximation the rotation matrix can be simplified to

$$\mathbf{R} = \begin{bmatrix} 1 & -R_z & R_y \\ R_z & 1 & -R_x \\ -R_y & R_x & 1 \end{bmatrix} \quad (6.7)$$

Which allow us to express the most common version of the Helmert transform, using the approximated rotation matrix:

$$\begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^B = \begin{bmatrix} T_x \\ T_y \\ T_z \end{bmatrix} + (1 + s \times 10^{-6}) \begin{bmatrix} 1 & -R_z & R_y \\ R_z & 1 & -R_x \\ -R_y & R_x & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^A \quad (6.7)$$

If the rotation matrix is transposed the transformation is effectively reversed. This is cause for some confusion since there is no correct way of defining the rotation matrix. Two conventions exists and they seem to be equally popular. PROJ uses the **Position Vector** rotation convention. The rotation matrix can be transposed by adding the `+transpose` flag in the transformation setup which makes PROJ follow the **Coordinate Frame** rotation convention.

Applying (6.1) we get the kinematic version of the approximated 3D Helmert:

$$\begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^B = \begin{bmatrix} \dot{T}_x \\ \dot{T}_y \\ \dot{T}_z \end{bmatrix} + (1 + \dot{s} \times 10^{-6}) \begin{bmatrix} 1 & -\dot{R}_z & \dot{R}_y \\ \dot{R}_z & 1 & -\dot{R}_x \\ -\dot{R}_y & \dot{R}_x & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^A \quad (6.7)$$

The Helmert transformation can be applied without using the rotation parameters, in which case it becomes a simple translation of the origin of the coordinate system. When using the Helmert in this version equation (6.2) simplifies to:

$$\begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^B = \begin{bmatrix} T_x \\ T_y \\ T_z \end{bmatrix} + \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^A \quad (6.7)$$

That after application of (6.1) has the following kinematic counterpart:

$$\begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^B = \begin{bmatrix} \dot{T}_x \\ \dot{T}_y \\ \dot{T}_z \end{bmatrix} + \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}^A \quad (6.7)$$

6.3.3 Molodensky transform

New in version 5.0.0.

The Molodensky transformation resembles a *Helmert transform* with zero rotations and a scale of unity, but converts directly from geodetic coordinates to geodetic coordinates, without the intermediate shifts to and from cartesian geocentric coordinates, associated with the Helmert transformation. The Molodensky transformation is simple to implement and to parameterize, requiring only the 3 shifts between the input and output frame, and the corresponding differences between the semimajor axes and flattening parameters of the reference ellipsoids. Due to its algorithmic simplicity, it was popular prior to the ubiquity of digital computers. Today, it is mostly interesting for historical reasons, but nevertheless indispensable due to the large amount of data that has already been transformed that way [[EversKnudsen2017](#)].

Alias	molodensky
Domain	3D
Input type	Geodetic coordinates (horizontal), meters (vertical)
output type	Geodetic coordinates (horizontal), meters (vertical)

The Molodensky transform can be used to perform a datum shift from coordinate (ϕ_1, λ_1, h_1) to (ϕ_2, λ_2, h_2) where the two coordinates are referenced to different ellipsoids. This is based on three assumptions:

1. The cartesian axes, X, Y, Z , of the two ellipsoids are parallel.
2. The offset, $\delta X, \delta Y, \delta Z$, between the two ellipsoid are known.
3. The characteristics of the two ellipsoids, expressed as the difference in semimajor axis (δa) and flattening (δf), are known.

The Molodensky transform is mostly used for transforming between old systems dating back to the time before computers. The advantage of the Molodensky transform is that it is fairly simple to compute by hand. The ease of computation come at the cost of limited accuracy.

A derivation of the mathematical formulas for the Molodensky transform can be found in [[Deakin2004](#)].

Examples

The abridged Molodensky:

```
proj=molodensky a=6378160 rf=298.25 da=-23 df=-8.120449e-8 dx=-134 dy=-48 dz=149
↪abridged
```

The same transformation using the standard Molodensky:

```
proj=molodensky a=6378160 rf=298.25 da=-23 df=-8.120449e-8 dx=-134 dy=-48 dz=149
```

Parameters

Required

+da=<value>
Difference in semimajor axis of the defining ellipsoids.

+df=<value>
Difference in flattening of the defining ellipsoids.

+dx=<value>
Offset of the X-axes of the defining ellipsoids.

+dy=<value>
Offset of the Y-axes of the defining ellipsoids.

+dz=<value>
Offset of the Z-axes of the defining ellipsoids.

+ellps=<value>
See [proj -le](#) for a list of available ellipsoids.

Defaults to “WGS84”.

Optional

+abridged
Use the abridged version of the Molodensky transform.

6.3.4 Horizontal grid shift

New in version 5.0.0.

Change of horizontal datum by grid shift.

Domain	2D, 3D and 4D
Input type	Geodetic coordinates (horizontal), meters (vertical), decimalyear (temporal)
Output type	Geodetic coordinates (horizontal), meters (vertical), decimalyear (temporal)

The horizontal grid shift is done by offsetting the planar input coordinates by a specific amount determined by the loaded grids. The simplest use case of the horizontal grid shift is applying a single grid:

```
+proj=hgridshift +grids=nzgr2kgrid0005.gsb
```

More than one grid can be loaded at the same time, for instance in case the dataset needs to be transformed spans several countries. In this example grids of the continental US, Alaska and Canada is loaded at the same time:

```
+proj=hgridshift +grids=@conus,@alaska,@ntv2_0.gsb,@ntv_can.dat
```

The @ in the above example states that the grid is optional, in case the grid is not found in the PROJ search path. The list of grids is prioritized so that grids in the start of the list takes precedence over the grids in the back of the list.

PROJ supports CTable2, NTv1 and NTv2 files for horizontal grid corrections. Details about all three formats can be found in the GDAL documentation. GDAL reads and writes all three formats. Using GDAL for construction of new grids is recommended.

Temporal gridshifting

New in version 5.1.0.

By initializing the horizontal gridshift operation with a central epoch, it can be used as a step function applying the grid offsets only if a coordinate is transformed from an epoch before grids central epoch to an epoch after. This is handy in transformations where it is necessary to handle deformations caused by seismic activity.

The central epoch of the grid is controlled with `+t_epoch` and the final epoch of the coordinate is set with `+t_final`. The observation epoch of the coordinate is part of the coordinate tuple.

Suppose we want to model the deformation of the 2008 earthquake in Iceland in a transformation of data from 2005 to 2009:

```
echo 63.992 -21.014 10.0 2005.0 | cct +proj=hgridshift +grids=iceland2008.gsb +t_
˓→epoch=2008.4071 +t_final=2009.0
63.9920021 -21.0140013 10.0 2005.0
```

Note: The timestamp of the resulting coordinate is still 2005.0. The observation time is always kept unchanged as it would otherwise be impossible to do the inverse transformation.

Temporal gridshifting is especially powerful in transformation pipelines where several gridshifts can be chained together, effectively acting as a series of step functions that can be applied to a coordinate that is propagated through time. In the following example we establish a pipeline that allows transformation of coordinates from any given epoch up until the current date, applying only those gridshifts that have central epochs between the observation epoch and the final epoch:

```
+proj=pipeline +t_final=now
+step +proj=hgridshift +grids=earthquake_1.gsb +t_epoch=2010.421
+step +proj=hgridshift +grids=earthquake_2.gsb +t_epoch=2013.853
+step +proj=hgridshift +grids=earthquake_3.gsb +t_epoch=2017.713
```

Note: The special epoch `now` is used when specifying the final epoch with `+t_final`. This results in coordinates being transformed to the current date. Additionally, `+t_final` is used as a *global pipeline parameter*, which means that it is applied to all the steps in the pipeline.

In the above transformation, a coordinate with observation epoch 2009.32 would be subject to all three gridshift steps in the pipeline. A coordinate with observation epoch 2014.12 would only be offset by the last step in the pipeline.

Parameters

Required

+grids=<list>

Comma-separated list of grids to load. If a grid is prefixed by an @ the grid is considered optional and PROJ will complain if the grid is not available.

Grids are expected to be in CTable2, NTv1 or NTv2 format.

Optional

+t_epoch=<time>

Central epoch of the transformation.

New in version 5.1.0.

+t_final=<time>

Final epoch that the coordinate will be propagated to after transformation. The special epoch *now* can be used instead of writing a specific period in time. When *now* is used, it is replaced internally with the epoch of the transformation. This means that the resulting coordinate will be slightly different if carried out again at a later date.

New in version 5.1.0.

6.3.5 Vertical grid shift

New in version 5.0.0.

Change Vertical datum change by grid shift

Domain	3D and 4D
Input type	Geodetic coordinates (horizontal), meters (vertical), decimalyear (temporal)
Output type	Geodetic coordinates (horizontal), meters (vertical), decimalyear (temporal)

The vertical grid shift is done by offsetting the vertical input coordinates by a specific amount determined by the loaded grids. The simplest use case of the horizontal grid shift is applying a single grid. Here we change the vertical reference from the ellipsoid to the global geoid model, EGM96:

```
+proj=vgridshift +grids=egm96_16.gtx
```

More than one grid can be loaded at the same time, for instance in the case where a better geoid model than the global is available for a certain area. Here the gridshift is set up so that the local DVR90 geoid model takes precedence over the global model:

```
+proj=vgridshift +grids=@dvr90.gtx,egm96_16.gtx
```

The @ in the above example states that the grid is optional, in case the grid is not found in the PROJ search path. The list of grids is prioritized so that grids in the start of the list takes precedence over the grids in the back of the list.

PROJ supports the GTX file format for vertical grid corrections. Details about all the format can be found in the GDAL documentation. GDAL both reads and writes the format. Using GDAL for construction of new grids is recommended.

Temporal gridshifting

New in version 5.1.0.

By initializing the vertical gridshift operation with a central epoch, it can be used as a step function applying the grid offsets only if a coordinate is transformed from an epoch before grids central epoch to an epoch after. This is handy in transformations where it is necessary to handle deformations caused by seismic activity.

The central epoch of the grid is controlled with `+t_epoch` and the final epoch of the coordinate is set with `+t_final`. The observation epoch of the coordinate is part of the coordinate tuple.

Suppose we want to model the deformation of the 2008 earthquake in Iceland in a transformation of data from 2005 to 2009:

```
echo 63.992 -21.014 10.0 2005.0 | cct +proj=vgridshift +grids=iceland2008.gtx +t_
→epoch=2008.4071 +t_final=2009.0
63.992 -21.014 10.11 2005.0
```

Note: The timestamp of the resulting coordinate is still 2005.0. The observation time is always kept unchanged as it would otherwise be impossible to do the inverse transformation.

Temporal gridshifting is especially powerful in transformation pipelines where several gridshifts can be chained together, effectively acting as a series of step functions that can be applied to a coordinate that is propagated through time. In the following example we establish a pipeline that allows transformation of coordinates from any given epoch up until the current date, applying only those gridshifts that have central epochs between the observation epoch and the final epoch:

```
+proj=pipeline +t_final=now
+step +proj=vgridshift +grids=earthquake_1.gtx +t_epoch=2010.421
+step +proj=vgridshift +grids=earthquake_2.gtx +t_epoch=2013.853
+step +proj=vgridshift +grids=earthquake_3.gtx +t_epoch=2017.713
```

Note: The special epoch *now* is used when specifying the final epoch with `+t_final`. This results in coordinates being transformed to the current date. Additionally, `+t_final` is used as a *global pipeline parameter*, which means that it is applied to all the steps in the pipeline.

In the above transformation, a coordinate with observation epoch 2009.32 would be subject to all three gridshift steps in the pipeline. A coordinate with observation epoch 2014.12 would only be offset by the last step in the pipeline.

Parameters

Required

`+grids=<list>`

Comma-separated list of grids to load. If a grid is prefixed by an @ the grid is considered optional and PROJ will not complain if the grid is not available.

Grids are expected to be in GTX format.

Optional

+t_epoch=<time>

Central epoch of the transformation.

New in version 5.1.0.

+t_final=<time>

Final epoch that the coordinate will be propagated to after transformation. The special epoch *now* can be used instead of writing a specific period in time. When *now* is used, it is replaced internally with the epoch of the transformation. This means that the resulting coordinate will be slightly different if carried out again at a later date.

New in version 5.1.0.

6.4 The pipeline operator

New in version 5.0.0.

Construct complex operations by daisy-chaining operations in a sequential pipeline.

Alias	pipeline
Domain	2D, 3D and 4D
Input type	Any
Output type	Any

Note: See the section on [Geodetic transformation](#) for a more thorough introduction to the concept of transformation pipelines in PROJ.

With the pipeline operation it is possible to perform several operations after each other on the same input data. This feature makes it possible to create transformations that are made up of more than one operation, e.g. performing a datum shift and then applying a suitable map projection. Theoretically any transformation between two coordinate reference systems is possible to perform using the pipeline operation, provided that the necessary coordinate operations in each step is available in PROJ.

A pipeline is made up of a number of steps, with each step being a coordinate operation in itself. By connecting these individual steps sequentially we end up with a concatenated coordinate operation. An example of this is a transformation from geodetic coordinates on the GRS80 ellipsoid to a projected system where the east-west and north-east axes has been swapped:

```
+proj=pipeline +ellps=GRS80 +step +proj=merc +step +proj=axisswap +order=2,1
```

Here the first step is applying the [Mercator](#) projection and the second step is applying the [Axis swap](#) conversion. Note that the `+ellps=GRS80` is specified before the first occurrence of `+step`. This means that the GRS80 ellipsoid is used in both steps, since any parameter stated before the first occurrence of `+step` is treated as a global parameter and is transferred to each individual steps.

6.4.1 Rules for pipelines

1. Pipelines must consist of at least one step.

```
+proj=pipeline
```

Will result in an error.

2. Pipelines can only be nested if the nested pipeline is defined in an init-file.

```
+proj=pipeline
+step +proj=pipeline +step +proj=merc +step +proj=axisswap +order=2,1
+step +proj=unitconvert +xy_in=m +xy_out=us-ft
```

Results in an error, while

```
+proj=pipeline
+step +init=predefined_pipelines:projectandswap
+step +proj=unitconvert +xy_in=m +xy_out=us-ft
```

does not.

3. Pipelines without a forward path can't be constructed.

```
+proj=pipeline +step +inv +proj=urm5
```

Will result in an error since *Urmaev V* does not have an inverse operation defined.

4. Parameters added before the first '+step' are global and will be applied to all steps.

In the following the GRS80 ellipsoid will be applied to all steps.

```
+proj=pipeline +ellps=GRS80
+step +proj=cart
+step +proj=helmert +x=10 +y=3 +z=1
+step +proj=cart +inv
+step +proj=merc
```

5. Units of operations must match between steps.

New in version 5.1.0.

The output units of step n must match the expected input unit of step $n+1$. E.g., you can't pass an operation that outputs projected coordinates to an operation that expects angular units (degrees). An example of such a unit mismatch is displayed below.

```
+proj=pipeline
+step +proj=merc # Mercator outputs projected coordinates
+step +proj=robin # The Robinson projection expects angular input
```

6.4.2 Parameters

Required

+step

Separate each step in a pipeline.

Optional

+inv

Invert a step in a pipeline.

RESOURCE FILES

A number of files containing preconfigured transformations and default parameters for certain projections are bundled with the PROJ distribution. Init files contains preconfigured proj-strings for various coordinate reference systems and the defaults file contains default values for parameters of select projections.

In addition to the bundled init-files the PROJ.4 project also distribute a number of packages containing transformation grids and additional init-files not included in the main PROJ package.

7.1 External resources

For a functioning PROJ installation of the [proj-datumgrid](#) is needed. If you have installed PROJ from a package system chances are that this will already be done for you. The *proj-datumgrid* package provides transformation grids that are essential for many of the predefined transformations in PROJ. Which grids are included in the package can be seen on the [proj-datumgrid repository](#) as well as descriptions of those grids.

In addition to the default *proj-datumgrid* package regional packages are also distributed. These include grids and init-files that are valid within the given region. The packages are divided into geographical regions in order to keep the needed disk space by PROJ at a minimum. Some users may have a use for resource files covering several regions in which case they can download more than one.

At the moment three regional resource file packages are distributed:

- Europe
- Oceania
- North America

Click the links to jump to the relevant README files for each package. Details on the content of the packages maintained there.

Links to the resource packages can be found in the [download section](#).

7.2 Transformation grids

Grid files are important for shifting and transforming between datums.

PROJ supports CTable2, NTv1 and NTv2 files for horizontal grid corrections and the GTX file format for vertical corrections. Details about the formats can be found in the [GDAL documentation](#). GDAL reads and writes all formats. Using GDAL for construction of new grids is recommended.

Below is a given a list of grid resources for various countries which are not included in the grid distributions mentioned above.

7.2.1 Free grids

Below is a list of grids distributed under a free and open license.

Switzerland

Background in ticket #145

We basically have two shift grids available. An official here:

Swiss CHENyx06 dataset in NTv2 format

And a derived in a temporary location which is probably going to disappear soon.

Main problem seems to be there's no mention of distributivity of the grid from the official website. It just tells: "you can use freely". The "contact" link is also broken, but maybe someone could make a phone call to ask for rephrasing that.

Hungary

Hungarian grid ETRS89 - HD72/EOV (epsg:23700), both horizontal and elevation grids

7.2.2 Non-Free Grids

Not all grid shift files have licensing that allows them to be freely distributed, but can be obtained by users through free and legal methods.

Canada NTv2.0

Although NTv1 grid shifts are provided freely with PROJ, the higher-quality NTv2.0 file needs to be downloaded from Natural Resources Canada. More info: http://www.geod.nrcan.gc.ca/tools-outils/ntv2_e.php.

Procedure:

1. Visit the [NTv2](#), and register/login
2. Follow the Download NTv2 link near the bottom of the page.
3. Unzip `ntv2_100325.zip` (or similar), and move the grid shift file `NTV2_0.GSB` to the `proj` directory (be sure to change the name to lowercase for consistency) e.g.: `mv NTV2_0.GSB /usr/local/share/proj/ntv2_0.gsb`
4. Test it using:

```
cs2cs +proj=latlong +ellps=clrk66 +nadgrids=@ntv2_0.gsb +to +proj=latlong
+ellps=GRS80 +datum=NAD83
-111 50
```

```
111d0'3.006"W 50d0'0.103"N 0.000 # correct answer
```

Australia

Geocentric Datum of Australia AGD66/AGD84

Canada

Canadian NTv2 grid shift binary for NAD27 <=> NAD83.

Germany

German BeTA2007 DHDN GK3 => ETRS89/UTM

Great Britain

Great Britain's OSTN15_NTv2: OSGB 1936 => ETRS89

Great Britain's OSTN02_NTv2: OSGB 1936 => ETRS89

Austria

Austrian Grid for MGI

Spain

Spanish grids for ED50.

Portugal

Portuguese grids for ED50, Lisbon 1890, Lisbon 1937 and Datum 73

Brazil

Brazilian grids for datums Corrego Alegre 1961, Corrego Alegre 1970-72, SAD69 and SAD69(96)

South Africa

South African grid (Cape to Hartebeesthoek94 or WGS84)

Netherlands

Dutch grid (Registration required before download)

7.2.3 HARN

With the support of i-cubed, Frank Warmerdam has written tools to translate the HPGN grids from NOAA/NGS from .los/.las format into NTv2 format for convenient use with PROJ. This project included implementing a .los/.las reader for GDAL, and an NTv2 reader/writer. Also, a script to do the bulk translation was implemented in <https://github.com/OSGeo/gdal/tree/trunk/gdal/swig/python/samples/loslas2ntv2.py>. The command to do the translation was:

```
loslas2ntv2.py -auto *hpgn.los
```

As GDAL uses NAD83/WGS84 as a pivot datum, the sense of the HPGN datum shift offsets were negated to map from HPGN to NAD83 instead of the other way. The files can be used with PROJ like this:

```
cs2cs +proj=latlong +datum=NAD83  
      +to +proj=latlong +nadgrids=./azhpgn.gsb +ellps=GRS80
```

```
# input:  
-112 34
```

```
# output:  
111d59'59.996"W 34d0'0.006"N -0.000
```

This was confirmed against the [NGS HPGN calculator](#).

The grids are available at http://download.osgeo.org/proj/hpgn_ntv2.zip

7.2.4 HTDP

This page documents use of the *crs2crs2grid.py* script and the HTDP (Horizontal Time Dependent Positioning) grid shift modelling program from NGS/NOAA to produce PROJ compatible grid shift files for fine grade conversions between various NAD83 epochs and WGS84. Traditionally PROJ has treated NAD83 and WGS84 as equivalent and failed to distinguish between different epochs or realizations of those datums. At the scales of much mapping this is adequate but as interest grows in high resolution imagery and other high resolution mapping this is inadequate. Also, as the North American crust drifts over time the displacement between NAD83 and WGS84 grows (more than one foot over the last two decades).

Getting and building HTDP

The HTDP modelling program is in written FORTRAN. The source and documentation can be found on the HTDP page at <http://www.ngs.noaa.gov/TOOLS/Htdp/Htdp.shtml>

On linux systems it will be necessary to install *gfortran* or some FORTRAN compiler. For ubuntu something like the following should work.

```
apt-get install gfortran
```

To compile the program do something like the following to produce the binary “htdp” from the source code.

```
gfortran htdp.for -o htdp
```

Getting crs2crs2grid.py

The *crs2crs2grid.py* script can be found at <https://github.com/OSGeo/gdal/tree/trunk/gdal/swig/python/samples/crs2crs2grid.py>

It depends on having the GDAL Python bindings operational. If they are not

```
Traceback (most recent call last):  
  File "./crs2crs2grid.py", line 37, in <module>  
    from osgeo import gdal, gdal_array, osr  
ImportError: No module named osgeo
```

Usage

```
crs2crs2grid.py
    <src_crs_id> <src_crs_date> <dst_crs_id> <dst_crs_year>
    [-griddef <ul_lon> <ul_lat> <ll_lon> <ll_lat> <lon_count> <lat_count>]
    [-htdp <path_to_exe>] [-wrkdir <dirpath>] [-kwf]
    -o <output_grid_name>

-griddef: by default the following values for roughly the continental USA
at a six minute step size are used:
-127 50 -66 25 251 611
-kwf: keep working files in the working directory for review.
```

```
crs2crs2grid.py 29 2002.0 8 2002.0 -o nad83_2002.ct2
```

The goal of *crs2crs2grid.py* is to produce a grid shift file for a designated region. The region is defined using the *-griddef* switch. When missing a continental US region is used. The script creates a set of sample points for the grid definition, runs the “htdp” program against it and then parses the resulting points and computes a point by point shift to encode into the final grid shift file. By default it is assumed the *htdp* program will be in the executable path. If not, please provide the path to the executable using the *-htdp* switch.

The *htdp* program supports transformations between many CRSes and for each (or most?) of them you need to provide a date at which the CRS is fixed. The full set of CRS IDs available in the HTDP program are:

```
1...NAD_83(2011) (North America tectonic plate fixed)
29...NAD_83(CORS96) (NAD_83(2011) will be used)
30...NAD_83(2007) (NAD_83(2011) will be used)
2...NAD_83(PA11) (Pacific tectonic plate fixed)
31...NAD_83(PACP00) (NAD_83(PA11) will be used)
3...NAD_83(MA11) (Mariana tectonic plate fixed)
32...NAD_83(MARP00) (NAD_83(MA11) will be used)

4...WGS_72
5...WGS_84(transit) = NAD_83(2011)
6...WGS_84(G730) = ITRF92
7...WGS_84(G873) = ITRF96
8...WGS_84(G1150) = ITRF2000
9...PNEOS_90 = ITRF90
10...NEOS_90 = ITRF90
11...SIO/MIT_92 = ITRF91
12...ITRF88
13...ITRF89
14...ITRF90
15...ITRF91
16...ITRF92
17...ITRF93
18...ITRF94 = ITRF96
19...ITRF96
20...ITRF97
21...IGS97 = ITRF97
22...ITRF2000
23...IGS00 = ITRF2000
24...IGb00 = ITRF2000
25...ITRF2005
26...IGS05 = ITRF2005
27...ITRF2008
28...IGS08 = ITRF2008
```

The typical use case is mapping from NAD83 on a particular date to WGS84 on some date. In this case the source CRS ID “29” (NAD_83(CORS96)) and the destination CRS ID is “8 (WGS_84(G1150)). It is also necessary to select the source and destination date (epoch). For example:

```
crs2crs2grid.py 29 2002.0 8 2002.0 -o nad83_2002.ct2
```

The output is a CTable2 format grid shift file suitable for use with PROJ (4.8.0 or newer). It might be utilized something like:

```
cs2cs +proj=latlong +ellps=GRS80 +nadgrids=./nad83_2002.ct2 +to +proj=latlong
↪+datum=WGS84
```

See Also

- <http://www.ngs.noaa.gov/TOOLS/Htdp/Htdp.shtml> - NGS/NOAA page about the HTDP model and program. Source for the HTDP program can be downloaded from here.

7.3 Init files

Init files are used for preconfiguring proj-strings for often used transformations, such as those found in the EPSG database. Most init files contain transformations from a given coordinate reference system to WGS84. This makes it easy to transformations between any two coordinate reference systems with `cs2cs`. Init files can however contain any proj-string and don't necessarily have to follow the `cs2cs` paradigm where WGS84 is used as a pivot datum. The ITRF init file is a good example of that.

A number of init files come pre-bundled with PROJ but it is also possible to add your own custom init files. PROJ looks for the init files in the directory listed in the `PROJ_LIB` environment variable.

The format of init files made up of a identifier in angled brackets and a proj-string:

```
<3819> +proj=longlat +ellps=bessel  
+towgs84=595.48,121.69,515.35,4.115,-2.9383,0.853,-3.408 +no_defs <>
```

The above example is the first entry from the `epsg` init file. So, this is the coordinate reference system with ID 3819 in the EPSG database. Comments can be inserted by prefixing them with a “#”. With version 4.10.0 a new special metadata entry is now accepted in init files. It can be parsed with a function from the public API. The metadata entry in the `epsg` init file looks like this at the time of writing:

```
<metadata> +version=9.0.0 +origin=EPSG +lastupdate=2017-01-10
```

Pre-configured proj-strings from init files are used in the following way:

```
$ cs2cs -v +proj=latlong +to +init=epsg:3819  
# ---- From Coordinate System ----  
#Lat/long (Geodetic alias)  
#  
# +proj=latlong +ellps=WGS84  
# ---- To Coordinate System ----  
#Lat/long (Geodetic alias)  
#  
# +init=epsg:3819 +proj=longlat +ellps=bessel  
# +towgs84=595.48,121.69,515.35,4.115,-2.9383,0.853,-3.408 +no_defs
```

It is possible to override parameters when using `+init`. Just add the parameter to the proj-string alongside the `+init` parameter. For instance by overriding the ellipsoid as in the following example

```
+init=epsg:25832 +ellps=intl
```

where the Hayford ellipsoid is used instead of the predefined GRS80 ellipsoid. It is also possible to add additional parameters not specified in the init file, for instance by adding an observation epoch when transforming from ITRF2000 to ITRF2005:

```
+init=ITRF2000:ITRF2005 +t_obs=2010.5
```

which then expands to

```
+proj=helmert +x=-0.0001 +y=0.0008 +z=0.0058 +s=-0.0004
+dx=0.0002 +dy=-0.0001 +dz=0.0018 +ds=-0.000008
+t_epoch=2000.0 +transpose
+t_obs=2010.5
```

Below is a list of the init files that are packaged with PROJ.

Name	Description
esri	Auto-generated mapping from Esri projection index. Not maintained any more
epsg	EPSG database
GL27	Great Lakes Grids
IGNF	French coordinate systems supplied by the IGNF
ITRF2000	Full set of transformation parameters between ITRF2000 and other ITRF's
ITRF2008	Full set of transformation parameters between ITRF2008 and other ITRF's
ITRF2014	Full set of transformation parameters between ITRF2014 and other ITRF's
nad27	State plane coordinate systems, North American Datum 1927
nad83	State plane coordinate systems, North American Datum 1983

7.4 The defaults file

The `proj_def.dat` file supplies default parameters for PROJ. It uses the same syntax as the init files described above. The identifiers in the defaults file describe to what the parameters should apply. If the `<general>` identifier is used, then all parameters in that section applies for all proj-strings. Otherwise the identifier is connected to a specific projection. With the defaults file supplied with PROJ the default ellipsoid is set to WGS84 (for all proj-strings). Apart from that only the Albers Equal Area, [Lambert Conic Conformal](#) and the [Lagrange](#) projections have default parameters. Defaults can be ignored by adding the `+no_def` parameter to a proj-string.

GEODESIC CALCULATIONS

8.1 Introduction

Consider an ellipsoid of revolution with equatorial radius a , polar semi-axis b , and flattening $f = (a - b)/a$. Points on the surface of the ellipsoid are characterized by their latitude ϕ and longitude λ . (Note that latitude here means the *geographical latitude*, the angle between the normal to the ellipsoid and the equatorial plane).

The shortest path between two points on the ellipsoid at (ϕ_1, λ_1) and (ϕ_2, λ_2) is called the geodesic. Its length is s_{12} and the geodesic from point 1 to point 2 has forward azimuths α_1 and α_2 at the two end points. In this figure, we have $\lambda_{12} = \lambda_2 - \lambda_1$.

A geodesic can be extended indefinitely by requiring that any sufficiently small segment is a shortest path; geodesics are also the straightest curves on the surface.

8.2 Solution of geodesic problems

Traditionally two geodesic problems are considered:

- the direct problem — given $\phi_1, \lambda_1, \alpha_1, s_{12}$, determine $\phi_2, \lambda_2, \alpha_2$.
- the inverse problem — given $\phi_1, \lambda_1, \phi_2, \lambda_2$, determine $s_{12}, \alpha_1, \alpha_2$.

PROJ incorporates [C library for Geodesics](#) from [GeographicLib](#). This library provides routines to solve the direct and inverse geodesic problems. Full double precision accuracy is maintained provided that $|f| < \frac{1}{50}$. Refer to the application programming interface

for full documentation. A brief summary of the routines is given in [geodesic\(3\)](#).

The interface to the geodesic routines differ in two respects from the rest of PROJ:

- angles (latitudes, longitudes, and azimuths) are in degrees (instead of in radians);
- the shape of ellipsoid is specified by the flattening f ; this can be negative to denote a prolate ellipsoid; setting $f = 0$ corresponds to a sphere, in which case the geodesic becomes a great circle.

PROJ also includes a command line tool, [`geod`\(1\)](#), for performing simple geodesic calculations.

8.3 Additional properties

The routines also calculate several other quantities of interest

- S_{12} is the area between the geodesic from point 1 to point 2 and the equator; i.e., it is the area, measured counter-clockwise, of the quadrilateral with corners (ϕ_1, λ_1) , $(0, \lambda_1)$, $(0, \lambda_2)$, and (ϕ_2, λ_2) . It is given in meters².
- m_{12} , the reduced length of the geodesic is defined such that if the initial azimuth is perturbed by $d\alpha_1$ (radians) then the second point is displaced by $m_{12} d\alpha_1$ in the direction perpendicular to the geodesic. m_{12} is given in meters. On a curved surface the reduced length obeys a symmetry relation, $m_{12} + m_{21} = 0$. On a flat surface, we have $m_{12} = s_{12}$.
- M_{12} and M_{21} are geodesic scales. If two geodesics are parallel at point 1 and separated by a small distance dt , then they are separated by a distance $M_{12} dt$ at point 2. M_{21} is defined similarly (with the geodesics being parallel to one another at point 2). M_{12} and M_{21} are dimensionless quantities. On a flat surface, we have $M_{12} = M_{21} = 1$.
- σ_{12} is the arc length on the auxiliary sphere. This is a construct for converting the problem to one in spherical trigonometry. The spherical arc length from one equator crossing to the next is always 180° .

If points 1, 2, and 3 lie on a single geodesic, then the following addition rules hold:

- $s_{13} = s_{12} + s_{23}$,
- $\sigma_{13} = \sigma_{12} + \sigma_{23}$,
- $S_{13} = S_{12} + S_{23}$,
- $m_{13} = m_{12}M_{23} + m_{23}M_{12}$,
- $M_{13} = M_{12}M_{23} - (1 - M_{12}M_{21})m_{23}/m_{12}$,
- $M_{31} = M_{32}M_{21} - (1 - M_{23}M_{32})m_{12}/m_{23}$.

8.4 Multiple shortest geodesics

The shortest distance found by solving the inverse problem is (obviously) uniquely defined. However, in a few special cases there are multiple azimuths which yield the same shortest distance. Here is a catalog of those cases:

- $\phi_1 = -\phi_2$ (with neither point at a pole). If $\alpha_1 = \alpha_2$, the geodesic is unique. Otherwise there are two geodesics and the second one is obtained by setting $[\alpha_1, \alpha_2] \leftarrow [\alpha_2, \alpha_1]$, $[M_{12}, M_{21}] \leftarrow [M_{21}, M_{12}]$, $S_{12} \leftarrow -S_{12}$. (This occurs when the longitude difference is near $\pm 180^\circ$ for oblate ellipsoids.)
- $\lambda_2 = \lambda_1 \pm 180^\circ$ (with neither point at a pole). If $\alpha_1 = 0^\circ$ or $\pm 180^\circ$, the geodesic is unique. Otherwise there are two geodesics and the second one is obtained by setting $[\alpha_1, \alpha_2] \leftarrow [-\alpha_1, -\alpha_2]$, $S_{12} \leftarrow -S_{12}$. (This occurs when ϕ_2 is near $-\phi_1$ for prolate ellipsoids.)
- Points 1 and 2 at opposite poles. There are infinitely many geodesics which can be generated by setting $[\alpha_1, \alpha_2] \leftarrow [\alpha_1, \alpha_2] + [\delta, -\delta]$, for arbitrary δ . (For spheres, this prescription applies when points 1 and 2 are antipodal.)
- $s_{12} = 0$ (coincident points). There are infinitely many geodesics which can be generated by setting $[\alpha_1, \alpha_2] \leftarrow [\alpha_1, \alpha_2] + [\delta, \delta]$, for arbitrary δ .

8.5 Background

The algorithms implemented by this package are given in [\[Karney2013\]](#) and are based on [\[Bessel1825\]](#) and [\[Helmert1880\]](#); the algorithm for areas is based on [\[Danielsen1989\]](#). These improve on the work of [\[Vincenty1975\]](#) in the following respects:

- The results are accurate to round-off for terrestrial ellipsoids (the error in the distance is less than 15 nanometers, compared to 0.1 mm for Vincenty).

- The solution of the inverse problem is always found. (Vincenty's method fails to converge for nearly antipodal points.)
- The routines calculate differential and integral properties of a geodesic. This allows, for example, the area of a geodesic polygon to be computed.

Additional background material is provided in [\[GeodesicBib\]](#), [\[GeodesicWiki\]](#), and [\[Karney2011\]](#).

DEVELOPMENT

These pages are primarily focused towards developers either contributing to the PROJ project or using the library in their own software.

9.1 Quick start

This is a short introduction to the PROJ API. In the following section we create a simple program that transforms a geodetic coordinate to UTM and back again. The program is explained a few lines at a time. The complete program can be seen at the end of the section.

See the following sections for more in-depth descriptions of different parts of the PROJ API or consult the [API reference](#) for specifics.

Before the PROJ API can be used it is necessary to include the `proj.h` header file. Here `stdio.h` is also included so we can print some text to the screen:

```
#include <stdio.h>
#include <proj.h>
```

Let's declare a few variables that'll be used later in the program. Each variable will be discussed below. See the [reference for more info on data types](#).

```
PJ_CONTEXT *C;
PJ *P;
PJ_COORD a, b;
```

For use in multi-threaded programs the `PJ_CONTEXT` threading-context is used. In this particular example it is not needed, but for the sake of completeness it created here. The section on [threads](#) discusses this in detail.

```
/* use PJ objects from only one thread */
```

Next we create the `PJ` transformation object `P` with the function `proj_create`. `proj_create` takes the threading context `C` created above, and a proj-string that defines the desired transformation. Here we transform from geodetic coordinate to UTM zone 32N. It is recommended to create one threading-context per thread used by the program. This ensures that all `PJ` objects created in the same context will be sharing resources such as error-numbers and loaded grids. In case the creation of the `PJ` object fails an error message is displayed and the program returns. See [Error handling](#) for further details.

```
P = proj_create (C, "+proj=utm +zone=32 +ellps=GRS80");
if (0==P)
```

PROJ uses its own data structures for handling coordinates. Here we use a PJ_COORD which is easily assigned with the function proj_coord. Note that the input values are converted to radians with proj_torad. This is necessary since PROJ is using radians internally. See [Transformations](#) for further details.

```
/* note: PROJ.4 works in radians, hence the proj_torad() calls */
```

The coordinate defined above is transformed with proj_trans_coord. For this a PJ object, a transformation direction (either forward or inverse) and the coordinate is needed. The transformed coordinate is returned in b. Here the forward (PJ_FWD) transformation from geodetic to UTM is made.

```
/* transform to UTM zone 32, then back to geographical */
b = proj_trans (P, PJ_FWD, a);
```

The inverse transformation (UTM to geodetic) is done similar to above, this time using PJ_INV as the direction.

```
printf ("easting: %g, northing: %g\n", b.enu.e, b.enu.n);
b = proj_trans (P, PJ_INV, b);
```

Before ending the program the allocated memory needs to be released again:

```
/* Clean up */
proj_destroy (P);
```

A complete compilable version of the above can be seen here:

```

1 #include <stdio.h>
2 #include <proj.h>
3
4 int main (void) {
5     PJ_CONTEXT *C;
6     PJ *P;
7     PJ_COORD a, b;
8
9     /* or you may set C=PJ_DEFAULT_CTX if you are sure you will      */
10    /* use PJ objects from only one thread                         */
11    C = proj_context_create();
12
13    P = proj_create (C, "+proj=utm +zone=32 +ellps=GRS80");
14    if (0==P)
15        return puts ("Oops"), 0;
16
17    /* a coordinate union representing Copenhagen: 55d N, 12d E      */
18    /* note: PROJ.4 works in radians, hence the proj_torad() calls */
19    a = proj_coord (proj_torad(12), proj_torad(55), 0, 0);
20
21    /* transform to UTM zone 32, then back to geographical */
22    b = proj_trans (P, PJ_FWD, a);
23    printf ("easting: %g, northing: %g\n", b.enu.e, b.enu.n);
24    b = proj_trans (P, PJ_INV, b);
25    printf ("longitude: %g, latitude: %g\n", b.lp.lam, b.lp.phi);
26
27    /* Clean up */
28    proj_destroy (P);
29    proj_context_destroy (C); /* may be omitted in the single threaded case */
30    return 0;
31 }
```

9.2 Transformations

9.3 Error handling

9.4 Threads

This page is about efforts to make PROJ thread safe.

9.4.1 Key Thread Safety Issues

- the global pj_errno variable is shared between threads and makes it essentially impossible to handle errors safely.
Being addressed with the introduction of the projCtx execution context.
- the datum shift using grid files uses globally shared lists of loaded grid information. Access to this has been made safe in 4.7.0 with the introduction of a PROJ mutex used to protect access to these memory structures (see pj_mutex.c).

9.4.2 projCtx

Primarily in order to avoid having pj_errno as a global variable, a “thread context” structure has been introduced into a variation of the PROJ API for the 4.8.0 release. The pj_init() and pj_init_plus() functions now have context variations called pj_init_ctx() and pj_init_plus_ctx() which take a projections context.

The projections context can be created with pj_ctx_alloc(), and there is a global default context used when one is not provided by the application. There is a pj_ctx_ set of functions to create, manipulate, query, and destroy contexts. The contexts are also used now to handle setting debugging mode, and to hold an error reporting function for textual error and debug messages. The API looks like:

```
projPJ pj_init_ctx( projCtx, int, char ** );
projPJ pj_init_plus_ctx( projCtx, const char * );

projCtx pj_get_default_ctx(void);
projCtx pj_get_ctx( projPJ );
void pj_set_ctx( projPJ, projCtx );
projCtx pj_ctx_alloc(void);
void pj_ctx_free( projCtx );
int pj_ctx_get_errno( projCtx );
void pj_ctx_set_errno( projCtx, int );
void pj_ctx_set_debug( projCtx, int );
void pj_ctx_set_logger( projCtx, void (*) (void *, int, const char *) );
void pj_ctx_set_app_data( projCtx, void * );
void *pj_ctx_get_app_data( projCtx );
```

Multithreaded applications are now expected to create a projCtx per thread using pj_ctx_alloc(). The context’s error handlers, and app data may be modified if desired, but at the very least each context has an internal error value accessed with pj_ctx_get_errno() as opposed to looking at pj_errno.

Note that pj_errno continues to exist, and it is set by pj_ctx_set_errno() (as well as setting the context specific error number), but pj_errno still suffers from the global shared problem between threads and should not be used by multithreaded applications.

Note that pj_init_ctx(), and pj_init_plus_ctx() will assign the projCtx to the created projPJ object. Functions like pj_transform(), pj_fwd() and pj_inv() will use the context of the projPJ for error reporting.

9.4.3 src/multistresstest.c

A small multi-threaded test program has been written (src/multistresstest.c) for testing multithreaded use of PROJ. It performs a series of reprojections to setup a table expected results, and then it does them many times in several threads to confirm that the results are consistent. At this time this program is not part of the builds but it can be built on linux like:

```
gcc -g multistresstest.c .libs/libproj.so -lpthread -o multistresstest  
./multistresstest
```

9.5 Reference

9.5.1 Data types

This section describes the numerous data types in use in PROJ.4. As a rule of thumb PROJ.4 data types are prefixed with `PJ_`, or in one particular case, is simply called `PJ`. A few notable exceptions can be traced back to the very early days of PROJ.4 when the `PJ_` prefix was not consistently used.

Transformation objects

`PJ`

Object containing everything related to a given projection or transformation. As a user of the PROJ.4 library you are only exposed to pointers to this object and the contents is hidden behind the public API. `PJ` objects are created with `proj_create()` and destroyed with `proj_destroy()`.

`PJ_DIRECTION`

Enumeration that is used to convey in which direction a given transformation should be performed. Used in transformation function call as described in the section on *transformation functions*.

Forward transformations are defined with the :c:

```
typedef enum proj_direction {  
    PJ_FWD    = 1, /* Forward */  
    PJ_IDENT  = 0, /* Do nothing */  
    PJ_INV    = -1 /* Inverse */  
} PJ_DIRECTION;
```

`PJ_FWD`

Perform transformation in the forward direction.

`PJ_IDENT`

Identity. Do nothing.

`PJ_INV`

Perform transformation in the inverse direction.

`PJ_CONTEXT`

Context objects enable safe multi-threaded usage of PROJ.4. Each `PJ` object is connected to a context (if not specified, the default context is used). All operations within a context should be performed in the same thread. `PJ_CONTEXT` objects are created with `proj_context_create()` and destroyed with `proj_context_destroy()`.

`PJ_AREA`

Opaque object describing an area in which a transformation is performed.

Note: This object is not fully implemented yet. It is to be used with `proj_create_crs_to_crs()` to select the best transformation between the two input coordinate reference systems.

2 dimensional coordinates

Various 2-dimensional coordinate data types.

PJ_LP

Geodetic coordinate, latitude and longitude. Usually in radians.

```
typedef struct { double lam, phi; } PJ_LP;
```

double **PJ_LP.lam**
Longitude. Lambda.

double **PJ_LP.phi**
Latitude. Phi.

PJ_XY

2-dimensional cartesian coordinate.

```
typedef struct { double x, y; } PJ_XY;
```

double **PJ_XY.x**
Easting.

double **PJ_XY.y**
Northing.

PJ_UV

2-dimensional generic coordinate. Usually used when contents can be either a `PJ_XY` or `PJ_LP`.

```
typedef struct { double u, v; } PJ_UV;
```

double **PJ_UV.u**
Longitude or easting, depending on use.

double **PJ_UV.v**
Latitude or northing, depending on use.

3 dimensional coordinates

The following data types are the 3-dimensional equivalents to the data types above.

PJ_LPZ

3-dimensional version of `PJ_LP`. Holds longitude, latitude and a vertical component.

```
typedef struct { double lam, phi, z; } PJ_LPZ;
```

double **PJ_LPZ.lam**
Longitude. Lambda.

double **PJ_LPZ.phi**
Latitude. Phi.

```
double PJ_LPZ.z  
Vertical component.
```

PJ_XYZ

Cartesian coordinate in 3 dimensions. Extension of [PJ_XY](#).

```
typedef struct { double x, y, z; } PJ_XYZ;
```

```
double PJ_XYZ.x  
Easting or the X component of a 3D cartesian system.
```

```
double PJ_XYZ.y  
Northing or the Y component of a 3D cartesian system.
```

```
double PJ_XYZ.z  
Vertical component or the Z component of a 3D cartesian system.
```

PJ_UVW

3-dimensional extension of [PJ_UV](#).

```
typedef struct { double u, v, w; } PJ_UVW;
```

```
double PJ_UVW.u  
Longitude or easting, depending on use.
```

```
double PJ_UVW.v  
Latitude or northing, depending on use.
```

```
double PJ_UVW.w  
Vertical component.
```

Spatiotemporal coordinate types

The following data types are extensions of the triplets above into the time domain.

PJ_LPZT

Spatiotemporal version of [PJ_LPZ](#).

```
typedef struct {  
    double lam;  
    double phi;  
    double z;  
    double t;  
} PJ_LPZT;
```

```
double PJ_LPZT.lam  
Longitude.
```

```
double PJ_LPZT.phi  
Latitude
```

```
double PJ_LPZT.z  
Vertical component.
```

```
double PJ_LPZT.t  
Time component.
```

PJ_XYZT

Generic spatiotemporal coordinate. Useful for e.g. cartesian coordinates with an attached time-stamp.

```
typedef struct {
    double x;
    double y;
    double z;
    double t;
} PJ_XYZT;
```

double PJ_XYZT.x
Easting or the X component of a 3D cartesian system.

double PJ_XYZT.y
Northing or the Y component of a 3D cartesian system.

double PJ_XYZT.z
Vertical or the Z component of a 3D cartesian system.

double PJ_XYZT.t
Time component.

PJ_UVWT

Spatiotemporal version of [PJ_UVW](#).

```
typedef struct { double u, v, w, t; } PJ_UVWT;
```

double PJ_UVWT.e
First horizontal component.

double PJ_UVWT.n
Second horizontal component.

double PJ_UVWT.w
Vertical component.

double PJ_UVWT.t
Temporal component.

Ancillary types for geodetic computations**PJ_OPK**

Rotations, for instance three euler angles.

```
typedef struct { double o, p, k; } PJ_OPK;
```

double PJ_OPK.o
First rotation angle, omega.

double PJ_OPK.p
Second rotation angle, phi.

double PJ_OPK.k
Third rotation angle, kappa.

Complex coordinate types**PJ_COORD**

General purpose coordinate union type, applicable in two, three and four dimensions. This is the default coordinate datatype used in PROJ.

```
typedef union {
    double v[4];
    PJ_XYZT xyzt;
    PJ_UVWT uvwt;
    PJ_LPZT lpzt;
    PJ_XYZ xyz;
    PJ_UVW uvw;
    PJ_LPZ lpz;
    PJ_XY xy;
    PJ_UV uv;
    PJ_LP lp;
} PJ_COORD ;
```

double v[4]

Generic four-dimensional vector.

PJ_XYZT PJ_COORD .xyzt

Spatiotemporal cartesian coordinate.

PJ_UVWT PJ_COORD .uvwt

Spatiotemporal generic coordinate.

PJ_LPZT PJ_COORD .lpzt

Longitude, latitude, vertical and time components.

PJ_XYZ PJ_COORD .xyz

3-dimensional cartesian coordinate.

PJ_UVW PJ_COORD .uvw

3-dimensional generic coordinate.

PJ_LPZ PJ_COORD .lpz

Longitude, latitude and vertical component.

PJ_XY PJ_COORD .xy

2-dimensional cartesian coordinate.

PJ_UV PJ_COORD .uv

2-dimensional generic coordinate.

PJ_LP PJ_COORD .lp

Longitude and latitude.

Projection derivatives

PJ_FACTORS

Various cartographic properties, such as scale factors, angular distortion and meridian convergence. Calculated with `proj_factors()`.

```
typedef struct {
    double meridional_scale;
    double parallel_scale;
    double areal_scale;

    double angular_distortion;
    double meridian_parallel_angle;
    double meridian_convergence;
```

(continues on next page)

(continued from previous page)

```

double tissot_semajor;
double tissot_seminor;

double dx_dlam;
double dx_dphi;
double dy_dlam;
double dy_dphi;
} PJ_FACTORS;

```

double PJ_FACTORS.meridional_scaleMeridional scale at coordinate (λ, ϕ).**double PJ_FACTORS.parallel_scale**Parallel scale at coordinate (λ, ϕ).**double PJ_FACTORS.areal_scale**Areal scale factor at coordinate (λ, ϕ).**double PJ_FACTORS.angular_distortion**Angular distortion at coordinate (λ, ϕ).**double PJ_FACTORS.meridian_parallel_angle**Meridian/parallel angle, θ' , at coordinate (λ, ϕ).**double PJ_FACTORS.meridian_convergence**Meridian convergence at coordinate (λ, ϕ). Sometimes also described as *grid declination*.**double PJ_FACTORS.tissot_semajor**

Maximum scale factor.

double PJ_FACTORS.tissot_seminor

Minimum scale factor.

double PJ_FACTORS.dx_dlamPartial derivative $\frac{\partial x}{\partial \lambda}$ of coordinate (λ, ϕ).**double PJ_FACTORS.dy_dlam**Partial derivative $\frac{\partial y}{\partial \lambda}$ of coordinate (λ, ϕ).**double PJ_FACTORS.dx_dphi**Partial derivative $\frac{\partial x}{\partial \phi}$ of coordinate (λ, ϕ).**double PJ_FACTORS.dy_dphi**Partial derivative $\frac{\partial y}{\partial \phi}$ of coordinate (λ, ϕ).**List structures****PJ_OPERATIONS**

Description a PROJ.4 operation

```

struct PJ_OPERATIONS {
    char      *id;           /* operation keyword */
    PJ (*proj) (PJ *);
    char      * const *descr; /* operation entry point */
                           /* description text */
};

```

char *id

Operation keyword.

```
PJ *(*op) (PJ *)
Operation entry point.
```

```
char * const *
Description of operation.
```

PJ_ELLPS

Description of ellipsoids defined in PROJ.4

```
struct PJ_ELLPS {
    char      *id;
    char      *major;
    char      *ell;
    char      *name;
};
```

```
char *id
Keyword name of the ellipsoid.
```

```
char *major
Semi-major axis of the ellipsoid, or radius in case of a sphere.
```

```
char *ell
Elliptical parameter, e.g. rf=298.257 or b=6356772.2.
```

```
char *name
Name of the ellipsoid
```

PJ_UNITS

Distance units defined in PROJ.

```
struct PJ_UNITS {
    char      *id;          /* units keyword */
    char      *to_meter;     /* multiply by value to get meters */
    char      *name;         /* comments */
    double    factor;        /* to_meter factor in actual numbers */
};
```

```
char *id
Keyword for the unit.
```

```
char *to_meter
Text representation of the factor that converts a given unit to meters
```

```
char *name
Name of the unit.
```

```
double factor
Conversion factor that converts the unit to meters.
```

PJ_PRIME_MERIDIANS

Prime meridians defined in PROJ.

```
struct PJ_PRIME_MERIDIANS {
    char      *id;
    char      *defn;
};
```

```
char *id
Keyword for the prime meridian
```

char ***def**
 Offset from Greenwich in DMS format.

Info structures

PJ_INFO

Struct holding information about the current instance of PROJ. Struct is populated by `proj_info()`.

```
typedef struct {
    int          major;
    int          minor;
    int          patch;
    const char   *release;
    const char   *version;
    const char   *searchpath;
} PJ_INFO;
```

const char *PJ_INFO.release

Release info. Version number and release date, e.g. “Rel. 4.9.3, 15 August 2016”.

const char *PJ_INFO.version

Text representation of the full version number, e.g. “4.9.3”.

int PJ_INFO.major

Major version number.

int PJ_INFO.minor

Minor version number.

int PJ_INFO.patch

Patch level of release.

const char PJ_INFO.searchpath

Search path for PROJ. List of directories separated by semicolons (Windows) or colons (non-Windows), e.g. “C:\Users\doctorwho;C:\OSGeo4W64\share\proj”. Grids and init files are looked for in directories in the search path.

PJ_PROJ_INFO

Struct holding information about a `PJ` object. Populated by `proj_pj_info()`. The `PJ_PROJ_INFO` object provides a view into the internals of a `PJ`, so once the `PJ` is destroyed or otherwise becomes invalid, so does the `PJ_PROJ_INFO`

```
typedef struct {
    const char   *id;
    const char   *description;
    const char   *definition;
    int          has_inverse;
    double       accuracy;
} PJ_PROJ_INFO;
```

const char *PJ_PROJ_INFO.id

Short ID of the operation the `PJ` object is based on, that is, what comes after the `+proj=` in a proj-string, e.g. “merc”.

const char *PJ_PROJ_INFO.description

Long describes of the operation the `PJ` object is based on, e.g. “Mercator Cyl, Sph&Ell lat_ts=”.

```
const char *PJ_PROJ_INFO.definition
The proj-string that was used to create the PJ object with, e.g. "+proj=merc +lat_0=24 +lon_0=53
+ellps=WGS84".
```

```
int PJ_PROJ_INFO.has_inverse
1 if an inverse mapping of the defined operation exists, otherwise 0.
```

```
double PJ_PROJ_INFO.accuracy
Expected accuracy of the transformation. -1 if unknown.
```

PJ_GRID_INFO

Struct holding information about a specific grid in the search path of PROJ. Populated with the function *proj_grid_info()*.

```
typedef struct {
    char        gridname[32];
    char        filename[260];
    char        format[8];
    LP          lowerleft;
    LP          upperright;
    int         n_lon, n_lat;
    double      cs_lon, cs_lat;
} PJ_GRID_INFO;
```

char PJ_GRID_INFO.gridname[32]

Name of grid, e.g. "BETA2007.gsb".

char PJ_GRID_INFO

Full path of grid file, e.g. "C:\OSGeo4W64\share\proj\BETA2007.gsb"

char PJ_GRID_INFO.format[8]

File format of grid file, e.g. "ntv2"

LP PJ_GRID_INFO.lowerleft

Geodetic coordinate of lower left corner of grid.

LP PJ_GRID_INFO.upperright

Geodetic coordinate of upper right corner of grid.

int PJ_GRID_INFO.n_lon

Number of grid cells in the longitudinal direction.

int PJ_GRID_INFO.n_lat

Number of grid cells in the latitudianl direction.

double PJ_GRID_INFO.cs_lon

Cell size in the longitudinal direction. In radians.

double PJ_GRID_INFO.cs_lat

Cell size in the latitudinal direction. In radians.

PJ_INIT_INFO

Struct holding information about a specific init file in the search path of PROJ. Populated with the function *proj_init_info()*.

```
typedef struct {
    char        name[32];
    char        filename[260];
    char        version[32];
    char        origin[32];
} PJ_INIT_INFO;
```

(continues on next page)

(continued from previous page)

```
    char          lastupdate[16];
} PJ_INIT_INFO;
```

char PJ_INIT_INFO.name[32]

Name of init file, e.g. “epsg”.

char PJ_INIT_INFO.filename[260]

Full path of init file, e.g. “C:\OSGeo4W64\share\proj\epsg”

char PJ_INIT_INFO.version[32]

Version number of init-file, e.g. “9.0.0”

char PJ_INIT_INFO.origin[32]

Originating entity of the init file, e.g. “EPSG”

char PJ_INIT_INFO.lastupdate

Date of last update of the init-file.

Logging

PJ_LOG_LEVEL

Enum of logging levels in PROJ. Used to set the logging level in PROJ. Usually using `proj_log_level()`.

PJ_LOG_NONE

Don’t log anything.

PJ_LOG_ERROR

Log only errors.

PJ_LOG_DEBUG

Log errors and additional debug information.

PJ_LOG_TRACE

Highest logging level. Log everything including very detailed debug information.

PJ_LOG_TELL

Special logging level that when used in `proj_log_level()` will return the current logging level set in PROJ.

New in version 5.1.0.

PJ_LOG_FUNC

Function prototype for the logging function used by PROJ. Defined as

```
typedef void (*PJ_LOG_FUNCTION) (void *, int, const char *);
```

where the `void` pointer references a data structure used by the calling application, the `int` is used to set the logging level and the `const char` pointer is the string that will be logged by the function.

New in version 5.1.0.

9.5.2 Functions

Threading contexts

`PJ_CONTEXT* proj_context_create(void)`

Create a new threading-context.

Returns `PJ_CONTEXT*`

`void proj_context_destroy (PJ_CONTEXT *ctx)`
Deallocate a threading-context.

Parameters

- `ctx (PJ_CONTEXT*)` – Threading context.

Transformation setup

`PJ* proj_create (PJ_CONTEXT *ctx, const char *definition)`
Create a transformation object from a proj-string.

Example call:

```
PJ *P = proj_create(0, "+proj=etmerc +lat_0=38 +lon_0=125 +ellps=bessel");
```

The returned `PJ`-pointer should be deallocated with `proj_destroy()`.

Parameters

- `ctx (PJ_CONTEXT*)` – Threading context.
- `definition (const char*)` – Proj-string of the desired transformation.

`PJ* proj_create_argv (PJ_CONTEXT *ctx, int argc, char **argv)`

Create transformation object with argc/argv-style initialization. For this application each parameter in the defining proj-string is an entry in argv.

Example call:

```
char *args[3] = {"proj=utm", "zone=32", "ellps=GRS80"};  
PJ* P = proj_create_argv(0, 3, args);
```

The returned `PJ`-pointer should be deallocated with `proj_destroy()`.

Parameters

- `ctx (PJ_CONTEXT*)` – Threading context
- `argc (int)` – Count of arguments in argv
- `argv (char**) – Vector of strings with proj-string parameters, e.g. +proj=merc`

Returns `PJ*`

`PJ* proj_create_crs_to_crs (PJ_CONTEXT *ctx, const char *srid_from, const char *srid_to,`
`PJ_AREA *area)`

Create a transformation object that is a pipeline between two known coordinate reference systems.

`srid_from` and `srid_to` should be the value part of a `+init=...` parameter set, i.e. “epsg:25833” or “IGNF:AMST63”. Any projection definition that can be found in a init-file in `PROJ_LIB` is a valid input to this function.

For now the function mimics the cs2cs app: An input and an output CRS is given and coordinates are transformed via a hub datum (WGS84). This transformation strategy is referred to as “early-binding” by the EPSG. The function can be extended to support “late-binding” transformations in the future without affecting users of the function. When the function is extended to the late-binding approach the `area` argument will be used. For now it is just a place-holder for a future improved implementation.

Example call:

```
PJ *P = proj_create_crs_to_crs(0, "epsg:25832", "epsg:25833", 0);
```

The returned `PJ`-pointer should be deallocated with `proj_destroy()`.

Parameters

- `ctx` (`PJ_CONTEXT*`) – Threading context.
- `srid_from` (`const char*`) – Source SRID.
- `srid_to` (`const char*`) – Destination SRID.
- `area` (`PJ_AREA`) – Descriptor of the desired area for the transformation.

Returns `PJ*`

`PJ* proj_destroy (PJ *P)`

Deallocate a `PJ` transformation object.

Parameters

- `P` (`PJ*`) –

Returns `PJ*`

Coordinate transformation

`PJ_COORD proj_trans (PJ *P, PJ_DIRECTION direction, PJ_COORD coord)`

Transform a single `PJ_COORD` coordinate.

Parameters

- `P` (`PJ*`) –
- `direction` (`PJ_DIRECTION`) – Transformation direction.
- `coord` (`PJ_COORD`) – Coordinate that will be transformed.

Returns `PJ_COORD`

`size_t proj_trans_generic (PJ *P, PJ_DIRECTION direction, double *x, size_t sx, size_t nx, double *y, size_t sy, size_t ny, double *z, size_t sz, size_t nz, double *t, size_t st, size_t nt)`

Transform a series of coordinates, where the individual coordinate dimension may be represented by an array that is either

1. fully populated
2. a null pointer and/or a length of zero, which will be treated as a fully populated array of zeroes
3. of length one, i.e. a constant, which will be treated as a fully populated array of that constant value

The strides, `sx`, `sy`, `sz`, `st`, represent the step length, in bytes, between consecutive elements of the corresponding array. This makes it possible for `proj_transform()` to handle transformation of a large class of application specific data structures, without necessarily understanding the data structure format, as in:

```
typedef struct {
    double x, y;
    int quality_level;
    char surveyor_name[134];
} XYQS;

XYQS survey[345];
```

(continues on next page)

(continued from previous page)

```

double height = 23.45;
size_t stride = sizeof (XYQS);

...
proj_trans_generic (
    P, PJ_INV, sizeof(XYQS),
    &(survey[0].x), stride, 345, /* We have 345 eastings */
    &(survey[0].y), stride, 345, /* ...and 345 northings. */
    &height, 1,                /* The height is the constant 23.45 m */
    0, 0                      /* and the time is the constant 0.00 s */
);

```

This is similar to the inner workings of the deprecated `pj_transform` function, but the stride functionality has been generalized to work for any size of basic unit, not just a fixed number of doubles.

In most cases, the stride will be identical for `x`, `y`, `z`, and `t`, since they will typically be either individual arrays (`stride = sizeof(double)`), or strided views into an array of application specific data structures (`stride = sizeof(...)`).

But in order to support cases where `x`, `y`, `z`, and `t` come from heterogeneous sources, individual strides, `sx`, `sy`, `sz`, `st`, are used.

Note: Since `proj_transform()` does its work *in place*, this means that even the supposedly constants (i.e. length 1 arrays) will return from the call in altered state. Hence, remember to reinitialize between repeated calls.

Parameters

- **P** (`PJ*`) – Transformation object
- **direction** – Transformation direction
- **x** (`double*`) – Array of x-coordinates
- **y** (`double*`) – Array of y-coordinates
- **z** (`double*`) – Array of z-coordinates
- **t** (`double*`) – Array of t-coordinates
- **sx** (`size_t`) – Step length, in bytes, between consecutive elements of the corresponding array
- **nx** (`size_t`) – Number of elements in the corresponding array
- **sy** (`size_t`) – Step length, in bytes, between consecutive elements of the corresponding array
- **nv** (`size_t`) – Number of elements in the corresponding array
- **sz** (`size_t`) – Step length, in bytes, between consecutive elements of the corresponding array
- **nz** (`size_t`) – Number of elements in the corresponding array
- **st** (`size_t`) – Step length, in bytes, between consecutive elements of the corresponding array
- **nt** (`size_t`) – Number of elements in the corresponding array

Returns Number of transformations successfully completed

`size_t proj_trans_array (PJ *P, PJ_DIRECTION direction, size_t n, PJ_COORD *coord)`
 Batch transform an array of `PJ_COORD`.

Parameters

- `P (PJ*)` –
- `direction (PJ_DIRECTION)` – Transformation direction
- `n (size_t)` – Number of coordinates in `coord`

Returns `size_t` 0 if all observations are transformed without error, otherwise returns error number

Error reporting

`int proj_errno (PJ *P)`

Get a reading of the current error-state of `P`. An non-zero error codes indicates an error either with the transformation setup or during a transformation.

Param `PJ* P`: Transformation object.

Returns `int`

`void proj_errno_set (PJ *P, int err)`

Change the error-state of `P` to `err`.

param PJ* P Transformation object.

param int err Error number.

`int proj_errno_reset (PJ *P)`

Clears the error number in `P`, and bubbles it up to the context.

Example:

```
void foo (PJ *P) {
    int last_errno = proj_errno_reset (P);

    do_something_with_P (P);

    /* failure - keep latest error status */
    if (proj_errno (P))
        return;
    /* success - restore previous error status */
    proj_errno_restore (P, last_errno);
    return;
}
```

Param `PJ* P`: Transformation object.

Returns `int` Returns the previous value of the `errno`, for convenient reset/restore operations.

`void proj_errno_restore (PJ *P, int err)`

Reduce some mental impedance in the canonical reset/restore use case: Basically, `proj_errno_restore()` is a synonym for `proj_errno_set()`, but the use cases are very different: `set` indicate an error to higher level user code, `restore` passes previously set error indicators in case of no errors at this level.

Hence, although the inner working is identical, we provide both options, to avoid some rather confusing real world code.

See usage example under `proj_errno_reset()`

Parameters

- **P** (`PJ*`) – Transformation object.
- **err** (`int`) – Error code.

`const char* proj_errno_string (int err)`

Get a text representation of an error number.

Parameters

- **err** (`int`) – Error number.

Returns `const char*` String with description of error.

Note: Available from version 5.1.0.

Logging

`PJ_LOG_LEVEL proj_log_level (PJ_CONTEXT *ctx, PJ_LOG_LEVEL level)`

Get and set logging level for a given context. Changes the log level to `level` and returns the previous logging level. If called with `level` set to `PJ_LOG_TELL` the function returns the current logging level without changing it.

Parameters

- **ctx** (`PJ_CONTEXT*`) – Threading context.
- **level** (`PJ_LOG_LEVEL`) – New logging level.

Returns `PJ_LOG_LEVEL`

New in version 5.1.0.

`void proj_log_func (PJ_CONTEXT *ctx, void *app_data, PJ_LOG_FUNCTION logf)`

Override the internal log function of PROJ.

Parameters

- **ctx** (`PJ_CONTEXT*`) – Threading context.
- **app_data** (`void*`) – Pointer to data structure used by the calling application.
- **logf** (`PJ_LOG_FUNCTION`) – Log function that overrides the PROJ log function.

New in version 5.1.0.

Info functions

`PJ_INFO proj_info (void)`

Get information about the current instance of the PROJ library.

Returns `PJ_INFO`

`PJ_PROJ_INFO proj_pj_info (const PJ *P)`

Get information about a specific transformation object, `P`.

Parameters

- **P** (`const PJ*`) – Transformation object

Returns `PJ_PROJ_INFO`

`PJ_GRID_INFO` **proj_grid_info** (const char **gridname*)

Get information about a specific grid.

Parameters

- **gridname** (*const char* *) – Gridname in the PROJ searchpath

Returns `PJ_GRID_INFO`

`PJ_INIT_INFO` **proj_init_info** (const char **initname*)

Get information about a specific init file.

Parameters

- **initname** (*const char* *) – Init file in the PROJ searchpath

Returns `PJ_INIT_INFO`

Lists

const `PJ_OPERATIONS*` **proj_list_operations** (void)

Get a pointer to an array of all operations in PROJ. The last entry of the returned array is a NULL-entry. The array is statically allocated and does not need to be freed after use.

Print a list of all operations in PROJ:

```
PJ_OPERATIONS *ops;
for (ops = proj_list_operations(); ops->id; ++ops)
    printf("%s\n", ops->id);
```

Returns `PJ_OPERATIONS*`

const `PJ_ELLPS*` **proj_list_ellps** (void)

Get a pointer to an array of ellipsoids defined in PROJ. The last entry of the returned array is a NULL-entry. The array is statically allocated and does not need to be freed after use.

Returns `PJ_ELLPS*`

const `PJ_UNITS*` **proj_list_units** (void)

Get a pointer to an array of distance units defined in PROJ. The last entry of the returned array is a NULL-entry. The array is statically allocated and does not need to be freed after use.

Returns `PJ_UNITS*`

const `PJ_PRIME_MERIDIANS*` **proj_list_prime_meridians** (void)

Get a pointer to an array of prime meridians defined in PROJ. The last entry of the returned array is a NULL-entry. The array is statically allocated and does not need to be freed after use.

Returns `PJ_PRIME_MERIDIANS*`

Distances

double **proj_lp_dist** (const `PJ` **P*, `PJ_COORD` *a*, `PJ_COORD` *b*)

Calculate geodesic distance between two points in geodetic coordinates. The calculated distance is between the two points located on the ellipsoid.

Parameters

- **P** (`PJ` *) – Transformation object

- **a** (`PJ_COORD`) – Coordinate of first point
- **b** (`PJ_COORD`) – Coordinate of second point

Returns double Distance between a and b in meters.

double `proj_lpz_dist` (const `PJ` **P*, `PJ_COORD` *a*, `PJ_COORD` *b*)

Calculate geodesic distance between two points in geodetic coordinates. Similar to `proj_lp_dist()` but also takes the height above the ellipsoid into account.

Parameters

- **P** (`PJ*`) – Transformation object
- **a** (`PJ_COORD`) – Coordinate of first point
- **b** (`PJ_COORD`) – Coordinate of second point

Returns double Distance between a and b in meters.

double `proj_xy_dist` (`PJ_COORD` *a*, `PJ_COORD` *b*)

Calculate 2-dimensional euclidean between two projected coordinates.

Parameters

- **a** (`PJ_COORD`) – First coordinate
- **b** (`PJ_COORD`) – Second coordinate

Returns double Distance between a and b in meters.

double `proj_xyz_dist` (`PJ_COORD` *a*, `PJ_COORD` *b*)

Calculate 3-dimensional euclidean between two projected coordinates.

Parameters

- **a** (`PJ_COORD`) – First coordinate
- **b** (`PJ_COORD`) – Second coordinate

Returns double Distance between a and b in meters.

Various

`PJ_COORD proj_coord`(double *x*, double *y*, double *z*, double *t*)

Initializer for the `PJ_COORD` union. The function is shorthand for the otherwise convoluted assignment. Equivalent to

```
PJ_COORD c = {{10.0, 20.0, 30.0, 40.0}};
```

or

```
PJ_COORD c;
// Assign using the PJ_XYZT struct in the union
c.xyzt.x = 10.0;
c.xyzt.y = 20.0;
c.xyzt.z = 30.0;
c.xyzt.t = 40.0;
```

Since `PJ_COORD` is a union of structs, the above assignment can also be expressed in terms of the other types in the union, e.g. `PJ_UVWT` or `PJ_LPZT`.

Parameters

- **x** (*double*) – 1st component in a *PJ_COORD*
- **y** (*double*) – 2nd component in a *PJ_COORD*
- **z** (*double*) – 3rd component in a *PJ_COORD*
- **t** (*double*) – 4th component in a *PJ_COORD*

Returns *PJ_COORD*

double proj_roundtrip (*PJ* **P*, *PJ_DIRECTION* *direction*, int *n*, *PJ_COORD* **coord*)

Measure internal consistency of a given transformation. The function performs *n* round trip transformations starting in either the forward or reverse *direction*. Returns the euclidean distance of the starting point *coo* and the resulting coordinate after *n* iterations back and forth.

Parameters

- **P** (*const PJ**) –
- **direction** (*PJ_DIRECTION*) – Starting direction of transformation
- **n** (*int*) – Number of roundtrip transformations
- **coord** (*PJ_COORD*) – Input coordinate

Returns double Distance between original coordinate and the resulting coordinate after *n* transformation iterations.

PJ_FACTORS **proj_factors** (*PJ* **P*, *PJ_COORD* *lp*)

Calculate various cartographic properties, such as scale factors, angular distortion and meridian convergence. Depending on the underlying projection values will be calculated either numerically (default) or analytically.

The function also calculates the partial derivatives of the given coordinate.

Parameters

- **P** (*const PJ**) – Transformation object
- **lp** (*const PJ_COORD*) – Geodetic coordinate

Returns *PJ_FACTORS*

double proj_torad (*double angle_in_degrees*)

Convert degrees to radians.

Parameters

- **angle_in_degrees** (*double*) – Degrees

Returns double Radians

double proj_todeg (*double angle_in_radians*)

Convert radians to degrees

Parameters

- **angle_in_radians** (*double*) – Radians

Returns double Degrees

double proj_dmstor (*const char* **is*, *char* ***rs*)

Convert string of degrees, minutes and seconds to radians. Works similarly to the C standard library function *strtod*().

Parameters

- **is** (*const char**) – Value to be converted to radians

- **rs** – Reference to an already allocated `char*`, whose value is set by the function to the next character in `s` after the numerical value.

`char *proj_rtodms (char *s, double r, int pos, int neg)`
Convert radians to string representation of degrees, minutes and seconds.

Parameters

- **s** (`char *`) – Buffer that holds the output string
- **r** (`double`) – Value to convert to dms-representation
- **pos** (`int`) – Character denoting positive direction, typically ‘N’ or ‘E’.
- **neg** (`int`) – Character denoting negative direction, typically ‘S’ or ‘W’.

Returns `char*` Pointer to output buffer (same as `s`)

`PJ_COORD proj_geocentric_latitude (const PJ *P, PJ_DIRECTION direction, PJ_COORD coord)`
Convert from geographical latitude to geocentric latitude.

Parameters

- **P** (`const PJ*`) – Transformation object
- **direction** (`PJ_DIRECTION`) – Starting direction of transformation
- **coord** (`PJ_COORD`) – Coordinate

Returns `PJ_COORD` Converted coordinate

`int proj_angular_input (PJ *P, enum PJ_DIRECTION dir)`
Check if a operation expects angular input.

Parameters

- **P** (`const PJ*`) – Transformation object
- **direction** (`PJ_DIRECTION`) – Starting direction of transformation

Returns `int` 1 if angular input is expected, otherwise 0

`int proj_angular_output (PJ *P, enum PJ_DIRECTION dir)`
Check if an operation returns angular output.

param P Transformation object
type P `const PJ*`
param direction Starting direction of transformation
type direction `PJ_DIRECTION`
returns `int` 1 if angular output is returned, otherwise 0

9.5.3 Deprecated API

Contents

- *Deprecated API*
 - *Introduction*
 - *Example*

- *API Functions*
 - * *pj_transform*
 - * *pj_init_plus*
 - * *pj_free*
 - * *pj_is_latlong*
 - * *pj_is_geocent*
 - * *pj_get_def*
 - * *pj_latlong_from_proj*
 - * *pj_set_finder*
 - * *pj_set_searchpath*
 - * *pj_deallocate_grids*
 - * *pj_strerror*
 - * *pj_get_errno_ref*
 - * *pj_get_release*

Introduction

Procedure `pj_init()` selects and initializes a cartographic projection with its argument control parameters. `argc` is the number of elements in the array of control strings `argv` that each contain individual cartographic control keyword assignments (+ proj arguments). The list must contain at least the proj=projection and Earth's radius or elliptical parameters. If the initialization of the projection is successful a valid address is returned otherwise a NULL value.

The `pj_init_plus()` function operates similarly to `pj_init()` but takes a single string containing the definition, with each parameter prefixed with a plus sign. For example +proj=utm +zone=11 +ellps=WGS84.

Once initialization is performed either forward or inverse projections can be performed with the returned value of `pj_init()` used as the argument `proj`. The argument structure `projUV` values `u` and `v` contain respective longitude and latitude or `x` and `y`. Latitude and longitude are in radians. If a projection operation fails, both elements of `projUV` are set to `HUGE_VAL` (defined in `math.h`).

Note: all projections have a forward mode, but some do not have an inverse projection. If the projection does not have an inverse the `projPJ` structure element `inv` will be NULL.

The `pj_transform` function may be used to transform points between the two provided coordinate systems. In addition to converting between cartographic projection coordinates and geographic coordinates, this function also takes care of datum shifts if possible between the source and destination coordinate system. Unlike `pj_fwd()` and `pj_inv()` it is also allowable for the coordinate system definitions (`projPJ *`) to be geographic coordinate systems (defined as +proj=latlong). The `x`, `y` and `z` arrays contain the input values of the points, and are replaced with the output values. The function returns zero on success, or the error number (also in `pj_errno`) on failure.

Memory associated with the projection may be freed with `pj_free()`.

Example

The following program reads latitude and longitude values in decimal degrees, performs Mercator projection with a Clarke 1866 ellipsoid and a 33° latitude of true scale and prints the projected cartesian values in meters:

```
#include <proj_api.h>

main(int argc, char **argv) {
    projPJ pj_merc, pj_latlong;
    double x, y;

    if (!(pj_merc = pj_init_plus("+proj=merc +ellps=clrk66 +lat_ts=33")) )
        exit(1);
    if (!(pj_latlong = pj_init_plus("+proj=latlong +ellps=clrk66")) )
        exit(1);
    while (scanf("%lf %lf", &x, &y) == 2) {
        x *= DEG_TO_RAD;
        y *= DEG_TO_RAD;
        p = pj_transform(pj_latlong, pj_merc, 1, 1, &x, &y, NULL );
        printf("%.2f\t%.2f\n", x, y);
    }
    exit(0);
}
```

For this program, an input of -16 20.25 would give a result of -1495284.21 1920596.79.

API Functions

pj_transform

```
int pj_transform( projPJ srcdefn,
                  projPJ dstdefn,
                  long point_count,
                  int point_offset,
                  double *x,
                  double *y,
                  double *z );
```

Transform the x/y/z points from the source coordinate system to the destination coordinate system.

srcdefn: source (input) coordinate system.

dstdefn: destination (output) coordinate system.

point_count: the number of points to be processed (the size of the x/y/z arrays).

point_offset: the step size from value to value (measured in doubles) within the x/y/z arrays - normally 1 for a packed array. May be used to operate on xyz interleaved point arrays.

x/y/z: The array of X, Y and Z coordinate values passed as input, and modified in place for output. The Z may optionally be NULL.

return: The return is zero on success, or a PROJ.4 error code.

The `pj_transform()` function transforms the passed in list of points from the source coordinate system to the destination coordinate system. Note that geographic locations need to be passed in radians, not decimal degrees, and will be returned similarly. The z array may be passed as NULL if Z values are not available.

If there is an overall failure, an error code will be returned from the function. If individual points fail to transform - for instance due to being over the horizon - then those x/y/z values will be set to `HUGE_VAL` on return. Input values that are `HUGE_VAL` will not be transformed.

pj_init_plus

```
projPJ pj_init_plus(const char *definition);
```

This function converts a string representation of a coordinate system definition into a projPJ object suitable for use with other API functions. On failure the function will return NULL and set pj_errno. The definition should be of the general form +proj=tmerc +lon_0 +datum=WGS84. Refer to PROJ.4 documentation and the [Geodetic transformation](#) notes for additional detail.

Coordinate system objects allocated with `pj_init_plus()` should be deallocated with `pj_free()`.

pj_free

```
void pj_free( projPJ pj );
```

Frees all resources associated with pj.

pj_is_latlong

```
int pj_is_latlong( projPJ pj );
```

Returns TRUE if the passed coordinate system is geographic (proj=latlong).

pj_is_geocent

```
int pj_is_geocent( projPJ pj );``
```

Returns TRUE if the coordinate system is geocentric (proj=geocent).

pj_get_def

```
char *pj_get_def( projPJ pj, int options);``
```

Returns the PROJ.4 initialization string suitable for use with `pj_init_plus()` that would produce this coordinate system, but with the definition expanded as much as possible (for instance +init= and +datum= definitions).

pj_latlong_from_proj

```
projPJ pj_latlong_from_proj( projPJ pj_in );``
```

Returns a new coordinate system definition which is the geographic coordinate (lat/long) system underlying `pj_in`.

pj_set_finder

```
void pj_set_finder( const char *(*new_finder)(const char *) );``
```

Install a custom function for finding init and grid shift files.

pj_set_searchpath

```
void pj_set_searchpath( int count, const char **path );``
```

Set a list of directories to search for init and grid shift files.

pj_deallocate_grids

```
void pj_deallocate_grids( void );``
```

Frees all resources associated with loaded and cached datum shift grids.

pj_strerror

```
char *pj_strerror( int );``
```

Returns the error text associated with the passed in error code.

pj_get_errno_ref

```
int *pj_get_errno_ref( void );``
```

Returns a pointer to the global pj_errno error variable.

pj_get_release

```
const char *pj_get_release( void );``
```

Returns an internal string describing the release version.

Obsolete Functions

```
XY pj_fwd( LP lp, PJ *P );
LP pj_inv( XY xy, PJ *P );
projPJ pj_init(int argc, char **argv);
```

9.6 Using PROJ in CMake projects

The recommended way to use the PROJ library in a CMake project is to link to the imported library target `${PROJ4_LIBRARIES}` provided by the CMake configuration which comes with the library. Typical usage is:

```
find_package(PROJ4)
target_link_libraries(MyApp ${PROJ4_LIBRARIES})
```

By adding the imported library target `PROJ4_LIBRARIES` to the target link libraries, CMake will also pass the include directories to the compiler. This requires that you use CMake version 2.8.11 or later. If you are using an older version of CMake, then add

```
include_directories(${PROJ4_INCLUDE_DIRS})
```

The CMake command `find_package` will look for the configuration in a number of places. The lookup can be adjusted for all packages by setting the cache variable or environment variable `CMAKE_PREFIX_PATH`. In particular, CMake will consult (and set) the cache variable `PROJ4_DIR`.

9.7 Language bindings

PROJ bindings are available for a number of different development platforms.

9.7.1 Python

`pypyproj`: Python interface (wrapper for PROJ)

9.7.2 Ruby

`proj4rb`: Bindings for PROJ in ruby

9.7.3 TCL

`proj4tcl`: Bindings for PROJ in tcl (critcl source)

9.7.4 MySQL

`fProj4`: Bindings for PROJ in MySQL

9.7.5 Excel

`proj.xll`: Excel add-in for PROJ map projections

9.7.6 Visual Basic

PROJ VB Wrappers: By Eric G. Miller.

9.8 Version 4 to 5 API Migration

This is a transition guide for developers wanting to migrate their code to use PROJ version 5.

9.8.1 Background

Before we go on, a bit of background is needed. The new API takes a different view of the world than the old because it is needed in order to obtain high accuracy transformations. The old API is constructed in such a way that any transformation between two coordinate reference systems *must* pass through the ill-defined WGS84 reference frame, using it as a hub. The new API does away with this limitation to transformations in PROJ. It is still possible to do that type of transformations but in many cases there will be a better alternative.

The world view represented by the old API is always sufficient if all you care about is meter level accuracy - and in many cases it will provide much higher accuracy than that. But the view that “WGS84 is the *true* foundation of the world, and everything else can be transformed natively to and from WGS84” is inherently flawed.

First and foremost because any time WGS84 is mentioned, you should ask yourself “Which of the six WGS84 realizations are we talking about here?”.

Second, because for many (especially legacy) systems, it may not be straightforward to transform to WGS84 (or actually ITRF-something, ETRS-something or NAD-something which appear to be the practical meaning of the term WGS84 in everyday PROJ related work), while centimeter-level accurate transformations may exist between pairs of older systems.

The concept of a hub reference frame (“datum”) is not inherently bad, but in many cases you need to handle and select that datum with more care than the old API allows. The primary aim of the new API is to allow just that. And to do that, you must realize that the world is inherently 4 dimensional. You may in many cases assume one or more of the coordinates to be constant, but basically, to obtain geodetic accuracy transformations, you need to work in 4 dimensions.

Now, having described the background for introducing the new API, let’s try to show how to use it. First note that in order to go from system A to system B, the old API starts by doing an **inverse** transformation from system A to WGS84, then does a **forward** transformation from WGS84 to system B.

With `cs2cs` being the command line interface to the old API, and `cct` being the same for the new, this example of doing the same thing in both world views will should give an idea of the differences:

```
$ echo 300000 6100000 | cs2cs +proj=utm +zone=33 +ellps=GRS80 +to +proj=utm +zone=32
˓→+ellps=GRS80
683687.87      6099299.66 0.00

$ echo 300000 6100000 0 0 | cct +proj=pipeline +step +inv +proj=utm +zone=33
˓→+ellps=GRS80 +step +proj=utm +zone=32 +ellps=GRS80
683687.8667    6099299.6624    0.0000    0.0000
```

Lookout for the `+inv` in the first `+step`, indicating an inverse transform.

9.8.2 Code example

The difference between the old and new API is shown here with a few examples. Below we implement the same program with the two different API’s. The program reads input latitude and longitude from the command line and convert them to projected coordinates with the Mercator projection.

We start by writing the program for PROJ v. 4:

```
#include <proj_api.h>

main(int argc, char **argv) {
    projPJ pj_merc, pj_latlong;
    double x, y;
```

(continues on next page)

(continued from previous page)

```

if (! (pj_merc = pj_init_plus("+proj=merc +ellps=clrk66 +lat_ts=33")) )
    return 1;
if (! (pj_latlong = pj_init_plus("+proj=latlong +ellps=clrk66")) )
    return 1;

while (scanf("%lf %lf", &x, &y) == 2) {
    x *= DEG_TO_RAD;
    y *= DEG_TO_RAD;
    p = pj_transform(pj_latlong, pj_merc, 1, 1, &x, &y, NULL );
    printf("%.2f\t%.2f\n", x, y);
}

return 0;
}

```

The same program implemented using PROJ v. 5:

```

#include <proj.h>

main(int argc, char **argv) {
    PJ *P;
    PJ_COORD c;

    P = proj_create(PJ_DEFAULT_CTX, "+proj=merc +ellps=clrk66 +lat_ts=33");
    if (P==0)
        return 1;

    while (scanf("%lf %lf", &c.lp.lam, &c.lp.phi) == 2) {
        c.lp.lam = proj_todeg(c.lp.lam);
        c.lp.phi = proj_todeg(c.lp.phi);
        c = proj_trans(P, PJ_FWD, c);
        printf("%.2f\t%.2f\n", c.xy.x, c.xy.y);
    }
}

```

Looking at the two different programs, there's a few immediate differences that catches the eye. First off, the included header file describing the API has changed from `proj_api.h` to simply `proj.h`. All functions in `proj.h` belongs to the `proj_` namespace.

With the new API also comes new datatypes. E.g. the transformation object `projPJ` which has been changed to a pointer of type `PJ`. This is done to highlight the actual nature of the object, instead of hiding it away behind a `typedef`. New data types for handling coordinates have also been introduced. In the above example we use the `PJ_COORD`, which is a union of various types. The benefit of this is that it is possible to use the various structs in the union to communicate what state the data is in at different points in the program. For instance as in the above example where the coordinate is read from STDIN as a geodetic coordinate, communicated to the reader of the code by using the `c.lp` struct. After it has been projected we print it to STDOUT by accessing the individual elements in `c.xy` to illustrate that the coordinate is now in projected space. Data types are prefixed with `PJ_`.

The final, and perhaps biggest, change is that the fundamental concept of transformations in PROJ are now handled in a single transformation object (`PJ`) and not by stating the source and destination systems as previously. It is of course still possible to do just that, but the transformation object now captures the whole transformation from source to destination in one. In the example with the old API the source system is described as `+proj=latlong +ellps=clrk66` and the destination system is described as `+proj=merc +ellps=clrk66 +lat_ts=33`. Since the Mercator projection accepts geodetic coordinates as its input, the description of the source in this case is superfluous. We use that to our advantage in the new API and simply state the destination. This is simple at a glance,

but is actually a big conceptual change. We are now focused on the path between two systems instead of what the source and destination systems are.

9.8.3 Function mapping from old to new API

Old API functions	New API functions
pj_fwd	proj_trans
pj_inv	proj_trans
pj_fwd3	proj_trans
pj_inv3	proj_trans
pj_transform	proj_trans_array or proj_trans_generic
pj_init	proj_create
pj_init_plus	proj_create
pj_free	proj_destroy
pj_is_latlong	proj-angular_output
pj_is_geocent	proj-angular_outout
pj_get_def	proj_pj_info
pj_latlong_from_proj	<i>No equivalent</i>
pj_set_finder	<i>No equivalent</i>
pj_set_searchpath	<i>No equivalent</i>
pj_deallocate_grids	<i>No equivalent</i>
pj_strerror	<i>No equivalent</i>
pj_get_errno_ref	proj_errno
pj_get_release	proj_info

COMMUNITY

The PROJ community is what makes the software stand out from its competitors. PROJ is used and developed by group of very enthusiastic, knowledgeable and friendly people. Whether you are a first time user of PROJ or a long-time contributor the community is always very welcoming.

10.1 Communication channels

10.1.1 Mailing list

Users and developers of the library are using the mailing list to discuss all things related to PROJ. The mailing list is the primary forum for asking for help with use of PROJ. The mailing list is also used for announcements, discussions about the development of the library and from time to time interesting discussions on geodesy appear as well. You are more than welcome to join in on the discussions!

The PROJ mailing list can be found at <http://lists.maptools.org/mailman/listinfo/proj>

10.1.2 GitHub

GitHub is the development platform we use for collaborating on the PROJ code. We use GitHub to keep track of the changes in the code and to index bug reports and feature requests. We are happy to take contributions in any form, either as code, bug reports, documentation or feature requests. See [Contributing](#) for more info on how you can help improve PROJ.

The PROJ GitHub page can be found at <https://github.com/OSGeo/proj.4>

Note: The issue tracker on GitHub is only meant to keep track of bugs, feature request and other things related to the development of PROJ. Please ask your questions about the use of PROJ on the mailing list instead.

10.2 Contributing

PROJ has a wide and varied user base. Some are highly skilled geodesists with a deep knowledge of map projections and reference systems, some are GIS software developers and others are GIS users. All users, regardless of the profession or skill level, has the ability to contribute to PROJ. Here's a few suggestion on how:

- Help PROJ-users that is less experienced than yourself.
- Write a bug report
- Request a new feature

- Write documentation for your favorite map projection
- Fix a bug
- Implement a new feature

In the following sections you can find some guidelines on how to contribute. As PROJ is managed on GitHub most contributions require that you have a GitHub account. Familiarity with [issues](#) and the [GitHub Flow](#) is an advantage.

10.2.1 Help a fellow PROJ user

The main forum for support for PROJ is the mailing list. You can subscribe to the mailing list [here](#) and read the archive [here](#).

If you have questions about the usage of PROJ the mailing list is also the place to go. Please *do not* use the GitHub issue tracker as a support forum. Your question is much more likely to be answered on the mailing list, as many more people follow that than the issue tracker.

10.2.2 Adding bug reports

Bug reports are handled in the [issue tracker](#) on PROJ's home on GitHub. Writing a good bug report is not easy. But fixing a poorly documented bug is not easy either, so please put in the effort it takes to create a thorough bug report.

A good bug report includes at least:

- A title that quickly explains the problem
- A description of the problem and how it can be reproduced
- Version of PROJ being used
- Version numbers of any other relevant software being used, e.g. operating system
- A description of what already has been done to solve the problem

The more information that is given up front, the more likely it is that a developer will find interest in solving the problem. You will probably get follow-up questions after submitting a bug report. Please answer them in a timely manner if you have an interest in getting the issue solved.

Finally, please only submit bug reports that are actually related to PROJ. If the issue materializes in software that uses PROJ it is likely a problem with that particular software. Make sure that it actually is a PROJ problem before you submit an issue. If you can reproduce the problem only by using tools from PROJ it is definitely a problem with PROJ.

10.2.3 Feature requests

Got an idea for a new feature in PROJ? Submit a thorough description of the new feature in the [issue tracker](#). Please include any technical documents that can help the developer make the new feature a reality. An example of this could be a publicly available academic paper that describes a new projection. Also, including a numerical test case will make it much easier to verify that an implementation of your requested feature actually works as you expect.

Note that not all feature requests are accepted.

10.2.4 Write documentation

PROJ is in dire need of better documentation. Any contributions of documentation are greatly appreciated. The PROJ documentation is available on [proj4.org](#). The website is generated with [Sphinx](#). Contributions to the documentation should be made as [Pull Requests](#) on GitHub.

If you intend to document one of PROJ's supported projections please use the *Mercator projection* as a template.

10.2.5 Code contributions

See *Code contributions*

Legalese

Committees are the front line gatekeepers to keep the code base clear of improperly contributed code. It is important to the PROJ users, developers and the OSGeo foundation to avoid contributing any code to the project without it being clearly licensed under the project license.

Generally speaking the key issues are that those providing code to be included in the repository understand that the code will be released under the MIT/X license, and that the person providing the code has the right to contribute the code. For the committer themselves understanding about the license is hopefully clear. For other contributors, the committer should verify the understanding unless the committer is very comfortable that the contributor understands the license (for instance frequent contributors).

If the contribution was developed on behalf of an employer (on work time, as part of a work project, etc) then it is important that an appropriate representative of the employer understand that the code will be contributed under the MIT/X license. The arrangement should be cleared with an authorized supervisor/manager, etc.

The code should be developed by the contributor, or the code should be from a source which can be rightfully contributed such as from the public domain, or from an open source project under a compatible license.

All unusual situations need to be discussed and/or documented.

Committees should adhere to the following guidelines, and may be personally legally liable for improperly contributing code to the source repository:

- Make sure the contributor (and possibly employer) is aware of the contribution terms.
- Code coming from a source other than the contributor (such as adapted from another project) should be clearly marked as to the original source, copyright holders, license terms and so forth. This information can be in the file headers, but should also be added to the project licensing file if not exactly matching normal project licensing (COPYING).
- Existing copyright headers and license text should never be stripped from a file. If a copyright holder wishes to give up copyright they must do so in writing to the foundation before copyright messages are removed. If license terms are changed it has to be by agreement (written in email is ok) of the copyright holders.
- Code with licenses requiring credit, or disclosure to users should be added to COPYING.
- When substantial contributions are added to a file (such as substantial patches) the author/contributor should be added to the list of copyright holders for the file.
- If there is uncertainty about whether a change is proper to contribute to the code base, please seek more information from the project steering committee, or the foundation legal counsel.

10.2.6 Additional Resources

- General GitHub documentation
- GitHub pull request documentation

10.2.7 Acknowledgements

The *code contribution* section of this CONTRIBUTING file is inspired by [PDAL's](#) and the *legalese* section is modified from [GDAL committer guidelines](#)

10.3 Guidelines for PROJ code contributors

This is a guide for PROJ, casual or regular, code contributors.

10.3.1 Code contributions.

Code contributions can be either bug fixes or new features. The process is the same for both, so they will be discussed together in this section.

Making Changes

- Create a topic branch from where you want to base your work.
- You usually should base your topic branch off of the master branch.
- To quickly create a topic branch: `git checkout -b my-topic-branch`
- Make commits of logical units.
- Check for unnecessary whitespace with `git diff --check` before committing.
- Make sure your commit messages are in the [proper format](#).
- Make sure you have added the necessary tests for your changes.
- Make sure that all tests pass

Submitting Changes

- Push your changes to a topic branch in your fork of the repository.
- Submit a pull request to the PROJ repository in the OSGeo organization.
- If your pull request fixes/references an issue, include that issue number in the pull request. For example:

```
Wiz the bang
```

```
Fixes #123.
```

- PROJ developers will look at your patch and take an appropriate action.

Coding conventions

Programming language

PROJ is developed strictly in ANSI C 89.

Coding style

We don't enforce any particular coding style, but please try to keep it as simple as possible. If improving existing code, please try to conform with the style of the locally surrounding code.

Whitespace

Throughout the PROJ code base you will see differing whitespace use. The general rule is to keep whitespace in whatever form it is in the file you are currently editing. If the file has a mix of tabs and space please convert the tabs to space in a separate commit before making any other changes. This makes it a lot easier to see the changes in diffs when evaluating the changed code. New files should use spaces as whitespace.

File names

Files in which projections are implemented are prefixed with an upper-case `PJ_` and most other files are prefixed with lower-case `pj_`. Some file deviate from this pattern, most of them dates back to the very early releases of PROJ. New contributions should follow the pj-prefix pattern. Unless there are obvious reasons not to.

10.3.2 Tools

cppcheck static analyzer

You can run locally `scripts/cppcheck.sh` that is a wrapper script around the `cppcheck` utility. It is known to work with `cppcheck 1.61` of Ubuntu Trusty 14.0, since this is what is currently used on Travis-CI (`travis/linux_gcc/before_install.sh`). At the time of writing, this also works with `cppcheck 1.72` of Ubuntu Xenial 16.04, and latest `cppcheck` master.

`cppcheck` can have false positives. In general, it is preferable to rework the code a bit to make it more ‘obvious’ and avoid those false positives. When not possible, you can add a comment in the code like

```
/* cppcheck-suppress duplicateBreak */
```

in the preceding line. Replace `duplicateBreak` with the actual name of the violated rule emitted by `cppcheck`.

CLang Static Analyzer (CSA)

CSA is run by the `travis/csa` build configuration. You may also run it locally.

Preliminary step: install clang. For example:

```
wget http://releases.llvm.org/6.0.0/clang+llvm-6.0.0-x86_64-linux-gnu-ubuntu-14.04.  
tar.xz  
tar xJf clang+llvm-6.0.0-x86_64-linux-gnu-ubuntu-14.04.tar.xz
```

Run configure under the `scan-build` utility of clang:

```
./clang+llvm-6.0.0-x86_64-linux-gnu-ubuntu-14.04/bin/scan-build ./configure
```

Build under `scan-build`:

```
./clang+llvm-6.0.0-x86_64-linux-gnu-ubuntu-14.04/bin/scan-build make [-j8]
```

If CSA finds errors, they will be emitted during the build. And in which case, at the end of the build process, scan-build will emit a warning message indicating errors have been found and how to display the error report. This is with something like

```
./clang+llvm-6.0.0-x86_64-linux-gnu-ubuntu-14.04/bin/scan-view /tmp/scan-build-2018-  
→03-15-121416-17476-1
```

This will open a web browser with the interactive report.

CSA may also have false positives. In general, this happens when the code is non-trivial / makes assumptions that hard to check at first sight. You will need to add extra checks or rework it a bit to make it more “obvious” for CSA. This will also help humans reading your code !

Type detection and fixes

Run `scripts/fix_typos.sh`

Include What You Use (IWYU)

Managing C includes is a pain. IWYU makes updating headers a bit easier. IWYU scans the code for functions that are called and makes sure that the headers for all those functions are present and in sorted order. However, you cannot blindly apply IWYU to PROJ. It does not understand ifdefs, other platforms, or the order requirements of PROJ internal headers. So the way to use it is to run it on a copy of the source and merge in only the changes that make sense. Additions of standard headers should always be safe to merge. The rest require careful evaluation. See the IWYU documentation for motivation and details.

[IWYU docs](#)

11.1 Where can I find the list of projections and their arguments?

There is no simple single location to find all the required information. The !PostScript/PDF documents listed on the [<http://trac.osgeo.org/proj/wiki> main] PROJ page under documentation are the authoritative source but projections and options are spread over several documents in a form more related to their order of implementation than anything else.

The “‘proj’” command itself can report the list of projections using the “‘-lp’” option, the list of ellipsoids with the “‘-le’” option, the list of units with the “‘-lu’” option, and the list of built-in datums with the “‘-ld’” option.

The [http://www.remotesensing.org/geotiff/proj_list/ GeoTIFF Projections Pages] include most of the common PROJ projections, and a definition of the projection specific options for each.

- How do I do datum shifts between NAD27 and NAD83?

While the “‘nad2nad’” program can be used in some cases, the “‘cs2cs’” is now the preferred mechanism. The following example demonstrates using the default shift parameters for NAD27 to NAD83:

```
% cs2cs +proj=latlong +datum=NAD27 +to +proj=latlong +datum=NAD83 -117 30
```

producing:

```
117d0'2.901"W 30d0'0.407"N 0.000
```

In order for datum shifting to work properly the various grid shift files must be available. See below. More details are available in the [[wiki:GenParms#nadgrids-GridBasedDatumAdjustments General Parameters](#)] document.

11.2 How do I build/configure PROJ to support datum shifting?

After downloading and unpacking the PROJ source, also download and unpack the set of datum shift files. See [Download](#) for instructions how to fetch and install these files

On Windows the extra nadshift target must be used. For instance nmake /f makefile.vc nadshift in the proj/src directory.

A default build and install on Unix will normally build knowledge of the directory where the grid shift files are installed into the PROJ library (usually /usr/local/share/proj). On Windows the library is normally built thinking that C:PROJNAD is the installed directory for the grid shift files. If the built in concept of the PROJ data directory is incorrect, the PROJ_LIB environment can be defined with the correct directory.

11.3 How do I debug problems with NAD27/NAD83 datum shifting?

1. Verify that you have the binary files (eg. /usr/local/share/proj/conus) installed on your system. If not, see the previous question.
2. Try a datum shifting operation in relative isolation, such as with the cs2cs command listed above. Do you get reasonable results? If not it is likely the grid shift files aren't being found. Perhaps you need to define PROJ_LIB?
3. The cs2cs command and the underlying pj_transform() API know how to do a grid shift as part of a more complex coordinate transformation; however, it is imperative that both the source and destination coordinate system be defined with appropriate datum information. That means that implicitly or explicitly there must be a +datum= clause, a +nadgrids= clause or a +towgs84= clause. For instance cs2cs +proj=latlong +datum=NAD27 +to +proj=latlong +ellps=WGS84 won't work because defining the output coordinate system as using the ellipse WGS84 isn't the same as defining it to use the datum WGS84 (use +datum=WGS84). If either the input or output are not identified as having a datum, the datum shifting (and ellipsoid change) step is just quietly skipped!
4. The PROJ_DEBUG environment can be defined (any value) to force extra output from the PROJ library to stderr (the text console normally) with information on what data files are being opened and in some cases why a transformation fails.

```
export PROJ_DEBUG=ON
cs2cs ...
```

Note: PROJ_DEBUG support is not yet very mature in the PROJ library.

5. The -v flag to cs2cs can be useful in establishing more detail on what parameters being used internally for a coordinate system. This will include expanding the definition of +datum clause.

11.4 How do I use EPSG coordinate system codes with PROJ?

There is somewhat imperfect translation between 2d geographic and projected coordinate system codes and PROJ descriptions of the coordinate system available in the epsg definition file that normally lives in the proj/nad directory. If installed (it is installed by default on Unix), it is possible to use EPSG numbers like this:

```
% cs2cs -v +init=epsg:26711
# ---- From Coordinate System ----
#Universal Transverse Mercator (UTM)
#      Cyl, Sph
#      zone= south
# +init=epsg:26711 +proj=utm +zone=11 +ellps=clrk66 +datum=NAD27 +units=m
# +no_defs +nadgrids=conus,ntv1_can.dat
#--- following specified but NOT used
# +ellps=clrk66
# ---- To Coordinate System ----
#Lat/long (Geodetic)
#
# +proj=latlong +datum=NAD27 +ellps=clrk66 +nadgrids=conus,ntv1_can.dat
```

The proj/nad/epsg file can be browsed and searched in a text editor for coordinate systems. There are known to be problems with some coordinate systems, and any coordinate systems with odd axes, a non-greenwich prime meridian or other quirks are unlikely to work properly. Caveat Emptor!

11.5 How do I use 3 parameter and 7 parameter datum shifting

Datum shifts can be approximated with 3 and 7 parameter transformations. Their use is more fully described in the [wiki:GenParms#towgs84-DatumtransformationtoWGS84 towgs84] parameter discussion.

11.6 Does PROJ work in different international numeric locales?

No. PROJ makes extensive use of sprintf() and atof() internally to translate numeric values. If a locale is in effect that modifies formatting of numbers, altering the role of commas and periods in numbers, then PROJ will not work. This problem is common in some European locales.

On unix-like platforms, this problem can be avoided by forcing the use of the default numeric locale by setting the LC_NUMERIC environment variable to C.

```
$ export LC_NUMERIC=C
$ proj ...
```

Note: NOTE: Per ticket #49, in PROJ 4.7.0 and later pj_init() operates with locale overridden to “C” to avoid most locale specific processing for applications using the API. Command line tools may still have issues.

11.7 Changing Ellipsoid / Why can't I convert from WGS84 to Google Earth / Virtual Globe Mercator?

The coordinate system definition for Google Earth, and Virtual Globe Mercator is as follows, which uses a sphere as the earth model for the Mercator projection.

```
+proj=merc +a=6378137 +b=6378137 +lat_ts=0.0 +lon_0=0.0
+x_0=0.0 +y_0=0 +k=1.0 +units=m +no_defs
```

But, if you do something like:

```
cs2cs +proj=latlong +datum=WGS84
+to +proj=merc +a=6378137 +b=6378137 +lat_ts=0.0 +lon_0=0.0
+x_0=0.0 +y_0=0 +k=1.0 +units=m +no_defs
```

to convert between WGS84 and mercator on the sphere there will be substantial shifts in the Y mercator coordinates. This is because internally cs2cs is having to adjust the lat/long coordinates from being on the sphere to being on the WGS84 datum which has a quite differently shaped ellipsoid.

In this case, and many other cases using spherical projections, the desired approach is to actually treat the lat/long locations on the sphere as if they were on WGS84 without any adjustments when using them for converting to other coordinate systems. The solution is to “trick” PROJ into applying no change to the lat/long values when going to (and through) WGS84. This can be accomplished by asking PROJ to use a null grid shift file for switching from your spherical lat/long coordinates to WGS84.

```
cs2cs +proj=latlong +datum=WGS84 \
+to +proj=merc +a=6378137 +b=6378137 +lat_ts=0.0 +lon_0=0.0 \
+x_0=0.0 +y_0=0 +k=1.0 +units=m +nadgrids=@null +no_defs
```

Note the strategic addition of `+nadgrids=@null` to the spherical projection definition.

Similar issues apply with many other datasets distributed with projections based on a spherical earth model - such as many NASA datasets. This coordinate system is now known by the EPSG code 3857 and has in the past been known as EPSG:3785 and EPSG:900913. When using this coordinate system with GDAL/OGR it is helpful to include the `+wktext` so the exact PROJ string will be preserved in the WKT representation (otherwise key parameters like `+nadgrids=@null` will be dropped):

```
+proj=merc +a=6378137 +b=6378137 +lat_ts=0.0 +lon_0=0.0 +x_0=0.0 +y_0=0 +k=1.0
+units=m +nadgrids=@null +wktext +no_defs
```

11.8 Why do I get different results with 4.5.0 and 4.6.0?

The default datum application behavior changed with the 4.6.0 release. PROJ will now only apply a datum shift if both the source and destination coordinate system have valid datum shift information.


From the **PROJ 4.6.0 Release Notes (in NEWS)**:

- MAJOR: Rework `pj_transform()` to avoid applying ellipsoid to ellipsoid transformations as a datum shift when no datum info is available.

11.9 How do I calculate distances/directions on the surface of the earth?

These are called geodesic calculations. There is a page about it here: [Geodesic calculations](#).

11.10 What is the HEALPix projection and how can I use it?



The HEALPix projection is area preserving and can be used with a spherical and ellipsoidal model. It was initially developed for mapping cosmic background microwave radiation. The image below is the graphical representation of the mapping and consists of eight isomorphic triangular interrupted map graticules. The north and south contains four in which straight meridians converge polewards to a point and unequally spaced horizontal parallels. HEALPix provides a mapping in which points of equal latitude and equally spaced longitude are mapped to points of equal latitude and equally spaced longitude with

the module of the polar interruptions. ||


To run a forward HEALPix projection on a unit sphere model, use the following command:

```
proj +proj=healpix +lon_0=0 +a=1 -E <<EOF
0 0
EOF
```

Output of the above command.

```
0 0 0.00 0.00
```

11.11 What is the rHEALPix projection and how can I use it?



model, use the following command:

```
proj +proj=rhealpix -f '%.2f' -I +lon_0=0 +a=1 +ellps=WGS84 +npole=0 +spole=0 -E <<EOF
0 0.7853981633974483
EOF
```

Where spole and npole are integers from the range of 0 to 3 inclusive and represent the positions of the north polar and south polar squares.

Output of above command:

```
0 0.7853981633974483 0.00 41.94
```

rHEALPix is a projection based on the HEALPix projection. The implementation of rHEALPix uses the HEALPix projection. The rHEALPix combines the peaks of the HEALPix into a square. The square's position can be translated and rotated across the x-axis which is a novel approach for the rHEALPix projection. The initial intention of using rHEALPix in the Spatial Computation Engine Science Collaboration Environment (SCENZGrid).

To run a inverse rHEALPix projection on a WGS84 ellipsoidal

11.12 What options does PROJ allow for the shape of the Earth (geodesy)?

See https://github.com/OSGeo/proj.4/blob/master/src/pj_ells.c for possible ellipse options. For example, putting +ellps=WGS84 uses the WGS84 Earth shape.

11.13 What if I want a spherical Earth?

Use `+ellps=sphere`. See https://github.com/OSGeo/proj.4/blob/master/src/pj_ellps.c for the radius used in this case.

11.14 How do I change the radius of the Earth? How do I use PROJ for work on Mars?

You can supply explicit values for the semi minor and semi major axes instead of using the symbolic “sphere” value. Eg, if the radius were 2000000m:

```
+proj=laea +lon_0=-40.000000 +lat_0=74.000000 +x_0=1000000 +y_0=1700000 +a=2000000  
↪+b=2000000"
```

11.15 How do I do False Eastings and False Northings?

Use `+x_0` and `+y_0` in the projection string.

CHAPTER
TWELVE

GLOSSARY

Pseudocylindrical Projection Pseudocylindrical projections have the mathematical characteristics of

$$\begin{aligned}x &= f(\lambda, \phi) \\y &= g(\phi)\end{aligned}$$

where the parallels of latitude are straight lines, like cylindrical projections, but the meridians are curved toward the center as they depart from the equator. This is an effort to minimize the distortion of the polar regions inherent in the cylindrical projections.

Pseudocylindrical projections are almost exclusively used for small scale global displays and, except for the Sinusoidal projection, only derived for a spherical Earth. Because of the basic definition none of the pseudo-cylindrical projections are conformal but many are equal area.

To further reduce distortion, pseudocylindrical are often presented in interrupted form that are made by joining several regions with appropriate central meridians and false easting and clipping boundaries. Interrupted Homolosine constructions are suited for showing respective global land and oceanic regions, for example. To reduce the lateral size of the map, some uses remove an irregular, North-South strip of the mid-Atlantic region so that the western tip of Africa is plotted north of the eastern tip of South America.

BIBLIOGRAPHY

- [AltamimiEtAl2002] Altamimi, Z., P. Sillard, and C. Boucher (2002), ITRF2000: A new release of the International Terrestrial Reference Frame for earth science applications, *J. Geophys. Res.*, 107(B10), 2214, doi:10.1029/2001JB000561.
- [Bessel1825] F. W. Bessel, 1825, *The calculation of longitude and latitude from geodesic measurements*, *Astron. Nachr.* **331**(8), 852–861 (2010), translated by C. F. F. Karney and R. E. Deakin.
- [CalabrettaGreisen2002] M. Calabretta and E. Greisen, 2002, “Representations of celestial coordinates in FITS”. *Astronomy & Astrophysics* 395, 3, 1077–1122.
- [ChanONeil1975] F. Chan and E. M. O’Neill, 1975, “Feasibility Study of a Quadrilateralized Spherical Cube Earth Data Base”, Tech. Rep. EPRF 2-75 (CSC), Environmental Prediction Research Facility.
- [Danielsen1989] J. Danielsen, 1989, *The area under the geodesic*, *Survey Review* **30**(232), 61–66.
- [Deakin2004] R.E. Deakin, 2004, *The Standard and Abridged Molodensky Coordinate Transformation Formulae*.
- [EberHewitt1979] L. E. Eber and R.P. Hewitt, 1979, *Conversion algorithms for the CalCOFI station grid*, California Cooperative Oceanic Fisheries Investigations Reports 20:135–137.
- [Evenden1995] G. I. Evenden, 1995, *Cartographic Projection Procedures for the UNIX Environment - A User’s Manual*.
- [Evenden2005] G. I. Evenden, 2005, *libproj4: A Comprehensive Library of Cartographic Projection Functions (Preliminary Draft)*.
- [EversKnudsen2017] K. Evers and T. Knudsen, 2017, *Transformation pipelines for PROJ.4*, FIG Working Week 2017 Proceedings.
- [GeodesicBib] *A geodesic bibliography*.
- [GeodesicWiki] The wikipedia page, *Geodesics on an ellipsoid*.
- [Häkli2016] P. Häkli, M. Lidberg, L. Jivall, et al, 2016, *The NKG2008 GPS Campaign - final transformation results and a new common Nordic reference frame*, *Journal of Geodetic Science*, 6(1).
- [Helmert1880] F. R. Helmert, 1880, *Mathematical and Physical Theories of Higher Geodesy*, Vol 1, (Teubner, Leipzig), Chaps. 5–7.
- [Karney2011] C. F. F. Karney, 2011, *Geodesics on an ellipsoid of revolution; errata*.
- [Karney2013] C. F. F. Karney, 2013, *Algorithms for geodesics*, *J. Geodesy* **87**(1) 43–55; addenda.
- [Komsta2016] L. Komsta, 2016, *ATPOL geobotanical grid revisited - a proposal of coordinate conversion algorithms*, *Annales UMCS Sectio E Agricultura* 71(1), 31–37.
- [LambersKolb2012] M. Lambers and A. Kolb, 2012, “Ellipsoidal Cube Maps for Accurate Rendering of Planetary-Scale Terrain Data”, Proc. Pacific Graphics (Short Papers).

- [ONeilLaubscher1976] E. M. O'Neill and R. E. Laubscher, 1976, “Extended Studies of a Quadrilateralized Spherical Cube Earth Data Base”, Tech. Rep. NEPRF 3-76 (CSC), Naval Environmental Prediction Research Facility.
- [Snyder1987] J. P. Snyder, 1987, *Map Projections - A Working Manual*. U.S. Geological Survey professional paper 1395.
- [Snyder1993] J. P. Snyder, 1993, *Flattening the Earth*, Chicago and London, The University of Chicago press.
- [Steers1970] J. A. Steers, 1970, An introduction to the study of map projections (15th ed.), London Univ. Press, p. 229.
- [Verey2017] M. Verey, 2017, Theoretical analysis and practical consequences of adopting an ATPOL grid model as a conical projection, defining the conversion of plane coordinates to the WGS-84 ellipsoid, *Fragmента Floristica et Geobotanica Polonica* (preprint submitted).
- [Vincenty1975] T. Vincenty, 1975, Direct and inverse solutions of geodesics on the ellipsoid with application of nested equations, *Survey Review* 23(176), 88–93.
- [WeberMoore2013] E. D. Weber and T.J. Moore, 2013, *Corrected Conversion Algorithms For The CalCOFI Station Grid And Their Implementation In Several Computer Languages*, California Cooperative Oceanic Fisheries Investigations Reports 54.
- [Zajac1978] A. Zajac, 1978, “Atlas of distribution of vascular plants in Poland (ATPOL)”, *Taxon* 27(5/6), 481–484.

INDEX

Symbols

- +R=<value>
 - command line option, 34, 36–40, 44, 46, 49, 58, 63, 66, 70, 73, 87, 90, 94, 97, 101, 118, 122, 131
- +abridged
 - command line option, 144
- +azi=<value>
 - command line option, 121
- +da=<value>
 - command line option, 144
- +datum=<value>
 - command line option, 135
- +df=<value>
 - command line option, 144
- +drx=<value>
 - command line option, 141
- +dry=<value>
 - command line option, 141
- +drz=<value>
 - command line option, 141
- +ds=<value>
 - command line option, 141
- +dx=<value>
 - command line option, 140, 144
- +dy=<value>
 - command line option, 140, 144
- +dz=<value>
 - command line option, 140, 144
- +ellps=<value>
 - command line option, 34, 36, 39, 44, 46, 58, 63, 66, 73, 75, 87, 110, 117, 134, 135, 144
- +exact
 - command line option, 141
- +grids=<list>
 - command line option, 146, 147
- +guam
 - command line option, 35
- +h=<value>
 - command line option, 65, 97, 121
- +inv
 - command line option, 149
- +k_0=<value>
- +lat_0=<value>
 - command line option, 35, 37, 40, 46, 57, 101, 110, 117, 122
- +lat_1=<value>
 - command line option, 34, 49
- +lat_2=<value>
 - command line option, 34
- +lat_b
 - command line option, 37
- +lat_ts=<value>
 - command line option, 35, 57, 87
- +lon_0=<value>
 - command line option, 34, 35, 37, 38, 40, 46, 49, 57, 63, 66, 70, 72, 75, 87, 90, 94, 97, 101, 110, 117, 122
- +no_cut
 - command line option, 37
- +north_square
 - command line option, 74
- +order=<list>
 - command line option, 134
- +rx=<value>
 - command line option, 140
- +ry=<value>
 - command line option, 140
- +rz=<value>
 - command line option, 140
- +s=<value>
 - command line option, 140
- +south_square
 - command line option, 74
- +step
 - command line option, 149
- +sweep=<axis>
 - command line option, 66
- +t_epoch=<time>
 - command line option, 146, 148
- +t_epoch=<value>
 - command line option, 138, 141
- +t_final=<time>
 - command line option, 146, 148

+t_in=<unit>
 command line option, 136
+t_obs=<value>
 command line option, 138, 141
+t_out=<unit>
 command line option, 136
+theta=<value>
 command line option, 140
+tilt=<value>
 command line option, 121
+towgs84=<list>
 command line option, 135
+transpose
 command line option, 141
+x=<value>
 command line option, 140
+x_0=<value>
 command line option, 34, 36–40, 46, 49, 57, 63, 66,
 70, 72, 75, 87, 90, 94, 97, 101, 110, 118, 122,
 131
+xy_grids=<list>
 command line option, 138
+xy_in=<unit>
 command line option, 136
+xy_out=<unit>
 command line option, 136
+y=<value>
 command line option, 140
+y_0=<value>
 command line option, 34, 36–40, 46, 49, 57, 63, 66,
 70, 72, 75, 87, 90, 94, 97, 101, 110, 118, 122,
 131
+z=<value>
 command line option, 140
+z_grids=<list>
 command line option, 138
+z_in=<unit>
 command line option, 136
+z_out=<unit>
 command line option, 136
-version
 cct command line option, 22
 command line option, 28
-E
 cs2cs command line option, 24
 proj command line option, 20
-F <format>
 geod command line option, 26
-I
 cct command line option, 22
 cs2cs command line option, 23
 geod command line option, 25
 proj command line option, 19
-S
 proj command line option, 20
-T <ulow,uh,i,vlow,vhi,res[,umax,vmax]>
 proj command line option, 21
-V
 proj command line option, 20
-W<n>
 cs2cs command line option, 24
 geod command line option, 26
 proj command line option, 20
-a
 geod command line option, 25
-b
 proj command line option, 19
-c <x,y,z,t>
 cct command line option, 22
-e <string>
 cs2cs command line option, 23
 proj command line option, 19
-f <format>
 cs2cs command line option, 24
 geod command line option, 26
 proj command line option, 20
-h, --help
 command line option, 27
-i
 proj command line option, 19
-l, --list
 command line option, 28
-IP
 cs2cs command line option, 24
 proj command line option, 20
-l<[=id]>
 cs2cs command line option, 24
 proj command line option, 20
-ld
 cs2cs command line option, 24
 proj command line option, 20
-le
 cs2cs command line option, 24
 geod command line option, 26
 proj command line option, 20
-lp
 cs2cs command line option, 24
 proj command line option, 20
-lu
 cs2cs command line option, 24
 geod command line option, 26
 proj command line option, 20
-m <mult>
 proj command line option, 20
-o
 proj command line option, 19
-o <file>, --output <file>
 command line option, 27

```

-o <output file name>, --output=<output file name>
    cct command line option, 22
-p
    geod command line option, 26
-q, -quiet
    command line option, 28
-r
    cs2cs command line option, 24
    proj command line option, 20
-s
    cs2cs command line option, 24
    proj command line option, 20
-s <n>, --skip-lines=<n>
    cct command line option, 22
-t <time>, --time=<time>
    cct command line option, 22
-t<a>
    cs2cs command line option, 23
    geod command line option, 25
    proj command line option, 19
-v
    cs2cs command line option, 24
    proj command line option, 20
-v, --verbose
    cct command line option, 22
    command line option, 28
-w<n>
    cs2cs command line option, 24
    geod command line option, 26
    proj command line option, 20
-z <height>, --height=<height>
    cct command line option, 22

A
accept <x y [z [t]]>
    command line option, 29

C
cct, 21
cct command line option
    -version, 22
    -I, 22
    -c <x,y,z,t>, 22
    -o <output file name>, --output=<output file name>, 22
    -s <n>, --skip-lines=<n>, 22
    -t <time>, --time=<time>, 22
    -v, --verbose, 22
    -z <height>, --height=<height>, 22
command line option
    +R=<value>, 34, 36–40, 44, 46, 49, 58, 63, 66, 70, 73, 87, 90, 94, 97, 101, 118, 122, 131
    +abridged, 144
    +azimuth=<value>, 121
    +da=<value>, 144
    +datum=<value>, 135
    +df=<value>, 144
    +drx=<value>, 141
    +dry=<value>, 141
    +drz=<value>, 141
    +ds=<value>, 141
    +dx=<value>, 140, 144
    +dy=<value>, 140, 144
    +dz=<value>, 140, 144
    +ellps=<value>, 34, 36, 39, 44, 46, 58, 63, 66, 73, 75, 87, 110, 117, 134, 135, 144
    +exact, 141
    +grids=<list>, 146, 147
    +guam, 35
    +h=<value>, 65, 97, 121
    +inv, 149
    +k_0=<value>, 35, 87, 118
    +lat_0=<value>, 35, 37, 40, 46, 57, 101, 110, 117, 122
    +lat_1=<value>, 34, 49
    +lat_2=<value>, 34
    +lat_b, 37
    +lat_ts=<value>, 35, 57, 87
    +lon_0=<value>, 34, 35, 37, 38, 40, 46, 49, 57, 63, 66, 70, 72, 75, 87, 90, 94, 97, 101, 110, 117, 122
    +no_cut, 37
    +north_square, 74
    +order=<list>, 134
    +rx=<value>, 140
    +ry=<value>, 140
    +rz=<value>, 140
    +s=<value>, 140
    +south_square, 74
    +step, 149
    +sweep=<axis>, 66
    +t_epoch=<time>, 146, 148
    +t_epoch=<value>, 138, 141
    +t_final=<time>, 146, 148
    +t_in=<unit>, 136
    +t_obs=<value>, 138, 141
    +t_out=<unit>, 136
    +theta=<value>, 140
    +tilt=<value>, 121
    +towgs84=<list>, 135
    +transpose, 141
    +x=<value>, 140
    +x_0=<value>, 34, 36–40, 46, 49, 57, 63, 66, 70, 72, 75, 87, 90, 94, 97, 101, 110, 118, 122, 131
    +xy_grids=<list>, 138
    +xy_in=<unit>, 136
    +xy_out=<unit>, 136
    +y=<value>, 140

```

+y_0=<value>, 34, 36–40, 46, 49, 57, 63, 66, 70, 72,
75, 87, 90, 94, 97, 101, 110, 118, 122, 131
+z=<value>, 140
+z_grids=<list>, 138
+z_in=<unit>, 136
+z_out=<unit>, 136
–version, 28
–h, –help, 27
–l, –list, 28
–o <file>, –output <file>, 27
–q, –quiet, 28
–v, –verbose, 28
accept <x y [z [t]]>, 29
direction <direction>, 30
echo <text>, 31
expect <x y [z [t]]> | <error code>, 29
ignore <error code>, 30
operation <+args>, 29
roundtrip <n> <tolerance>, 30
skip, 31
tolerance <tolerance>, 29

cs2cs command line option
–E, 24
–I, 23
–W<n>, 24
–e <string>, 23
–f <format>, 24
–IP, 24
–l<[=id]>, 24
–ld, 24
–le, 24
–lp, 24
–lu, 24
–r, 24
–s, 24
–t<a>, 23
–v, 24
–w<n>, 24

D
direction <direction>
command line option, 30

E
echo <text>
command line option, 31
environment variable
PROJ_DEBUG, 17
PROJ_LIB, 7, 8, 17, 21, 24, 176
expect <x y [z [t]]> | <error code>
command line option, 29

G
geod command line option

–F <format>, 26
–I, 25
–W<n>, 26
–a, 25
–f <format>, 26
–le, 26
–lu, 26
–p, 26
–t<a>, 25
–w<n>, 26
gie, 27

I
ignore <error code>
command line option, 30

O
operation <+args>
command line option, 29

P
PJ (C type), 166
PJ_AREA (C type), 166
PJ_CONTEXT (C type), 166
PJ_COORD (C type), 169
PJ_COORD.PJ_COORD.lp (C member), 170
PJ_COORD.PJ_COORD.lpz (C member), 170
PJ_COORD.PJ_COORD.lpzt (C member), 170
PJ_COORD.PJ_COORD.uv (C member), 170
PJ_COORD.PJ_COORD.uvw (C member), 170
PJ_COORD.PJ_COORD.uvwt (C member), 170
PJ_COORD.PJ_COORD.xy (C member), 170
PJ_COORD.PJ_COORD.xyz (C member), 170
PJ_COORD.PJ_COORD.xyzt (C member), 170
PJ_DIRECTION (C type), 166
PJ_DIRECTION.PJ_FWD (C member), 166
PJ_DIRECTION.PJ_IDENT (C member), 166
PJ_DIRECTION.PJ_INV (C member), 166
PJ_ELLPS (C type), 172
PJ_ELLPS.ell (C member), 172
PJ_ELLPS.id (C member), 172
PJ_ELLPS.major (C member), 172
PJ_ELLPS.name (C member), 172
PJ_FACTORS (C type), 170
PJ_FACTORS.PJ_FACTORS.angular_distortion (C member), 171
PJ_FACTORS.PJ_FACTORS.areal_scale (C member), 171
PJ_FACTORS.PJ_FACTORS.dx_dlam (C member), 171
PJ_FACTORS.PJ_FACTORS.dx_dphi (C member), 171
PJ_FACTORS.PJ_FACTORS.dy_dlam (C member), 171
PJ_FACTORS.PJ_FACTORS.dy_dphi (C member), 171
PJ_FACTORS.PJ_FACTORS.meridian_convergence (C member), 171

PJ_FACTORS.PJ_FACTORS.meridian_parallel_angle
(C member), 171

PJ_FACTORS.PJ_FACTORS.meridional_scale (C member), 171

PJ_FACTORS.PJ_FACTORS.parallel_scale (C member), 171

PJ_FACTORS.PJ_FACTORS.tissot_semmajor (C member), 171

PJ_FACTORS.PJ_FACTORS.tissot_seminor (C member), 171

PJ_GRID_INFO (C type), 174

PJ_GRID_INFO.PJ_GRID_INFO (C member), 174

PJ_GRID_INFO.PJ_GRID_INFO.cs_lat (C member), 174

PJ_GRID_INFO.PJ_GRID_INFO.cs_lon (C member), 174

PJ_GRID_INFO.PJ_GRID_INFO.lowerleft (C member), 174

PJ_GRID_INFO.PJ_GRID_INFO.n_lat (C member), 174

PJ_GRID_INFO.PJ_GRID_INFO.n_lon (C member), 174

PJ_GRID_INFO.PJ_GRID_INFO.upperright (C member), 174

PJ_INFO (C type), 173

PJ_INFO.PJ_INFO.major (C member), 173

PJ_INFO.PJ_INFO.minor (C member), 173

PJ_INFO.PJ_INFO.patch (C member), 173

PJ_INFO.PJ_INFO.release (C member), 173

PJ_INFO.PJ_INFO.searchpath (C member), 173

PJ_INFO.PJ_INFO.version (C member), 173

PJ_INIT_INFO (C type), 174

PJ_INIT_INFO.PJ_INIT_INFO.lastupdate (C member), 175

PJ_LOG_FUNC (C type), 175

PJ_LOG_LEVEL (C type), 175

PJ_LOG_LEVEL.PJ_LOG_DEBUG (C member), 175

PJ_LOG_LEVEL.PJ_LOG_ERROR (C member), 175

PJ_LOG_LEVEL.PJ_LOG_NONE (C member), 175

PJ_LOG_LEVEL.PJ_LOG_TELL (C member), 175

PJ_LOG_LEVEL.PJ_LOG_TRACE (C member), 175

PJ_LP (C type), 167

PJ_LP.PJ_LP.lam (C member), 167

PJ_LP.PJ_LP.phi (C member), 167

PJ_LPZ (C type), 167

PJ_LPZ.PJ_LPZ.lam (C member), 167

PJ_LPZ.PJ_LPZ.phi (C member), 167

PJ_LPZ.PJ_LPZ.z (C member), 167

PJ_LPZT (C type), 168

PJ_LPZT.PJ_LPZT.lam (C member), 168

PJ_LPZT.PJ_LPZT.phi (C member), 168

PJ_LPZT.PJ_LPZT.t (C member), 168

PJ_LPZT.PJ_LPZT.z (C member), 168

PJ_OPERATIONS (C type), 171

PJ_OPERATIONS.id (C member), 171

PJ_OPERATIONS.op (C member), 171

PJ_OPK (C type), 169

PJ_OPK.PJ_OPK.k (C member), 169

PJ_OPK.PJ_OPK.o (C member), 169

PJ_OPK.PJ_OPK.p (C member), 169

PJ_PRIME_MERIDIANS (C type), 172

PJ_PRIME_MERIDIANS.def (C member), 172

PJ_PRIME_MERIDIANS.id (C member), 172

PJ_PROJ_INFO (C type), 173

PJ_PROJ_INFO.PJ_PROJ_INFO.accuracy (C member), 174

PJ_PROJ_INFO.PJ_PROJ_INFO.definition (C member), 173

PJ_PROJ_INFO.PJ_PROJ_INFO.description (C member), 173

PJ_PROJ_INFO.PJ_PROJ_INFO.has_inverse (C member), 174

PJ_PROJ_INFO.PJ_PROJ_INFO.id (C member), 173

PJ_UNITS (C type), 172

PJ_UNITS.factor (C member), 172

PJ_UNITS.id (C member), 172

PJ_UNITS.name (C member), 172

PJ_UNITS.to_meter (C member), 172

PJ_UV (C type), 167

PJ_UV.PJ_UV.u (C member), 167

PJ_UV.PJ_UV.v (C member), 167

PJ_UVW (C type), 168

PJ_UVW.PJ_UVW.u (C member), 168

PJ_UVW.PJ_UVW.v (C member), 168

PJ_UVW.PJ_UVW.w (C member), 168

PJ_UVWT (C type), 169

PJ_UVWT.PJ_UVWT.e (C member), 169

PJ_UVWT.PJ_UVWT.n (C member), 169

PJ_UVWT.PJ_UVWT.t (C member), 169

PJ_UVWT.PJ_UVWT.w (C member), 169

PJ_XY (C type), 167

PJ_XY.PJ_XY.x (C member), 167

PJ_XY.PJ_XY.y (C member), 167

PJ_XYZ (C type), 168

PJ_XYZ.PJ_XYZ.x (C member), 168

PJ_XYZ.PJ_XYZ.y (C member), 168

PJ_XYZ.PJ_XYZ.z (C member), 168

PJ_XYZT (C type), 168

PJ_XYZT.PJ_XYZT.t (C member), 169

PJ_XYZT.PJ_XYZT.x (C member), 169

PJ_XYZT.PJ_XYZT.y (C member), 169

PJ_XYZT.PJ_XYZT.z (C member), 169

proj, 19

proj command line option

- E, 20
- I, 19
- S, 20
- T <ulow,uhi,vlow,vhi,res[,umax,vmax]>, 21
- V, 20

-W<n>, 20
-b, 19
-e <string>, 19
-f <format>, 20
-i, 19
-IP, 20
-l<[=id]>, 20
-ld, 20
-le, 20
-lp, 20
-lu, 20
-m <mult>, 20
-o, 19
-r, 20
-s, 20
-t<a>, 19
-v, 20
-w<n>, 20

proj_angular_input (C function), 184
proj_angular_output (C function), 184
proj_context_create (C function), 175
proj_context_destroy (C function), 176
proj_coord (C function), 182
proj_create (C function), 176
proj_create_argv (C function), 176
proj_create_crs_to_crs (C function), 176
proj_destroy (C function), 177
proj_dmstor (C function), 183
proj_errno (C function), 179
proj_errno_reset (C function), 179
proj_errno_restore (C function), 179
proj_errno_set (C function), 179
proj_errno_string (C function), 180
proj_factors (C function), 183
proj_geocentric_latitude (C function), 184
proj_grid_info (C function), 180
proj_info (C function), 180
proj_init_info (C function), 181
PROJ_LIB, 7, 8, 17, 21, 24, 176
proj_list_ells (C function), 181
proj_list_operations (C function), 181
proj_list_prime_meridians (C function), 181
proj_list_units (C function), 181
proj_log_func (C function), 180
proj_log_level (C function), 180
proj_lp_dist (C function), 181
proj_lpz_dist (C function), 182
proj_pj_info (C function), 180
proj_roundtrip (C function), 183
proj_rtodms (C function), 184
proj_todeg (C function), 183
proj_torad (C function), 183
proj_trans (C function), 177
proj_trans_array (C function), 179

proj_trans_generic (C function), 177
proj_xy_dist (C function), 182
proj_xyz_dist (C function), 182
Pseudocylindrical Projection, 205

R

roundtrip <n> <tolerance>
command line option, 30

S

skip
command line option, 31

T

tolerance <tolerance>
command line option, 29