



Introduction to Machine Learning.


Lec.10 K-Nearest Neighbors

Aidos Sarsembayev, IITU, 2018


Before k-NN




A new data point



A new data point



After k-NN applied



k-NN algorithm step-by-step

- STEP 1: Choose the number K of neighbors

k-NN algorithm step-by-step

- STEP 1: Choose the number k of neighbors

Most commonly $k=5$ (it's better to choose odd numbers)

k-NN algorithm step-by-step

- STEP 1: Choose the number K of neighbors
- STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.

k-NN algorithm step-by-step

- STEP 1: Choose the number K of neighbors
- STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.

$$d(p_1, p_2) = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2} \text{ where } p_1 = (x_1, y_1) \text{ and } p_2 = (x_2, y_2)$$

k-NN algorithm step-by-step

- STEP 1: Choose the number K of neighbors
- STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.

$$d(p_1, p_2) = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2} \text{ where } p_1 = (x_1, y_1) \text{ and } p_2 = (x_2, y_2)$$

you don't strictly have to use Euclidean distance, but it's the most common one


k-NN algorithm step-by-step

- STEP 1: Choose the number K of neighbors
- STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.
- STEP 3: Among these k neighbors, count the number of data points in each category

k-NN algorithm step-by-step

- STEP 1: Choose the number K of neighbors
- STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.
- STEP 3: Among these k neighbors, count the number of data points in each category
- STEP 4: Assign the new data point to the category where you counted the most neighbors

STEP I: Choose the number K of neighbors (K=5)





How to choose k ?


K-NEAREST NEIGHBORS




K=3

risovach.ru

STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.



STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.




STEP 2: Take the k nearest neighbors of the new data point, according to the Euclidean Distance.



STEP 3: Among these k neighbors, count the number of data points in each category



STEP 3: Among these k neighbors, count the number of data points in each category



STEP 4: Assign the new data point to the category where you counted the most neighbors



Class creation

- `sklearn.neighbors -> KNeighborsClassifier`

Class creation

- `sklearn.neighbors -> KNeighborsClassifier`
- Parameters:

Class creation

- `sklearn.neighbors -> KNeighborsClassifier`
- Parameters:
`n_neighbors` (i.g. `n_neighbors= 5`)

Class creation

- `sklearn.neighbors -> KNeighborsClassifier`
- Parameters:
 `n_neighbors` (i.g. `n_neighbors= 5`)
 `metric` (i.g. `metric = 'minkowski'`)

Class creation

- `sklearn.neighbors -> KNeighborsClassifier`
- Parameters:
 - `n_neighbors` (i.g. `n_neighbors= 5`)
 - `metric` (i.g. `metric = 'minkowski'`)
 - `p` (i.g. `p =2` is Euclidean distance)



This is it ;-)