NUTRISMART

Probation Period — Unified Academic Report

Development of an intelligent system for monitoring and analyzing dietary intake

Astana IT University | 24 October 2026

Student: Abdikarim Nurmukhammed | Group: SE-2430

Supervisor: Bakayeva Bakyt | Individual project

Report structure

1. Project proposal and scope

2. Evidence of relevance and user research

3. Critical literature review

4. Existing-system comparison

5. Technology alternatives

6. Functional and non-functional requirements

7. Architecture and editable diagram evidence

8. UX prototype

9. Verification and evaluation plan

10. Project management, progress and risks

11. Supervisor consultation (no review evidence submitted)

Appendix A. Diagram exports and YouTrack board evidence

1. Project proposal NUTRISMART

Project Proposal and Scope | Probation Period

Development of an intelligent system for monitoring and analyzing dietary intake

Executive Summary

NutriSmart is a proposed mobile-first intelligent system for monitoring and analyzing dietary intake. It is intended to simplify recording meals, estimating calories and macronutrients, viewing intake history, and generating understandable informational insights. A future image-assisted workflow will propose food items from a photograph and ask the user to confirm ingredients and portion sizes before calculating nutritional values.

1. Project Identification

Diploma project: Development of an intelligent system for monitoring and analyzing dietary intake.

Working product name: NutriSmart.

Student: Abdikarim Nurmukhammed (individual project).

Supervisor: Bakayeva Bakyt.

GitHub repository: https://github.com/Nurmukhammed070/intelligent-nutrition-system

YouTrack: https://nurmukhammedabdikarim.youtrack.cloud

Academic group: SE-2430.

2. Problem Statement

Manual food logging requires users to identify ingredients, estimate portions, and search for nutritional values. These repetitive steps may reduce the convenience of continuous tracking. Image-assisted estimation can shorten the process, but food classification, portion estimation and nutrient calculations have distinct sources of error. An application must make estimates transparent and correctable.

3. Intended Users

Primary users: adults who wish to maintain a personal food diary and review estimated calorie and macronutrient intake without specialized nutrition knowledge. Secondary stakeholder: academic supervisor and evaluators reviewing functionality, usability, architecture, and measurement methods. The initial scope excludes clinical diagnosis and nutrition treatment.

4. Aim

To design, develop and evaluate a mobile-oriented intelligent nutrition monitoring system that supports structured and convenient food recording, transparent nutritional calculations and explainable analysis, with a researched path toward photograph-assisted food identification.

5. Objectives

1. Investigate relevant scientific and technical approaches to dietary tracking, food-image recognition, portion estimation and usability.

2. Gather and analyze potential user needs through real discussions and clearly distinguish evidence from assumptions.

3. Compare existing nutrition products and alternative technology stacks.

4. Define measurable functional and non-functional requirements, architecture and data model.

5. Implement and test food search, meal logging, nutrient calculation, goals and historical summaries.

6. Evaluate an image-assisted workflow, including recognition uncertainty and user confirmation, before claiming automatic estimation.

7. Measure correctness and usability using documented tests and a repeatable baseline.

6. Proposed Scope

In scope for initial implementation: responsive prototype, food catalogue/search, user-confirmed servings, calories and macronutrients, food diary, local persistence, goals, basic rule-based insights, testing and documentation.

Research/next stage: mobile Android integration, authoritative food data source, real vision model/API, portion estimation evaluation, persistent server database, authentication and synchronization.

Out of scope for the current checkpoint: validated clinical recommendations, guaranteed calorie estimation from images and completed production-grade mobile application.

7. Engineering Approach

Initial client: Kotlin with Jetpack Compose for native Android; responsive HTML/CSS/JavaScript UX prototype remains an independent usability demonstrator. Backend direction: Node.js REST services; storage options (Room/SQLite vs PostgreSQL) require the documented architectural choice. Proposed image pipeline: acquire photo -> recognize candidate foods -> estimate/confirm portions -> retrieve nutrient values with provenance -> calculate totals -> user review -> save. No photo estimate should be presented as exact.

8. Expected Deliverables

Source code and a runnable prototype; requirements and acceptance criteria; system context, use-case and component diagrams (editable sources and readable exports); research evidence and critical literature review; existing-system and technology comparisons; test and evaluation plan; risk register; project-management traceability; supervisor feedback with revisions; probation-stage tagged repository state.

9. Status at the Probation Checkpoint

An interactive browser-based prototype has been developed and manually checked by the student, including fixes to contrast and photograph removal. Earlier versions include food logging, nutritional calculations and diary features. Claims concerning the latest backend, automated tests, Android runtime, or real AI image recognition must be reverified against the specific repository commit before submission. User-study results, completed scientific review, source-backed competitor comparison, YouTrack history and supervisor feedback are not yet verified.

10. Main Risks and Mitigations

Food recognition uncertainty: require confirmation and evaluate accuracy against measured samples. Portion uncertainty: never infer weight from a single photograph without qualification. Nutrition provenance: select a documented source and store source metadata. Privacy: use local-first storage initially; obtain explicit consent for any future photo uploads. Time/scope: prioritize evidence, demonstrable features and honest limitations for the probation checkpoint.

11. Success Criteria

The prototype can demonstrate an end-to-end meal-entry flow; calorie/macronutrient calculations are checked against known arithmetic cases; major requirements map to verification methods; diagrams agree with the implemented architecture; usability feedback is recorded from actual participants; future image-recognition performance is assessed separately from the photo-upload demonstration.

2. Evidence of relevance — exploratory survey NutriSmart

USER RELEVANCE RESEARCH | INITIAL SURVEY FINDINGS

Diploma project: Development of an intelligent system for monitoring and analyzing dietary intake

Student: Abdikarim Nurmukhammed • Supervisor: Bakayeva Bakyt

Evidence source: screenshots of Google Forms response summaries provided by the student on 24 October 2026. Counts below reflect only what is visible in these screenshots.

1. Method and scope

An exploratory online questionnaire was administered using Google Forms. The screenshots show five responses to the main multiple-choice questions. Some open-ended questions received only three or four responses. Sampling method and respondent demographics were not provided. Therefore, findings should be treated as early user feedback, not representative population estimates.

Important distinction: five completed questionnaires are NOT documented as five individual interviews. The university requirement mentioning 3–5 discussions with user representatives should be addressed by conducting and recording actual follow-up conversations or by obtaining supervisor approval for an alternative method.

2. Quantitative findings (n = 5, where indicated)

Question / measure	Observed answers	Interpretation
Prior use of food tracking apps	3 yes (60%); 2 no (40%)	Participants have mixed prior experience.
Food tracking frequency	Daily: 1 (20%); a few times/week: 2 (40%); occasionally: 1 (20%); never: 1 (20%)	Use patterns vary; avoid assuming continuous daily tracking.
Difficulties with logging (multiple choices)	Manual entry: 3 (60%); understanding nutrition values: 3 (60%); portion estimation: 2 (40%); finding food: 1 (20%); staying consistent: 1 (20%)	Reduce manual effort and explain nutrition values.
Preferred input method	Take photo: 3 (60%); type a meal: 1 (20%); all methods: 1 (20%); food search: 0	Photo entry should be prominent, with editable alternatives.
Usefulness of automatic calorie/macro calculation (1–5)	1: 0; 2: 1; 3: 1; 4: 1; 5: 2	3/5 rated it 4–5; small, mixed sample.
Would review AI photo suggestions	Yes: 2 (40%); maybe: 2 (40%); no: 1 (20%)	Offer confirmation and editing, never force acceptance.
Most valuable features (multiple choices)	Goals: 4 (80%); recommendations: 4 (80%);	Goals, explanations and diary deserve prominent navigation.

	daily diary: 3 (60%); photo suggestions: 2 (40%); food search: 1 (20%); charts: 1 (20%); export history: 1 (20%)	
Willing to join follow-up discussion	Yes: 2 (40%); no: 3 (60%)	Two respondents indicated willingness; their participation is not yet confirmed.

3. Qualitative feedback

Four respondents answered what would make them distrust a food estimate. The answers concerned actual food weight, lack of independent verification, incorrect data, and hidden or complex ingredients. These are separate responses rather than a ranked frequency distribution.

Three respondents answered the privacy question. One expressed detailed concern about dietary data sharing and possible secondary uses; other answers broadly emphasized privacy and safety. These answers motivate clear data-processing disclosures and cautious handling of food photos.

Four respondents answered what to improve in existing apps. Suggestions included greater accuracy and access to specialist/AI assistance, while two answers expressed no specific improvement. These comments do not establish a validated demand for professional consultation features.

4. Requirements informed by the observations

Question / measure	Observed answers	Interpretation
UR-01 | Fast entry	Manual input was a frequent difficulty	Prioritize photo-first workflow alongside editable text and search.
UR-02 | Visible calculations	Nutrition comprehension and accuracy concerns	Show portion mass, nutrient values per 100 g, data source, and formula.
UR-03 | Human confirmation	Four of five selected yes/maybe for review	Let users correct recognized foods and portions before saving.
UR-04 | Goals and insights	Goals and recommendations each selected by four	Offer adjustable targets and explainable, non-medical insights.
UR-05 | Privacy controls	Privacy concerns raised in free-text answers	Specify whether photos are processed locally or uploaded; provide deletion.

5. Limitations

- Small convenience sample (five responses), with no demographic breakdown supplied.
- Open-ended items have different response counts; no missing answers were invented.
- The screenshots do not show completion of interviews, user testing sessions, or supervisor validation.
- Reported preferences do not measure actual usability or model accuracy.

- Future photo recognition needs separate evaluation of food classification, portion estimation, nutrient lookup, and uncertainty.

6. Next validation step: real conversations

Invite the two respondents who selected “Yes” to the follow-up question, if contact was collected with consent. Recruit 1–3 additional willing potential users independently. Hold short 10–15 minute conversations and document dates, participant codes, consent, actual responses, design implications, and prototype feedback. Do not backdate or invent sessions. Confirm the approach with the supervisor.

7. Submission evidence checklist

- Preserve the original response summary screenshots or export charts from Google Forms.
- Export anonymized response summaries (do not disclose names or sensitive information).
- Add this report to docs/research/ in the existing repository.
- After real discussions, append a factual interview-log table with dates and results.
- Record any subsequent scope decisions and changes made to requirements.

Status: initial survey evidence collected; interview/discussion requirement still requires verification.

3. Critical literature review — working research draft Critical Literature Review

Development of an intelligent system for monitoring and analyzing dietary intake

Student: Abdikarim Nurmukhammed | Supervisor: Bakayeva Bakyt | 24 October 2026

RESEARCH DRAFT — Source metadata and accessible abstracts checked for selected records. Full-text methodological verification remains necessary for the entire set. Do not describe this document as a completed systematic review.

1. Scope and method

This focused narrative review evaluates mobile dietary recording, food-image recognition, portion estimation, nutrient inference and validation. Thirteen scholarly candidates were retained from an earlier project matrix. This update checks publication metadata and expands the synthesis while distinguishing peer-reviewed evidence from engineering assumptions. It is not a systematic search: database search dates, complete search strings and screening flow were not recorded. The university requires 12 meaningfully used sources, at least eight scientific publications.

2. Synthesis of evidence

2.1 User burden, app data quality and privacy

König et al. [3] review 117 publications and 129 smartphone tools; the mix of photo, portion, free-text and food-database functions indicates that no single input mode solves every recording problem. Gioia et al. [4] compared 11 diet apps and evaluated time stamps, usability, privacy, and nutrient estimates; their example food records revealed

discrepancies relative to a dietitian/reference-database comparison. NutriSmart will provide text/search as a dependable fallback, allow users to correct records, and document data handling. Unlike these studies, the five-person NutriSmart survey measures stated preferences rather than real logging accuracy.

2.2 Recognition is not portion measurement

Dalakleidi et al. [2] review image-based food-recognition systems, while Konstantakopoulos et al. [1] emphasize the relationship and separation of visual recognition and volume estimation. The Mediterranean-food imaging system [9] illustrates an approach dependent on a particular capture workflow; Schenk et al. [13] investigate 3D images and food descriptions rather than unconstrained single photos. Therefore NutriSmart will treat recognized labels as editable candidates and will not infer precise mass from a casual image without measured validation.

2.3 Datasets, models and generalization

Nutrition5k [10] provides dish images with weight/nutrition references, enabling evaluation of the whole nutritional-estimation pipeline. Zhao et al. [12] combine segmentation and regression and report a percentage mean absolute error of 17.06% for evaluated nutrition components in their reported setup. Those outcomes are research-specific; neither establishes accuracy for home-cooked Kazakh foods, different cameras, or lighting. NutriSmart must record food coverage, collect suitable examples, and evaluate performance on a held-out local test set.

2.4 Validation, reliability and explainability

Shonkoff et al. [6] reviewed 52 image-based AI studies; differing datasets and reporting prevented meta-analysis. Zheng et al. [5] provide a broader scoping review of AI assessment workflows. Cofre et al. [11] review validation evidence and discuss risk of bias. Consequently, NutriSmart should separately evaluate classification (top-1/top-3), portion mass (MAE in grams) and nutritional totals (MAE in kcal/grams), against weighed portions and documented food composition values. A confidence value without calibration must not be shown as a guarantee.

2.5 Usability and practical deployment

MyDietCam [7] documents a mobile-app design and usability context, supporting iterative review with actual users rather than assuming that photo input is effortless. The dietary-data collection review candidate [8] additionally raises questions about collection burden. Compared with model-only research, NutriSmart will evaluate task completion and time-to-log across manual entry and future photo-assisted entry. Privacy consent and image retention will be explicit.

3. Critical comparison and design implications

Approach	Value	Limitation	NutriSmart response
Manual text/search [3,4,8]	User confirms items and grams	High input burden; database matching errors	Minimum viable baseline; timed usability tasks
Image recognition [1,2,5]	May generate food candidates quickly	Similar-looking foods and hidden ingredients	Editable candidates; top-1/top-3 evaluation
Vision + 3D/portion [9,13]	Potential quantity estimation	Capture and scale requirements	Do not promise photo-only exact mass
End-to-end nutrient models [10,12]	Direct nutrient prediction	Dataset transfer and compounded errors	Separate food match, portion, nutrient source
AI assessment reviews [6,11]	Evaluation methods and limitations	Heterogeneous outcomes and risk of	Use weighed ground truth and absolute

	bias	error

4. Source audit and evidence matrix

Status: A = publicly indexed metadata and summary checked in this review; B = present in prior matrix, with full-text and/or bibliographic checks outstanding. A does not mean complete full-text critical reading.

[1] Konstantakopoulos et al. (2024). A Review of Image-Based Food Recognition and Volume Estimation Artificial Intelligence Systems. [B] Distinguish identification from volume estimation; check review inclusion and limitations. https://pubmed.ncbi.nlm.nih.gov/37276096/

[2] Dalakleidi et al. (2022). Applying Image-Based Food-Recognition Systems on Dietary Assessment: A Systematic Review. [A] Survey mobile image-recognition methods; heterogeneous recognition/portion pipelines. https://doi.org/10.1093/advances/nmac078

[3] König et al. (2022). Characteristics of smartphone-based dietary assessment tools: a systematic review. [A] 117 publications, 129 tools; modalities and completeness vary. https://doi.org/10.1080/17437199.2021.2016066

[4] Gioia et al. (2023). Mobile Apps for Dietary and Food Timing Assessment: Evaluation for Use in Clinical Research. [A] 11 apps; usability, privacy, time stamps, and estimates assessed. https://doi.org/10.2196/35858

[5] Zheng et al. (2024). Artificial Intelligence Applications to Measure Food and Nutrient Intakes: Scoping Review. [B] Pipeline stages and heterogeneity; verify full methods. https://www.jmir.org/2024/1/e54557

[6] Shonkoff et al. (2023). AI-based digital image dietary assessment methods compared to humans and ground truth: a systematic review. [A] 52 studies; varied datasets; no meta-analysis; report absolute error. https://doi.org/10.1080/07853890.2023.2273497

[7] MyDietCam study (2023). MyDietCam: Development and Usability Study. [B] UX research example; confirm full formal citation and protocol. https://pubmed.ncbi.nlm.nih.gov/36644664/

[8] Dietary data collection review (2022). Improving dietary data collection tools for better nutritional assessment. [B] Review candidate; publisher access limited; verify complete record. https://www.sciencedirect.com/science/article/pii/S2666990022000180

[9] Mediterranean food image study (2023). An Automated Image-Based Dietary Assessment System for Mediterranean Foods. [B] Food recognition with constrained imaging / stereo estimation. https://pmc.ncbi.nlm.nih.gov/articles/PMC10202193/

[10] Thames et al. (2021). Nutrition5k: Towards Automatic Nutritional Understanding of Generic Food. [B] Benchmark dataset with weight and nutrient annotation. https://openaccess.thecvf.com/content/CVPR2021/html/Thames_Nutrition5k_Towards_Automatic_Nutritional_Understanding_of_Generic_Food_CVPR_2021_paper.html

[11] Cofre et al. (2025). Validity and Accuracy of Artificial Intelligence-Based Dietary Intake Assessment Methods: A Systematic Review. [B] Validation methods and risk of bias; verify results. https://pubmed.ncbi.nlm.nih.gov/40207441/

[12] Zhao et al. (2024). Visual nutrition analysis: leveraging segmentation and regression for food nutrient estimation. [A] Segmentation and regression; reported PMAE 17.06% in study setting. https://doi.org/10.3389/fnut.2024.1469878

[13] Schenk et al. (2024). The Use of Three-Dimensional Images and Food Descriptions from a Smartphone Device Is Feasible and Accurate for Dietary Assessment. [A] 3D imaging with food descriptions; not directly equivalent to one photo.
https://doi.org/10.3390/nu16060828

4–11. Design, requirements, evaluation and project management

NUTRISMART

Criteria 4–10: Evidence-based Design & Preparation

Development of an intelligent system for monitoring and analyzing dietary intake

Student: Abdikarim Nurmukhammed | Supervisor: Bakayeva Bakyt | Individual project

DOCUMENT STATUS — Working draft for supervisor review. Do not present pending interviews, unreviewed scientific papers, mock photo recognition, or uncreated YouTrack issues as completed results.

4. Existing system comparison

Method: four contemporary food-tracking products were selected. Features below are taken from official support pages available on 24 October 2026. “Not verified” means the capability was not established from the sources reviewed, NOT that the product lacks it. NutriSmart column describes project scope, not a claim of feature parity.

Criterion	MyFitnessPal	Cronometer	YAZIO	Lose It!	NutriSmart
Food diary	Supported [MFP]	Supported [CR]	Supported [YA]	Supported [LI]	Interactive browser prototype
Photo-assisted logging	Meal Scan; Premium, English [MFP]	Photo Logging; Gold [CR]	AI calorie tracker; Pro [YA]	Snap It; Premium [LI]	UI workflow only; AI not connected
Can edit detected foods / portions	Yes [MFP]	Yes [CR]	Yes [YA]	Yes [LI]	Demo candidate / portion edit
Automated kcal / nutrition from photo	Suggested food linked to DB [MFP]	Matched foods / energy summary [CR]	Rough nutrition estimate [YA]	Suggested foods and servings [LI]	Not implemented
Food search / manual input	Supported [MFP]	Supported [CR]	Supported [YA]	Supported [LI]	Prototype has catalog/text input
Macronutrients	Supported [MFP]	Supported [CR]	Supported [YA]	Supported [LI]	Prototype calculation
Language / access caveats	Meal Scan English, OS and Premium limits [MFP]	Gold for photo [CR]	Photo AI in Pro [YA]	Snap It English/Premium [LI]	English UI; local prototype
Source /	Verified database	Nutrient-source list	AI results called rough	Verified-food	Planned source+confidence

transparency	described [MFP]	[CR]	[YA]	system [LI]	disclosure

Analysis: camera-assisted food tracking already exists in leading apps, so NutriSmart must not claim originality merely for adding a camera. A defensible project focus is an auditable nutrition pipeline, human corrections, measurable uncertainty, and a transparent comparison with manual logging. A comparative user test is still pending.

Official sources (read/accessed 24 October 2026):

[MFP] https://support.myfitnesspal.com/hc/en-us/articles/360045761612-How-to-use-the-Meal-Scanner

[CR] https://support.cronometer.com/hc/en-us/articles/39013533811092-Mobile-Photo-Logging

[YA] https://help.yazio.com/hc/en-us/articles/39137901903889-What-is-the-AI-Calorie-Tracking-Feature-and-how-does-it-work

[LI] https://loseit.zendesk.com/hc/en-us/articles/47771695186580-How-to-Use-Snap-It

[CR-data] https://cronometer.com/features/photo-voice-logging.html

[LI-manual] https://loseit.zendesk.com/hc/en-us/articles/49210381551380-How-to-Log-Food-in-Lose-It

5. Technology comparison

The selected mobile direction is Kotlin + Jetpack Compose with a local Room/SQLite datastore. The working browser prototype remains a UX demonstration and is not evidence of a production Android release.

Decision	Alternative	Advantages	Trade-offs	Choice
Mobile app	Kotlin + Compose	Native Android; type safety; Android Studio available	Android-only	Selected
Mobile app	Flutter	Cross-platform UI	New Flutter installation, another language/toolchain	Deferred
Mobile app	SwiftUI	Native iOS	No Android delivery without another client	Not selected
Data persistence	Room / SQLite	Offline-first; simple prototype deployment	Local-device only	Selected MVP
Data persistence	PostgreSQL + REST API	Relational model, multi-device scaling	Deployment/auth/security work	Future stage
Data persistence	Firebase	Managed auth/sync	Provider dependency and privacy evaluation	Alternative
Image analysis	On-device model	Offline; potentially privacy-friendly	Model size, accuracy, integration, evaluation	Candidate
Image analysis	Cloud vision/food API	Fast prototype integration	Cost, image privacy, network and vendor constraints	Candidate

Image analysis	Custom trained model	Research control	Dataset, ML expertise, evaluation cost	Research option
Food value source	Curated static catalog	Deterministic demo	Limited coverage; illustrative values	Existing prototype
Food value source	USDA FoodData Central	Source-based nutrient lookup	Coverage/mapping and API integration	Evaluate
Food value source	Regional/national database	Potential local-dish coverage	Availability/license/quality	Evaluate

Decision rationale: keep the first production Android slice local-first and testable; separate photo classification, serving estimation and nutrient lookup. Before adopting a vision provider, measure classification accuracy, kcal/portion error, latency, privacy, and operating costs.

6. Requirements traceability

ID	Requirement	Priority	Acceptance criterion	Test ID	Status
FR-01	Record food from catalog/text with portion	P0	Entry stored and nutritional totals update	T-01,T-02	Prototype: available
FR-02	Automatic kcal/P/F/C calculation	P0	200 g multiplies per-100g values by 2	T-01	Prototype: available; values illustrative
FR-03	Remove/edit entry	P0	Diary recalculates after deletion	T-03	Delete: available; editing verify
FR-04	Browse diary by date	P0	Date selection changes visible entries	T-04	Prototype: available
FR-05	Set daily goals	P0	Goals persist and progress updates	T-05	Prototype: verify
FR-06	Select/remove photo	P0	Remove clears preview; repeat upload works	T-06	Prototype: user checked v0.6
FR-07	Real food recognition from photo	P2	Accuracy evaluated on labelled meals; editable predictions	T-09	Not implemented
FR-08	Estimate portion size	P2	Mass error tested against	T-10	Not

	from photo		weighed ground truth		implemented
FR-09	Save diary in persistent Android database	P1	Room records persist across restarts	T-07	Android starter unverified
FR-10	Explainable nutrition insights	P1	Shows trigger, source and calculation	T-08	Concept/partial prototype

Non-functional: NFR-01 offline local diary; NFR-02 contrast and keyboard/mobile usability; NFR-03 clear distinction between measured, user-entered, and AI-estimated values; NFR-04 no secret/API key in Git; NFR-05 no medical diagnosis; NFR-06 photo consent and retention documentation; NFR-07 API error handling/latency tests.

7. Architecture and diagrams

The editable DOT diagram sources and rendered PNGs are included under diagrams/. Diagrams depict a staged target architecture: solid lines are baseline interactions; dashed lines indicate future integrations. The browser prototype does not yet connect to a production Android backend.

System Context — see diagrams/system-context.dot (editable) and diagrams/system-context.png (export).

Use Cases — see diagrams/use-cases.dot (editable) and diagrams/use-cases.png (export).

Components — see diagrams/components.dot (editable) and diagrams/components.png (export).

8. UX / prototype

The user-verified responsive browser prototype includes overview, calorie/macronutrient summary, food logging, date-aware diary, goal settings, photo upload/removal, CSV export and a planned photo-analysis interaction. It must be clearly labelled a browser UX prototype, not a native Android production application. Real image-based nutrition inference is not yet implemented.

Demo scenarios: (1) search Rice → adjust grams → confirm values → save; (2) change date → review diary; (3) upload photo → remove → upload a different photo; (4) update daily goal → review dashboard; (5) export local CSV.

9. Verification and evaluation plan

Baseline: manual food logging and explicit user-entered portion measurements. AI-assisted logging (when implemented) will be measured against the same meals using weighed ingredient/portion ground truth. Do not count test files as passed tests without a recent test run.

Test	Method	Metric	Pass condition
T-01	200 g food with 130 kcal/100 g	kcal absolute error	Result = 260 kcal
T-02	Add entries from food catalogue	Completion / calculation	Saved entry shown; totals correct
T-03	Delete logged meal	Data consistency	Removed everywhere, totals updated

T-04	Switch diary date	Date accuracy	Only selected date shown
T-05	Set new daily goals	Persistence / UI	Reload preserves goal
T-06	Upload, remove, upload again	UI / state reset	Old preview and stale response absent
T-07	Restart native Android app	Persistence	Room records survive restart
T-08	Trigger insight	Explainability	Rule and input values displayed
T-09	Future photo classification	Top-1/top-3 accuracy	Target established with supervisor
T-10	Future image portion estimates	Mass MAE / kcal MAE	Compare to weighed food

Formative usability plan: 3–5 user discussions, timed manual-entry tasks, completion/error rates, post-task difficulty rating and qualitative concerns. No interviews or participant results are claimed here. For scientific evaluation report confidence intervals where practical and disclose the sample limitations.

10. Project management and risks

Repository to retain: https://github.com/Nurmukhammed070/intelligent-nutrition-system. Git tag for Microsoft Forms: prob-period-1. These URLs do not prove the repository has been populated or tagged; verify on GitHub.

Issue template	Deliverable	Acceptance	Priority	Owner
Project proposal	Reviewed proposal	Scope and aim approved or feedback logged	High	Abdikarim Nurmukhammed
User study	3–5 discussions + optional Google Form	Real responses and findings/assumptions separated	High	Abdikarim Nurmukhammed
Literature	12 used sources, 8 scientific	Critical synthesis with complete citations	High	Abdikarim Nurmukhammed
Competitor analysis	4 systems × 8 criteria	Source-backed matrix	High	Abdikarim Nurmukhammed
Architecture	3 diagrams + files	Editable DOT and exported diagrams	High	Abdikarim Nurmukhammed
UX tests	Screenshots + findings	Repeatable user flows and results	High	Abdikarim Nurmukhammed
Supervisor review	Comment/decision record	Actual feedback and response documented	High	Abdikarim Nurmukhammed
Checkpoint packaging	README/PDF/screenshots/tag	Matches version and is accessible	High	Abdikarim Nurmukhammed

Do not paste invented YouTrack IDs. Create tasks in YouTrack, then append real IDs, links, branch/commit references and deadlines. Link evidence only after it exists.

Risk	Impact	Mitigation
Photo cannot reveal exact mass	Misleading calorie numbers	Require portion confirmation, disclose error
Food data gaps and regional dishes	Low coverage	Track source, allow manual override
Uploaded meal images may be sensitive	Privacy concern	Consent, minimal retention and server policy
Limited time at checkpoint	Incomplete evidence	Prioritize mandatory research and verified docs
Unreviewed decisions	Supervisor may reject scope	Request tracked feedback and revise

Appendix A. Required diagrams and board evidence

A1. System context diagram

Diagram export from the current architecture materials. Maintain editable source files in the project repository.

A2. Use case diagram

Diagram export from the current architecture materials. Maintain editable source files in the project repository.

A3. Component diagram

Diagram export from the current architecture materials. Maintain editable source files in the project repository.

A4. YouTrack project management evidence

15 issues created (NUT-1 to NUT-15): Backlog 6, Development 1, Review 8, Test 0 as seen on 24 October 2026. Screenshots are also provided as a separate required PDF. This document does not assert that all acceptance criteria are met.