Effective April 21, 2020

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

HAND SANITIZER

1. Substance/Preparation And Company Identification

Name of the Product: Hand Sanitizer
Other Means of Identification: Solution to kill Bacteria
Recommended use: Hand Sanitizer
Supplier Information
Company: Certified Color Corporation
1441 West Collins Ave
Orange, CA 92867
Company Phone Number: 714-997-7519
Emergency Phone Number 24 hours per day: 714-322-5493
Information Phone Number: 800-282-4895

2. Hazards Identification

GHS Classifications

Physical Hazards: Waterborne. No Physical hazards.
Health Hazards Acute Toxicity: Category 5: Warning. H303, May be harmful if swallowed.
Skin Corrosion/Irritation: None.
Eye Irritation: Category 2B: Warning. H320, Causes eye irritation.
Inhalation Hazard: Category 5: Warning. H333, May be harmful if inhaled.
Aspiration Hazard: None
Emergency Overview:
If the solution is swallowed, some stomach discomfort can be expected.
Route of Entry: Inhalation: yes. Skin: yes. Ingestion: yes.
Carcinogenicity: NTP: no. IARC: no. OSHA: no.
Reproductive Toxicity: No reproductive toxins.
Target Organ Systemic Toxicity (TOST): No target organs are indicated.

Effects of Exposure:
Acute: Eye: Moderate to severe irritation, redness, tearing and blurred vision.
Skin: Prolonged/repeated exposure can cause moderate irritation, de-fatting and dermatitis.
Inhalation: The low vapor pressure does not pose a significant threat to humans through inhalation.
Signs and Symptoms of Overexposure: Lethargy.
Medical Conditions Aggravated by Exposure: Dermatitis.
Carcinogenicity: No Carcinogenic ingredients over 0.1% in formula.
LABELING:
Product identifier: Hand Sanitizer
Signal Word: Warning
Hazard statements:
H303, May be harmful if swallowed.
H313, May be harmful in contact with skin.
H333, May be harmful if inhaled.
H305, May be harmful if swallowed and enters airways.
Symbols:
None

FIRST AID
EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
SKIN: In case of prolonged contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops and persists.

COMPANY NAME; CERTIFIED COLOR CORPORATION
ADDRESS: 1441 West Collins Ave
Orange, CA 92867
Phone number: 714-997-7519

Precautionary Statements
P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P305 +P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. If present and easy to do. Continue rinsing.

3. Composition/Information On Hazardous Ingredients

Hazardous Ingredient	w/w%	CAS No	OSHA PEL
Ethyl Alcohol	<15	64-17-5	1000 ppm
Methyl Ethyl Ketone	<2	78-93-3	200 ppm
Propylene Glycol	<4	57-55-6	None Established

Note: NE=Not Established
Note: Further safety information can be found in subsequent sections.

4. First aid measures

General Information: Discard contaminated clothing immediately.
Eye: Flush with clean, lukewarm water for at least 15 minutes, occasionally lifting eyelids.
Obtain medical attention.
Skin: Remove contaminated clothing. Wash affected skin areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse.
Inhalation: Remove victim to fresh air.
Ingestion: Keep person warm and quiet. Get immediate medical attention. Do not induce vomiting because of risk of aspiration of material into lungs. Drink several glasses of water to dilute the product in the stomach.

5. Fire Fighting Measures

Flammability Summary (OSHA): Waterborne. Not flammable.
Flash Point Method: Setaflash
Flash Point: Waterborne. No Flash Point.
Upper Flammable/Explosive Limit, % in air: NA
Lower Flammable/Explosive Limit, % in air: NA
When dry:
Upper Flammable /explosive limit, % in air: NA
Lower Flammable / explosive limit, % in air: NA
Unusual Fire/Explosion Hazards: Closed containers may explode when exposed to fire due to pressure buildup.
Extinguishing Media: Not Flammable. Can be made to burn if part of an existing fire due to Ethanol content.

Fire Fighting Instructions: Water spray may be used for cooling containers to prevent possible pressure build up and auto ignition/explosion when exposed. Guard against toxic gasses released by fire. If safe, remove containers from fire zone.
Products of Combustion: Dried product can be made to burn, releasing Carbon Dioxide, Carbon Monoxide.

6. Accidental Release Measures

Evacuate the area of all unnecessary personnel. Ventilate area. Equip employees with appropriate protective equipment. Dike around spilled material. Cover spill with inert/absorbent material and shovel with non-sparking tools into container. Remove containers to safe area and seal. Use sand or absorbent to collect material and to prevent flow into storm water or ground.
Waste Disposal Methods: Waste material must be disposed of in accordance with federal, state and local environmental regulatory controls.

7. Handling And Storage

Handling: Some containers are heavy. Lift properly to avoid back strain.
Drums: Protect against physical damage.
Bulk: Storage should be in standard lidded storage tanks.
Other Precautions: Clean up spills quickly to prevent slipping on the wet surface.

8. Exposure Controls and Personal Protection

Respiratory Protection:
Hazardous air contaminants are not present above the reporting levels, therefore self-contained breathing apparatus is not required.

Ventilation:
Local exhaust must be sufficient to keep airborne vapor concentrations below TLV limit.
Protective Gloves: None required.
Eye Protection: Chemical workers' goggles.
Other Protective Equipment: Waterproof aprons.
Eye bath and safety shower. To prevent repeated or prolonged skin contact wear impervious clothing and boots.
Work Hygiene Practices: Wash hands and clothing after exposure.

Supplemental Safety and Health: First aid procedures: Vomit can cause chemical pneumonia which can be fatal.
Ventilation: Filters to reduce environmental contamination. Ventilation should be adequate to keep exposure below the PEL levels.
Effects of overexposure: Dermatitis from oils in skin being removed with long term contact.
Medical conditions aggravated by exposure: Any respiratory or skin condition.
Exposure Limits:

Hazardous Ingredient	w/w%	CAS No	OSHA PEL
Ethyl Alcohol	<15	64-17-5	1000 ppm
Methyl Ethyl Ketone	<2	78-93-3	200 ppm
Propylene Glycol	<4	57-55-6	None Established

9. Physical and Chemical Properties

Physical State: Liquid
Color: Clear
Odor: faint hydrocarbon
Odor Threshold: not known
pH: 7
Melting Point/freezing point: Not known.
Initial boiling point and boiling range: 100C(212F)
Flash Point: Waterborne. No Flash Point. Setaflash
Evaporation rate: Slower than butyl acetate
Flammability of solid or gas: NA
Upper Flammability Limit: NA
Lower Flammability Limit: NA
Vapor Pressure: Not known.
Vapor Density: Heavier than air
Solubility in Water: dispersible.
Specific Gravity relative to water: 1.15
Density: 7.25 pounds per gallon
Partition coefficient: n-octanol/water: Not known.
Auto-ignition temperature: Not known.
Decomposition temperature: Not known.
Viscosity: water thin
Non Volatile: Not known
Volatile: Not known

VOC: Not known

10. **Stability and Reactivity**

Stability and Reactivity Summary: Stable under normal conditions
Reactive Properties:
Sensitivity to mechanical shock: None
Hazardous Polymerization: Will not occur
Conditions to Avoid: Do not heat closed containers
Chemical Incompatibility: Strong oxidizing agents
Hazardous Decomposition Products: CO, CO2

11. **Toxicological Information**

Hazardous Ingredient	w/w%	CAS No	LD50 Male Rat, 4 hour exposure
Ethyl Alcohol	<15	64-17-5	7060 ppm
Methyl Ethyl Ketone	<2	78-93-3	2740 ppm
Propylene Glycol	<4	57-55-6	None Established
Toluene	<1	108-88-3	7500 ppm Toluene has been known to cause birth defects

12. **Ecological Information**

Hazardous Ingredient	w/w%	CAS No	Toxicity Information
Ethyl Alcohol	<15	64-17-5	S.gairdneri: (96hr LC50)

13. **Disposal Considerations**

Disposal Methods:
Dispose of in accordance with local, state and federal regulations.

14. **Transport Information**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT): UN ID Number: UN1987
Proper shipping name: Alcohols, n.o.s. (ETHYL ALCOHOL, ISOPROPYL ALCOHOL, METHYL ETHYL KETONE, N-PROPYL ACETATE, TOLUENE)

IMO: Not Regulated for Transportation. Not a marine pollutant.
IATA: Not Regulated for Transportation.

15. **Regulatory Information**

UNITED STATES:
Toxic Substances Control Act (TSCA): The components of this product are listed on the TSCA Inventory of Existing Chemical Substances.
Superfund Amendments and Reauthorization Act (SARA) Title III:
No listed components.
Sections 311/312 Hazard Categories (40 CFR 370.2):
Immediate/Acute Health Hazard: Yes
Delayed/Chronic Health Hazard: Yes
Fire Hazard: No
Pressure Hazard: No
Reactivity Hazard: No
Federal and State Regulations: No

California prop. 65: TOLUENE is present below 1%. It is considered a toxic substance and developmental substance.

HMIS Ratings:
Health Hazard: 1
Fire Hazard: 0
Reactivity: 0
Personal Protection: B
National Fire Protection Association (U.S.A.):
Health: 1
Flammability: 0
Reactivity: 0
Specific hazard: Keep out of reach of unsupervised children.

16. **Other Information**

This information should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to its use. No warranties of any kind neither express nor implied, including warranties of merchantability or fitness for a particular purpose are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, information, data and designs furnished by CERTIFIED COLOR CORPORATION hereunder are given gratis and CERTIFIED COLOR CORPORATION assumes no obligation or liability for the description, information, data and designs given or results obtained, all such being given and accepted at your risk. We believe this information to be reliable and up to date as of its publication date, but make

no warranty that it is. If this SDS is more than one year old you should contact CERTIFIED COLOR CORPORATION to make sure the information is still current.
Revision Date: New
Date of Original Document: April 22, 2020
Prepared by: V.C. Bud Jenkins, BS, MBA, JD, Certified Hazardous Materials Manager, Certified Hazardous Waste Practitioner.
www.coatingsscientist.com