
1. Please check claims and evidence.

1.1

- **H1 (Detection Coverage):** EADD detects a broader range of temporal drift patterns than D3. H1a compares the drift streams that each detector detects (Experiments 1 and 4), and H1b compares detection delay on the streams that both EADD and D3 detect.

no point to present synthetic data.



not a good design

only count correct detections that both method detect ?

H1b


H1a

check significant test for MTD (lower) & Recall (Higher)

1.2


- **H2 (False Alarm Reduction):** EADD produces significantly fewer false alarms than D3 on stable data. Formally, H_0: $\mathrm{FA}_{\mathrm{EADD}} \geq \mathrm{FA}_{\mathrm{D3}}$ vs H_1: $\mathrm{FA}_{\mathrm{EADD}} < \mathrm{FA}_{\mathrm{D3}}$, where FA is the number of false alarms per stream. The hypothesis is tested with a one-sided Mann–Whitney U test ($\alpha = 0.05$) at several D3 thresholds ($\tau \in \{0.6, 0.7, 0.8\}$) in Experiment 3.

significant test



1.3 ASPT does not hurt the performance (Recall, MTD, FA) and run faster (runtime, reject rate)

Significant test



2. Unannotated real data → Please check Lukas for reporting.

3. Organize experiments in RQs (or Hypotheses)

4. Keep result findings short and direct to the Hypotheses.
   DO NOT USE ENUMERATION (1, 2, 3...)

5. We do not need D3 without LightGBM. Please keep confounds minimal (e.g.,
   LightGBM vs LogisticRe, 300/12 vs 500/200)

ENHANCED ADVERSARIAL DRIFT DETECTION (EADD) FOR MLOPS FEATURE MONITORING

NUSRAT BEGUM

A THESIS SUBMITTED IN PARTIAL FULFILLMENT
OF THE REQUIREMENTS FOR THE DEGREE OF
MASTER OF SCIENCE (COMPUTER SCIENCE)
FACULTY OF GRADUATE STUDIES
MAHIDOL UNIVERSITY
2026

COPYRIGHT OF MAHIDOL UNIVERSITY

Thesis
entitled

ENHANCED ADVERSARIAL DRIFT DETECTION (EADD) FOR MLOPS FEATURE MONITORING

was submitted to the Faculty of Graduate Studies, Mahidol University
for the degree of Master of Science (Computer Science)
on
December 2026

Thesis Advisory Committees

Major Advisor

.....
Ms. Nusrat Begum
Candidate

.....
Asst. Prof. Thanapon Noraset,
Ph.D. (Computer Science)

.....
Assoc. Prof. Suppawong Tuarob,
Ph.D. (Computer Science)

.....
Prof. Dr. Chartchalerm
Isarankura-Na-Ayudhya,
Ph.D. (Medical Technology)
Dean
Faculty of Graduate Studies
Mahidol University

.....
Assoc. Prof. Boonsit Yimwadsana,
Ph.D. (Computer Science)
Program Director
Master of Science Programme
in Computer Science
Faculty of Information and
Communication Technology
Mahidol University

Thesis
entitled

ENHANCED ADVERSARIAL DRIFT DETECTION (EADD) FOR MLOPS FEATURE MONITORING

was submitted to the Faculty of Graduate Studies, Mahidol University
for the degree of Master of Science (Computer Science)
on
December 2026

Thesis Examination Committees

Chair

.....
Ms. Nusrat Begum
Candidate

.....
Asst. Prof. Akara Supratak,
Ph.D. (Computer Science)

.....
Asst. Prof. Thanapon Noraset,
Ph.D. (Computer Science)

.....
Assoc. Prof. Suppawong Tuarob,
Ph.D. (Computer Science)

.....
Prof. Dr. Chartchalerm
Isarankura-Na-Ayudhya,
Ph.D. (Medical Technology)
Dean
Faculty of Graduate Studies
Mahidol University

.....
Dr. Pattanasak Mongkolwat,
Ph.D. (Computer Science)
Dean
Faculty of Information and
Communication Technology
Mahidol University

ACKNOWLEDGEMENTS

I would like to express my sincere gratitude to my major advisor, Asst. Prof. Thanapon Noraset, Ph.D., for his guidance, patience and detailed feedback throughout this research. I also thank my co-advisor, Assoc. Prof. Suppawong Tuarob, Ph.D., for the advice and support given during my study.

I am grateful to the chair of the thesis examination committee, Asst. Prof. Akara Supratak, Ph.D., for the time and valuable comments given to this work.

I thank the co-authors of the JCSSE 2026 paper, Phaphontee Yamchote and Chainarong Amornbunchornvej, Ph.D., for their contributions, and the Faculty of Information and Communication Technology, Mahidol University, for its support.

Finally, I thank my family for their constant encouragement.

Nusrat Begum

ENHANCED ADVERSARIAL DRIFT DETECTION (EADD) FOR MLOPS FEATURE MONITORING

NUSRAT BEGUM 6638009 ITCS/M

M.Sc. (COMPUTER SCIENCE)

THESIS ADVISORY COMMITTEE: THANAPON NORASET, Ph.D., SUPPAWONG TUAROB, Ph.D.

ABSTRACT

Machine learning models in production can lose accuracy without warning when the distribution of their input data drifts. Unsupervised drift detectors can signal that drift has occurred, but D3, a discriminative detector recommended by a recent benchmark, relies on an uncalibrated AUC threshold, compares two short adjacent windows, and gives no indication of which features changed. This thesis proposes Enhanced Adversarial Drift Detection (EADD), an integrated framework that combines a LightGBM classifier two-sample test, a reservoir-sampled reference window, prediction entropy monitoring and an adaptive sequential permutation test (ASPT), and that ranks the features behind each confirmed drift with TreeSHAP. ASPT applies sequential Monte Carlo stopping to the permutation test, so that each alarm receives a permutation p-value after a small fraction of the maximum number of permutations. EADD was compared with seven unsupervised detectors on synthetic and real-world data streams. It was the only detector to detect all four synthetic drift types (abrupt, gradual, incremental and recurring) without false alarms, and on the real-world streams it detected drift on three of four annotated streams, sooner than D3. An ablation in which D3 was given a LightGBM classifier showed that EADD's advantage on gradual and incremental drift comes from its long-memory reference window rather than from the classifier, that D3's false alarms on stable data were caused by its small windows, and that the permutation test changes the decisions only when the AUC threshold is lowered.

KEYWORDS: DRIFT DETECTION / CLASSIFIER TWO-SAMPLE TEST / PERMUTATION TEST / COVARIATE DRIFT / MLOPS

86 pages

TABLE OF CONTENTS

		Page
ACKNOWLEDGEMENTS		iii
ABSTRACT		iv
LIST OF TABLES		vii
LIST OF FIGURES		viii
LIST OF ABBREVIATIONS		ix
CHAPTER 1	INTRODUCTION	1
CHAPTER 2	LITERATURE REVIEW	7
CHAPTER 3	RESEARCH METHODOLOGY	23
CHAPTER 4	RESULTS	40
CHAPTER 5	DISCUSSION	61

TABLE OF CONTENTS (cont.)

	Page
CHAPTER 6 CONCLUSION AND RECOMMENDATIONS	**68**
APPENDICES	**83**
APPENDIX A IMPLEMENTATION DETAILS	**84**
BIOGRAPHY	**86**

LIST OF TABLES

Table **Page**

LIST OF FIGURES

Figure **Page**

LIST OF ABBREVIATIONS

ADWIN	Adaptive Windowing
AR(1)	First-Order Autoregressive Process
ASPT	Adaptive Sequential Permutation Test
AUC	Area Under the Receiver Operating Characteristic Curve
C2ST	Classifier Two-Sample Test
D3	Discriminative Drift Detector
DDM	Drift Detection Method
EADD	Enhanced Adversarial Drift Detection
EDDM	Early Drift Detection Method
FA	False Alarms
H_{pred}	Prediction Entropy Monitoring Signal
KS	Kolmogorov–Smirnov (test)
LightGBM	Light Gradient Boosting Machine
MDR	Missed Detection Rate
MMD	Maximum Mean Discrepancy
MLOps	Machine Learning Operations
MTD	Mean Time to Detection
PCA	Principal Component Analysis
PSI	Population Stability Index
SHAP	SHapley Additive exPlanations
TreeSHAP	Tree-based SHAP implementation

CHAPTER 1
INTRODUCTION

1.1 Background and Significance

Machine learning models deployed in production environments operate under the assumption that future data will resemble training data. This assumption is routinely violated: the statistical properties of input features, label distributions, or the conditional relationship between inputs and outputs evolve over time, a phenomenon collectively termed *distribution drift* [1, 2]. Left undetected, drift degrades model performance silently, accumulating technical debt and operational risk [3, 4]. Widmer and Kubat [5] established that early detection of such changes is essential for maintaining reliable inference in non-stationary environments.

The practical consequences are well documented. Vela et al. [6] demonstrated that clinical prediction models exhibit measurable accuracy degradation within months of deployment due to temporal distribution shift. Nestor et al. [7] corroborated this finding, showing that models for common clinical tasks failed to generalise across temporally shifted patient cohorts within the same hospital system. In such settings, an alarm that only states that drift occurred leaves practitioners to work out whether the cause is a specific feature pipeline, a population-level shift, or a data quality failure [3].

The drift detection landscape has matured considerably. Statistical methods employ hypothesis tests such as the Kolmogorov–Smirnov test or Maximum Mean Discrepancy to compare reference and current distributions [8, 9]. Adaptive windowing methods like ADWIN dynamically adjust historical baselines [10]. Supervised error-based detectors (DDM, EDDM) monitor model error rates but require ground-truth labels [11, 12]. Prediction-based methods track model outputs but depend on calibration quality [13, 14]. Despite this diversity, several challenges remain. Univariate tests are run once per feature, so they raise more false alarms as the number of features grows; supervised

methods cannot operate when labels are delayed or unavailable; and most detectors report only whether drift occurred, not which features changed [1, 15].

The discriminative approach recasts distribution comparison as a classification problem. Lopez-Paz and Oquab [16] formalised this as the *classifier two-sample test* (C2ST): if an auxiliary classifier can reliably separate reference from current data based solely on features, the distributions differ. Gözüaçık et al. [17] adapted this principle for streaming drift detection as the Discriminative Drift Detector (D3), which is one of the three detectors recommended by the benchmark of Lukats et al. [18] and achieved the best mean time ratio in its experiments. D3 has three practical limitations. First, it signals drift when the AUC of a logistic regression classifier exceeds a fixed threshold of 0.7, and this threshold is not calibrated as a statistical test. Second, it compares two short adjacent windows, so a slow drift that changes both windows together can go unnoticed. Third, it discards the trained classifier after computing the AUC, so it gives no indication of which features drove the alarm.

Each of these limitations has been studied separately. Permutation tests can calibrate the C2ST statistic [16], and sequential Monte Carlo methods reduce the number of permutations that such tests need [19]. SHAP [20] has been applied to domain classifiers to rank drifted features [21] and to the explanations of deployed models to detect shifts that change model behaviour [22]. Panda et al. [23] test feature interactions for drift, but the interactions must be specified in advance and the cost grows quadratically with the number of features. Feng et al. [24] attribute performance changes to features but need ground-truth labels, and Hinder et al. [25] define feature-wise drift formally without providing a streaming detector. This thesis combines a calibrated and cheaper significance test, a long-memory reference window and a feature ranking in one unsupervised streaming detector, and measures which of these components causes the differences from D3.

1.2 Research Objectives

The objectives of this thesis are:

1. To develop an unsupervised drift detection framework, Enhanced Adversarial Drift Detection (EADD), that extends the discriminative approach of D3 [17] with a LightGBM classifier [26], a reservoir-sampled reference window [27] and a permutation test that confirms each alarm.
2. To reduce the cost of the permutation test with an adaptive sequential stopping rule [19] while keeping its Type I error control.
3. To evaluate EADD against seven unsupervised drift detectors on synthetic and real-world data streams in terms of detection delay, missed detections and false alarms, and to measure the effect of each EADD component.

1.3 Scope of the Study

This thesis studies unsupervised detection of feature drift, that is, changes in the input distribution $P(X)$, in data streams with numerical features. Labels are not used for detection, so changes in $P(y \mid X)$ that leave $P(X)$ unchanged are outside the scope. The evaluation uses synthetic streams with five features and known drift points, stable synthetic streams without drift, and thirteen real-world streams with 2 to 72 features from the benchmark of Lukats et al. [18]. EADD is compared with the seven unsupervised detectors evaluated in that benchmark. The TreeSHAP feature ranking that EADD reports with each detection is described but its accuracy is not evaluated, and drift adaptation, such as retraining the deployed model, is not studied.

move to Chapter 3, before research questions

1.4 Conceptual Framework

Figure 1.1 shows the conceptual framework of this thesis. A discriminative drift detector is defined by a few design choices: the classifier that separates the reference and current windows, the sizes of the two windows, the way the reference window is maintained, and the rule that turns the classifier's AUC into a drift decision. These choices determine the detection outcomes: how quickly drift is detected, how many drifts are missed, how many false alarms are raised on stable data, and how much computation

is needed. EADD and D3 differ in all four choices. The experiments therefore compare the full detectors and also change one design choice at a time.




Figure 1.1: Conceptual framework: the design choices of a discriminative drift detector determine its detection outcomes.

1.5 Hypotheses

Two hypotheses are tested. H1 states that EADD detects a broader range of temporal drift patterns than D3. H2 states that EADD produces fewer false alarms than D3 on stable data. Section 3.2 states both hypotheses formally, together with the research questions they address.

1.6 Brief Research Methodology

The methodology has three steps, described in Chapter 3. First, synthetic streams with known drift points, stable synthetic streams and thirteen real-world benchmark streams are collected. Second, each stream is processed by EADD, by the seven detectors of the Lukats et al. [18] benchmark, and by ablated versions of D3 and EADD that change one design choice at a time. Third, the detections are compared with the known drift points, or counted on streams without drift, and the differences are tested with one-sided Mann–Whitney U tests.

1.7 Assumptions

The study relies on the following assumptions:

1. The reference window contains data from the distribution that is considered normal, so that a difference between the reference and current windows indicates drift.
2. Under the null hypothesis of no drift, the samples in the reference and current windows are exchangeable. The permutation test is only valid under this assumption, which is violated when consecutive samples are correlated.
3. The drift points annotated in the INSECTS streams [28] mark the true changes in their distributions.
4. The synthetic generators represent the four temporal drift patterns (abrupt, gradual, incremental and recurring) described in the literature [2].

1.8 Definitions of Terms

Feature drift (covariate drift): a change over time in the distribution of the input features $P(X)$.

Concept drift: a change over time in the conditional distribution $P(y \mid X)$.

Classifier two-sample test (C2ST): a test of whether two samples come from the same distribution, based on how well a classifier can tell them apart [16].

Reference window and current window: the baseline sample W_{ref} and the most recent sample W_{cur} that a drift detector compares.

AUC: the area under the receiver operating characteristic curve of the classifier that separates the two windows; 0.5 means the windows cannot be separated.

Permutation test: a test that compares the observed AUC with the AUCs obtained after randomly shuffling the window labels.

False alarm: a detection that does not correspond to a true drift point; on a stream without drift, every detection is a false alarm.

Mean time to detection (MTD): the average number of samples between a true drift point and its first matching detection.

Missed detection rate (MDR): the proportion of true drift points that are not detected within the tolerance window.

1.9 Research Contribution

This thesis makes the following contributions:

1. We propose EADD, an integrated framework for unsupervised feature drift detection that combines a ~~LightGBM~~ classifier two-sample test, a reservoir-sampled reference window, prediction entropy monitoring and an adaptive sequential permutation test, and that ranks the features behind each confirmed drift ~~with TreeSHAP [20]~~ (Chapter 3).
2. We apply sequential Monte Carlo stopping [19] to the permutation test of the classifier two-sample test. The resulting adaptive sequential permutation test (ASPT) confirms a clear drift after 20 of the 199 available permutations, a 90% saving over a fixed-budget test. Experiment 4 shows that, with the default AUC threshold, ASPT confirms every alarm it tests, and that it reduces false alarms when the threshold is lowered (Chapters 3 and 4).
3. We evaluate EADD against seven unsupervised detectors on synthetic and real-world streams. The evaluation includes an ablation with D3 using a LightGBM classifier, which separates the effects of the classifier, the reference window and the permutation test (Chapter 4).

CHAPTER 2
LITERATURE REVIEW




Figure 2.1: Comparison of no drift versus drift scenarios. Left: When distributions overlap, the discriminative classifier cannot distinguish data sources (AUC $\approx$ 0.5). Right: When drift occurs, distributions shift and the classifier can distinguish sources (AUC $\gg$ 0.5).

2.1 Overview

Drift detection addresses the challenge that arises when the statistical characteristics of data evolve over time in a manner that impacts the validity of a machine learning model [1, 2]. According to Bayram et al. [4], when users, environments, data sources, or the relationships between labels and features change, model accuracy can diminish. Gama et al. [2] and Sculley et al. [3] emphasise that drift detection identifies such modifications early, allowing practitioners to adapt, retrain, or update the model accordingly. A robust understanding of drift types and detection methods is essential for designing effective monitoring systems.

2.2 Historical Evolution of Drift Detection

The study of distribution drift has evolved from foundational statistical concepts to integrated AI governance over roughly seven decades. Table 2.1 summarises the major eras.

Table 2.1: Historical evolution of drift detection research.

Era	Key Developments
Early Foundations (1950s–1980s)	Statistical process control and sequential analysis laid the groundwork. Page [29] introduced the cumulative-sum (CUSUM) change-point test, which remains foundational for sequential change detection. Reservoir sampling [27] enabled representative subsampling of data streams.
Identification Era (1996–2004)	The term "concept drift" gained formal academic recognition [5]. Gama et al. [11] introduced the Drift Detection Method (DDM), using PAC-learning error-rate bounds to trigger alerts and establishing the supervised error-monitoring paradigm.
Windowing & Statistical Tests (2007–2015)	Bifet and Gavaldà [10] proposed ADWIN (Adaptive Windowing), enabling drift detection without fixed window sizes by applying statistical tests over dynamically adjusted sub-windows. Non-parametric tests (KS, MMD) became standard for comparing reference and current distributions [8, 9].
Deep Learning & High-Dimensionality (2018–2023)	As models moved to unstructured data, detection shifted toward monitoring internal latent representations [8, 30]. Gözüaçık et al. [17] introduced D3, demonstrating that discriminative classifiers could serve as powerful multivariate drift detectors. Lopez-Paz and Oquab [16] formalised the classifier two-sample test (C2ST), providing theoretical backing for this approach.
Governance & Attribution Era (2024–2026)	Drift detection became embedded in AI governance frameworks, and attention moved toward interpretable and statistically rigorous detection: TRIPODD [23] introduced feature-interaction hypothesis testing; E-C2ST [31] enabled anytime-valid sequential testing via e-values; HDPD [24] decomposed performance gaps into $P(X)$ and $P(y\|X)$ components with attributions. Cloud platforms added SHAP-based feature attribution monitoring [32, 33]. Hinder et al. [34] exposed vulnerabilities in discriminative detectors to adversarial evasion.

This progression, from reactive error monitoring to proactive analysis of feature distributions and attributions, provides the historical context for the present work.

2.3 Types of Drift

Drift can be categorised along two main dimensions: by the nature of the change (what component of the data-generating process is affected) and by the temporal pattern of the change (how the drift manifests over time) [1, 2].

2.3.1 Drift by Nature of Change

Based on which component of the joint distribution $P(X, y)$ changes, the literature [1, 2, 35] classifies drift into the following types:

Concept Drift (Real Drift): The conditional distribution $P(y|X)$ changes over time while the feature distribution $P(X)$ may or may not change [1, 36]. This represents a change in the underlying relationship between inputs and outputs: the "concept" the model has learned becomes invalid. For example, the factors that determine creditworthiness may evolve due to economic shifts, even if the applicant characteristics (features) remain similar [2]. Concept drift directly degrades model performance because the learned decision boundaries no longer reflect the true input-output relationship [1].

Covariate Drift (Feature Drift / Virtual Drift): The marginal distribution of input features $P(X)$ changes over time while the conditional relationship $P(y|X)$ remains stable [35, 37]. The ground-truth concept does not change, but the model may encounter inputs outside its training distribution. For example, a fraud detection model trained on transaction patterns from one demographic may receive data from a different user population, even though the definition of fraud remains unchanged [35]. Covariate drift can degrade model performance because the model is exposed to feature regions where it may not generalise well [37].

Prior Probability Drift (Label Shift): The marginal distribution of labels $P(y)$ changes over time while $P(X|y)$ remains stable [35]. This occurs when the prevalence of different classes changes, for instance a seasonal increase in a particular disease that alters the class balance in medical diagnosis. This is sometimes called class imbalance shift [1].

Note on Terminology: The literature uses varied terminology [1]. The term "concept drift" is sometimes used as an umbrella term for any distribution change affecting model performance [2], while some reserve it specifically for changes in $P(y|X)$ [35].

This thesis focuses primarily on covariate (feature) drift detection, as it enables early warning without requiring labels.

2.3.2 Drift by Temporal Pattern

Based on how drift manifests over time, the literature [1, 2, 36] categorises drift as follows:

- **Abrupt (Sudden) Drift:** A rapid, discrete change where the data distribution shifts quickly from one state to another within a short time period [2].
- **Gradual Drift:** A new distribution progressively replacing the old one over an extended duration, with samples from both distributions interleaved during the transition period [1].
- **Incremental Drift:** Small but continuous changes accumulating over time, eventually resulting in a significant distributional shift [36].
- **Recurring (Seasonal) Drift:** Previously observed distributions reappearing periodically due to cyclical patterns, such as seasonal effects in retail or recurring user behaviour patterns [1, 2].

Understanding drift patterns is important for detector design: abrupt drift requires rapid response, gradual drift requires sustained sensitivity, and recurring drift benefits from mechanisms that can recognise previously seen distributions [2].

Figure 2.2 illustrates the four patterns with the synthetic streams used in the experiments of this thesis (Section 3.4).

2.3.3 Summary Taxonomy

Table 2.2 consolidates the drift classification used throughout this thesis.

This thesis focuses primarily on **feature (covariate) drift**, that is, changes in $P(X)$, because it can be detected without ground-truth labels and provides early warning before model performance degrades.




Figure 2.2: The four temporal drift patterns in the synthetic streams of this thesis, shown for one feature. Grey points are individual samples, the black line is a rolling mean over 100 samples, and dashed lines mark the drift points.

Table 2.2: Taxonomy of drift types referenced in this thesis.

Category	**Type**	**Description**
By Cause [1, 2]	Data / Feature Drift	Change in the input distribution $P(X)$ without changing the relationship to the target.
	Concept Drift	Change in the conditional $P(y \mid X)$, invalidating learned decision boundaries.
	Prior Probability Drift	Change in the label distribution $P(y)$ while $P(X \mid y)$ is stable.
By Pattern [2, 36]	Sudden (Abrupt)	Rapid, discrete shift between two distinct distributions.
	Gradual	Old concept progressively replaced by a new one over an extended period.
	Incremental	Small, continuous changes accumulating into a significant shift.
	Recurring (Seasonal)	Previously observed distributions reappearing cyclically.

2.4 Classification of Drift Detection Methods

Based on surveys of the drift detection literature [1, 2, 35, 38], drift detection methods can be classified along several dimensions. According to Lu et al. [1], the most fundamental distinction is based on label availability: whether the method requires access to ground-truth labels (supervised) or operates without them (unsupervised).

2.4.1 Supervised Drift Detection Methods

Supervised detectors require ground-truth labels and monitor the error stream of the deployed model [2, 11]. They assume that a change in error behaviour, such as a higher error rate, errors that occur closer together, or a shift in the mean of a monitored loss, indicates drift [11, 12]. The methods in this group differ mainly in the statistic they track and in the bound they use to decide that a change is significant. DDM compares the error rate and its standard deviation with thresholds derived from the binomial distribution [11]. EDDM tracks the distance between consecutive errors, which makes it more sensitive to gradual drift [12]. The Page–Hinkley test accumulates the deviations of the monitored signal from its mean [29], and HDDM-A and HDDM-W replace distributional assumptions with Hoeffding's inequality, using moving averages for abrupt change and weighted windows for gradual change [39].

Because these methods all watch the model's errors, they share the same strengths and weaknesses. Their alarms are tied directly to model performance, and their thresholds have a clear statistical meaning. However, they need labels, which are often delayed, expensive, or unavailable in production [1, 13]. They also react only after drift has already degraded performance, and they cannot detect a change in $P(X)$ that has not yet affected the error rate.

2.4.2 Unsupervised Drift Detection Methods

Unsupervised drift detection methods do not require ground-truth labels and instead monitor changes in data distribution, model outputs, or internal representations [35, 38]. These methods enable earlier detection of distributional shifts, before performance degradation becomes observable, which makes them valuable in production environments with label delays [13].

2.4.2.1 Statistical Distribution-Based Methods

Statistical methods compare a reference window with a current window through hypothesis tests or distance measures [8, 40, 10]. They differ in what they compare. ADWIN compares the means of sub-windows of an adaptive window and shrinks the window when they differ, with guarantees on its false positive and false negative rates [10]. KSWIN applies the Kolmogorov–Smirnov test to one feature at a time over sliding windows [40], and chi-squared tests play the same role for categorical or discretised features [1]. Divergence measures such as the Kullback–Leibler divergence, the Jensen–Shannon divergence and the Hellinger distance quantify how far apart two estimated distributions are [41, 42], while the Maximum Mean Discrepancy (MMD) compares whole multivariate distributions through kernel embeddings [9].

As a group, these methods are label-free, theoretically grounded and easy to interpret [8]. Most of them, however, test one feature at a time. With d features this requires d tests, so unless the significance level is corrected, the probability of at least one false alarm grows with d, and changes in the joint distribution that leave every marginal unchanged are missed [1, 15]. Multivariate tests such as MMD avoid the per-feature problem, but their power depends on the choice of kernel [9].

Table 2.3 compares two widely used univariate methods, the Population Stability Index (PSI) and the KS test, with the multivariate discriminative approach used in this thesis.

Because PSI and the KS test are univariate, monitoring d features requires d separate tests. The discriminative approach instead tests the joint distribution of all d features with a single classifier.

2.4.2.2 Model-Based Discriminative Methods

Discriminative methods train an auxiliary classifier to tell reference samples from current samples [16, 43, 13]. If the classifier separates the two sets better than chance, the distributions differ. The methods in this group differ in what they read from the classifier. Domain classifiers, also called adversarial validation in industry practice, use the accuracy or AUC of a logistic regression, random forest, or gradient boosting model trained on the two windows [43, 44]. D3 applies this idea to data streams with a logistic regression classifier and a fixed AUC threshold [17], and it is one of the three

Table 2.3: Comparison of drift detection approaches.

Method	Approach	Strengths	Limitations
PSI (Population Stability Index)	Compares binned distributions of single features; PSI > 0.25 indicates significant drift	Simple, interpretable, industry standard	Univariate only; requires binning; misses feature correlations
KS Test (Kolmogorov-Smirnov)	Non-parametric test comparing cumulative distributions per feature	No distributional assumptions; exact p-values	Univariate only; multiple testing problem with many features
Discriminative Classification	Trains classifier to distinguish old vs. new data; uses AUC as drift signal	Multivariate; captures feature interactions; single unified test	Requires classifier training; no built-in feature attribution

detectors recommended by a recent benchmark [18]. Margin density methods such as MD3 instead track the proportion of samples that fall close to the decision boundary of a classifier [13].

The main strength of the group is that one classifier tests all features jointly and can capture non-linear changes that marginal tests miss [16]. No labels are needed, only the window that each sample came from [43]. The costs are that a classifier must be trained at every monitoring step, that the results depend on the classifier and its hyperparameters, and that a raw AUC or margin value has no statistical calibration unless a test, such as a permutation test, is added [13, 16].

2.4.2.3 Representation-Based Methods

Representation-based methods monitor learned representations rather than raw features [8, 30]. They compute distances such as the Wasserstein distance or MMD between reference and current embeddings taken from intermediate layers of a neural network [8], or they track the stability of learned representations using ideas from domain adaptation and transfer learning [45]. These methods suit deep learning systems in which raw feature distributions do not reflect semantically meaningful changes [30], but they require a representation model and are less relevant for the tabular streams studied in this thesis.

2.4.2.4 Prediction-Based and Output-Based Methods

Prediction-based methods monitor the outputs of the deployed model without checking whether they are correct [13, 17]. They track the distribution of predicted classes or scores [17], or the entropy and confidence of the predictions, under the assumption that rising uncertainty indicates out-of-distribution inputs [14]. Their weakness is calibration: modern models, deep networks in particular, are often poorly calibrated, and under distribution shift their confidence may not change in step with their errors [14, 46]. The prediction entropy signal used in EADD (Chapter 3) differs from these methods because it is computed from the discriminator that separates the two windows, not from the deployed model.

2.4.2.5 Unsupervised Detectors Evaluated in Recent Benchmarks

Lukats et al. [18] reviewed ten fully unsupervised drift detectors and evaluated seven of them on eleven real-world data streams; the other three were too slow or depended too much on chance. They also found that the size of the observed samples was one of the most influential hyperparameters. The detectors they studied can be grouped by the mechanism they use.

The discriminative group is represented by D3 [17], which achieved the best mean time ratio in the benchmark but, like the other detectors, reports only that drift occurred [18].

Clustering-based detectors summarise each window with clusters and test whether the clusters change. CSDDM reduces dimensionality with PCA, clusters the data with K-Means, and applies statistical tests to the clusters [47], while UCDD assigns pseudo-labels from cluster membership and monitors shifts of the cluster boundary [48]. CSDDM was among the detectors that performed well on the benchmark's lift-per-drift metric, which measures how much classifier accuracy improves per detected drift [18].

Density-based detectors model the reference distribution and flag new data that fit the model poorly. SPLL fits a semi-parametric density model and monitors the log-likelihood of new observations [49], NN-DVI tracks changes in nearest-neighbour density [50], OCDD fits a one-class SVM to the reference data and counts the samples that fall outside its boundary [51], and BNDM compares windows with a Bayesian non-parametric Pólya tree test. These detectors respond well to sudden changes in density, but

they are sensitive to the size of the reference sample: BNDM signalled drift periodically when it observed few samples, and many OCDD configurations showed the same periodic behaviour [18].

A last group reduces the stream to a simpler signal. IBDD converts windows of numerical data into images and compares the images [52], and UDetect applies Shewhart control charts to the standard deviation of each window. IBDD achieved the best classifier accuracy in the benchmark because it can signal drift again immediately after a reset, but it was among the worst detectors on mean time ratio, and 45% of the UDetect configurations detected no drift at all [18].

Across these groups, the benchmarked detectors report whether drift occurred but not where it occurred [18]. D3 is the only discriminative detector in the benchmark, and it relies on a fixed AUC threshold rather than a calibrated test.

2.4.3 Hybrid and Ensemble Methods

Hybrid approaches combine several sources of information, such as model predictions, embeddings, operational signals and metadata, into a single context-weighted drift score, while ensemble approaches combine several base detectors through voting, weighting, or meta-learning to reduce both false alarms and missed detections [2, 53]. These approaches can be more robust than any single detector, but they inherit the label or context requirements of their components, and misspecified context can cause missed detections or spurious alarms [53].

2.5 Limitations of Existing Methods

Each group of methods has characteristic limitations. Supervised methods need timely labels and detect drift only after performance has degraded [1, 13]. Statistical tests are sensitive to noise, mostly test marginal distributions, and raise more false alarms as the number of tested features grows [8, 1, 15]. Prediction-based and uncertainty-based methods depend on model calibration, which is often poor under distribution shift [14, 46], and context-aware methods depend on context variables that may be incomplete or may drift themselves [53].

Discriminative tests avoid several of these problems. They test the joint feature distribution directly, need neither labels nor calibrated model outputs, and make no assumption about which features matter [16, 43]. In streaming drift detection, however, they have mostly been used with fixed thresholds, as in D3 [17].

2.6 Drift Mitigation and Adaptation Strategies

Detecting drift is only the first step; production systems must also respond to it. The literature describes five principal mitigation strategies, each with distinct trade-offs [1, 2, 53]:

1. **Periodic Retraining:** The model is retrained on the latest data at fixed intervals (e.g., weekly or monthly) or triggered by drift alerts. This is the most common industrial approach because of its operational simplicity, but fixed schedules may retrain unnecessarily or react too slowly [2].
2. **Weighted Retraining:** Old and new data are combined for retraining, but recent examples receive higher weights. This preserves long-term knowledge while prioritising current patterns, and is particularly effective for gradual drift [53].
3. **Ensemble Methods:** A library of models (for example, one per season or data regime) is maintained, and predictions are combined via voting, stacking, or dynamic weighting. When drift is detected, poorly performing members are discarded and new ones trained on the current distribution [53].
4. **Online / Incremental Learning:** The model is updated continuously as each new data point (or mini-batch) arrives, making it naturally adaptive to gradual and incremental drift. This is common in streaming applications such as fraud detection and recommendation systems [2, 54].
5. **Human-in-the-Loop:** Uncertain or drifted samples are routed to human experts for re-labelling, which feeds into the next training iteration.

This strategy is essential in domains where errors carry high cost (e.g., healthcare, autonomous driving) and labelling is expensive [1].

2.7 Related Work: Discriminative and Attribution Approaches

2.7.1 Discriminative Distribution Testing

Discriminative approaches to distribution comparison reframe the problem as a binary classification task: a classifier is trained to predict whether each instance originates from a reference distribution or a target distribution. High discriminative performance (AUC $\gg 0.5$) indicates the distributions are statistically separable; near-random performance suggests they are indistinguishable [43, 44].

Pan et al. [43] used this approach at Uber for the MaLTA user targeting system, training a classifier to detect mismatch between training and deployment data and retraining when the two were strongly separable. Qian et al. [44] applied discriminative testing to manage dataset shift in credit scoring. D3 [17] turned the idea into a streaming detector that trains logistic regression classifiers on sliding windows and signals drift when the AUC exceeds a fixed threshold of 0.7. D3 achieved the best mean time ratio in the Lukats et al. [18] benchmark. However, D3 applies no formal significance test; its fixed threshold is not calibrated, which can make it vulnerable to false alarms on autocorrelated data.

The *classifier two-sample test* (C2ST), formalised by Lopez-Paz and Oquab [16], provided theoretical foundations for the discriminative approach: significance is calibrated via permutation testing, allowing principled Type I error control. The approach is label-independent, model-agnostic, and makes no assumptions about which features are important. Pandeva et al. [31] extended C2ST with anytime-valid e-values for sequential monitoring, and Wan et al. [55] proposed Maximum Concept Discrepancy, which uses contrastive learning as an alternative to classifier-based testing for online drift detection. C2ST and E-C2ST were designed for distribution testing rather than for streaming drift detection, and neither provides feature-level attribution of the detected shift.

D3 and other C2ST-based streaming detectors usually discard the trained classifier after computing the AUC. Practitioners therefore learn whether drift occurred

but receive no guidance on which features caused it, even though the classifier has learned which features separate the two windows.

2.7.2 Drift Localisation

Drift localisation asks where a drift occurs [56]. The question can be posed for regions of the data space, that is, which samples are affected, or for features, that is, which input dimensions are affected. Hinder et al. [56] formalise localisation as finding the smallest region of the data space whose removal leaves no drift, and they survey the methods that address it. Most of these methods are built on local drift detection. Binning methods such as kdq-trees partition the data space and compare the samples in each cell [41]. Neighbourhood methods compare the local density around each sample, as in the local drift degree of Liu et al. [57]. Model-based methods train a probabilistic classifier to separate time periods and read the affected regions from its predictions [56].

Feature-level localisation has developed alongside this work. Kulinski et al. [58] framed the question of which features have shifted as a set of conditional distribution tests, one per feature, and proposed parametric and non-parametric versions based on the score function of a density model. Hinder et al. [25] gave formal definitions of feature-wise drift that allow detector-agnostic selection of drifting features. TRIPODD [23] tests pre-specified feature interactions with power guarantees, at a cost that grows quadratically with the number of features.

Localisation methods therefore already exist for samples, regions and features. They differ in what they require: a density model [58], pre-specified interactions [23], or batch access to the data [25]. A further option, discussed next, is to explain the classifier that a discriminative test has already trained.

2.7.3 Feature Attribution for Drift Detection

Feature attribution methods explain the output of a model in terms of its input features. SHAP assigns each feature its Shapley value [59] in a cooperative game whose players are the features [20], and TreeSHAP computes these values exactly and in polynomial time for tree ensembles [60]. Attribution has been connected to drift in two main ways.

The first way explains a domain classifier. Maggio [21] trained a classifier to separate old data from new data and ranked the features by the mean absolute SHAP value of the classifier's output. In that study, the SHAP ranking identified the corrupted features more reliably than the classifier's impurity-based feature importance. This is the same classifier that a discriminative drift detector already trains, so the ranking adds feature-level localisation at little extra cost. Its limitations come from SHAP itself: the attributions describe the classifier rather than the data-generating process, and they are correlational rather than causal [61].

The second way monitors the attributions of the deployed model. Lundberg et al. [60] monitored the SHAP values of a deployed model over time to find problems in its data pipeline. Mougan et al. [22] defined explanation shift as a change in the distribution of a model's explanations between training data and new data, and showed that it can reveal shifts that change model behaviour, including changes in feature interactions that per-feature distribution tests miss. Commercial monitoring services follow the same idea: Google Vertex AI and Amazon SageMaker Clarify compare the feature attributions of production predictions with a baseline computed during training [32, 33].

A related line of work attributes changes in model performance, rather than changes in the data distribution, to features or to parts of the data-generating process. Zhang et al. [62] treated the distributions that make up the data-generating process as players in a cooperative game and attributed a model's performance change to them with Shapley values. HDPD decomposes a performance gap into covariate and conditional components with per-feature attributions [24], DBShap separates virtual and real drift with distributional Shapley values [63], and XPE combines optimal transport with Shapley values to explain how feature shifts affect performance [64]. These methods require labels. A recent systematic review found that most work on explaining drift adapts static explanation methods to streaming data without addressing scalability or interactions between features [65].

SHAP-based ranking of the features that separate two windows has therefore been used before [21]. This thesis does not claim it as a contribution; EADD uses it as one component of the framework.

2.7.4 Other Recent Directions

Other recent work has addressed label efficiency, explanation quality and robustness. Semi-supervised and student–teacher methods reduce or remove the need for labels [66, 67], per-label embedding monitoring extends drift detection to unstructured data [68], and autoregressive error monitoring adds confidence intervals to supervised detection [69]. For explanations, SGShift characterises concept shift with generalised additive models and controls the false discovery rate with knockoffs [70], and Komnick et al. [61] argue that drift explanations need causal rather than correlational attribution to guide remediation. Hinder et al. [34] showed that adversarially constructed data streams can evade common drift detectors, including discriminative ones.

2.8 Gap in the Literature

The review shows that the components of a discriminative drift detector that is both calibrated and interpretable already exist, but they have not been combined and evaluated together in a streaming setting. A classifier two-sample test can be calibrated with a permutation test [16], but a fixed-budget permutation test retrains the classifier many times at every alarm, and D3, which a recent benchmark recommends, uses an uncalibrated fixed threshold instead [17, 18]. Sequential stopping rules that preserve the Type I error of Monte Carlo tests [19] have not, to our knowledge, been applied to discriminative drift detection, and e-value tests [31] were designed for distribution testing rather than for streaming detection.

A second gap concerns how discriminative detectors are compared. A new discriminative detector usually differs from D3 in its classifier, its window sizes, and the way it maintains its reference data. A comparison that changes all of these at once cannot show which of them causes the differences in detection delay, missed drifts and false alarms. Finally, feature-level localisation methods [58, 25, 23] and SHAP explanations of domain classifiers [21, 22] answer the question of which features drifted, but they are usually run separately from, and after, detection.

This thesis addresses these gaps with EADD, an integrated framework that combines a LightGBM classifier two-sample test, a reservoir-sampled reference window,

prediction entropy monitoring and an adaptive sequential permutation test, and that reports a TreeSHAP feature ranking for every confirmed drift. The evaluation includes an ablation that changes one design choice at a time.

CHAPTER 3
RESEARCH METHODOLOGY

This chapter first states the research questions and hypotheses, then gives an overview of the methodology and describes each of its steps: the datasets, the EADD framework, the baseline detectors, the implementation and its validation, the evaluation metrics, and the experimental design with its statistical analysis.

3.1 Research Questions

Based on the gaps identified in Chapter 2, this thesis investigates two research questions:

- **RQ1 ~~(Detection Accuracy)~~:** Does EADD achieve comparable or better drift detection performance (detection delay and missed detections) than state-of-the-art unsupervised detectors on synthetic and real-world data streams?
- **RQ2 (~~Robustness~~):** Does EADD's permutation test reduce false alarm rates on stable data compared with threshold-based approaches such as D3?

3.2 Hypotheses

Two formal hypotheses were tested:

- **H1 (Detection Coverage):** EADD detects a broader range of temporal drift patterns than D3. H1a compares the drift streams that each detector detects (Experiments 1 and 4), and H1b compares detection delay on the streams that both EADD and D3 detect.

- **H2 (False Alarm Reduction):** EADD produces significantly fewer false alarms than D3 on stable data. Formally, H_0: $\text{FA}_{\text{EADD}} \geq \text{FA}_{\text{D3}}$ vs H_1: $\text{FA}_{\text{EADD}} < \text{FA}_{\text{D3}}$, where FA is the number of false alarms per stream. The hypothesis is tested with a one-sided Mann–Whitney U test ($\alpha = 0.05$) at several D3 thresholds ($\tau \in \{0.6, 0.7, 0.8\}$) in Experiment 3.

3.3 Overview of the Methodology

Figure 3.1 summarises the methodology. First, synthetic, semi-synthetic and real-world data streams are collected (Section 3.4). Second, each stream is processed by EADD (Section 3.5) and by the baseline detectors (Section 3.6). The baselines include seven unsupervised detectors from the Lukats et al. [18] benchmark and ablated versions of D3 and EADD that change one design choice at a time. Third, the detections are compared with the known drift points, or counted on stable streams that contain no drift, using the metrics in Section 3.8. Section 3.9 describes the four experiments and the statistical tests.




Figure 3.1: Overview of the research methodology: data collection, drift detection with EADD and the baseline detectors, and evaluation.

3.4 Datasets

The population of interest is numerical data streams that are monitored for feature drift without labels. Following the benchmark of Lukats et al. [18], the experiments use a sample of synthetic streams with known drift points, semi-synthetic streams, and real-world streams.

Synthetic Drift Streams: Each synthetic drift stream has $n = 5{,}000$ samples and $d = 5$ independent features. Before the drift, each feature follows $\mathcal{N}(0, 1)$; after the drift, its mean is shifted to 2. The four streams differ in how the shift happens:

- **Abrupt:** the mean shifts at $t = 2{,}500$.
- **Gradual:** between $t = 2{,}000$ and $t = 3{,}000$, each sample is drawn from the new distribution with a probability that rises linearly from 0 to 1.
- **Incremental:** the mean rises linearly from 0 to 2 between $t = 1{,}500$ and $t = 3{,}500$.
- **Recurring:** the stream alternates between the two distributions every 1,250 samples, giving drift points at $t = 1{,}250$, $2{,}500$ and $3{,}750$.

Synthetic Stable Streams: Four stable streams with $n = 10{,}000$ samples, $d = 5$ features and no drift are used to measure false alarms:

- **Gaussian i.i.d.:** independent samples from $\mathcal{N}(0, 1)$.
- **Autocorrelated AR(1):** $x_t = 0.7\, x_{t-1} + \epsilon_t$ with $\epsilon_t \sim \mathcal{N}(0, 1)$.
- **Heteroscedastic:** zero mean with a time-varying standard deviation

$$\sigma_t = 1 + 0.15 \sin(2\pi t / 2{,}000).$$

- **Correlated features:** multivariate normal with correlation $0.5^{|i-j|}$ between features i and j.

Semi-Synthetic Streams: SineClusters and WaveformDrift2 from the Lukats et al. [18] framework have annotated drift points and are used in the supplementary multi-detector run of Experiment 2.

Real-World Benchmark Datasets: Thirteen data streams were used for the primary real-world evaluation, drawn from the Lukats et al. [18] benchmark suite and spanning diverse domains and drift characteristics. Four streams have annotated ground-truth drift points; nine are unannotated.

Annotated (known drift points):

- **INSECTS Abrupt Balanced** [28]: 52,848 samples $\times$ 33 features; abrupt sensor drift in insect flight patterns (5 annotated drift points).
- **INSECTS Gradual Balanced** [28]: 24,150 samples $\times$ 33 features; slow gradual sensor drift (1 annotated drift point).
- **INSECTS Incremental-Abrupt Balanced** [28]: 79,986 samples $\times$ 33 features; incremental drift followed by abrupt reset (2 annotated drift points).
- **INSECTS Incremental-Reoccurring Balanced** [28]: 79,986 samples $\times$ 33 features; incremental drift with reoccurring concept (2 annotated drift points).

Unannotated (no ground-truth drift labels):

- **Electricity (Elec2)** [71]: 45,312 samples $\times$ 8 features; electricity pricing data with natural market fluctuations.
- **INSECTS Incremental Balanced** [28]: 57,018 samples $\times$ 33 features.
- **Luxembourg** [18]: 1,900 samples $\times$ 31 features; financial data stream.
- **NOAA Weather** [18]: 18,159 samples $\times$ 8 features; weather measurements with temporal drift.
- **Outdoor Objects** [18]: 4,000 samples $\times$ 21 features; object recognition features with environmental variation.
- **Ozone** [18]: 2,534 samples $\times$ 72 features; atmospheric ozone level monitoring.
- **PokerHand** [18]: 829,201 samples $\times$ 10 features, of which the first 100,000 were used; card hand classification stream.

- **Powersupply** [18]: 29,928 samples $\times$ 2 features; power consumption data with usage pattern changes.
- **RialtoBridge Timelapse** [18]: 82,250 samples $\times$ 27 features; visual feature stream from a bridge camera.

All datasets were processed in streaming fashion, with features used for drift detection. For datasets with known drift points (e.g., INSECTS variants with drift indices at specific sample positions), ground truth was used for computing detection metrics. The INSECTS datasets were particularly valuable as they provide exact drift timestamps, enabling precise measurement of detection delay and false alarm rates.

3.5 The EADD Framework

EADD treats feature drift ($P(X)$ shift) detection as binary classification: if a classifier can reliably distinguish reference data from current data based solely on features, the distributions have diverged [16, 17]. D3 [17] uses this principle with a fixed AUC threshold, and Lopez-Paz and Oquab [16] showed how to calibrate the test with permutations. EADD combines these ideas with a long-memory reference window, a sequential version of the permutation test, and a feature ranking for each confirmed drift.

3.5.1 Problem Formulation

Let $\{x_t\}_{t=1}^{T}$, with $x_t \in \mathbb{R}^d$, denote a stream of feature vectors. At each monitoring point t, a detector compares two windows:

- a reference window W_{ref} of N_{ref} samples, assumed to represent the baseline feature distribution $P_{ref}(X)$, and
- a current window W_{cur} containing the N_{cur} most recent samples, drawn from the current distribution $P_{cur}(X)$.

Feature drift at time t means $P_{cur}(X) \neq P_{ref}(X)$. The detector therefore tests

$$H_0 : P_{ref}(X) = P_{cur}(X) \quad \text{versus} \quad H_1 : P_{ref}(X) \neq P_{cur}(X) \tag{3.1}$$

and outputs a decision $d_t \in \{0, 1\}$, where $d_t = 1$ signals drift. In EADD, the test statistic is the cross-validated AUC of a classifier f_θ trained to separate W_{ref} from W_{cur}. The symbol τ denotes the AUC screening threshold, α the significance level, and $B_{\min}$ and $B_{\max}$ the minimum and maximum numbers of permutations used by the permutation test.

Figure 3.2 shows the steps of EADD, and Table 3.1 lists the methods each step builds on.




Figure 3.2: Architecture of EADD: adaptive reference windowing, discriminative classification, ASPT significance testing, and TreeSHAP feature ranking for each confirmed drift.

Table 3.1: EADD components and the methods they build on.

Component	EADD Step	Based On
Reference memory	Step 1: reservoir-sampled W_{ref}	Reservoir sampling [27]
Drift statistic	Step 2: cross-validated AUC of a LightGBM classifier	C2ST [16]; D3 [17]; LightGBM [26]
Uncertainty signal	Step 2b: prediction entropy H_{pred}	Shannon entropy [72]
Statistical confirmation	Step 3: adaptive sequential permutation test	Sequential Monte Carlo tests [19]
Feature ranking	Step 4: TreeSHAP ranking	SHAP [20, 60]; Maggio [21]

3.5.2 Step 1: Adaptive Reference Windowing

To detect feature drift, the current data must be compared against a stable baseline. EADD maintains two windows consistent with established methodologies [10, 35]:

Reference Window (W_{ref}): A buffer containing N_{ref} historical samples representing the stable feature distribution $P_{ref}(X)$. Unlike sliding windows, which forget older data quickly, EADD uses **reservoir sampling** [27] so that the reference represents all samples seen since the last confirmed drift, not just the most recent batches.

Current Window (W_{cur}): A buffer containing the N_{cur} most recent observations representing the current feature distribution $P_{cur}(X)$. As new data arrives, older samples are discarded to maintain responsiveness to recent changes.

Update Mechanism: At each monitoring step:

- New samples enter W_{cur}
- Oldest samples exit W_{cur}
- Reservoir sampling maintains representative W_{ref}
- Upon confirmed drift, W_{ref} is reset to the current window

According to Lu et al. [1], window sizes represent a bias-variance tradeoff: larger windows provide more stable estimates but slower response; smaller windows enable faster detection but higher variance.

3.5.3 Step 2: Discriminative Classification

This step implements the **classifier two-sample test** (C2ST) [16], also referred to as "discriminative classification" or "adversarial validation" in industry practice [43], which forms the foundation of both D3 [17] and EADD. The question it asks is whether a model can tell the difference between old and new data.

Construct Binary Classification Dataset:

- Label all samples from W_{ref} as class 0 ("old" / reference)
- Label all samples from W_{cur} as class 1 ("new" / current)
- Combined dataset: $X = W_{ref} \cup W_{cur}$, $y = \{0\}^{N_{ref}} \cup \{1\}^{N_{cur}}$

Train Discriminative Classifier: A binary classifier f_θ is trained to predict the data source from the features alone. EADD uses **LightGBM** [26], a gradient boosting decision tree ensemble, as the default classifier. D3 [17] uses logistic regression, which can only separate the windows with a linear boundary; LightGBM can also capture non-linear differences and feature interactions. Experiment 4 measures how much this choice matters on its own.

Measure Discriminative Performance: Classifier performance is evaluated with stratified 5-fold cross-validation:

- **AUC-ROC:** the primary metric, the area under the ROC curve
- AUC $\approx$ 0.5: the classifier cannot distinguish W_{ref} from W_{cur} $\rightarrow$ **no feature drift**
- AUC $\gg$ 0.5: the classifier separates the windows $\rightarrow P_{ref}(X) \neq P_{cur}(X)$ $\rightarrow$ **feature drift suspected**

If the AUC exceeds the screening threshold τ, the alarm is passed to the significance test in Step 3. The term "adversarial" in EADD's name refers to this C2ST setting, in which a classifier is trained to distinguish two data sources, and not to adversarial attacks in the security or robustness sense.

3.5.4 Step 2b: Prediction Entropy Monitoring (H_{pred})

After training the discriminative classifier (Step 2), EADD computes the **prediction entropy** H_{pred} as an early-warning signal for distributional instability. This is the binary Shannon entropy [72] of the C2ST discriminator's output probabilities, averaged over all samples:

$$H_{\text{pred}} = \frac{-1}{n} \sum_{i=1}^{n} [\hat{p}_i \ln \hat{p}_i + (1 - \hat{p}_i) \ln(1 - \hat{p}_i)] \tag{3.2}$$

where $\hat{p}_i = f_\theta(x_i)$ is the discriminative classifier's predicted probability that sample i belongs to the current window (W_{cur}), and $n = |W_{ref}| + |W_{cur}|$ is the combined sample count.

Interpretation:

- $H_{\text{pred}} \approx \ln 2$: Maximum entropy; the classifier cannot distinguish windows $\rightarrow$ no distributional difference
- $H_{\text{pred}} \rightarrow 0$: Low entropy; the classifier clearly separates windows $\rightarrow$ strong drift signal
- Intermediate H_{pred}: Subtle distributional change that may not yet reach statistical significance

Monitoring Property: H_{pred} is computed at every monitoring step, including steps where the AUC has not yet reached τ, so it gives a continuous view of how confidently the discriminator separates the two windows. It was intended as an early-warning signal for gradual and incremental drift. In the logs of the real-world experiments, however, H_{pred} fell together with the AUC rather than ahead of it (Section 4.7), so this thesis does not claim an early-warning effect. A quantitative evaluation, including threshold selection and the precision and recall of pre-alarm warnings, is left to future work.

Relationship to AUC: H_{pred} and AUC are complementary signals. AUC measures overall discriminability, while H_{pred} measures the confidence distribution of individual predictions. A high AUC with low entropy indicates clear, systematic drift; a moderately elevated AUC with higher entropy may indicate localised or emerging drift affecting only a subset of samples.

3.5.5 Step 3: Adaptive Sequential Permutation Test (ASPT)

A raw AUC score (e.g., 0.65) is inconclusive, as it may reflect genuine distributional change or statistical noise. D3 [17] relies on a fixed threshold (AUC > 0.7) without a significance test. Lopez-Paz and Oquab [16] proposed the classifier two-sample test (C2ST) with significance testing, typically implemented as a fixed-budget permutation test [73] with a predetermined number B of permutations.

The Computational Problem: A fixed-budget permutation test (e.g., $B = 50$) wastes computation when the evidence is clear. If the actual AUC is 0.95, the first few permutations already establish significance and the remaining permutations add cost without information. Conversely, if the AUC is 0.52, early permutations quickly reveal non-significance.

Adaptive Sequential Permutation Testing: EADD uses an **adaptive sequential permutation test** based on the sequential Monte Carlo framework of Gandy [19]. Instead of committing to a fixed budget B, ASPT monitors evidence accumulation after each permutation and terminates early when the decision boundary is crossed:

1. **Initialise:** Set maximum budget $B_{\max}$, nominal significance level α, and minimum sequential budget $B_{\min}$.
2. **Sequential Execution:** For each permutation $i = 1, \ldots, B_{\max}$:
   - Shuffle labels, retrain the discriminative classifier, compute $\text{AUC}_{\text{perm}}^{(i)}$
   - Update running count: $c_i = \#\{j \leq i : \text{AUC}_{\text{perm}}^{(j)} \geq \text{AUC}_{\text{actual}}\}$
   - **Early reject H_0 (confirm drift):** If $c_i = 0$ and $i \geq B_{\min}$ and the conservative bound $1/(i+1) < \alpha$ holds, terminate and confirm drift with $p = 1/(i+1)$.
   - **Early accept H_0 (no drift):** If $c_i/i > 2\alpha$ and $i \geq B_{\min}$, the running exceedance rate far exceeds the nominal level; terminate and declare no drift with $p = (c_i + 1)/(i+1)$.
3. **Terminal decision:** If $B_{\max}$ is reached, compute the standard empirical p-value: $p = (c_{B_{\max}} + 1)/(B_{\max} + 1)$. Drift is confirmed if $p < \alpha$.

Statistical Validity Note: ASPT preserves the standard permutation p-value at termination, either by the full-budget estimate $p = (c_B + 1)/(B + 1)$ or by the

conservative early-reject upper bound $p = 1/(i+1)$ when no exceedances are observed. This keeps the stopping rule aligned with the permutation-test interpretation.

Computational Savings: ASPT logs the number of permutations executed per invocation. With $\alpha = 0.05$ and $B_{\min} = 10$, the earliest possible confirmation is at $i = 20$, where $1/21 \approx 0.048 < \alpha$, so a clear drift costs 20 permutations instead of $B_{\max} = 199$. Clear non-drift cases can stop after $B_{\min} = 10$ permutations, and only cases close to the decision boundary use the full budget.

Interaction with the AUC Threshold: ASPT runs only when the AUC exceeds the screening threshold τ. Under the null hypothesis, the AUC of a classifier trained on shuffled labels stays close to 0.5, and with $N_{ref} = 500$ and $N_{cur} = 200$ it rarely moves far from that value. An observed AUC above $\tau = 0.7$ is therefore far into the tail of the permutation distribution, and ASPT is expected to confirm almost every alarm that reaches it. ASPT affects the decision mainly when τ is set closer to 0.5, which Experiment 4 examines.

3.5.6 Step 4: Feature Ranking via TreeSHAP

Once ASPT confirms drift ($p < \alpha$), EADD reports which features drive the separation between the two windows. D3 [17] discards the trained classifier after computing the AUC, although the classifier has learned which features differentiate the reference data from the current data. Following Maggio [21], EADD explains the discriminative classifier with SHAP.

EADD applies **TreeSHAP** [20, 60] to a LightGBM classifier trained on $W_{ref} \cup W_{cur}$. TreeSHAP computes exact Shapley values [59] in polynomial time for tree-based models. The per-feature ranking is computed as follows:

1. Compute SHAP values using TreeSHAP
2. Calculate the mean absolute SHAP value per feature: $\text{Importance}_i = \frac{1}{n}\sum_{j=1}^{n} |\text{SHAP}_{ij}|$
3. Normalise to a contribution vector: $s_i = \frac{\text{Importance}_i}{\sum_k \text{Importance}_k}$, so that $\mathbf{s} = (s_1, \ldots, s_d)$ sums to 1
4. Rank the features by s_i

EADD also computes TreeSHAP interaction values [60] on a sample of 100 points and reports their mean absolute values for each feature pair. The ranking and the interaction values are provided as diagnostic output; their accuracy is not evaluated in this thesis.

3.5.7 Model Adaptation Strategies

According to Gama et al. [2], upon drift detection, the primary prediction model can be adapted:

Strategy 1: Drift-Triggered Retraining

- Model is trained at initialisation
- Retraining occurs only when drift alarm is raised
- Reference window resets to current data after retraining
- According to Pan et al. [43], advantage: Conserves resources; exploits early detection for timely updates

Strategy 2: Periodic Retraining (Baseline)

- Model is retrained at fixed intervals regardless of drift signals
- Advantage: Simple; does not depend on detector reliability
- According to Gama et al. [2], disadvantage: May retrain unnecessarily or too late

Strategy 3: Continuous Update with Drift Weighting

- Online learning with sample weighting based on drift score
- According to Krawczyk et al. [53], recent samples receive higher weights when drift is detected

3.6 Baseline Drift Detectors

EADD was benchmarked against seven state-of-the-art unsupervised drift detectors evaluated in the Lukats et al. [18] survey, all of which operate without ground-truth labels:

- **D3 (Discriminative Drift Detector)** [17]: Trains a logistic regression classifier to distinguish old from new data windows, using AUC as the drift signal. One of the three detectors recommended by the Lukats et al. [18] benchmark.
- **BNDM (Bayesian Non-parametric Drift Monitor):** Uses a Pólya tree test to detect distributional changes without parametric assumptions.
- **CSDDM (Clustered Statistical Drift Detection Method)** [47]: Applies PCA dimensionality reduction followed by K-Means clustering, then uses statistical tests to detect cluster shifts.
- **IBDD (Image-Based Drift Detector)** [52]: Converts numerical data streams into images and applies image comparison techniques to detect distributional changes.
- **OCDD (One-Class Drift Detector)** [51]: Uses one-class SVMs to define "normal" data boundaries and flags drift when incoming data falls outside these boundaries.
- **SPLL (Semi-Parametric Log-Likelihood)** [49]: Fits probability density models to reference data and detects drift when new observations have anomalously low likelihood.
- **UDetect (Univariate Detection):** Monitors standard deviation changes using Shewhart control charts.

Existing benchmark results for these seven detectors from the Lukats et al. [18] framework were used for direct comparison with EADD's detection performance across the same datasets.

Ablation Variants: EADD differs from D3 in its classifier, its window sizes, its reference memory, and its permutation test. To measure the effect of each difference, Experiment 4 adds the following variants, each of which changes one design choice:

- **D3-LightGBM:** D3 with its logistic regression replaced by LightGBM with the same hyperparameters as EADD. Windows, 2-fold cross-validation and the fixed AUC threshold are unchanged.

- **D3-LightGBM (matched windows):** D3-LightGBM with EADD's window sizes ($N_{ref} = 500$, $N_{cur} = 200$).
- **EADD-NoASPT:** EADD without the permutation test; every alarm with AUC $> \tau$ is accepted.
- **EADD-NoASPT (fixed reference):** EADD-NoASPT in which W_{ref} keeps the first N_{ref} samples after the last confirmed drift instead of being updated by reservoir sampling.
- **Lower thresholds:** EADD and EADD-NoASPT with $\tau \in \{0.5, 0.6\}$ in addition to the default $\tau = 0.7$, so that ASPT, rather than the threshold, decides most alarms.

3.7 Implementation and Validation

All detectors were run in Python. The seven baseline detectors and the dataset loaders come from the open-source implementation of the Lukats et al. [18] benchmark, whose authors only included algorithms that could be implemented faithfully from their original descriptions; their unit tests were kept. EADD (`detectors/eadd.py`) and D3-LightGBM (`detectors/d3_lightgbm.py`) were added to this code base and use LightGBM [26] and scikit-learn. Unit tests check that ASPT confirms a clear shift after exactly 20 permutations with $p = 1/21$, that it stops early without a shift, that EADD raises no alarm on a stable stream and detects an abrupt shift after its onset, and that D3-LightGBM detects a simple shift once. All experiments use fixed random seeds, and the code, scripts and result files are available in the project repository[1].

3.8 Evaluation Metrics

Following Lu et al. [1], Lukats et al. [18], and Souza et al. [28], the following metrics were used to evaluate drift detection performance:

[1] https://github.com/NusratBegum/unsupervised-concept-drift-detection

- **Mean Time to Detection (MTD):** Average number of samples between a true drift point and the first detection within a tolerance window after it. Lower is better.
- **Missed Detection Rate (MDR):** Proportion of true drifts that were not detected within the tolerance window. Lower is better.
- **False Alarms (FA):** Number of detections that are not matched to a true drift point. On stable streams, every detection is a false alarm. Lower is better.
- **Precision and Recall:** On annotated real-world streams, the proportion of detections that match a known drift point and the proportion of known drift points that are detected. A detection matches a drift point if it occurs within 500 samples after it.
- **Detection Count:** On unannotated real-world streams, the number of detections, used as an indicator of selectivity.
- **Runtime:** Wall-clock time to process a stream.

3.9 Experimental Design

Rerun ?

Four experiments were designed to answer the research questions:

Experiment 1: Multi-Detector Sensitivity to Temporal Drift Patterns

Compared all eight detectors (EADD, D3, BNDM, CSDDM, IBDD, OCDD, SPLL, UDetect) on the four synthetic drift streams ($n = 5{,}000$), using the default configurations from the Lukats et al. [18] framework. This experiment addresses RQ1 and H1.

Experiment 2: Real-World Benchmark Comparison

Benchmarked EADD against D3 across 13 real-world benchmark data streams (4 annotated + 9 unannotated) with three seeds, measuring precision, recall, MTD and detection counts. A supplementary multi-detector comparison (EADD, D3, BNDM, CSDDM, IBDD, OCDD, SPLL, UDetect) was also conducted on the first 20,000 samples

of an 11-stream subset to place EADD within the full Lukats et al. [18] benchmark field. This experiment addresses RQ1.

Experiment 3: Robustness to Stable Data (False Alarm Evaluation)

Counted false alarms on the four stable synthetic streams with zero actual drift (Gaussian i.i.d., autocorrelated, heteroscedastic, correlated features) over five runs, and compared EADD with D3 at AUC thresholds $\tau \in \{0.6, 0.7, 0.8\}$. This experiment addresses RQ2 and H2.

Experiment 4: Component Ablation with a LightGBM D3

Ran D3, the ablation variants of Section 3.6, and EADD on the synthetic drift streams of Experiment 1 (five seeds), on the stable streams of Experiment 3 (five runs), and on the 13 real-world streams of Experiment 2 (three seeds). Changing one design choice at a time shows whether EADD's results come from the classifier, the window sizes, the reference memory, the AUC threshold, or the permutation test. This experiment addresses RQ1 and RQ2.

3.9.1 Statistical Analysis

Results over several seeds or runs are summarised by their mean, and by their range where it matters for interpretation. H1a is tested with an exact one-sided sign test on the 20 synthetic drift streams of Experiment 4 (four drift types and five seeds): each stream counts for EADD if only EADD detects its drift and for D3 if only D3 does. H1b is tested with a two-sided Wilcoxon signed-rank test on the detection delays of the streams that both detectors detect. H2 is tested with a one-sided Mann–Whitney U test on the mean number of false alarms per stable stream type. Because only four stream types are compared, the exact p-value of this test is reported together with the normal approximation. All tests use $\alpha = 0.05$.

3.10 Practical Considerations

Class Imbalance: When $|W_{ref}| \neq |W_{cur}|$, use:

- Stratified cross-validation

- Class-weighted classifiers
- According to Lopez-Paz and Oquab [16], AUC-ROC rather than accuracy

Computational Efficiency:

- Use efficient classifiers (logistic regression, small random forests)
- Consider approximate methods for large windows
- According to Pan et al. [43], implement incremental training where possible

Temporal Leakage Prevention:

- Use purged cross-validation to avoid temporal overlap between folds
- According to Souza et al. [28], ensure strict temporal ordering in train/test splits

Threshold Calibration:

- Use validation data with known drift to tune τ
- According to Pan et al. [43], consider adaptive thresholds based on baseline variance

CHAPTER 4
RESULTS

This chapter presents the results of the four experiments described in Section 3.9: sensitivity to temporal drift patterns, the real-world benchmark, false alarms on stable data, and the component ablation. The research questions and hypotheses are stated in Sections 3.1 and 3.2.

4.1 Experimental Setup

Environment: Experiments 1 and 3 were run in Python 3.10. Experiments 2 and 4 were run with Python 3.13, LightGBM 4.6 and scikit-learn 1.8 on the same code base (Section 3.7).

EADD Configuration:

- **Reference Window (N_{ref}):** 500 samples
- **Current Window (N_{cur}):** 200 samples
- **AUC Threshold (τ):** 0.7, as in D3 [17]
- **ASPT:** $B_{\max} = 199$ permutations, $B_{\min} = 10$, $\alpha = 0.05$ (adaptive early stopping)
- **LightGBM:** 50 estimators, learning rate 0.1, max depth $= -1$ (unlimited), 31 leaves
- **Cross-Validation:** Stratified 5-fold within each detection cycle
- **Monitoring Frequency:** Every 50 samples

D3 Baseline Configuration:

- Logistic regression classifier with 2-fold cross-validation
- AUC threshold of 0.7 (also 0.6 and 0.8 in Experiment 3); no permutation test

- Window sizes: $N_{ref} = 300$, $N_{cur} = 120$ in Experiment 1; $N_{ref} = 500$, $N_{cur} = 200$ (the same as EADD) in Experiment 2; $N_{ref} = 100$, $N_{cur} = 50$ in Experiment 3

Baselines: EADD was compared against seven unsupervised detectors from the Lukats et al. [18] benchmark: D3 [17] (primary comparison), BNDM, CSDDM, IBDD, OCDD, SPLL, and UDetect. All baselines were run with their default configurations as provided in the benchmark framework. A per-detector timeout of 120 seconds was applied in the multi-detector real-world run to handle scalability limitations of certain detectors (e.g., BNDM on high-dimensional data).

4.2 Experiment 1: Multi-Detector Sensitivity to Temporal Drift Patterns

Objective: Compare EADD with seven state-of-the-art unsupervised drift detectors on the four major temporal drift patterns (abrupt, gradual, incremental and recurring), and evaluate the trade-offs between detection speed, missed drifts and false alarms.

Data: The four synthetic drift streams described in Section 3.4 were used ($n = 5{,}000$ samples, $d = 5$ features, seed 42). A detection was matched to a drift point if it occurred within 1,000 samples after it for abrupt and recurring drift, 2,000 samples for gradual drift, and 3,000 samples for incremental drift. All eight detectors were run under identical conditions with their default configurations from the Lukats et al. [18] benchmark framework.

Results:

Table 4.1 presents the detection performance across all eight detectors and four drift types.

Figure 4.1 presents heatmaps of detection performance across all detector and drift-type combinations, providing a visual summary of Table 4.1.

Figure 4.2 shows the feature distributions before and after drift injection, visualising the distributional shift that each detector must detect.




Figure 4.1: Heatmaps of detection performance on synthetic drift. Top: Mean Time to Detection (lower is better; white cells indicate complete miss). Bottom: False Alarm count (lower is better).




Figure 4.2: Bell curves showing feature distributions before (blue) and after (red) drift injection. Top: Abrupt drift with clear separation. Bottom: Gradual drift with overlapping distributions, the subtle shift that D3, SPLL, and UDetect all failed to detect.

Table 4.1: Experiment 1: Multi-Detector Comparison on Synthetic Drift Patterns (one stream per drift type). MTD = Mean Time to Detection (samples); MDR = Missed Detection Rate; FA = False Alarms. Bold marks the lowest MTD and the zero false alarm counts of EADD. "–" indicates that the detector missed all drift points.

	Abrupt			**Gradual**			**Incremental**			**Recurring**		
Detector	MTD	MDR	FA	MTD	MDR	FA	MTD	MDR	FA	MTD	MDR	FA
EADD	149	0.0	**0**	699	0.0	**0**	849	0.0	**0**	149	0.0	**0**
D3	98	0.0	0	–	1.0	–	–	1.0	–	157	0.0	0
BNDM	272	0.0	4	**26**	0.0	6	383	0.0	6	219	0.0	3
CSDDM	206	0.0	5	413	0.0	6	**9**	0.0	5	84	0.0	6
IBDD	**18**	0.0	41	153	0.0	48	156	0.0	47	**11**	0.0	49
OCDD	249	0.0	18	249	0.0	18	249	0.0	18	249	0.0	16
SPLL	66	0.0	0	–	1.0	–	–	1.0	–	72	0.0	0
UDetect	–	1.0	–	–	1.0	–	–	1.0	–	–	1.0	–

Figure 4.3 shows the multi-detector time-series comparison, plotting each detector's AUC or detection score over time alongside the true drift point.

Key Findings: The multi-detector comparison reveals three groups of detectors:

explain in paragraphs

1. **Complete Coverage without False Alarms:** EADD was the only detector that detected all four drift types (4/4 coverage, MTD: 149–849) with zero false alarms, including the gradual and incremental drift that D3 and SPLL missed entirely. Experiment 4 shows that this coverage comes from EADD's reservoir-sampled reference window rather than from its classifier or its permutation test. EADD's detection delays are longer than those of the fastest detectors (e.g., IBDD's 11–18 samples). EADD also reports a feature ranking with each detection, which the other detectors do not provide.

2. **High-Sensitivity Detectors with False Alarm Costs:** BNDM, CSDDM, IBDD, and OCDD also achieved 4/4 drift-type coverage, but with substantially higher false alarm rates (3–49 per drift type). IBDD was the fastest (MTD of 11–18 samples) but generated 41–49 false alarms per type, rendering it impractical for production monitoring. OCDD produced 16–18 false alarms per type with no speed advantage over EADD.




Figure 4.3: Time-series comparison of all eight detectors. Top: Abrupt drift; most detectors respond near the true drift point (dashed line). Bottom: Gradual drift; only EADD, BNDM, CSDDM, IBDD, and OCDD detect the shift, while D3, SPLL, and UDetect remain silent.

3. **Missed Drift Types:** D3 and SPLL both missed gradual and incremental drift entirely (MDR = 1.0), detecting only 2/4 types. UDetect failed on all four types.

4.3 Experiment 2: Real-World Benchmark

Objective: Evaluate EADD and the baseline detectors on real-world data streams from the Lukats et al. [18] benchmark, where drift patterns are unknown, complex, and multi-dimensional.

Procedure: Thirteen real-world datasets (Section 3.4) were processed in streaming fashion by EADD and D3, with D3 using the same window sizes as EADD, for up to 100,000 samples per stream and with three seeds (42, 142 and 242). For the four annotated datasets (InsectsAbrupt, InsectsGradual, InsectsIncrAbrupt, InsectsIncrRecur), precision, recall and MTD were computed against the known drift points, with a detection counted as correct if it occurred within 500 samples after a drift point. For the nine unannotated datasets, the total number of detections was recorded as a selectivity indicator.

A supplementary multi-detector run compared all eight detectors on the first 20,000 samples of an 11-stream subset of the same benchmark (excluding Luxembourg, Ozone, PokerHand and RialtoBridge). A per-detector timeout of 120 seconds was applied in this run, as BNDM's computation exceeded practical limits on the 33-feature INSECTS datasets.

Results:

Table 4.2 presents the results on datasets with known drift points.

Table 4.3 summarises detection activity on the nine unannotated datasets.

Multi-Detector Context (11-stream subset): Table 4.4 presents the supplementary multi-detector comparison, including the semi-synthetic benchmarks SineClusters and WaveformDrift2, which have annotated drift points in the Lukats et al. [18] framework. Because this run used only the first 20,000 samples of each stream and a single run, its values for EADD and D3 differ from those in Table 4.2.

Table 4.2: Experiment 2: EADD vs. D3 on the four annotated real-world datasets, averaged over three seeds. MTD = Mean Time to Detection (samples; lower is better). Bold indicates that EADD outperforms D3. "–" = all known drift points missed. Low precision on incremental datasets reflects the INSECTS annotation convention: only major transition boundaries are annotated; additional detections may correspond to unannotated continuous incremental changes rather than false alarms.

	Precision		**Recall**		**MTD**	
Dataset	EADD	D3	EADD	D3	EADD	D3
InsectsAbrupt	0.33	0.41	0.60	0.73	**124**	166
InsectsGradual	0.00	0.00	0.00	0.00	–	–
InsectsIncrAbrupt	0.14	0.29	1.00	1.00	**50**	126
InsectsIncrRecur	0.12	0.18	0.83	1.00	**84**	256

Table 4.3: Experiment 2: Mean number of detections over three seeds on the nine unannotated real-world datasets (EADD vs. D3). Ground-truth drift counts are unknown; counts indicate detection activity, not false alarm rates.

Dataset	**EADD**	**D3**
Electricity	90.0	86.0
INSECTS Incremental	1.0	0.7
Luxembourg	3.0	1.0
NOAAWeather	12.7	29.7
OutdoorObjects	6.0	1.0
Ozone	1.0	4.0
PokerHand	199.0	193.0
Powersupply	10.0	18.3
RialtoBridge	152.0	138.0
Total	**474.7**	**471.7**

what is the point?

Table 4.4: Supplementary multi-detector comparison on the first 20,000 samples of the annotated streams in the 11-stream subset. MTD = Mean Time to Detection (samples); bold marks the lowest MTD per stream. "–" = detector missed all annotated drifts or timed out. MTD ignores false alarms: IBDD, for example, raised 72 detections on InsectsAbrupt.

Detector	InsectsAbrupt	InsectsGradual	SineClusters	WaveformDrift2
EADD	148	–	299	99
D3	152.5	–	219	179
BNDM	–	–	499	60
CSDDM	44	143	**35**	359
IBDD	28	88	45	**8**
OCDD	254	–	249	249
SPLL	**25**	**39**	249	22
UDetect	–	–	36	21

Figure 4.4 presents heatmaps summarising detection performance across all detector and dataset combinations of the supplementary run.

Figure 4.5 shows time-series visualisations of detection behaviour on two semi-synthetic datasets.

Figure 4.6 shows the feature distributions for representative real-world datasets, illustrating the distributional complexity that detectors must handle.

Key Findings: The real-world benchmark reveals important trade-offs among detectors:

1. **EADD's Real-World Performance:** EADD detected drift on three of the four annotated datasets (Table 4.2) and had a lower mean MTD than D3 on all three: InsectsAbrupt (124 vs. 166), InsectsIncrAbrupt (50 vs. 126) and InsectsIncrRecur (84 vs. 256). The difference is largest on the incremental drift types. D3 had a higher recall on InsectsAbrupt (0.73 vs. 0.60) and InsectsIncrRecur (1.00 vs. 0.83), and a higher precision on all three. On the nine unannotated datasets (Table 4.3), EADD and D3 produced almost the same total number of detections (474.7 and 471.7), indicating comparable selectivity when both use the same window sizes.

2. **Variation across Runs:** Results varied between seeds because D3's cross-




Figure 4.4: Heatmaps of the supplementary multi-detector real-world run. Top: Mean Time to Detection (lower is better; white cells indicate missed drifts or timeout). Bottom: Missed Detection Rate (0.0 is perfect).




Figure 4.5: Time-series comparison on benchmark datasets from the multi-detector supplementary run. Top: WaveformDrift2 (semi-synthetic); EADD detects all three drift points (MTD=99), faster than D3 (MTD=179). Bottom: SineClusters (semi-synthetic); IBDD detects rapidly but with many excess detections, illustrating the sensitivity and specificity trade-off.




Figure 4.6: Feature distribution bell curves. Top: WaveformDrift2 (semi-synthetic) showing multi-dimensional distributional shift across 21 features. Bottom: InsectsAbrupt showing abrupt distributional changes across 33 features.

validation folds and EADD's reservoir sampling and permutations are random. For example, EADD's MTD on InsectsIncrAbrupt ranged from 33 to 58, and D3's MTD on InsectsIncrRecur from 172 to 324. An earlier single run without fixed seeds, reported in the conference version of this work, gave larger differences in favour of EADD (e.g., 33 vs. 272.5 on InsectsIncrAbrupt); the three-seed averages above are more reliable.

3. **IBDD's False Alarm Problem:** In the supplementary run, IBDD demonstrated the fastest raw detection times (MTD = 8–88) but at enormous false alarm cost: 726 detections on Electricity, 485 on NOAAWeather and 163 on Powersupply. Over the 11 streams, IBDD raised 2,509 detections and OCDD 700, compared with 99 for EADD and 129 for D3.
4. **BNDM's Scalability Limitation:** BNDM timed out on all 33-feature datasets (InsectsAbrupt, InsectsGradual, InsectsIncrAbrupt, InsectsIncremental, InsectsReoccurring), making it impractical for high-dimensional real-world data.
5. **InsectsGradual Challenge:** InsectsGradual remained one of the hardest datasets: EADD, D3, BNDM, OCDD and UDetect all missed the annotated drift point, while CSDDM, IBDD and SPLL detected it at the cost of more detections on other datasets. EADD raised an alarm 29 samples before the annotated drift point in the run with seed 42; because the matching rule only accepts detections at or after the drift point, this alarm counts as a false alarm.

4.4 Experiment 3: Robustness to Stable Data (False Alarm Evaluation)

Objective: Measure false alarm rates on stable data streams that contain no drift.

Experimental Design: The four stable streams described in Section 3.4 (Gaussian i.i.d., autocorrelated AR(1), heteroscedastic, and correlated features; $n =$

10,000 each) were each generated five times with different seeds. EADD ($N_{ref} = 500$, $N_{cur} = 200$) and D3 ($N_{ref} = 100$, $N_{cur} = 50$) were run on every stream, with D3 at AUC thresholds $\tau \in \{0.6, 0.7, 0.8\}$.

Results: EADD produced zero false alarms across all four stream types. D3 was particularly vulnerable to autocorrelated data: 87.4 mean false alarms at τ=0.6, 54.6 at τ=0.7 and 13.8 at τ=0.8. At τ=0.6, D3 also raised about 10 false alarms on each of the other three streams. Table 4.6 in Experiment 4 reports the full results.

Key Finding: EADD produced no false alarms, whereas D3 with its small windows raised many false alarms on autocorrelated data at every threshold. D3 used smaller windows than EADD in this experiment, so the comparison does not show whether the difference comes from the window sizes, the classifier, or the permutation test. Experiment 4 separates these effects. The result is consistent with Experiment 2, where D3 used the same window sizes as EADD and both detectors produced almost the same number of detections on the nine unannotated streams.

4.5 Experiment 4: Component Ablation

Objective: Determine which of EADD's design choices causes its differences from D3: the classifier, the window sizes, the reference memory, the AUC threshold, or the permutation test.

Procedure: D3, the ablation variants of Section 3.6, and EADD were run on the four synthetic drift streams of Experiment 1 with five seeds (42, 142, 242, 342 and 442), on the four stable streams of Experiment 3 with five runs each, and on the 13 real-world streams of Experiment 2 with three seeds. On the synthetic drift streams, D3 and D3-LightGBM used the window sizes of Experiment 1 ($N_{ref} = 300$, $N_{cur} = 120$). On the stable streams, they used the window sizes of Experiment 3 ($N_{ref} = 100$, $N_{cur} = 50$) at $\tau \in \{0.6, 0.7, 0.8\}$, and EADD's window sizes ($N_{ref} = 500$, $N_{cur} = 200$) at $\tau = 0.7$. On the real-world streams, all variants used EADD's window sizes. D3-LightGBM used the same LightGBM hyperparameters as EADD.

4.5.1 Synthetic Streams

Table 4.5 reports detection on the synthetic drift streams, and Table 4.6 reports false alarms on the stable streams.

Table 4.5: Experiment 4: Detection on the synthetic drift streams over five seeds. Det. = number of seeds in which the drift was detected; MTD = mean time to detection (samples) over the detected seeds; "–" = not detected in any seed. Windows are given as N_{ref}/N_{cur}.

		Abrupt		Gradual		Incremental		Recurring	
Detector	**Windows**	Det.	MTD	Det.	MTD	Det.	MTD	Det.	MTD
D3	300/120	5/5	98	0/5	–	0/5	–	5/5	133
D3-LightGBM	300/120	5/5	98	0/5	–	0/5	–	5/5	117
D3-LightGBM	500/200	5/5	210	0/5	–	1/5	1411	5/5	175
EADD-NoASPT, fixed ref.	500/200	5/5	109	5/5	549	5/5	589	5/5	132
EADD-NoASPT	500/200	5/5	139	5/5	699	5/5	859	5/5	149
EADD	500/200	5/5	139	5/5	699	5/5	859	5/5	149

What?

All detectors in Table 4.5 raised no false alarms on the drift streams, with three exceptions: EADD-NoASPT with a fixed reference raised a mean of 1.0 false alarms per stream on gradual drift and 2.0 on incremental drift, and EADD-NoASPT raised 0.2 on incremental drift (one false alarm in five seeds).

Table 4.6: Experiment 4: Mean number of false alarms on the stable streams over five runs. Windows are given as N_{ref}/N_{cur}.

Detector	**Windows**	τ	**Gaussian**	**AR(1)**	**Heterosc.**	**Correlated**
D3	100/50	0.6	10.4	87.4	10.4	10.0
D3	100/50	0.7	0.0	54.6	0.0	0.0
D3	100/50	0.8	0.0	13.8	0.0	0.0
D3-LightGBM	100/50	0.6	12.2	83.8	11.8	10.8
D3-LightGBM	100/50	0.7	0.0	52.2	0.0	0.0
D3-LightGBM	100/50	0.8	0.0	8.6	0.0	0.0
D3	500/200	0.7	0.0	0.0	0.0	0.0
D3-LightGBM	500/200	0.7	0.0	0.2	0.0	0.0
EADD-NoASPT	500/200	0.7	0.0	0.0	0.0	0.0
EADD	500/200	0.7	0.0	0.0	0.0	0.0

4.5.2 Real-World Streams

Table 4.7 reports the ablation on the real-world streams, where all variants used the same window sizes ($N_{ref} = 500$, $N_{cur} = 200$). All variants missed the drift in

InsectsGradual.

Table 4.7: Experiment 4: Ablation on the real-world streams, averaged over three seeds. Rec. = recall; MTD = mean time to detection (samples); the last column is the total number of detections on the nine unannotated streams.

Detector	InsectsAbrupt Rec.	InsectsAbrupt MTD	InsectsIncrAbrupt Rec.	InsectsIncrAbrupt MTD	InsectsIncrRecur Rec.	InsectsIncrRecur MTD	Unannotated detections
D3	0.73	166	1.00	126	1.00	256	471.7
D3-LightGBM	0.80	130	1.00	176	0.67	197	511.7
EADD-NoASPT	0.60	107	0.33	85	1.00	108	477.1
EADD	0.60	124	1.00	50	0.83	84	474.7

4.5.3 Effect of the AUC Threshold

Because ASPT runs only when the AUC exceeds τ, its effect depends on the threshold. Table 4.8 compares EADD with and without ASPT at $\tau \in \{0.5, 0.6, 0.7\}$ on the synthetic streams. Every variant detected every synthetic drift in all five seeds.

Table 4.8: Experiment 4: Effect of the AUC threshold τ on EADD with and without ASPT (synthetic streams; five seeds or runs). FA = mean false alarms per stable stream; MTD = mean time to detection on the drift streams; the last column gives the mean number of ASPT invocations and rejections per stable stream.

τ	Variant	Stable FA	MTD Abrupt	MTD Gradual	MTD Incremental	ASPT invoked / rejected
0.5	EADD-NoASPT	4.35	79	229	369	–
0.5	EADD	2.10	79	369	559	25.6 / 23.5
0.6	EADD-NoASPT	0.70	99	539	639	–
0.6	EADD	0.70	99	539	639	0.7 / 0.0
0.7	EADD-NoASPT	0.00	139	699	859	–
0.7	EADD	0.00	139	699	859	0.0 / 0.0

Lowering τ made detection faster but raised more false alarms. At $\tau = 0.5$, ASPT rejected 92% of the alarms it tested on the stable streams and halved the false alarms (2.10 vs. 4.35 per stream), at the cost of slower detection of gradual and incremental drift (MTD 369 vs. 229 and 559 vs. 369). At $\tau = 0.6$ and $\tau = 0.7$, ASPT rejected no alarm, so EADD and EADD-NoASPT behaved the same. Even with ASPT, EADD at $\tau = 0.5$ raised 2.10 false alarms per stable stream and 5.2 on the autocorrelated stream, because

every monitoring check is a separate test at $\alpha = 0.05$ and autocorrelation violates the exchangeability that the permutation test assumes.

Key Findings:

1. **Classifier:** Replacing logistic regression with LightGBM in D3 changed little. On the synthetic streams, D3-LightGBM detected the same drift types as D3, abrupt and recurring drift, and missed gradual and incremental drift in all five seeds; on stable data it produced false alarm counts similar to D3 (52.2 vs. 54.6 on AR(1) at $\tau = 0.7$). On the real-world streams, D3-LightGBM had a higher recall than D3 on InsectsAbrupt (0.80 vs. 0.73) but a lower recall on InsectsIncrRecur (0.67 vs. 1.00), and it raised more detections on the unannotated streams (511.7 vs. 471.7). The LightGBM classifier is therefore not what allows EADD to detect gradual and incremental drift.
2. **Window size:** With EADD's window sizes, D3 and D3-LightGBM produced almost no false alarms on the stable streams (0.0 and 0.2 on AR(1)). The false alarms of D3 in Experiment 3 are therefore caused mainly by its small windows, which make the AUC estimate noisy, especially when consecutive samples are correlated. Larger windows alone did not let D3-LightGBM detect gradual drift, and it detected incremental drift in only one of five seeds, 1,411 samples after onset.
3. **Reference memory:** Every variant with a long-memory reference window detected all four synthetic drift types in all five seeds. D3 compares two adjacent windows that move forward together, so a drift that develops over 1,000 to 2,000 samples never makes the two windows very different. EADD's reference window instead represents all samples since the last confirmed drift, through reservoir sampling, or keeps the first samples after it (fixed reference), so a slow change accumulates in the comparison. The fixed reference detected gradual and incremental drift sooner (MTD 549 and 589 vs. 699 and 859) but raised 1.0 and 2.0 false alarms per stream, while reservoir sampling raised 0.0 and 0.2. On the real-world

streams, EADD detected the two incremental INSECTS streams much sooner than D3-LightGBM, which uses the same classifier and window sizes (MTD 50 vs. 176 and 84 vs. 197).

4. **Permutation test and threshold:** ASPT never overturned an alarm at the default threshold $\tau = 0.7$. EADD-NoASPT, which accepts every AUC above τ, raised no false alarms on the stable streams, so the AUC never exceeded $\tau = 0.7$ there and ASPT was never invoked. On the real-world streams, ASPT was invoked at 1,548 of 20,322 monitoring checks (7.6%) and confirmed drift every time. The small differences between EADD and EADD-NoASPT in Tables 4.5 and 4.7 come from the random numbers that ASPT draws, which change the later reservoir samples, and not from ASPT rejecting alarms. ASPT changed the decisions only at $\tau = 0.5$, where it halved the false alarms (Table 4.8).

5. **Runtime:** On the stable streams, EADD and EADD-NoASPT took about 11.9 seconds per 10,000-sample stream, compared with 0.2 to 0.5 seconds for D3 and 0.9 to 1.3 seconds for D3-LightGBM. Processing all 13 real-world streams once took about 27.5 minutes for EADD, 1.7 minutes for D3-LightGBM and 0.5 minutes for D3. Most of EADD's cost comes from training a LightGBM classifier with 5-fold cross-validation every 50 samples.

4.6 Statistical Hypothesis Testing

4.6.1 H1: Detection Coverage and Delay

H1a: Drift Type Coverage

Table 4.9 summarises the drift-type coverage of the eight detectors in Experiment 1.

EADD is the only detector that achieved full drift-type coverage (4/4) with zero false alarms. BNDM, CSDDM, IBDD, and OCDD also achieved 4/4 coverage but with substantially higher false alarm counts (4.75–46.25 per type). D3 and SPLL each

Table 4.9: Drift Type Coverage Summary (out of 4 types: Abrupt, Gradual, Incremental, Recurring)

Detector	Types Detected	Coverage	Mean FA per Type
EADD	**4/4**	**100%**	**0.00**
BNDM	4/4	100%	4.75
CSDDM	4/4	100%	5.50
IBDD	4/4	100%	46.25
OCDD	4/4	100%	17.50
D3	2/4	50%	0.00
SPLL	2/4	50%	0.00
UDetect	0/4	0%	–

cover only 2/4 types (failing on gradual and incremental drift), while UDetect fails on all four types.

To test H1a, the 20 synthetic drift streams of Experiment 4 (four drift types and five seeds) were compared pairwise. EADD detected the drift in 10 streams where D3 missed it (all gradual and incremental streams), and D3 detected none that EADD missed. The exact one-sided sign test gives $p = 0.001$, so H1a is supported.

H1b: Detection Delay Comparison

On the 10 synthetic streams where both detectors detected the drift (abrupt and recurring), D3 was faster than EADD by 28.6 samples on average (98 vs. 139 on abrupt drift and 133 vs. 149 on recurring drift). The two-sided Wilcoxon signed-rank test gives $p = 0.020$. H1b, that EADD's delay is comparable to D3's where both detect, is therefore not supported on the synthetic streams: D3 detects abrupt and recurring drift sooner, partly because its windows are smaller. On the real-world streams, where both detectors used the same window sizes, EADD had the lower mean MTD on all three detected streams (Table 4.2).

4.6.2 H2: False Alarm Reduction (Mann–Whitney U Test)

False alarm counts from EADD and D3 over the four stable stream types were compared using one-sided Mann–Whitney U tests (Experiment 3, Section 4.4).

Result (vs D3 τ=0.6): $U = 0.0$, exact $p = 0.014$ (normal approximation $p = 0.010$). The difference is statistically significant: EADD produced 0 mean false alarms in total, compared with 118.2 for D3.

Result (vs D3 τ=0.7): $U = 6.0$, exact $p = 0.343$ (normal approximation $p = 0.227$). Not statistically significant at the $\alpha = 0.05$ level.

H2 is therefore supported at $\tau = 0.6$ for D3 with its small windows. Experiment 4 shows, however, that D3 with EADD's window sizes also produces no false alarms on these streams, so the difference cannot be attributed to the permutation test.

4.7 Component Analysis on Real-World Data

The monitoring logs of EADD on the real-world streams of Experiments 2 and 4 (13 streams, three seeds, 20,322 monitoring checks) show how each component behaves.

AUC Trajectory. On InsectsAbrupt, the cross-validated AUC before the first drift point ($t = 14{,}352$) averaged 0.45 and ranged from 0.22 to 0.77. After the drift point it rose from 0.36 to 0.46, 0.58 and 0.76 over three consecutive checks, and EADD confirmed the drift at $t = 14{,}499$, 147 samples after onset (seed 42). Values of the AUC below 0.5 are expected under cross-validation when the windows cannot be separated.

ASPT Behaviour. ASPT was invoked at 1,548 checks (7.6%), each time because the AUC exceeded $\tau = 0.7$. It confirmed drift in every invocation and always stopped at $i = 20$ permutations, the earliest stopping point for $\alpha = 0.05$ ($p = 1/21 \approx 0.048$). A fixed-budget test with 199 permutations would have retrained the classifier 199 times at each of these checks, so ASPT saved 90% of the permutations. ASPT never stopped early to accept the null hypothesis on these streams, because it was never invoked on an AUC below 0.7.

Prediction Entropy. H_{pred} was about 0.45 to 0.47 on stable segments and fell together with the AUC as drift appeared, for example to 0.39 and 0.30 in the two checks before the first detection on InsectsAbrupt. Across all checks, the Spearman correlation between H_{pred} and the AUC was -0.56. On InsectsGradual, H_{pred} stayed between 0.44 and 0.47 around the annotated drift point. These logs do not show H_{pred} declining consistently before the AUC, so its value as an early-warning signal is not established.

Component Summary. The reservoir-sampled reference window gives EADD its broader detection coverage over D3; the LightGBM classifier alone does not (Experiment 4). At the default threshold, ASPT confirmed every alarm that reached it at 10% of the cost of a fixed-budget permutation test, so its effect on the decisions depends on the threshold. H_{pred} provides a continuous monitoring signal but moved together with the AUC. The TreeSHAP feature ranking adds diagnostic output without affecting detection decisions.

CHAPTER 5
DISCUSSION

This chapter interprets the results of Chapter 4, answers the research questions, and relates the findings to the studies reviewed in Chapter 2.

5.1 Answers to the Research Questions

5.1.1 RQ1: Detection Accuracy

Does EADD achieve comparable or better drift detection performance than state-of-the-art unsupervised detectors?

The experiments give a nuanced answer: EADD is not the *fastest* detector, but it achieves the best *balance* of coverage and false alarm control among the eight detectors tested.

- **Synthetic Data (Experiments 1 and 4):** EADD detected all four drift types (4/4) with zero false alarms, the only detector among the eight to achieve this combination. BNDM, CSDDM, IBDD, and OCDD also detected 4/4 types but with 4.75–46.25 false alarms per type. D3 and SPLL detected only 2/4 types, failing on gradual and incremental drift. Over 20 paired synthetic streams, EADD detected 10 drifts that D3 missed and D3 none that EADD missed (sign test $p = 0.001$, H1a supported). Where both detected the drift, D3 was faster (Wilcoxon $p = 0.020$, H1b not supported).
- **Real-World Data (Experiment 2):** With matched window sizes and three seeds, EADD detected drift on 3 of 4 annotated INSECTS datasets and had a lower mean MTD than D3 on all three (124 vs. 166, 50 vs. 126, and 84 vs. 256 samples), while D3 had a higher recall on two of them. On nine unannotated datasets, EADD and D3 produced almost the same number of detections (474.7 and 471.7).

- **Source of the Coverage:** Experiment 4 shows that EADD's advantage on gradual and incremental drift comes from its long-memory reference window. D3 with a LightGBM classifier still missed these drift types, even with EADD's window sizes, while EADD without its permutation test detected them in all five seeds.

Among the eight detectors, EADD was the only one to combine complete synthetic drift-type coverage with zero false alarms, and on the real-world streams it detected incremental drift sooner than D3.

5.1.2 RQ2: Robustness

Does EADD's permutation test reduce false alarm rates on stable data compared with threshold-based approaches such as D3?

EADD produced no false alarms on the four stable streams, while D3 with $N_{ref} = 100$ produced up to 87.4 false alarms at $\tau = 0.6$ and 54.6 at $\tau = 0.7$ on the autocorrelated stream (Experiment 3). The difference at $\tau = 0.6$ was statistically significant (H2, exact $p = 0.014$). The ablation in Experiment 4, however, shows that the permutation test is not the cause of this difference:

- **Window size:** D3 with EADD's window sizes produced no false alarms on any stable stream, and D3-LightGBM produced 0.2 on the autocorrelated stream. The false alarms of D3 in Experiment 3 come from its small windows, which give a noisy AUC estimate when consecutive samples are correlated.
- **Permutation test at the default threshold:** With $\tau = 0.7$, ASPT never rejected an alarm. On the stable streams the AUC never exceeded the threshold, and on the real-world streams ASPT confirmed all 1,548 alarms it tested.
- **Permutation test at a lower threshold:** With $\tau = 0.5$, ASPT rejected 92% of the alarms it tested and halved the false alarms on the stable streams (2.10 vs. 4.35 per stream), but EADD still raised more false

alarms than at $\tau = 0.7$ and detected gradual and incremental drift more slowly than without ASPT.

The answer to RQ2 is therefore that EADD raises fewer false alarms than D3 in its benchmark configuration, but that, at the default threshold, the permutation test did not measurably reduce false alarms. The AUC threshold and the window sizes did. ASPT reduces false alarms only when the threshold is close to 0.5, and even then it cannot keep the number of false alarms per stream at the nominal level, because each monitoring check is a separate test.

5.2 Relation to Previous Studies

Several results agree with the studies reviewed in Chapter 2. Lukats et al. [18] found that the size of the observed samples was one of the most influential hyperparameters of unsupervised drift detectors, and that D3 is sensitive to noise. The ablation confirms both points for discriminative detectors: changing D3's windows from 100/50 to 500/200 samples removed almost all of its false alarms, while changing its classifier did not. Lukats et al. [18] also questioned whether purging the data windows after a detection, as most detectors do, suits incremental and gradual drift. The results support this concern from the other side: D3, which compares two adjacent sliding windows, missed every slow synthetic drift, while EADD, whose reference window summarises all data since the last detection, detected all of them.

The behaviour of ASPT follows from the theory of the classifier two-sample test [16]. Under the null hypothesis, the AUC of a classifier trained on shuffled labels concentrates near 0.5, with a spread that shrinks as the windows grow. With 700 samples per test, an AUC of 0.7 lies far in the tail of this distribution, so a permutation test confirms almost every alarm that passes the threshold. The sequential stopping rule of Gandy [19] still reduced the cost of the test by 90%, as expected when the evidence is clear. The remaining false alarms at $\tau = 0.5$ illustrate a known limitation of repeated significance testing on a stream: a test at level α at every check does not control the

error rate over the whole stream, which is the motivation for anytime-valid tests such as E-C2ST [31].

The feature ranking in EADD follows the domain-classifier approach of Maggio [21], and the monitoring of explanation distributions by Mougan et al. [22] offers an alternative that observes the deployed model instead. Because the accuracy of the ranking was not evaluated in this thesis, the results neither confirm nor contradict the reports that SHAP rankings identify drifted features. Finally, prediction-based monitoring depends on calibrated outputs [14, 46]. In EADD, the prediction entropy of the discriminator moved together with its AUC, so it added little information beyond the AUC in these experiments.

5.3 Practical Implementation Considerations

5.3.1 Window Size and Threshold Selection

The experiments used $N_{ref} = 500$ and $N_{cur} = 200$ for EADD throughout, which proved effective across both synthetic and real-world datasets. However, the optimal window configuration is dataset-dependent:

Table 5.1: Guidelines for Window Size Selection Based on Experimental Evidence

Factor	**Consideration**	**Recommendation**
Dataset Size	Larger datasets allow larger windows	N_{ref}: 1–10% of total data
Expected Drift Type	Abrupt: smaller windows; Gradual: larger windows	Abrupt: 200–500; Gradual: 500–2000
Detection Latency	Smaller windows = faster detection	Trade-off with statistical power
Computational Budget	Larger windows = more expensive training	Balance accuracy vs. speed

Experiment 4 shows that window size matters more than the classifier for false alarms on autocorrelated data. With $N_{ref} = 100$, D3 raised false alarms at every threshold from 0.6 to 0.8, while with $N_{ref} = 500$ it raised none at $\tau = 0.7$. The reference memory matters for slow drift: a reference window that summarises all data since the last drift detected gradual and incremental drift that two adjacent sliding windows missed.

The threshold sets a trade-off between speed and false alarms: lowering τ from 0.7 to 0.5 halved the detection delay on gradual drift but introduced false alarms, and ASPT is useful only in that low-threshold setting.

5.3.2 Proposed MLOps Deployment Architecture

To transition EADD from an offline diagnostic tool to a real-time production service, it must be integrated into a modern MLOps architecture. We propose a microservices-based deployment utilising standard data engineering frameworks:

- **Data Ingestion Layer (e.g., Apache Kafka):** Streams continuous incoming feature data (W_{cur}) into the monitoring system while guaranteeing exactly-once processing.
- **EADD Monitoring Microservice:** An isolated container running the LightGBM discriminative classifier and SHAP explainer. It utilises Reservoir Sampling to maintain the historical baseline (W_{ref}) in an in-memory database (e.g., Redis) for rapid access.
- **Orchestration & Model Registry (e.g., MLflow / Apache Airflow):** When EADD confirms drift, it pushes a drift report containing the AUC, the p-value, H_{pred} and the feature ranking to the orchestrator. The orchestrator can then trigger the training pipeline to fetch new data, retrain the primary model and log the new artifact in MLflow, or alert the data engineering team to inspect the upstream pipelines of the top-ranked features.

This architecture decouples the computational overhead of the discriminator and the permutation test from the primary model's inference latency, allowing EADD to run asynchronously as an independent monitoring service.

5.4 Limitations and Threats to Validity

Covariate Drift Only: EADD detects feature drift ($P(X)$ changes) but cannot directly detect pure concept drift ($P(y|X)$ changes with stable $P(X)$). The

hierarchical decomposition of Feng et al. [24] addresses this gap but requires labelled data.

Synthetic Streams: The synthetic streams have five independent Gaussian features and mean shifts of two standard deviations. Correlated features, smaller shifts and drift in only some features were not studied in the drift streams, so the results may be optimistic for harder drifts.

Few Annotated Real-World Drifts: Only four real-world streams have annotated drift points, with ten annotated drifts in total, and the annotation marks only major transitions. Precision on these streams is therefore uncertain, and the nine unannotated streams can only be compared by their detection counts.

Number of Runs: Experiment 1 used one stream per drift type and Experiment 3 five runs per stream type, and the real-world results varied between seeds (Section 4.3). The statistical tests are based on small samples, such as four stream types for H2.

Window Sizes in Experiment 3: In Experiment 3, D3 used smaller windows than EADD. The H2 result therefore reflects the window sizes as well as the detectors themselves, as Experiment 4 shows.

Repeated Testing: EADD tests for drift at every monitoring check without correcting for the number of tests, and the permutation test assumes exchangeable samples, which autocorrelated streams violate. The false alarm rate per stream is therefore not controlled at α.

Computational Overhead: EADD took about 11.9 seconds per 10,000-sample stable stream, compared with 0.2 to 0.5 seconds for D3, and about 27.5 minutes for one pass over the 13 real-world streams, compared with 0.5 minutes for D3. Each permutation is independent, so the permutation test can be distributed across compute clusters for high-velocity applications.

Unevaluated Feature Ranking: The TreeSHAP feature ranking is reported with each detection but its accuracy is not evaluated in this thesis. SHAP explanations are also correlational rather than causal [61], so in production they may direct attention to symptomatic rather than root-cause features.

Difference from the Conference Paper: The conference version of this work

reported a single unseeded real-world run, the Drift Severity Index, and an evaluation of the feature ranking on three synthetic scenarios. This thesis replaces the real-world results with three-seed averages and leaves out the severity index and the ranking evaluation, so some numbers differ between the two documents.

Adversarial Vulnerability: Hinder et al. [34] demonstrated that discriminative drift detectors can be evaded by adversarial data streams. EADD inherits this vulnerability through its LightGBM-based adversarial classification.

5.5 Chapter Summary

EADD was the only detector to achieve 4/4 synthetic drift-type coverage with zero false alarms, and it detected the slow synthetic drifts that D3 missed (RQ1, H1a supported); where both detected the drift, D3 was faster (H1b not supported). On the real-world streams with matched windows, EADD detected incremental drift sooner than D3, and both raised a similar number of detections. EADD produced no false alarms on the stable streams, while D3 with small windows produced up to 87.4 (RQ2, H2 supported at $\tau = 0.6$). The ablation showed that EADD's coverage of slow drift comes from its reservoir-sampled reference window, that D3's false alarms come from its small windows, that replacing D3's logistic regression with LightGBM changes little, and that ASPT changes the decisions only when the AUC threshold is lowered to 0.5. The remaining detection limitation is InsectsGradual, where EADD (along with D3, BNDM, OCDD, and UDetect) missed the annotated drift point.

CHAPTER 6
CONCLUSION AND RECOMMENDATIONS

6.1 Summary of Findings

This thesis addressed three gaps in D3's operational utility: the lack of a formal significance test, a reference window that moves with the current window, and the absence of any feature-level output. D3 [17] demonstrated that discriminative classification can detect distribution changes, and recent work [23, 24, 31] advanced individual aspects of drift detection, but these components had not been combined and evaluated together in an unsupervised streaming detector.

We proposed **Enhanced Adversarial Drift Detection (EADD)** and made the following contributions:

1. An integrated framework that combines a LightGBM classifier two-sample test [16, 26], a reservoir-sampled reference window [27], prediction entropy monitoring (H_{pred}) and an adaptive sequential permutation test, and that ranks the features behind each confirmed drift with TreeSHAP [20].
2. An adaptive sequential permutation test (ASPT) that applies sequential Monte Carlo stopping [19] to the classifier two-sample test. ASPT confirmed a clear drift after 20 of 199 permutations, a 90% saving over a fixed-budget test.
3. An experimental evaluation against seven unsupervised detectors on synthetic and real-world streams, including an ablation with a LightGBM version of D3 that separates the effects of the classifier, the window sizes, the reference memory, the threshold and the permutation test.

The experimental evaluation (Chapter 4) produced the following key findings:

- **Experiment 1:** EADD detected all four synthetic drift types (4/4) with zero false alarms, the only detector to achieve this combination. BNDM, CSDDM, IBDD, and OCDD achieved 4/4 coverage but with substantially higher false alarm counts.
- **Experiment 2:** With matched window sizes and three seeds, EADD detected drift on 3 of 4 annotated INSECTS datasets and had a lower mean MTD than D3 on all three (124 vs. 166, 50 vs. 126, and 84 vs. 256 samples), while D3 had a higher recall on two of them. On nine unannotated datasets, both detectors raised a similar number of detections (474.7 and 471.7).
- **Experiment 3:** EADD produced no false alarms on 4 stable stream types, compared with D3's 87.4 mean false alarms on autocorrelated data at $\tau = 0.6$ with $N_{ref} = 100$.
- **Experiment 4:** D3 with a LightGBM classifier behaved like the original D3. With EADD's window sizes, D3 raised almost no false alarms. EADD's coverage of slow drift came from its reservoir-sampled reference window. ASPT changed the decisions only at $\tau = 0.5$, where it halved the false alarms.

Statistical testing supported H1a (sign test $p = 0.001$) and H2 at $\tau = 0.6$ (exact Mann–Whitney $p = 0.014$), but not H1b: D3 detected abrupt and recurring drift sooner on the synthetic streams. The ablation showed that the H2 difference is explained by D3's smaller windows rather than by the permutation test.

6.2 Limitations

The main limitations of this study, discussed in Section 5.4, are the following. EADD detects only covariate drift. The synthetic streams have independent features and large mean shifts, and only four real-world streams have annotated drift points. Several analyses rely on few runs or stream types. EADD tests at every check without controlling

the error rate over a whole stream, and its runtime is 25 to 55 times that of D3. Finally, the TreeSHAP feature ranking was not evaluated.

6.3 Recommendations for Application

The results lead to the following recommendations for practitioners who deploy discriminative drift detectors:

Check the Windows First: For discriminative detectors, the design of the windows matters more than the choice of classifier. A reference window that summarises all data since the last drift detects slow drift that adjacent sliding windows miss, and windows that are too small cause false alarms on autocorrelated data. Window sizes and reference memory should be checked before the classifier or the threshold is changed.

Choose the Threshold Deliberately: With windows of 500 and 200 samples, an AUC threshold of 0.7 gave no false alarms on the stable streams, and a permutation test added nothing at that threshold. A lower threshold detects drift sooner but needs a significance test, such as ASPT, to limit false alarms, and even then some false alarms remain on autocorrelated data.

Use ASPT to Make Significance Testing Affordable: When a permutation test is used, the adaptive sequential stopping rule reduces its cost by about 90% for clear decisions, making permutation-based calibration practical for moderate-frequency monitoring.

Budget for Computation: EADD's LightGBM classifier with 5-fold cross-validation every 50 samples made it 25 to 55 times slower than D3 in our experiments. Monitoring less often, training fewer trees or running the monitor asynchronously from the primary model can reduce this cost.

Treat the Feature Ranking as a Lead: The TreeSHAP ranking points to the features that separate the two windows, which can direct engineers to upstream data sources before a full retraining. Because its accuracy has not been evaluated and SHAP is correlational [61], it should be treated as a lead for investigation rather than as a diagnosis. In regulated sectors, where "black box" model adaptations may violate transparency

requirements [74], the ranking can also document which features changed before each drift-triggered update.

6.4 Suggestions for Future Research

Based on the experimental findings and the rapidly evolving literature, future research should pursue the following directions:

1. **Evaluating the Feature Ranking:** Measuring how accurately the Tree-SHAP ranking identifies drifting features on streams with correlated and interacting features, and on real-world streams with documented causes of drift.
2. **Anytime-Valid Testing:** Replacing the per-check permutation p-value with e-values [31] would control the false alarm rate over a whole stream rather than at each check, which the low-threshold results show is needed.
3. **Harder Synthetic Drifts and More Annotated Streams:** Evaluating the detectors on correlated features, smaller shifts and drifts in subsets of features, and on more real-world streams with annotated drift points.
4. **Prediction Entropy as an Early Warning:** Testing whether H_{pred}, alone or combined with the AUC trend, gives warnings earlier than the AUC threshold, with a quantitative evaluation of its lead time and false warnings.
5. **Causal Drift Attribution:** Extending EADD's correlational SHAP explanations toward causal drift attribution [61] would help remediation target root causes rather than correlated symptoms.
6. **Covariate and Concept Drift Decomposition:** Integrating the hierarchical decomposition framework of Feng et al. [24] to separate $P(X)$ shifts from $P(y|X)$ shifts when delayed labels become available.

7. **Adversarial Robustness:** Developing defences against adversarial drift evasion attacks [34], potentially through ensemble diversification or randomised smoothing of the discriminative classifier.
8. **Deep Learning Extension:** Adapting EADD for unstructured data (images, text) using deep learning classifiers and embedding-space attribution, building on DriftLens [68].

6.5 Concluding Remarks

This thesis proposed EADD, an integrated framework that combines established methods: the classifier two-sample test [16], reservoir sampling [27], sequential Monte Carlo testing [19] and TreeSHAP [20, 60]. In a single unsupervised streaming pipeline, these components report whether the discriminator can separate recent data from the reference data, whether the separation is statistically significant, and which features drive it. EADD was the only detector in the evaluation to achieve complete synthetic drift-type coverage (4/4) with zero false alarms, and on the real-world streams it detected incremental drift sooner than D3. The ablation showed that much of this behaviour comes from the design of the reference window rather than from the classifier or the permutation test, a result that applies to discriminative drift detectors in general.

REFERENCES

1 Jie Lu, Anjin Liu, Fan Dong, Feng Gu, João Gama, and Guangquan Zhang. Learning under concept drift: A review. *IEEE Transactions on Knowledge and Data Engineering*, 31(12):2346–2363, 2018. doi: 10.1109/TKDE.2018.2876857.

2 João Gama, Indrė Žliobaitė, Albert Bifet, Mykola Pechenizkiy, and Abdelhamid Bouchachia. A survey on concept drift adaptation. *ACM Computing Surveys*, 46(4): 1–37, 2014. doi: 10.1145/2523813.

3 D. Sculley, Gary Holt, Daniel Golovin, Eugene Davydov, Todd Phillips, Dietmar Ebner, Vinay Chaudhary, Michael Young, Jean-François Crespo, and Dan Dennison. Hidden technical debt in machine learning systems. In *Advances in Neural Information Processing Systems 28 (NIPS)*, pages 2503–2511, 2015.

4 Firas Bayram, Bestoun S. Ahmed, and Andreas Kassler. From concept drift to model degradation: An overview on performance-aware drift detectors. *Knowledge-Based Systems*, 245:108632, 2022. doi: 10.1016/j.knosys.2022.108632. Authors verified: F. Bayram, B.S. Ahmed, A. Kassler.

5 Gerhard Widmer and Miroslav Kubat. Learning in the presence of concept drift and hidden contexts. *Machine Learning*, 23(1):69–101, 1996. doi: 10.1007/BF00116900.

6 Diego Vela, Andrew Sharp, Richard Zhang, Trang Nguyen, An Hoang, and Oscar N. Pianykh. Temporal quality degradation in AI models. *Scientific Reports*, 12(1):11654, 2022. doi: 10.1038/s41598-022-15245-z.

7 Bret Nestor, Matthew B. A. McDermott, Willie Boag, Gabriela Berner, Tristan Naumann, Michael C. Hughes, Anna Goldenberg, and Marzyeh Ghassemi. Feature robustness in non-stationary health records: Caveats to deployable model performance in common clinical machine learning tasks. *Proceedings of Machine Learning Research (ML4H at NeurIPS)*, 106:1–23, 2019.

8 Stephan Rabanser, Stephan Günnemann, and Zachary C. Lipton. Failing loudly: An empirical study of methods for detecting dataset shift. In *Advances in Neural Information Processing Systems 32 (NeurIPS)*, 2019.

9 Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *Journal of Machine Learning Research*, 13(25):723–773, 2012.

10 Albert Bifet and Ricard Gavaldà. Learning from time-changing data with adaptive windowing. In *Proceedings of the 2007 SIAM International Conference on Data Mining (SDM)*, pages 443–448. SIAM, 2007. doi: 10.1137/1.9781611972771.42.

11 João Gama, Pedro Medas, Gladys Castillo, and Pedro Rodrigues. Learning with drift detection. In *Advances in Artificial Intelligence – SBIA 2004*, volume 3171 of *LNCS*, pages 286–295. Springer, 2004. doi: 10.1007/978-3-540-28645-5_29.

12 Manuel Baena-García, José del Campo-Ávila, Raúl Fidalgo, Albert Bifet, Ricard Gavaldà, and Rafael Morales-Bueno. Early drift detection method. In *Proceedings of the Fourth International Workshop on Knowledge Discovery from Data Streams (IWKDDS)*, pages 77–86, 2006.

13 Tegjyot Singh Sethi and Mehmed Kantardzic. On the reliable detection of concept drift from streaming unlabeled data. *Expert Systems with Applications*, 82:77–99, 2017. doi: 10.1016/j.eswa.2017.04.008.

14 Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, volume 70 of *PMLR*, pages 1321–1330, 2017.

15 Geoffrey I. Webb, Roy Hyde, Hong Cao, Hai Long Nguyen, and François Petitjean. Characterizing concept drift. *Data Mining and Knowledge Discovery*, 30(4):964–994, 2016. doi: 10.1007/s10618-015-0448-4.

16 David Lopez-Paz and Maxime Oquab. Revisiting classifier two-sample tests. In *International Conference on Learning Representations (ICLR)*, 2017. URL https://openreview.net/forum?id=SJkXfE5xx.

17 Ömer Gözüaçık, Alican Büyükçakır, Hamed Bonab, and Fazli Can. Unsupervised concept drift detection with a discriminative classifier. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management (CIKM)*, pages 2365–2368, 2019. doi: 10.1145/3357384.3358144.

18 Daniel Lukats, Oliver Zielinski, Axel Hahn, and Frederic Stahl. A benchmark and survey of fully unsupervised concept drift detectors on real-world data streams. *International Journal of Data Science and Analytics*, 19:1–31, 2024. doi: 10.1007/s41060-024-00620-y.

19 Axel Gandy. Sequential implementation of Monte Carlo tests with uniformly bounded resampling risk. *Journal of the American Statistical Association*, 104(488):1504–1511, 2009. doi: 10.1198/jasa.2009.tm08368.

20 Scott M. Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems 30 (NIPS)*, pages 4765–4774, 2017.

21 Simona Maggio. Why is my data drifting? Dataiku Tech Blog, 2021. Published 11 January 2021. https://www.dataiku.com/blog/why-is-my-data-drifting.

22 Carlos Mougan, Klaus Broelemann, Gjergji Kasneci, Thanassis Tiropanis, and Steffen Staab. Explanation shift: How did the distribution shift impact the model? *Transactions on Machine Learning Research*, 2025. arXiv:2303.08081.

23 Pranoy Panda, Sai Srinivas Kancheti, Vineeth N. Balasubramanian, and Gaurav Sinha. Interpretable model drift detection. In *Proceedings of the 7th Joint International Conference on Data Science and Management of Data (ACM IKDD CODS-COMAD)*, 2024. doi: 10.1145/3632410.3632434. TRIPODD: feature-inTeraction awaRe Interpretable mOdel Drift Detection. Extended version: arXiv:2503.06606.

24 Jean Feng, Harvineet Singh, Fan Xia, Adarsh Subbaswamy, and Alexej Gossmann. A hierarchical decomposition for explaining ML performance discrepancies. In *Advances in Neural Information Processing Systems 37 (NeurIPS)*, 2024. https://arxiv.org/abs/2402.14254.

25 Fabian Hinder, Valerie Vaquet, and Barbara Hammer. Feature-based analyses of concept drift. *Neurocomputing*, 600:127968, 2024. doi: 10.1016/j.neucom.2024.127968.

26 Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. LightGBM: A highly efficient gradient boosting decision tree. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 3146–3154, 2017.

27 Jeffrey S. Vitter. Random sampling with a reservoir. *ACM Transactions on Mathematical Software*, 11(1):37–57, 1985. doi: 10.1145/3147.3165.

28 Vítor M. A. Souza, Denis M. Reis, André G. Maletzke, and Gustavo E. A. P. A. Batista. Challenges in benchmarking stream learning algorithms with real-world data. *Data Mining and Knowledge Discovery*, 34(6):1805–1858, 2020. doi: 10.1007/s10618-020-00698-5.

29 E. S. Page. Continuous inspection schemes. *Biometrika*, 41(1/2):100–115, 1954. doi: 10.2307/2333009.

30 Feng Liu, Wenkai Xu, Jie Lu, Guangquan Zhang, Arthur Gretton, and Danica J. Sutherland. Learning deep kernels for non-parametric two-sample tests. In *International Conference on Machine Learning (ICML)*, volume 119 of *PMLR*, pages 6316–6326, 2020.

31 Teodora Pandeva, Tim Bakker, Christian A. Naesseth, and Patrick Forré. E-valuating classifier two-sample tests. *Transactions on Machine Learning Research*, 2024. arXiv:2210.13027. https://openreview.net/forum?id=dwFRov8xhr.

32 Ankur Taly and Kaz Sato. Monitoring feature attributions: How Google saved one of the largest ML services in trouble. Google Cloud Blog, 2021. Published 29 September 2021. https://cloud.google.com/blog/topics/developers-practitioners/monitoring-feature-attributions-how-google-saved-one-largest-ml-services-trouble.

33 Amazon Web Services. Feature attribution drift for models in production

– Amazon SageMaker AI. https://docs.aws.amazon.com/sagemaker/latest/dg/clarify-model-monitor-feature-attribution-drift.html, 2025. Accessed: 2026-02-25.

34 Fabian Hinder, Valerie Vaquet, and Barbara Hammer. Adversarial attacks for drift detection. *arXiv preprint arXiv:2411.16591*, 2024. Extended version of ESANN 2024 paper. https://arxiv.org/abs/2411.16591.

35 Alexey Tsymbal. The problem of concept drift: Definitions and related work. Technical Report TCD-CS-2004-15, Trinity College Dublin, Department of Computer Science, 2004.

36 Indrė Žliobaitė. Learning under concept drift: An overview. *arXiv preprint arXiv:1010.4784*, 2010.

37 Hidetoshi Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of Statistical Planning and Inference*, 90(2):227–244, 2000. doi: 10.1016/S0378-3758(00)00115-4.

38 Fabian Hinder, Valerie Vaquet, and Barbara Hammer. One or two things we know about concept drift—a survey on monitoring in evolving environments. Part A: Detecting concept drift. *Frontiers in Artificial Intelligence*, 7:1330257, 2024. doi: 10.3389/frai.2024.1330257.

39 Isvani Frias-Blanco, José del Campo-Ávila, Gonzalo Ramos-Jiménez, Rafael Morales-Bueno, Agustín Ortiz-Díaz, and Yailé Caballero-Mota. Online and non-parametric drift detection methods based on Hoeffding's bounds. *IEEE Transactions on Knowledge and Data Engineering*, 27(3):810–823, 2015. doi: 10.1109/TKDE.2014.2345382.

40 Christoph Raab, Moritz Heusinger, and Frank-Michael Schleif. Reactive soft prototype computing for concept drift streams. *Neurocomputing*, 416:340–351, 2020. doi: 10.1016/j.neucom.2019.11.111.

41 Tamraparni Dasu, Shankar Krishnan, Suresh Venkatasubramanian, and Ke Yi. An information-theoretic approach to detecting changes in multi-dimensional data

streams. In *Proceedings of the 38th Symposium on the Interface of Statistics, Computing Science, and Applications*, 2006.

42 Gregory Ditzler and Robi Polikar. Hellinger distance based drift detection for nonstationary environments. In *IEEE Symposium on Computational Intelligence in Dynamic and Uncertain Environments (CIDUE)*, pages 41–48, 2011. doi: 10.1109/CIDUE.2011.5948491.

43 Jing Pan, Vincent Pham, Mohan Dorairaj, Huigang Chen, and Jeong-Yoon Lee. Adversarial validation approach to concept drift problem in user targeting automation systems at Uber. In *Proceedings of the AdKDD Workshop at KDD*, 2020. arXiv:2004.03045.

44 Hongyi Qian, Baohui Wang, Ping Ma, Lei Peng, Songfeng Gao, and You Song. Managing dataset shift by adversarial validation for credit scoring. *arXiv preprint arXiv:2112.10078*, 2021.

45 Mingsheng Long, Han Zhu, Jianmin Wang, and Michael I. Jordan. Unsupervised domain adaptation with residual transfer networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 29, 2016.

46 Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D. Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems 32 (NeurIPS)*, pages 13991–14002, 2019.

47 Jones Sai-Wang Wan and Sheng-De Wang. Concept drift detection based on preclustering and statistical testing. *Journal of Internet Technology*, 22(2):465–472, 2021. doi: 10.3966/160792642021032202020. CSDDM: Clustered Statistical test Drift Detection Method.

48 Dan Shang, Guangquan Zhang, and Jie Lu. Fast concept drift detection using unlabeled data. In *Developments of Artificial Intelligence Technologies in Computation*

and Robotics: Proceedings of the 14th International FLINS Conference (FLINS 2020), pages 133–140. World Scientific, 2020.

49 Ludmila I. Kuncheva. Change detection in streaming multivariate data using likelihood detectors. *IEEE Transactions on Knowledge and Data Engineering*, 25(5): 1175–1180, 2013. doi: 10.1109/TKDE.2011.226. Semi-Parametric Log-Likelihood (SPLL) detector.

50 Anjin Liu, Jie Lu, Feng Liu, and Guangquan Zhang. Accumulating regional density dissimilarity for concept drift detection in data streams. *Pattern Recognition*, 76: 256–272, 2018. doi: 10.1016/j.patcog.2017.11.009.

51 Ömer Gözüaçık and Fazli Can. Concept learning using one-class classifiers for implicit drift detection in evolving data streams. *Artificial Intelligence Review*, 54(5): 3725–3747, 2021. doi: 10.1007/s10462-020-09939-x.

52 Vítor M. A. Souza, Antonio R. S. Parmezan, Faisal A. Chowdhury, and Abdullah Mueen. Efficient unsupervised drift detector for fast and high-dimensional data streams. *Knowledge and Information Systems*, 63(6):1497–1527, 2021. doi: 10.1007/s10115-021-01564-6.

53 Bartosz Krawczyk, Leandro L. Minku, João Gama, Jerzy Stefanowski, and Michał Woźniak. Ensemble learning for data stream analysis: A survey. *Information Fusion*, 37:132–156, 2017. doi: 10.1016/j.inffus.2017.02.004.

54 Gregory Ditzler, Manuel Roveri, Cesare Alippi, and Robi Polikar. Learning in nonstationary environments: A survey. *IEEE Computational Intelligence Magazine*, 10(4):12–25, 2015. doi: 10.1109/MCI.2015.2471196.

55 Ke Wan, Yi Liang, and Susik Yoon. Online drift detection with maximum concept discrepancy. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, pages 2924–2935, 2024. doi: 10.1145/3637528.3672016.

56 Fabian Hinder, Valerie Vaquet, and Barbara Hammer. One or two things we know about concept drift—a survey on monitoring in evolving environments. Part B: Locat-

ing and explaining concept drift. *Frontiers in Artificial Intelligence*, 7:1330258, 2024. doi: 10.3389/frai.2024.1330258.

57 Anjin Liu, Yiliao Song, Guangquan Zhang, and Jie Lu. Regional concept drift detection and density synchronized drift adaptation. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 2280–2286, 2017.

58 Sean Kulinski, Saurabh Bagchi, and David I. Inouye. Feature shift detection: Localizing which features have shifted via conditional distribution tests. In *Advances in Neural Information Processing Systems 33 (NeurIPS)*, pages 19523–19533, 2020.

59 Lloyd S. Shapley. A value for n-person games. In Harold W. Kuhn and Albert W. Tucker, editors, *Contributions to the Theory of Games*, volume 2, pages 307–317. Princeton University Press, 1953.

60 Scott M. Lundberg, Gabriel Erion, Hugh Chen, Alex DeGrave, Jordan M. Prutkin, Bala Nair, Ronit Katz, Jonathan Himmelfarb, Nisha Bansal, and Su-In Lee. From local explanations to global understanding with explainable AI for trees. *Nature Machine Intelligence*, 2:56–67, 2020. doi: 10.1038/s42256-019-0138-9.

61 David Komnick, Kathrin Lammers, Barbara Hammer, Valerie Vaquet, and Fabian Hinder. Causal explanation of concept drift – a truly actionable approach. In *TempXAI Workshop at the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML PKDD)*, 2025. arXiv:2507.23389.

62 Haoran Zhang, Harvineet Singh, Marzyeh Ghassemi, and Shalmali Joshi. "why did the model fail?": Attributing model performance changes to distribution shifts. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202 of *Proceedings of Machine Learning Research*, pages 41550–41578, 2023.

63 Narayanan U. Edakunni, Utkarsh Tekriwal, and Anukriti Jain. Explaining drift using shapley values. *arXiv preprint arXiv:2401.09756*, 2024. https://arxiv.org/abs/2401.09756.

64 Thomas Decker, Alexander Koebler, Michael Lebacher, Ingo Thon, Volker Tresp, and Florian Buettner. Explanatory model monitoring to understand the effects of feature shifts on performance. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2024. arXiv:2408.13648.

65 Davide Pelosi, Diomidis Cacciagrano, and Marco Piangerelli. Explainability and interpretability in concept and data drift: A systematic literature review. *Algorithms*, 18(7):443, 2025. doi: 10.3390/a18070443.

66 Tri Minh Triet Pham, Karthikeyan Premkumar, Mohamed Naili, and Jinqiu Yang. Time to retrain? Detecting concept drifts in machine learning systems. In *Proceedings of the 47th IEEE/ACM International Conference on Software Engineering (ICSE)*, 2025. arXiv:2410.09190.

67 Vitor Cerqueira, Heitor Murilo Gomes, Albert Bifet, and Luis Torgo. STUDD: A student–teacher method for unsupervised concept drift detection. *Machine Learning*, 112:4351–4378, 2023. doi: 10.1007/s10994-022-06188-7.

68 Salvatore Greco, Bartolomeo Vacchetti, Daniele Apiletti, and Tania Cerquitelli. Unsupervised concept drift detection from deep learning representations in real-time. *arXiv preprint arXiv:2406.17813*, 2024. Accepted at IEEE Transactions on Knowledge and Data Engineering.

69 Mansour Zoubeirou A Mayaki and Michel Riveill. Autoregressive based drift detection method. In *Proceedings of the International Joint Conference on Neural Networks (IJCNN)*, 2022. arXiv:2203.04769.

70 Ruiqi Lyu, Alistair Turcan, and Bryan Wilder. Explaining concept shift with interpretable feature attribution. *arXiv preprint arXiv:2505.20634*, 2025. https://arxiv.org/abs/2505.20634.

71 Michael Harries. Splice-2 comparative evaluation: Electricity pricing. Technical report, University of New South Wales, 1999.

72 Claude E. Shannon. A mathematical theory of communication. *Bell System Technical Journal*, 27(3):379–423, 1948. doi: 10.1002/j.1538-7305.1948.tb01338.x.

73 Phillip I. Good. *Permutation, Parametric, and Bootstrap Tests of Hypotheses*. Springer, 3rd edition, 2005. doi: 10.1007/b138696.

74 Bryce Goodman and Seth Flaxman. European union regulations on algorithmic decision making and a "right to explanation". *AI Magazine*, 38(3):50–57, 2017. doi: 10.1609/aimag.v38i3.2741.

APPENDICES

APPENDIX A
IMPLEMENTATION DETAILS

To ensure reproducibility, the specific hyperparameters and algorithmic configurations used for the EADD framework are detailed below.

A.1 Adversarial Classifier (LightGBM)

The adversarial classifier utilises LightGBM [26], a high-performance gradient boosting framework, with the following configuration. The LightGBM version of D3 used in Experiment 4 uses the same configuration.

Table A.1: LightGBM Hyperparameters

Parameter	**Value**
Boosting Type	gbdt
Number of Estimators	50
Learning Rate	0.1
Max Depth	-1
Num Leaves	31
Objective	Binary Classification
Metric	AUC
Verbosity	-1

A.2 Windowing and Monitoring

- **Reference Window (W_{ref}):** 500 samples, maintained via Reservoir Sampling [27].
- **Current Window (W_{cur}):** 200 samples, sliding window.
- **Monitoring Frequency:** Every 50 samples.

A.3 Uncertainty and Statistical Testing

- **Prediction Entropy (H_{pred}):** Mean binary Shannon entropy of the discriminator's predicted probabilities, computed at every monitoring step.
- **Adaptive Sequential Permutation Test (ASPT):** $B_{\max} = 199$ permutations, $B_{\min} = 10$, $\alpha = 0.05$; only invoked when the AUC exceeds $\tau = 0.7$.

BIOGRAPHY

NAME	Ms. Nusrat Begum
DATE OF BIRTH	21 February 1998
PLACE OF BIRTH	Chattogram, Bangladesh
INSTITUTIONS ATTENDED	Stamford International University, 2017–2022 Bachelor of Business Administration (International Business Management) Mahidol University, 2024–2026 Master of Science (Computer Science) Mahidol University
RESEARCH GRANTS	-
E-MAIL	nusrat.beg@student.mahidol.edu
PUBLICATION/PRESENTATION	Begum N, Yamchote P, Amornbunchornvej C, Noraset T. Enhanced Adversarial Drift Detection for MLOps Feature Monitoring. In: Proc. JCSSE 2026. IEEE; 2026.