≡ Submission Detail

ID	#509618
Problem	Missing Numbers (https://ejudge.it.kmitl.ac.th/problem/2910)
Username	it60070183(นายธีรภัทร ไกรศรีสิริกุล) (https://ejudge.it.kmitl.ac.th/account/1506)
Language	Python
Correctness Score	100 Points
Bonus Score	900 Points
Quality	100% [How to improve your code]
Summary Score	1000 Points
Time	2017-11-01 00:30:37

➡ Details

Case 1 [#5040] : 〔 Passed 〕   0.42660000 sec.
Case 2 [#5041] : 〔 Passed 〕   0.13663000 sec.
Case 3 [#5042] : 〔 Passed 〕   0.05324700 sec.
Case 4 [#5043] : 〔 Passed 〕   0.04411900 sec.
Case 5 [#5044] : 〔 Passed 〕   0.04350300 sec.
Case 6 [#5045] : 〔 Passed 〕   0.04695600 sec.
Case 7 [#5046] : 〔 Passed 〕   0.04455700 sec.
Case 8 [#5047] : 〔 Passed 〕   0.04374700 sec.
Case 9 [#5048] : 〔 Passed 〕   0.04356100 sec.
Case 10 [#5049] :〔 Passed 〕   0.04831900 sec.

🖥 Code

```
Pointers=false&textReferences=false&showOnlyOutputs=false&py=3&rawInputLstJSON=%5B%5D&curInstr=0)
```

```python
"""
PSIT Pair-Programming (19th October 2017)
#1 - Supakit Theanthunyakit (it60070098)
#2 - Teerapat Kraisrisirikul (it60070183)
"""

def main():
    """ Main function """
    num_seq = [i for i in range(1, int(input())+1)]

    while True:
        num = int(input())
        if num == 0:
            break
        num_seq.remove(num)

    _ = [print(i) for i in sorted(num_seq)]

main()
```