


# Logistic Regression

- Logistic regression is a statistical method that is primarily used for binary classification/
- It can be used for classification problems, such as spam detection, diabetes prediction and cancer detection problems.
- Instead of fitting a line to the data, logistic regression fits an S-shaped curve (called sigmoid function).
- Logistic regression computes the probability of a data point along with predictive classification.
- Simple logistic regression: Here, a single independent variable is used to predict the output.
- Multiple logistic regression: Here, multiple independent variables are used to predict the output.
- Logistic regression can be extended to solve multiclass classification problems.

Samples divided into two groups using logistic regression



## Common Interview Questions:

- Why can linear regression be used for binary classification?
- Why is logistic regression called “regression” but still used for “classification” problems?
- List the advantages and disadvantages of using logistic regression for classification problems.
- What is the impact of outliers on logistic regression?
- Do residues exist in logistic regression? If not, why?
- How will you evaluate the performance of a logistic regression-based model?
- Explain the cost function used in logistic regression models.
- What is the one-vs-all method in logistic regression?
- How will you compare the performance of multiple logistic regression models?

## Assumptions of the Logistic Regression Model

- The dependent variable must be linearly separable.
- Groups must be mutually exclusive and exhaustive.
- Absence of strong outliers

## Types of Logistic Regression

**Binary logistic regression:** The target variable has only two possible outcomes: Gmail inbox message is spam or not spam.

**Multinomial logistic regression:** The target variable has three or more nominal categories (e.g., predicting the type of wine).


**Ordinal logistic regression:** The target variable has three or more ordinal categories, such as a rating of 1–5.

# Logistic Regression

## Sigmoid Function (logistic function)

$$f(x) = \frac{1}{1 + e^{-x}}$$

- S-shaped curve
- Takes any real number as an input and gives a value between 0 and 1




- As x tends toward  $\pm$  infinity, the output becomes  $\pm 1$ .
- These properties of the sigmoid function are used to estimate t.
- The sigmoid function is used as the “cost function” in logistic regression
- We can replace f(x) with p (probability) and x with a linear equation to get the following:

$$p = \frac{1}{1 + e^{-(\beta_0 + \beta_1 X_1 + \beta_2 X_2 + \dots + \beta_n X_n)}}$$

## Decision Boundary

If  $f(x) > 0.5$ , then “A;” otherwise, it will be “B.” This will create a “decision boundary,” which can classify samples into two different groups.



## Best Fit

- Linear regression is estimated using ordinary least squares (OLS), whereas logistic regression is estimated using the maximum likelihood estimation (MLE) approach.
- The MLE approach is a “likelihood” maximisation method, whereas OLS is a distance-minimising approximation method.

## Code

```
model = LogisticRegression(solver='liblinear')
model.fit(x,y)
```

note - max\_iter parameter can be used in LogisticRegression to increase the iteration of model

# Logistic Regression

## Odd Logs

$$\text{ODDS} = \frac{\text{Probability of winning}}{\text{Probability of losing}} = \frac{p}{1-p}$$

- Taking the log of odds will fix the scale and help compare events.
- Log(odds) is also known as the "logit" function.

$$\text{Logit Function} = \log \left( \frac{p}{1-p} \right)$$

## Multi-Variate Logistic Regression

- These have more than one input variable.
- The equation used in the case of univariate logistic regression is given below.

$$p = \frac{1}{1 + e^{-(\beta_0 + \beta_1 X)}}$$

So, for multivariate logistic regression, the equation will be as follows.

$$p = \frac{1}{1 + e^{-(\beta_0 + \beta_1 X_1 + \beta_2 X_2 + \beta_3 X_3 + \dots + \beta_n X_n)}}$$

## RFE

- RFE stands for Recursive Feature Elimination.
- It is used to eliminate features from a data set that might not be important for the model.
- Redundant features can be mostly eliminated.
- This saves processing power and memory space.
- RFE is used before applying the model to the data.

Here is the code for using RFE before logistic regression.

```
from sklearn.feature_selection import RFE
from sklearn.linear_model import LogisticRegression
model = LogisticRegression()
rfe = RFE(model, 4) # selecting 4 top features
fit = rfe.fit(X, Y) # Logistics regression model
```

# Logistic Regression

## Model Performance

The confusion matrix is used to define the performance of a classification algorithm

Predicted Class	
True Class	True Positive (TP)
	False Negative (FN)
True Class	False Positive (FP)
	True Negative (TN)

To evaluate this performance, we can use these measures:

**Precision** : Indicates the precision of predictions

**Recall**: Indicates the approximate percentage of classes captured by the model

**Accuracy**: Indicates the accuracy of predictions

**F1 score**: Is similar to the weighted average of the precision and recall values.

Here's how these can be calculated

$$\text{precision} = \frac{TP}{TP + FP}$$

$$\text{recall} = \frac{TP}{TP + F}$$

$$F1 = \frac{2 \times \text{precision} \times \text{recall}}{\text{precision} + \text{recall}}$$


$$\text{accuracy} = \frac{TP + TN}{TP + FN + TN + FP}$$

$$\text{specificity} = \frac{TN}{TN + FP}$$

## ROC Curve

- This is used for determining the best cutoff value.
- The ROC curve gives information on the trade-off between sensitivity (or TPR) and specificity (1 - FPR).
- This indicates the performance of a classification model at all classification thresholds.
- The curve is plotted against two parameters: true positive rate and false positive rate.

### Example of ROC curve



Here:

True positive rate (TPR) = True Positives / (True Positives + False Negatives)

False positive rate (FPR) = False Positives / (False Positives + True Negatives)

Note: TPR is also known as sensitivity and FPR = 1 - specificity.