

明

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

LECTURE 8 Course Review



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

LECTURE 1 INTRODUCTION



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

TOPIC and Reference OF THIS COURSE

<http://www.cs.cmu.edu/~15210/>

<https://www.diderot.one/courses/121/books>

- This course covers
 - defining precisely the problem you want to solve,
 - learning the different algorithm-design techniques for solving problems,
 - designing abstract data types and the data structures that implement them
 - analyzing and comparing the cost of algorithms and data structures



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

SYNOPSIS

- **Parallelism**
- **Specification, Problem, and Implementation**



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

Exercise

- Prove: when using a greedy schedule on a computation with W work and S span, the runtime will be at most:

$$T \leq \frac{W}{P} + S.$$



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

求是
创新

厚学

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

LECTURE 2 SPARC



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

SYNOPSIS

- Functional Algorithms
- The Lambda Calculus
- The SPARC Language
 - Syntax and Semantics
 - Type System of SPARC
- Threads, Concurrency, and Parallelism
- Critical Sections and Mutual Exclusion



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

德厚學

求是創新



LECTURE 3

ALGORITHMIC ANALYSIS




華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

SYNOPSIS

- **Asymptotics**
- **Cost Models**
- **Recurrences**



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

Exercise

1. Prove that for all k , $f(n)=n$ asymptotically dominates $g(n)=\ln^k n$.
2. Prove that asymptotic dominance is transitive.
3. Prove or disprove the following statement:
if $g(n) \in O(f(n))$ and $g(n)$ is a finite function ($g(n)$ is finite for all n),
then it follows that there exist constants k_1 and k_2 such that for
all $n \geq 1$,
$$g(n) \leq k_1 \cdot f(n) + k_2.$$
4. Describe the conditions under which a parallel algorithm would obtain near perfect speedups.



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

Exercise

5. For each of the following recurrences state whether it is leaf dominated, root dominated or balanced, and then solve the recurrence

$$W(n) = 3W(n/2) + n$$

$$W(n) = 2W(n/3) + n$$

$$W(n) = 3W(n/3) + n$$

$$W(n) = W(n-1) + n$$

$$W(n) = \sqrt{n}W(\sqrt{n}) + n^2$$

$$W(n) = W(\sqrt{n}) + W(n/2) + n$$



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

LECTURE 4 SEQUENCE



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

SYNOPSIS

- **Defining Sequences**
- **The Sequence Abstract Data Type**
- **Array Sequence**
- **Cost Specification**
- **Examples**
- **Ephemeral and Single-Threaded Sequences**



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Excercise

1. Design an algorithm that, for each element in a sequence of integers, finds the rightmost positive number to its left. If there is no positive element to the left of an element, the algorithm returns $-\infty$ for that element. For example, given the sequence $\langle 1, 0, -1, 2, 3, 0, -5, 7 \rangle$ the algorithm would return $\langle -\infty, 1, 1, 1, 2, 3, 3, 3 \rangle$.
2. Give an example function f , a left identity x , and an input sequence a such that $\text{iterate } f \ x \ a$ and $\text{reduce } f \ x \ a$ return different results.
3. Given that reduce and iterate are equivalent for associative functions, why would we use reduce ?
4. Analyze the cost of the algorithm for generating 2D points [given above](#).
5. Present an algorithm that generates all contiguous subsequences of a given sequence.
6. Analyze the cost of your algorithm for Exercise [All contiguous subsequences](#).
7. Given sequences a of natural numbers and b of letters of the alphabet, we wish to compute the sequence that pairs each even element of a with all elements of b that are vowels.
8. To generate all composite numbers between 2 and n , prove that it suffices to consider all $i \in \mathbb{N}_i \ 1 \leq i \leq \sqrt{n}$ and all of i 's multiples up to n/i .



明

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

德厚學

求是創新



LECTURE 5 Algorithm-Design



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

SYNOPSIS

- Basic Techniques
- Divide and Conquer
- Contraction
- Maximum Contiguous Subsequence Sum



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

Exercise

- The analysis given in the example above is not “tight” in the sense that there is a bound that is asymptotically dominated by $O(|a| \cdot |b|)$. Can you improve on the bound?
- Describe the changes to the algorithms Algorithm MCS: Brute Force and Algorithm MCSS: Brute Force to implement the strengthening described above. How does strengthening impact the work and span costs?
- Prove the MCSSE Extension lemma.



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

德厚學

求是創新



LECTURE 6

Randomized Algorithms



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

SYNOPSIS

- Introduction
- Order Statistics

求是
學
創新



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

Exercise

- Consider a game in which we draw some number of tasks at random such that a task has length n with probability $1/n$ and has length 1 otherwise. The expected length of a task is therefore bounded by 2. Imagine now drawing n tasks and waiting for all them to complete, assuming that each task can proceed in parallel independently of other tasks. Prove that the expected completion time is not constant.
- Prove that the pivot tree has $O(\lg n)$ height, and is therefore balanced, with high probability.



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

PARALLEL AND SEQUENTIAL ALGORITHMS AND DATA STRUCTURES

德厚學

求是創新



LECTURE 8

Graphs and Graph Search



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

Synopsis

- **Graph and their Representation**
- **Graph Search**
- **Breadth-First Search**



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Exercises

- Prove that for a graph with n vertices and m edges, $O(\lg m) = O(\lg n)$
- What is the cost of deleting a vertex with out-degree d ?
- What is the cost of finding the out-neighbors of a vertex?
- Why does the cost of mapping over all edges require $\Omega(n)$ work?
- Give a constant-span algorithm for deleting an edge from a graph.
- Give a constant-span algorithm for computing the complement of a graph.
- Does the algorithm visit all the vertices in the graph?
- Present a multi-source version of the [single-source graph search algorithm](#).
- The computation of the new F is not quite defined in the same way as in the [generic graph search](#). Prove that the technique used here is consistent with that of the generic algorithm.
- Prove that the algorithm is correct, i.e., visits all reachable vertices from the source in the order of their distances to the source
- Prove that the queue based implementation of sequential BFS is correct.



明

Exercises

- Prove that the queue based implementation of sequential BFS is correct.
- In general, from which frontiers could the vertices in $N_G(F_i)$ come when the graph is undirected? What if the graph is directed?



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

明

德厚学

求是创新


LAB



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Entry-level Problem 4: Fast Powering



$$3^1 * 3^1 = 3^2$$

$$3^2 * 3^2 = 3^4$$

$$3^4 * 3^4 = 3^8$$

$$3^8 * 3^8 = 3^{16}$$

$$3^{20} \% 5 = (3^{10} * 3^{10}) \% 5$$

$$3^{20} \% 5 = ((3^{10} \% 5) * (3^{10} \% 5)) \% 5$$

$$\text{设 half} = 3^{10} \% 5$$

$$3^{20} \% 5 = (\text{half} * \text{half}) \% 5$$

$$3^{21} \% 5 = (3^{20} * 3) \% 5$$

$$3^{21} \% 5 = ((3^{20} \% 5) * (3 \% 5)) \% 5$$

$$3^{21} \% 5 = (((\text{half} * \text{half}) \% 5) * (3 \% 5)) \% 5$$

明

德厚学

求是创新

Entry-level Problem 6: Fibonacci

1. 更大的斐波那契数列.

首先, 这道题的数学基础是递推公式

$$\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} F_n \\ F_{n-1} \end{bmatrix} = \begin{bmatrix} F_n + F_{n-1} \\ F_n \end{bmatrix} = \begin{bmatrix} F_{n+1} \\ F_n \end{bmatrix}$$

于是我们有

$$\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} F_2 \\ F_1 \end{bmatrix} = \begin{bmatrix} F_3 \\ F_2 \end{bmatrix}$$

$$\begin{bmatrix} F_4 \\ F_3 \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} F_3 \\ F_2 \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \left(\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} F_2 \\ F_1 \end{bmatrix} \right) = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^2 \begin{bmatrix} F_2 \\ F_1 \end{bmatrix}$$

递推下去, 我们得到


$$\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^{n-1} \begin{bmatrix} F_2 \\ F_1 \end{bmatrix} = \begin{bmatrix} F_{n+1} \\ F_n \end{bmatrix}$$

那么如何计算矩阵的幂呢? 我们应该已经写过计算整数的高次幂的算法, 只需要把传入的参数类型从无穷精度整数换成矩阵, 并且把对应的整数乘法换成 (2×2) 矩阵乘法即可完成。

科技大学

SITY OF SCIENCE AND TECHNOLOGY

Entry-level Problem 20: Promoted Pawn



$$F[I, J] = 0 \{ G[I, J] = 1 \}$$

$$F[I, 0] = F[I-1, 0] \{ I > 0, G[I, 0] = 0 \}$$

$$F[0, J] = F[0, J-1] \{ J > 0, G[0, J] = 0 \}$$


$$F[I, J] = F[I-1, J] + F[I, J-1] \{ I > 0, J > 0, G[I, J] = 0 \}$$

華中科技大學

HUZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Med-level Problem 2: Shortest-Path

- Adjacency Matrix



	0	1	2	3	4	5	6	7
0	∞	∞	∞	∞	∞	∞	∞	∞
1	∞	0	∞	∞	3	∞	1	∞
2	∞	∞	0	∞	2	∞	∞	1
3	∞	∞	∞	0	3	∞	4	3
4	∞	3	2	3	0	∞	∞	∞
5	∞	∞	∞	∞	∞	0	3	5
6	∞	1	∞	4	∞	3	0	∞
7	∞	∞	1	3	∞	5	∞	0

Med-level Problem 2: Shortest-Path

• Dijkstra Algorithm

因为题目明确给出各个边的权值非负，因此我们可以放心的使用 Dijkstra 最短路径算法，从源点不断向外扩张，直至能够以最短路径到达并标记到所有的节点，对于无法到达和标记到的节点，用默认的 -1 值来初始化即可。在给出伪代码之前，我们不妨证明一下该算法的正确性。

Dijkstra 算法主要由以下几步构成


- 找出未标记过的离源点最近的点 (如果没有的话，便回退)
- 以该点为中心点更新该点周围的点 (更新方法为取最小值，一开始将所有点到源点的距离都初始化为无穷大)
- 一直执行，直到找到所有的点，将未更新过的点改为 -1 ，表示无法到达。

该算法主要基于一个性质：一个最短路径的任意子路都是最短路径。证明如下

证明. 假设最短路径 p 有一条子路径 q 不是自己起始点之间的最短路径，那么必然存在一条 $q < q'$ ，将 q 替换成 q' ，得到一条新路径 $p' > p$ ，与 p 是最短路径矛盾，故该性质成立 \square

Med-level Problem 2: Shortest-Path

- Dijkstra Algorithm



Med-level Problem 3: Longest parenthesis distance

Algorithm 3: The Longest Distance

Data: S : 被处理过的序列 (即每一个原始数据前加上下标形成 (i, x_i) 的形式 ts : 存储的左括弧值, m : 当前的符合要求的最大值)

Result: m : 最大括号距离

```
1 TheLongestDistance  $S( \langle (0, x_1), (1, x_2), \dots \rangle ) =$   
2 let  
3   match  $(i, x), (ts, m) =$   
4   if  $x = 0$  then  
5     |  $(i ++ ts, m)$   
6   else if  $|ts| = 0$  then  
7     |  $([], m)$   
8   else  
9     let  
10      |  $h \leftarrow \text{hd } ts$   
11      |  $ms \leftarrow \max(m, i - h + 1)$   
12      |  $rem \leftarrow \text{tl } ts$   
13      in  
14      |  $(rem, ms)$   
15      end  
16   end  
17 in  
18   second reduce match  $([], 0) S$   
19 end
```


明

結

Med-level Problem 4: Skyline

Algorithm 4: The skyline solving algorithm

Data: $B_s = \langle (l_1, r_1, h_1), (l_2, r_2, h_2), \dots, (l_n, r_n, h_n) \rangle$

Result: $[(x_1, y_1), (x_2, y_2), \dots]$

```
1 Skyline  $B_s =$ 
2 if  $|B_s| = 1$  then
3    $[(l_1, h_1), (r_1, 0)]$ 
4 else
5   let
6      $len \leftarrow \frac{|B_s|}{2}$ 
7      $B_l \leftarrow \text{Skyline } \langle (l_1, r_1, h_1), (l_2, r_2, h_2), \dots, (l_{len}, r_{len}, h_{len}) \rangle$ 
8      $B_r \leftarrow \text{Skyline } \langle (l_{len+1}, r_{len+1}, h_{len+1}), \dots, (l_n, r_n, h_n) \rangle$ 
9   in
10    merge  $B_l$   $B_r$ 
11  end
12 end
```


大學

AND TECHNOLOGY

明

Med-level Problem 4: Skyline

- How to merge?




華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Med-level Problem 6: Arbitrary-Precision Arithmetic

- **BigNum x Integer**
— (1337 x 42)




华中科技大学

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Med-level Problem 6: Arbitrary-Precision Arithmetic

- BigNum x BigNum

$$1337 \times 42 \\ = 10 \times (1337 \times 4) + 1337 \times 2$$



Med-level Problem 7: Cut-Vertex & Cut-Edge

- Tarjan Algorithm

Algorithm 9: Tarjan 算法

Data: u : 节点, v : u 的子节点 (即存在一条边使得 u 能到达 v)

Result: ce : 割边, cn : 割点



```
1 Tarjan  $u =$   
2 Initialization :  $dfn[u] = low[u] = ++Index$   
3 Stack.push( $u$ )  
4 foreach  $(u, v) \in E$  do  
5   if  $v$  is not visited then  
6     Tarjan( $v$ )  
7      $low[u] = \min(low[u], low[v])$   
8   else  
9      $low[u] = \min(low[u], low[v])$   
10  end  
11  /* 接下来开始判断割边和割点 */  
12  if  $low[v] = dfn[u]$  then  
13     $cn \leftarrow cn + 1$  if  $u$  is not counted  
14  end  
15  if  $low[v] > dfn[u]$  then  
16     $cn \leftarrow cn + 1$  if  $u$  is not counted  
17     $ce \leftarrow ce + 1$   
18  end  
19 end
```

*/

明

Med-level Problem 8: Non-update Range Min/Max Querying

- Sparse Table
- Exists an integer s , such that arbitrary interval (l, r) can be written as $(l, l + 2^s - 1) \cup (r - 2^s + 1, r)$



Med-level Problem 8:

Non-update Range Min/Max Querying

Algorithm 10: RMQ 的 ST 解决算法


Data: $F[i][j]$ 表示在 sequence $\langle a_0, a_1, \dots, a_n \rangle$ 中从 i 开始长度为 2^j 的最大值, 其中 $F[i][0]$ 就是 a_i 本身, N 表示输入的串 S 的长度, S' 表示查询的串, 其元素为 (x_i, y_i) 表示查询从 x 到 y 的最大值

Result: 一系列查询到的值

```
1 preprocess S=  
2 while  $i < N$  do  
3   for  $j$  to  $i + 2^j - 1 \leq N$  do  
4      $F[i][j] \leftarrow \max\{F[i][j-1], F[i + 2^{j-1}][j-1]\}$   
5   end  
6 end  
7 querySequence  $S' =$   
8 let  
9   query  $(x, y) =$   
10  let  
11     $k \leftarrow \lceil \log_2(y - x + 1) \rceil$   
12  in  
13     $\max\{F[x][k], F[y - 2^k + 1][k]\}$   
14  end  
15 in  
16   map query  $S'$   
17 end
```


Med-level Problem 8: Non-update RMQ

- Segment Tree



Med-level Problem 9: Prime Query

- Fermat's Little Theorem (Th.1)

$$a^p \equiv a \pmod{p}, \quad p \text{ 是一个素数}$$

- Select several base numbers $a < p$, if $a^p \bmod p = a$, then p might be a prime number
- Quadratic Probing (Th. 2)

如果 p 是一个素数, $0 < x < p$, 则方程 $x^2 \equiv 1 \pmod{p}$ 的解为 $x = 1$ 或 $x = p - 1$



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY

Med-level Problem 9: Prime Query

• Miller-Rabin Algorithm

Algorithm 11: Miller-Rabin 算法

Data: n : 待检测数 $n \geq 2, (s, t): n - 1 = t \cdot 2^s$

Result: bool 值表明是否为素数

```
1 Miller-Rabin  $a\ n =$   
2 if  $n = 2$  then  
3   | True  
4 else if  $(x < 2) \vee (x \text{ is even})$  then  
5   | False  
6 else  
7   | let  
8     |  $at \leftarrow a^t \bmod n$   
9   | in  
10  | twicejudge( $s, at$ )  
11  end  
12 end
```


明

试题类型

- 是非题 (约 $6*3$)
- 简答题 (约 $6*5$)
- 复杂度计算 (约 $2*6$)
- 计算证明题 (约 $1*12$)
- 算法题 (约 $1*12$)
- 实验题 (约 $1*16$)



華中科技大學

HUAZHONG UNIVERSITY OF SCIENCE AND TECHNOLOGY