

## KPIs and Experimentation

### Day 1 Lab

#### Transcript:

for it excited you check out

55:39

the lab what I want you to do is make sure you're on the latest version of the codebase uh pull pull from Main if

55:45

you're not you're going to need to uh set this uh stat Sig API key environment

55:51

variable if you have not done that um I can show you all how to do that if you um

55:57

uh like later on like hopefully hopefully you all have some experience of setting an environment variable but

56:03

so flask is a way of building out a web server so what I want to uh do is first

56:11

I want to show you all how to set this up so let me um open Terminal real

56:19

quick okay

56:27

okay so I want to be in uh here and the whole idea here is I if if you do um

56:34

Python and then you do Source server.py this is going to set up you see how it

56:41

says running on this uh domain if we go to that uh domain you'll see like hello

56:47

this is a flask API so that's essentially uh this is like the hello world sort of web server and what you

56:54

can do is what I want to show show you though is if I go to tasks right you'll

57:00

see that I'm like okay it's saying experiment group Green and then it's saying odd tasks for blue and green even

57:06

for red and orange so that's probably wild right and you'll see like I have a

57:11

a user identifier here so this is all based on configurations from stat Sig

57:19

and this is an experiment I'm doing uh called like button colors or something like that and uh we're going to go over

57:26

in more details how this works from stats Sig but let's kind of like walk through that code real quick first so

57:34

you'll see here uh we have this um app. route uh it's on line 33 here uh this

57:41

tasks route which is going to be what supplies this uh this link for this web

57:46

server and then uh you'll see we essentially are trying to figure out the way to get the the hash string so you'll

57:56

see uh one of the hash strings uh the initial H hash string is based on the remote Adder so this is going to be like

58:03

your IP address essentially and then uh this is essentially saying uh we can

58:08

also specify random and what random does is it will change our user ID so if I

58:14

say question mark random equals true then I will be assigned like a different

58:19

group right you see how like that's probably kind of nuts right you see how like because now that my user ID is

58:25

essentially set at random and I'm not uh my logged out user ID is just a random

58:30

number now and so I I'll get assigned a random group right but you see if I if I

58:36

don't put random my IP address I always consistently get green and that's like

58:41

kind of what you would expect so let's kind of go over how to build out this experiment and I'm going to essentially

58:47

make another version of this experiment so that y'all can um go ahead and start with

58:53

me okay so this is uh you see if you

58:58

made your account on stat Sig this is kind of like the stat Sig uh API or like

59:04

the stat UI that uh it's pretty cool um if we go in and you'll see over here on

59:10

the left there's like a bunch of different options here there's like feature Gates experiments metrics all

59:15

sorts of really cool stuff here I'm very happy that I integrated with stat Sig but so if I go to experiments I'm going

59:22

to show you first the experiment that I made and then I'm going to create new one to show you how to make your own so

59:28

you'll see in experiments here we have button color V2 and saying we're refreshing your

59:36

pulse results okay whatever uh it's like taken a million years so uh you'll see

59:43

we have um so this this is the experiment so as you see like see this button color V2 the name here if you go

59:50

look in the code base here you see this like line 40 here you see this like stats

59:56

.g experiment and then I pass it a stat Sig user and then I pass it button color

1:00:02

V2 and then I want to get the attribute button color and then uh this is like

1:00:07

the default value if for some reason the user can't be put into an experiment so let's go to setup real

1:00:14

quick because I think that is probably a little bit confusing okay so what we are looking at

1:00:20

here is initially this is how it works right so uh you you want to and yeah but

1:00:26

you can't edit edit any of the parameters okay because once you start an experiment you can't edit any of

1:00:33

these things it's like it's like set essentially so here's how it works right

1:00:38

remember how I was talking about like okay what percent of users are going to be allocated to this experiment and then

1:00:44

uh I say okay 100% so we're saying and then it's like 100% of what users so you can say like 100% of chrome users 100%

1:00:51

of Android users 100% of all users right and then you have to split you can uh

1:00:58

and this is your split between all your groups and uh in this case I have four

1:01:03

groups I have control is blue you have uh test is red or test one is red test

1:01:09

two is green and test three is orange so that's those are the three tests and

1:01:15

groups and this is essentially how this experiment works and um and this will essentially go ahead

1:01:22

and collect data and we'll have data here and this like pulse uh results some

1:01:28

of this stuff we won't actually end up doing because this is like a local web server and we can't collect as much data

1:01:34

but that's the whole point here as data Engineers my whole point here is I'm trying to teach y'all how experimentation Works underneath the

1:01:41

hood so that you can like have a better appreciation for how things get split up

1:01:47

so if we go back to the experiments tab here and uh what we want to do is we want to hit create we want to hit this

1:01:52

blue create button and I'm going to call this button color uh let's going to call this button color V3 and then I'm going

1:01:59

to say I think the red button the red button

1:02:05

is is the best one all right and then uh this is where remember I was talking

1:02:11

about like you can either use user ID or stable ID uh you can use either one here um I would say user ID because if you

1:02:17

pick stable ID the problem is is like since it's local you're only going to

1:02:22

get assigned one group and then you're done like that's all that there's nothing else you can do about it but um

1:02:29

if you pick stable ID then that's what and normally that's fine because like if you're a different user you'll be on a

1:02:36

different device and a different location but like for us we want to have control over the user

1:02:41

IDs so we're going to hit create awesome so now we have our uh kind of experiment

1:02:49

kind of set up um one of the other things you need to do is you want to think about the metrics that you could

1:02:56

uh potentially be looking at right and so these are uh like there's a bunch of

1:03:01

metrics that statti gives you for free like uh daily active users I14 I28 all

1:03:07

these are like very um kind of baked into the platform you'll see some of these like I have like user confirmed

1:03:13

successful and sign up successful and visited sign up these are uh uh custom

1:03:19

events that I added into stats Sig and uh I'm going to show you how you can we're going to log our own events as

1:03:25

well so in this case what I want to look at is I want to look mostly at daily active

1:03:31

users so you have to pick a metric here so what I'm saying is like I don't know I think that the red button is the best

1:03:37

one and then you know the the null hypothesis in this case is that color doesn't impact things

1:03:44

so then uh if we go down here you'll see we have our and originally it it breaks

1:03:51

it out into see how it breaks it out into groups and then we have test and control

1:03:56

and what I want to do is I want to add a parameter here and we're going to call this button color we're going to add so

1:04:03

then uh control we're going to say is blue and test we're going to say is red and say we want more groups you can

1:04:10

click this plus over here and then I can say green and I can hit plus again and I can say orange and so now we have

1:04:18

essentially uh an experiment that's going to run that is an even split 25 25

1:04:24

25 25 between blue blue red green and orange and we can see how that impacts our metrics the metric that we are

1:04:31

caring about is daily active users obviously let's let's throw in another metric here uh let's say let's do um

1:04:38

visited sign up let's add that metric as well and so uh this is pretty much ready

1:04:46

so what you want to do next here is you want to hit save always remember save like save

1:04:51

always messes me up so now since we have defined our Hy hypothesis right we have our primary

1:04:58

metrics we're looking to track we are we have defined our groups and we can uh

1:05:03

keep in mind each group can have its own parameters right I might add like U maybe I can add like paragraph text

1:05:10

right and then I can be like uh you know data engineering boot camp and then here

1:05:16

I can be like data engineering self-paced course and here are going to be like data

1:05:22

engineering uh I don't know Academy and here I can be like that I could also

1:05:28

put like de um boot camp and because maybe people don't like to read all of

1:05:33

it and they like the abbreviations but like you can see you can add whatever other uh parameters you want to each uh

1:05:41

version of this so that like you can imagine that I could swap out different titles with this or different paragraphs

1:05:47

of things this way so I'm going to hit save here before we hit start so okay so now we have uh our our

1:05:55

experiment is essentially ready to go uh the only other thing we need to do here is we want to hit start and then and

1:06:03

then it's going to yell at us cuz uh you haven't tested your experiment in a non-production environment yet and um

1:06:09

obviously you can you can do that if you want to test stuff uh I'm just going to hit launch though it's uh it's

1:06:17

fine okay so we have launched great and so now what we want to do is let's go

1:06:24

back into pie charm and yeah on line 40 here we can change button color V2 change this the button

1:06:31

color V3 right and then I also want to get the

1:06:36

uh I want to get the paragraph text or the title text we call this title

1:06:42

text uh par no it's called paragraph text right that's what I called it in the paragraph text and then this is

1:06:49

um paragraph text then in here I'm just going to say data engineering boot camp

1:06:58

and so uh now I have my paragraph text and I want to add this paragraph text just as

1:07:05

um as another um HTML element here I'm going to put it here paragraph text I

1:07:12

don't know if y'all have uh ever written some HTML just saying in the lab or in

1:07:17

the homework for this week y'all are going to be doing some of this stuff so you'll see I switched to uh button color

1:07:24

V3 and I have my data engineering boot cap as my um this is essentially the

1:07:30

default if for some reason stat Sig can't put a user into a group it will

1:07:36

just use that paragraph text so now if we go back here and we refresh so you

1:07:42

see now it's saying data engineering self-paced course right but I'm going to be forever in red because of this is my

1:07:48

user identifier and now I'm in red forever but obviously if you throw on random equals true you can see how this

1:07:55

will uh essentially swap like whatever group I'm

1:08:00

in and so this is kind of the idea behind how this stuff works is you have

1:08:08

um uh different groups and this assigns and then you have a different experience

1:08:13

depending on the user that you are and the user that is kind of working with

1:08:20

this stuff so how does this like so okay cool y'all are probably like wow Zach

1:08:26

you made uh different colorful images show up in the lab today but it's like how does this make any difference in uh

1:08:34

experiments like so well on one side we now are tracking daily active users so

1:08:40

we will know whether or not someone's daily active just based on whether or not they hit this uh URL and then that's

1:08:47

automatically logged in stat Sig um but we we need more right we need to see

1:08:53

like okay if they go here do they actually visit another page so you saw

1:09:00

how we had that uh we're tracking that other um metric you see this visited

1:09:05

signup we probably want to track that metric as well so that's going to be the

1:09:11

next thing that we want to do is we're going to add another metric into this another event that so that we can track

1:09:17

that and we can see what happens as things kind of uh progress as we're

1:09:23

adding more metrics and more engagement to this if we go back to pie charm one of the things is is what we want to do

1:09:31

is you'll see there's a bunch of different routes and stuff for this API and you see this like Hello World

1:09:38

route so you want to essentially copy lines 28 to 30 and then paste it again

1:09:46

and then what you want to change here is this backslash make it back slash

1:09:52

signup so now this is going to be and then you want to change the string in here to be like this is the signup

1:10:01

page so uh oh yeah sign up page we'll put it all one word there so so now what

1:10:06

this is going to do is this GNA this is going to give us another web page on our server that we can look at so if we go

1:10:14

here and then we essentially go to instead of back slash tasks we go to back SL signup you can't have you got to

1:10:20

change this from Hello to sign up that's why because we have two functions with the same name so now now now flask won't

1:10:28

be mad at us um okay so now it's working in Safari and I'm going to put that signup route back because it was right

1:10:35

so now um for some reason it wasn't working but now if we put sign up

1:10:41

here see now this is the signup page great but we probably want to put a route in the other page as well so um I

1:10:51

don't know if y'all have ever done like so in this get tasks function you'll see this ends up rendering a lot of like

1:10:57

HTML what I want you to do is at the bottom here we're just going to say um we're going to make an a tag and you

1:11:03

want to use an href here uh if y'all have worked with HTML this is going to we're just going to say inside here

1:11:09

we're going to say go to sign up and then in the href here we're going to just put back slash signup and I'll show why



1:11:16

we want to do this so um so that we can kind of have a a better time here so

1:11:22

let's go back to tasks okay okay so you see uh wow blue

1:11:27

is really hard to read okay but like you see down here this says like you see

1:11:33

this like there's this go to sign up page that you can click and this this links back over to the sign up page kind

1:11:38

of the basic sign up page so this is kind of the idea right is okay green is way easier to read so then we can say go

1:11:45

to sign up great now we are at this new sign up page and so this we want this

1:11:52

action to be logged so that we can see like okay if people go to this tasks

1:11:58

page how many of them click on this link and actually follow up so that's going to be our first thing that we want to do

1:12:05

and the way that you do that is with um so stat has another um so we say like

1:12:13

stat Sig then we got like there like log event and then in this case we have uh

1:12:21

visited sign up and uh but we need to get our stat Sig user so in this case

1:12:29

our stat Sig user is going to be based on um like it's going to be based on the

1:12:37

same sort of Randomness or it's going to be based on the same user ID from uh all of this stuff so uh if you copy the

1:12:46

lines what 41 to 45 here this will give us our user ID that's going to be the

1:12:51

hash and then then we have our stat Sig user stat Sig user is going to be stat

1:12:58

Sig user user ID so now this will be our logged stat Sig user and then you just

1:13:04

have to pass him in here as kind of a that's that's right I'm pretty sure

1:13:11

like so and then that will log the event for that specific stat Sig user so what

1:13:16

we want to do is go back up to the server here and we need to import that um so we can say from stat sig. staig

1:13:24

event import stat Sig event that's so lame

1:13:29

that's the way that you have to do it so in this case uh then we're going to have a stat Sig

1:13:34

event in this case that's going to be a new stat Sig event and then inside here there's going to be a user and that's

1:13:41

going to be a stat Sig user and then we have a event name that's going to be

1:13:48

visited sign up and then this is and then you pass it

1:13:54

in all together like that that's how it that's what it's expecting so this is going to be our

1:14:01

kind of way that we're going to be adding more code into uh the signup page

1:14:06

and this will give us our event logging that we're looking for so now uh I'm

1:14:11

pretty sure if I like hit sign up again there we go so now we're actually getting uh like actual event logging

1:14:18

here that you would expect um so this is now we have our signup page and then we

1:14:24

have our tasks page right because we go to tasks okay we're in the orange group

1:14:29

you go to sign up boom and then so now that is going to be a logged event so we

1:14:36

should be able to see that actually if we go to button color V3 should be able

1:14:42

to go to like Diagnostics okay there we go so you'll

1:14:47

see in um stat Sig we have uh these are going to be all of the exposures of

1:14:53

different users right and you'll see a lot of them were like the those random users that I was implementing before

1:15:00

with that um question random equals true so these are going to be all these users that were exposed to our um different

1:15:09

kind of logging or or to our different uh in tests right so you see like okay this user got test two this one got

1:15:15

control this one got test so you can get all sorts of different uh rules and uh

1:15:22

splits that for users and you can see EX exactly how they're going to come in this way um and then if you go to the

1:15:28

metrics tab one of the things that you should see here is oh there's going to

1:15:34

also this is going to also have all of like my websites metrics in it too right

1:15:39

yeah okay that's not it's not going to be there is is there one in here that's going to work does this have like metric

1:15:45

lift at all okay okay I forget staing does take a little bit of time before

1:15:51

you can actually see any of the um the actual metrics involved with stuff it

1:15:57

takes like a little bit of time to like like log and show metrics so um that's

1:16:03

kind of the idea behind how these metrics and these uh things are set up

1:16:09

one of the things that's important to think about is when you're building out like apis and stuff like that is okay

1:16:17

when is stuff logged and like so for example in this case one of the things

1:16:22

that you might be uh that might be interesting here to y'all is that this

1:16:29

is going to be logged on the server side as opposed to being logged like in the HTML because you could also put like an

1:16:35

onclick here you can put onclick and then you could put like a function in here like bust out JavaScript in in

1:16:42

python or whatever but like I don't recommend that but um that's like you could also potentially put the logging

1:16:48

on the client side so that it happens before you even hit the signup page because that can be another way to uh

1:16:56

kind of log stuff and so you can do client side logging and server side logging and they have their different uh

1:17:03

benefits and risks right so serers side logging is generally easier to set up like you saw how I set this up in like I

1:17:10

don't know like five seconds um and so that is the great thing about servers side logging client side logging is a

1:17:17

little bit trickier because of the fact that uh we don't want like and here's the problem with client side logging is

1:17:23

we don't want to give random clients the ability to just log

1:17:28

whatever they want to our servers so you have to do this thing called like OA like uh OAuth like um authorization with

1:17:36

your client which like is a little bit more complicated uh but the thing is is

1:17:41

like you also get better Fidelity data that way because you get the you get the

1:17:46

event when they clicked and like when they did the action in the client not when the server picked it up so like you

1:17:53

actually get like better events and higher quality events and like you also can get things like scroll time and like

1:18:00

uh view time and like I know at Facebook they have this this notion of this thing

1:18:06

called time spent which is like how long someone is spending in the feed and that could be another uh powerful thing for

1:18:13

people to work with uh and that time spent is mostly a client side uh logging

1:18:19

kind of mechanism and all those metrics can be very important for experimentation as well

1:18:25

so this is kind of the idea right is you want to set up uh your servers to do

1:18:31

both and generally speaking you want to start with doing uh server side logging

1:18:37

because it's like it's just easier just so much easier and then uh after a while

1:18:43

what you can do is you can set up other sort of things right so one of the things I don't know if y'all saw but if

1:18:49

you go to like Zack Wilson. Tech and um I'm currently running an experiment here

1:18:54

on this sign up button so this sign up button uh for some people is red and for some people it's blue depending on uh

1:19:02

like who you are it's the way I have it set up right now is it's 80% red 20% blue and so that's just uh something to

1:19:09

to see and uh definitely know that that's like a thing that's happening but uh let me show you how that works

1:19:16

because for that experiment like I actually didn't use I didn't run an experiment with it what I did was I used

1:19:22

what's called a feature gate so there's a couple differences there um feature gate one of the big things about

1:19:28

it is like you don't get groups you only get a yes or a no and in this case I

1:19:35

have like red or blue which is also just if you have two outcomes then like you can use a feature gate as well and

1:19:41

feature Gates can sometimes be uh simpler to work with than experiments because feature Gates don't have like

1:19:47

you'll see like when you're in this feature gate page you'll see there's no like make a decision and you can also

1:19:53

edit things like as whenever you want whereas experiments like are a little bit more like controlled where you have

1:19:59

to just like they have to be fixed at a certain time but feature gates are awesome especially like you know how I

1:20:05

was talking about those long-term holdouts of like people who don't receive notifications on Facebook or

1:20:11

different sort of things like that so what you get in this case is this is going to be my uh kind of homepage show

1:20:18

new homepage which which it's just filtering that that button right so you see the split here so we have like 80 %

1:20:25

uh means the 80% gets red and 20% gets blue and obviously I can change this I

1:20:30

can make this 50% if I wanted to and then that's not going to that's going to just that's going to be fine and that

1:20:36

will like and it will just it will just change the environment of the thing but

1:20:42

the idea behind this is you can also kind of do longer term experiments here

1:20:47

so let me let me show you what I mean by like okay so here's my uh here's the results so I set this up like two

1:20:54

days ago I think yeah August 11th I set this up on like on it was like more on Saturday but so in that time in the last

1:21:02

two days there's been uh like 2700 people who have like been part of this

1:21:08

experiment uh in the last like two two two three days and we don't have

1:21:13

Monday's data yet but uh you'll see like it's keeping that nice like 8020 split

1:21:20

like so what that means is 2200 people have seen the red button and 500 people

1:21:27

have seen the blue button and it's keeping that nice 8020 split that we're expecting um so this is where you get

1:21:36

more data behind like statistical significance so one of the things you'll notice here is um for our 90% confidence

1:21:46

interval you'll see that like every single bar overlaps zero so if any of

1:21:53

these bars overlap zero what that means is like the effect could be negative or

1:21:58

positive like we don't know and so uh that's like kind of uh like frustrating

1:22:05

but like what what essentially that means from this experiment so far is

1:22:10

that it doesn't matter that much right red versus red button versus Blue Button does not matter that much but you'll see

1:22:17

like I can go in here and I can edit this confidence interval so let me show you like what the difference here is

1:22:23

let's go to 80 % confidence interval and you'll see okay with the 80% confidence

1:22:29

interval now we have a statistically significant result we have this guy here uh this uh visited signup but um because

1:22:38

its P value is 0.17 and that's less than 0.2 uh but

1:22:43

like most data scientists might look at this and be like I don't know if I can trust that because there still is like almost a 20% chance that this could be

1:22:50

random and so that's a thing to remember when you're like interpreting these results is that the the confidence

1:22:58

interval matters quite a bit and so generally speaking you want it to be set to uh 95 so you see how this is like

1:23:06

Alpha equals .2 Alpha equals .05 that's essentially the probab Alpha is the

1:23:12

probability that you're wrong the probability that you are saying that this is not a coincidence when it

1:23:18

actually is a coincidence and that's where uh the the the the 95% confidence

1:23:24

interval generally speaking is the better play but one of the things that

1:23:29

uh I want to show as well though is these things aren't necessarily uh just you can look at

1:23:36

things more specific right so for example this one this like so you see

1:23:43

this is a not this is that visited signup not a stat a statistically significant result and you'll see like

1:23:49

okay even if you group it by different countries like you see okay Canada Great Britain India they're all not

1:23:55

statistically significant but if we drop this to 80% the only reason I'm doing this is to show y'all like kind of uh

1:24:02

how things can be different here though but you see okay so now this experiment that like is statistically significant

1:24:09

overall it's actually not statistically significant in India and it's not

1:24:15

significant statistically significant in Great Britain but apparently the US and

1:24:21

Canada they just freaking love they just the US in particular really loves like

1:24:26

red buttons right this is almost like you almost can get you can almost use 0.9 as your uh confidence interval like

1:24:33

a 90% confidence interval for the us but you'll notice that like for India and Great Britain like the color really does

1:24:39

not matter and so uh that's one of the things to think about when you are also

1:24:45

running your statistical tests is is there actually an underlying population

1:24:52

where things might be different where things might be like for example maybe I

1:24:57

run a test where instead of putting my prices in dollars I put my prices in INR

1:25:03

and if I put my prices in INR like I would imagine uh it would hurt the us and it would help India so like that's a

1:25:11

just a you know an obvious like duh sort of example that would have a like of an

1:25:16

experiment that would have a very strong impact on like a a a certain slice of

1:25:22

your users and in probably a detrimental Slice on another set of users and so

1:25:29

that's a thing to think about when you're like building out this kind of stuff is when you're running experiments like you might not get like a clean

1:25:36

thing where it's like okay yeah overall we get a a a bump but like for some

1:25:42

users it might be a drop and for other users it might be a gain it's not always

1:25:47

like a a clean and cut like everybody wins and it's always a better exper

1:25:53

exper experience for everybody so that's a another thing to think about when you're kind of like building out

1:25:59

different things so that's what so feature gates are really powerful in that way and uh and they can do some

1:26:05

really some really good stuff one of the things that I I I just wanted to kind of end with here with experimentation is

1:26:14

that experiments are going to be one of the most important ways to have impact

1:26:19

as a data engineer and It's tricky because of the fact that

1:26:25

when you are doing experimentation and setting stuff up and like getting this far where you end up having these like

1:26:33

actual Pages where you can look at stuff is like it's very far removed from the

1:26:40



actual data engineering job and like that's one of the things that like I think will change in some regards and

1:26:47

I'm hoping that some of y'all you picked the analytics track and I'm I'm my uh

1:26:52

understanding is that some of y'all that picked the analytics track actually your goal might be to be more of like an

1:26:58

analytics engineer or a data scientist or like another kind of role like that and that's where like having this

1:27:04

knowledge can be very useful but it can also be very useful for data Engineers as well because it's like okay what

1:27:11

metrics like what other numbers do we need in these charts like this so that

1:27:16

uh data scientists can have a clearer picture of their experiments so like

1:27:23

that's one of the big things that they do in big Tech right so this is one of the things that Airbnb is kind of like

1:27:28

uh like leading the way on is they have this thing called manura which is like a metric repository of all the metrics

1:27:35

that like Airbnb could care about and then an and so then in an experiment you

1:27:40

can have all these metrics and one of the things that uh you can do with some of these metrics so if I go to metrics

1:27:46

and let me go to like visited signup so if I go into this metric here and I go

1:27:52

to um setup here uh there should be a way isn't there a way to do

1:27:57

it you can't do it in here oh that's lame okay well anyways uh most metrics

1:28:04

have a way of being what's called uh is it metric catalog go here I think this

1:28:10

is where it is okay so you can catalog metrics and then I think in here you can add manage tags there we go there we go

1:28:17

so like in here you can create a new tag and then we can say like guard rail right so

1:28:24

um these are all the metrics that should never go

1:28:30

down right okay so now I have my tags and uh I have this tag for guardrail and

1:28:36

now that will be what we can use for our different metrics catalogs and you'll see now if I add that to here I can be

1:28:44

like guard rail metric and then I can add another guard rail metric so what guardrail metrics do is they are metrics

1:28:51

that are so important to the business that like if uh if an experiment causes

1:28:56

these numbers to go down that experiment is essentially blocked from deploying um

1:29:02

for example uh at uh at Airbnb uh uh the guard rail metric that I worked on was

1:29:08

reservation profitability so it's like if we have an experiment that significantly drops uh profitability

1:29:15

then that experiment probably is not going to launch that that's not a like that's a that's a nogo right and so

1:29:23

that's and that is where um data Engineers can actually have a very

1:29:29

important impact and play a very important role in experimentation is if

1:29:35

your company has the notion of a guardrail metric that metric can be owned essentially by you as a data

1:29:41

engineer or an analytics engineer and that is it's essentially a way to

1:29:46

prevent data scientists and product Managers from like going too wild and

1:29:52

doing all sorts of crazy because like you don't want them to do that right because if they are doing crazy stuff like like that's going to hurt the

1:29:58

business and it's going to hurt these metrics and so and you don't want them to do that like that's not like a that's

1:30:05

not a that's not a solid way to to go about doing stuff you know and so I I

1:30:10

would recommend in those cases to uh like really invest in quality because

1:30:16

that was one of the things that was the problem with uh like with guard with guardrail metrics when you create them

1:30:23

they have to be very high quality right you can't have crazy quality bugs in your gandom metrics cuz like they're

1:30:29

going to stop experiments right they have to be very trusted so like they're G to they have to have very high quality

1:30:35

they also have to be very fresh because you can't have like your guard rail data being behind where where you have your

1:30:43

data scientists who needed to determine do I do I launch this experiment do I not launch this experiment right you

1:30:49

have to do that as well and like if you do that like okay like how do you have like a a regular ly

1:30:55

refreshing uh metric that is a guardrail metric that people can use that will

1:31:01

then prevent them from launching bad experiments and making bad decisions and that's where I I'm hoping that between

1:31:07

like weeks three when we were talking a lot about um uh data quality and talking

1:31:14

about like how to have high high high data quality using things like write audit publish and then in week four

1:31:19

we're talking about like analytical patterns where you have those State change patterns those state change patterns are very often guard rail

1:31:25

metrics where you don't have you don't want to have too many users churning you also don't want to have too many users

1:31:31

who are uh like stale or like too many or too many fake accounts that are

1:31:37

coming in right there could be all sorts of different uh things that can happen that can make guardrail metrics uh very

1:31:43

important for launching experiments so that's the kind of the last thing I wanted to talk about at least in this

1:31:48

kind of UI and how you can kind of catalog these different metrics into different buckets of things congrats on

1:31:54

getting to the end of the day one lab if you're taking this class for credit make sure to switch over to the other tab so you can get credit

