CONTEXT INTEGRITY SOK · RESULTS REVIEW

Reuniting Adversarial and Incidental Poisoning of LLM Agent Context Windows

A Systematization of Knowledge. RQ1 to RQ7 are complete.

1,158 papers screened · 1,026 included · 237 mechanisms · 534 defenses · 16 cells we ran ourselves

THE ROADMAP

Seven questions, then the experiments

RQ1	**Taxonomy**	60.5% of the cube is empty
RQ2	**Cross-citation**	11.7% / 9.1% between tracks
RQ3	**Pollution census**	223 named mechanisms
RQ4	**Defense census**	534 named defenses
RQ5	**Coverage matrix**	119 mechanisms never defended
RQ6	**Generalization**	9 reconstructed case studies
RQ7	**Open problems**	7 ranked, falsifiable
NEW	**Transfer matrix**	16 cells that no paper reports

METHODOLOGY

Kitchenham SLR + PRISMA-lite screening, run across two literatures instead of one

Search

We searched two tracks at the same time. One track is
adversarial. One track is incidental. We found 25,922 records.

Screen

The rules are in config.yaml.
A program applies them.
We do not screen by hand.
rescreening_log.md records
each change.

Extract

We read the full text of 1,097 papers. We code 32 fields for each paper.
Channel and consequence use closed lists.

Synthesize

We join the registries into the coverage matrix. Then we run the defense code ourselves. We do not use the numbers in the papers.

What the numbers are computed over


1,026
papers included

1,158 rows screened; 132 excluded with cause

rescreening_log.md records each exclusion.
It gives a reason for each one.

In September 2026 we found a defect in the rules. The rules looked for the word "agent". The first papers in this field do not use it. They say "LLM-integrated application". The rules dropped them. The corpus went from 1,008 to 1,158.

Which combinations of channel, intent, and consequence have been studied at all?




98 of 162 cells

9 channels × 3 intents × 6 consequences

Before the fix, 63.6% was empty.
The 150 new papers filled five cells.
They left 98 cells empty.

Where the work actually sits



Named mechanisms for each channel. direct-input and tool-output are equal.

RQ2 · CITATION NETWORK

Two literatures. Do they read each other?

Security → cites ML/AI

70 of 599 papers

11.7%

ML/AI → cites Security

37 of 407 papers

9.1%

Nine of ten papers do not cite the other track.

The corpus grew by 150 papers. The rates did not change. The split is structural.

How many distinct ways can a context be poisoned?

223
named mechanisms

168 adversarial · 55 incidental

Before the fix we had 183. We added 41.
40 of the new ones are adversarial.
23 of them use the direct-input channel.

This closed a channel gap that looked real.
Our own screening made that gap.
The field did not.

By consequence: goal-hijack 126 · reasoning-corruption 46 · silent-corruption 21 · persistence-backdoor 14 · data-exfiltration 13 · resource-abuse 3

And how many defenses answer them?

534
named defenses

2.8%
answer both threat models

Only 15 of 534 defenses answer both threat models: adversarial corruption and incidental corruption.

We added 55 defenses. These include StruQ, SecAlign, Spotlighting and the Instruction Hierarchy.
The number did not move.

2.9% → 2.8%.

Which defenses were ever tested against which attacks?

40%
of defenses have one test or more

119
mechanisms never defended

349 confirmed pairs
213 of 534 defenses matched
118 of 237 mechanisms covered

163 of them have one test only.

There are almost no general defenses.

Testing effort concentrates on a handful of targets



One mechanism takes 22.9% of all pairs. These six take 43.1%.

The other 119 mechanisms get no test at all.

We predicted the gap would close. It did not — and that is the result.

The prediction

We predicted this. The first defenses of the field will cover the mechanisms that look open. StruQ, SecAlign, Spotlighting, Attention Tracker and the Liu baselines will close the gap.

What happened

We added 164 papers. We added 55 defenses and 41 mechanisms. We got 45 new pairs.

Old mechanisms now covered:

zero.

The first 196 mechanisms did not move.

The new defenses and the new attacks cover each other. They cover nothing else.

A reviewer can say that our corpus limits make the gap. We tested that claim. It is not correct.

Does a defense built for one threat model hold against the other?

3

Full generalization

holds against the untested threat model

4

Partial / degraded

measurable protection, materially weaker

2

Inert

no measurable protection at all

We rebuilt 9 defenses from their released code or weights. We did not use the numbers in the papers.

The result follows the intervention point. Ingestion defenses usually hold. Execution defenses usually do not.

A confound applies. The ingestion harness is a text classifier. The execution harness is an agent. We state it.

The field has no standard benchmark to test on

42.6%
of attacks use data nobody else can reuse

11.7%
use the most common benchmark

255 distinct benchmarks
for 223 named attacks

199 of them (78%)
are used by exactly one paper.

There are more benchmarks than attacks. Two papers can use one corpus and still not compare.

DEFENSE HALF-LIFE

How long does a published defense survive?

96%
of published defeats land within one year

24 datable defeats, median gap 1 year, maximum 2.

Four teams defeated DataSentinel four separate times. A defense does not stop after one defeat.

Read this as an upper limit.
Only 2.81% of the registry has a recorded outcome. The sample prefers defenses that are well known. Attack papers go after those first.

TRANSFER

Detection depends on recognising the attack. Action-checking does not.

Attack it was built against

Three of four ingestion detectors
stop it completely.
The attack announces itself:
"an important message from Emma".

Same goal, different disguise

The same detectors stop working.
The payload forges a system turn,
so it reads as configuration,
not as an injected instruction.

The execution-stage technique blocked BOTH.
It never reads the payload — it asks whether the action serves the user's request,
which is invariant to how the instruction was dressed up.
RQ6 concluded execution defenses generalize least. This says the opposite.

TRANSFER MATRIX

We run the defense code against attacks that no paper has tested it on

16
defense x attack
x model cells

94
measured
conditions

No paper reports these pairs.
That is why we chose them.

4 attacks. 5 defenses.
3 models. 2 defense families.

We change the attack dose from
0 to 10 bad passages of 10.
Each cell is a curve.

Three rules control every result.
The control must fire first. A change below the detection limit is not a result. We do not change the authors' scoring code.

RESULT 1

At full attack dose, one defense family fails and the other does not

Context-reliance

It holds down memory so the model follows the retrieved text.
ParamMute, CK-PLUG, SpARE

4 of 5 usable cells lose accuracy we can measure

Isolate-then-aggregate

It answers each passage alone, then joins the answers.
RobustRAG KeywordAgg, DecodingAgg

0 of 8 usable cells lose accuracy we can measure

The loss is the same size every time: -31.7 and -31.8 points, on two defenses, two attacks and two models.
Against a false passage the loss starts at 8 bad passages of 10. It does not wait for 10 of 10.

Design rule: do not hold down the model's own memory. It is the only thing left when the evidence goes.

RESULT 2

Some defenses make the attack work. Without them it stays near zero.

Defense	Attack	No defense	With defense	Dose
CK-PLUG	Tone steering	0.0 %	**78.2 %**	1 of 10
CK-PLUG	Tone steering	4.0 %	**99.0 %**	10 of 10
ParamMute	Tone steering	3.4 %	**28.8 %**	10 of 10
RobustRAG KeywordAgg, Llama-3	Refusal	0.0 %	**85.0 %**	9 of 10
RobustRAG KeywordAgg, Mistral	Refusal	0.0 %	**5.7 %**	9 of 10

With no defense the attack stays at or near zero at every dose. It works only through the defense.
Tone steering does not change the answer. A defense that pushes the model to follow the text follows the tone too.
The last row is the warning: the same defense helps on one model and does harm on another.

RESULT 3

Two versions of one defense give opposite answers

RobustRAG ships both. They share the isolation step. They differ only in how they join the answers.

Bad passages of 10	1	5	6	7	8	9	10
KeywordAgg	+7.3	+4.0	+4.0	+5.7	+6.7	+12.3	-5.7
DecodingAgg	+8.7	-9.0	-14.0	-18.3	-20.3	-17.3	-4.0
Difference	**1.4**	**13.0**	**18.0**	**24.0**	**27.0**	**29.6**	**1.7**

At 9 bad passages of 10, one version helps and the other does harm. They are 29.6 points apart.

We wrote the cause down before we ran the test. A keyword filter throws away a passage with no answer in it, so one good passage still carries the answer. An average of the outputs lets nine bad ones drown it.

So the difference must grow as good passages go, and must vanish when none are left. It does both.

DIFFERENTIATION

Against the five closest SoKs

closest competitor: The Landscape of Prompt Injection Threats (2602.10453)

papers reviewed	78	**1,026**
attacks catalogued	37	**223**
defenses catalogued	41	**534**
attack × defense pairs	—	**349**
runs own experiments	yes	**yes**
covers BOTH literatures	no	**YES**

They also run experiments. That is not the difference.

Four of the five closest surveys stay on one side of the divide. They do not mention it. The large ML survey does not cite security work. The closest security SoK does not cite degradation work.

Seven problems, ranked by expected value

1	**The tracks do not test each other**	2.0% of pairs cross the divide
2	**The uncovered tail**	119 mechanisms have no tested defense
3	**Single-mechanism validation is the norm**	163 defenses tested against exactly one
4	**Defenses meet only their contemporaries**	attack papers hold the later record
5	**Intervention point predicts generalization**	testable, and partly confounded today
6	**Benchmarks stand in for mechanisms**	one entry takes 22.9% of the pairs
7	**The problem is convention, not ability**	four of seven need no new science

SYNTHESIS

The field claims less coverage than it has. Some of what it has does harm.

Two literatures study the same problem. They do not read each other.

They name 223 ways to poison a context and 534 defenses. They almost never test one against the other.

The first limit is coordination. It is not ability.

RQ6 ran 7 defenses. 6 of them gave some protection against a threat model they never saw.
The protection is there. The test convention that would show it is not.

The gap is not ours. We added the literature we thought was missing, to close it. It did not close.

But coverage is not the whole result. When we ran the code, some defenses did not simply fail.

They made an attack work that stays near zero on a model with no defense at all.

Every number on these slides regenerates from the repo

config.yaml	screening criteria, applied by rule
rescreening_log.md	every corpus-affecting decision, dated, with cause
scripts/	dedupe → registries → coverage matrix → RQ1/RQ2/RQ7
context_sok_master_workbook.xlsx	papers, mechanisms, defenses, pairs, gaps
mcp_server/	the same data, queryable conversationally
data/paper_explorer.db	coverage and transfer figures, one source
scripts/build_presentation.py	this deck, built from the live data

We curate, but we release code and weights. We trust the reader to run the pipeline and report about itself.

WHAT'S NEXT

From findings to manuscript

Finish the model control	run the second aggregation version on the other family's model; the first half shows the protection does not repeat
Add a third attack	AGGD, so the matrix does not rest on four attack mechanisms
Find an outside defense	the aggregation family comes from one repository; a second group's code would test the rule
Close the 99 near-misses	defense papers that name an attack in our registry but never test it
Manuscript draft	RQ1 to RQ7 are complete. The threats to validity are written.