

# Folder SEM 3\Exp1

## 1 printable files

(file list disabled)

### SEM 3\Exp1\SLL\_implementation.c

```
1 // program to implement singly linked list
2
3 #include <stdio.h>
4 #include <stdlib.h>
5
6 // Core structure of Node that forms Linked List
7 struct node
8 {
9     int data;
10    struct node *next;
11 };
12
13 // End of the linked list should not point to anything(NULL)
14 struct node *head = NULL;
15
16 // Function to insert a node at the beginning of the list
17 void insertFirst(int data)
18 {
19     struct node *new_node = (struct node *)malloc(sizeof(struct node));
20
21     new_node->data = data;
22     new_node->next = head;
23
24     head = new_node;
25 }
26
27 // Function to insert a node at the end of the list
28 void insertEnd(int data)
29 {
30     struct node *new_node = (struct node *)malloc(sizeof(struct node));
31
32     new_node->data = data;
33     new_node->next = NULL;
34
35     if (head == NULL)
36     {
37         head = new_node;
38         return;
39     }
40
41     struct node *temp = head;
42
43     while (temp->next != NULL)
44     {
45         temp = temp->next;
```

```
46     }
47
48     temp→next = new_node;
49 }
50
51 void insertPos(int data, int pos)
52 {
53     struct node *new_node = (struct node *)malloc(sizeof(struct node));
54
55     new_node→data = data;
56
57     int curr_pos = 0;
58     struct node *temp = head;
59
60     while (temp→next ≠ NULL && curr_pos < pos - 1)
61     {
62         temp = temp→next;
63         curr_pos++;
64     }
65
66     new_node→next = temp→next;
67     temp→next = new_node;
68 }
69
70 void deleteFirst()
71 {
72     if (head == NULL)
73     {
74         printf("List is empty");
75         return;
76     }
77
78     struct node *temp = head;
79     head = head→next;
80     free(temp);
81 }
82
83 void deleteEnd()
84 {
85     if (head == NULL)
86     {
87         printf("List is empty");
88         return;
89     }
90
91     struct node *temp = head;
92     struct node *prev = NULL;
93
94     while (temp→next ≠ NULL)
95     {
96         prev = temp;
97         temp = temp→next;
98     }
99 }
```

```
100     prev→next = NULL;
101     free(temp);
102 }
103
104 void deletePos(int pos)
105 {
106     if (head == NULL)
107     {
108         printf("List is empty");
109         return;
110     }
111
112     struct node *temp = head;
113     struct node *prev = NULL;
114     int curr_pos = 0;
115
116     while (temp→next ≠ NULL && curr_pos < pos - 1)
117     {
118         prev = temp;
119         temp = temp→next;
120         curr_pos++;
121     }
122
123     prev→next = temp→next;
124     free(temp);
125 }
126
127 void display()
128 {
129     struct node *temp = head;
130
131     while (temp ≠ NULL)
132     {
133         printf("%d → ", temp→data);
134         temp = temp→next;
135     }
136     printf("NULL\n");
137 }
138
139 int main()
140 {
141     printf("Linked List creation and Manipulation\n");
142     printf("Enter from the following options:\n");
143     printf("1. Insert at the beginning of the list\n");
144     printf("2. Insert at the end of the list\n");
145     printf("3. Insert at a specific position in the list\n");
146     printf("4. Delete from the beginning of the list\n");
147     printf("5. Delete from the end of the list\n");
148     printf("6. Delete from a specific position in the list\n");
149     printf("7. Display the list\n");
150     printf("8. Exit\n");
151
152     int choice;
153     int data;
```

```
154     int pos;
155
156     while (1)
157     {
158         printf("Enter your choice: ");
159         scanf("%d", &choice);
160
161         switch (choice)
162         {
163             case 1:
164                 printf("Enter the data to be inserted: ");
165                 scanf("%d", &data);
166                 insertFirst(data);
167                 break;
168             case 2:
169                 printf("Enter the data to be inserted: ");
170                 scanf("%d", &data);
171                 insertEnd(data);
172                 break;
173             case 3:
174                 printf("Enter the data to be inserted: ");
175                 scanf("%d", &data);
176                 printf("Enter the position to insert the data: ");
177                 scanf("%d", &pos);
178                 insertPos(data, pos);
179                 break;
180             case 4:
181                 deleteFirst();
182                 break;
183             case 5:
184                 deleteEnd();
185                 break;
186             case 6:
187                 printf("Enter the position to delete the data: ");
188                 scanf("%d", &pos);
189                 deletePos(pos);
190                 break;
191             case 7:
192                 display();
193                 break;
194             case 8:
195                 exit(0);
196             default:
197                 printf("Invalid choice");
198                 break;
199         }
200     }
201
202     return 0;
203 }
```