





Create domain [Info](#)

Name

Domain name

The name must start with a lowercase letter and must be between 3 and 28 characters. Valid characters are a-z (lowercase only), 0-9, and - (hyphen).

Domain creation method

Domain creation method



Easy create

Quickly create an OpenSearch domain using 'Multi-AZ with Standby' for high availability. You can change some configuration options after the domain is created.



Standard create

Create an OpenSearch domain with your preferred configuration. You can choose all configuration options, including availability zone(s), instances and storages, and security configurations.

Templates

Templates specify common settings for your use case. After creating the domain, you can change these settings at any time.

Templates



Production

Use for production workloads for high-availability and performance. Defaults follow the recommended best practices.



Dev/test

Use for development or testing Amazon OpenSearch Service

Deployment option(s)

Select a deployment option that corresponds to the availability goals for your application. [Learn more](#)

Deployment option(s)



Domain with standby

Nodes in one of the Availability Zone (AZ) are reserved as standby. Automatic failover to standby. Provides 99.99% availability and consistent performance. (Recommended)



Domain without standby

Nodes are distributed across Availability Zone(s). Availability depends on the number of AZs and copies of data.

Availability Zone(s)

☐ 3-AZ☐ 2-AZ☒ 1-AZ

This deployment option achieves this standard by mandating a number best practices, such as a specified data node count, master node count, instance type, replica count, software update settings, and Auto-Tune turned on. For more information, see [Multi-AZ with Standby](#)

Note: Migrating from domain without standby to domain with standby will automatically enable Auto-Tune.

Engine options

Version

Certain features require specific OpenSearch/Elasticsearch versions. We recommend choosing the latest version. [Learn more](#)



Summary

[Engine version](#)

[Privacy](#) [Terms](#)



Number of data nodes

t3.small.search
1 total data nodes
EBS - GP3
10 GiB

Network

Public access
Dual stack

Fine-grained access control

admin

Encryption

HTTPS for all traffic to the domain
Node-to-node encryption
Enable encryption of data at rest

Cancel

Create



i If you select a version other than **OpenSearch_3.7 (latest)**, certain features may be disabled. Many OpenSearch Service features have a minimum OpenSearch version requirement or legacy Elasticsearch OSS version requirement. To learn more about features by engine version [visit documentation](#)

☐ Include older versions

Number of data nodes

Data nodes handle compute, memory, and storage operations based on workload requirements. Node specifications align with your application's query complexity, data processing needs, and volume patterns. Optimal node count balances performance and resource efficiency. [Learn more](#)

Instance family

Choose an instance family to filter instance types.

General purpose

Instance type

t3.small.search

t3.small.search instance type needs EBS storage. The AWS Free Tier includes usage of up to 750 hours per month of t3.small instance usage and up to 20 GiB of General Purpose EBS storage. [Learn more](#)

☐ Include previous generation instance types

T3 instance types are suitable only for testing and development purposes. For production workloads, we recommend using latest generation instance types - general purpose, memory optimized, compute optimized, or storage optimized.

Number of data nodes

[Learn more](#)

1

The number must be minimum of 1. The default maximum number is 10 but can be increased if you request a quota increase.

Storage type

EBS

EBS volume type

EBS volumes enable you to independently scale the storage resources of your domain from its compute resources. EBS volumes are most useful for domains with very large data sets, but without the need for large compute resources.

General Purpose (SSD) - gp3

☐ Include previous generation EBS volume types

EBS storage size per node

10

EBS storage size per node in GiB. Minimum 10 GiB and maximum 100 GiB.

Advanced volume type options (IOPs and throughput configurations)

Total IOPs per node

3000

IOPs



The total IOPs to volume size ratio should not exceed 500:1.

3000

5000 IOPs

Number of data nodes*

AZ	Nodes	Total storage (GB)
AZ	1	10
Total	1	10

* Indicative representation of node distribution across AZ(s). Service recommends equal number of nodes in each of the AZ

exceed 1:4.

Warm and cold data storage

Store data efficiently with flexible storage tiers. Warm storage maintains interactive analysis capabilities while reducing costs for larger datasets. [Learn more](#)

Cold storage offers the lowest-cost option for rarely accessed historical data, which moves through warm storage for querying. [Learn more](#)

 UltraWarm data nodes feature is not supported by the data instance type you selected.

 Cold storage is currently only supported on Elasticsearch version 7.9 and above.

Number of master nodes

Dedicated master nodes improve the stability of your domain. For production domains, three is recommended. [Learn more](#)

☐ Enable dedicated master nodes

 Dedicated master nodes are required for domains with more than 200 nodes, running OpenSearch 2.17 and above.

Dedicated coordinator nodes - *new* [Info](#)

Dedicated coordinator nodes relieve data nodes from the responsibilities of traffic coordination and hosting of OpenSearch Dashboards. [Learn more](#)

☐ Enable dedicated coordinator nodes

Snapshot configuration

Amazon OpenSearch Service takes an automated snapshot of your cluster. [Learn more](#)

Frequency

Hourly

 Elasticsearch version 5.3 and above have hourly snapshots only.

Automated Snapshot Pause Configuration

Pause automated snapshots for a specific duration.

☐ Enable temporary disablement
Allow customers to pause automated snapshots for a specific duration.

Custom endpoint

Each Amazon OpenSearch Service domain has an auto-generated endpoint, but you can also add a custom endpoint using AWS Certificate Manager (ACM). [Learn more](#)

☐ Enable custom endpoint

**Network**

- ☐ VPC access - *recommended*
- ☒ Public access

IP address type - new | [Info](#)

Select the type of IP address that your subnets use.

- ☒ Dual-stack mode - *recommended*
Your resources can communicate over IPv4, IPv6, or both.

- ☐ IPv4 only
Your resources can communicate over IPv4 only.

OpenSearch UI settings

OpenSearch UI (Dashboards) is the next-generation and redesigned OpenSearch Dashboards experience that can connect to multiple data sources. An OpenSearch application has its own endpoint and can be easily shared to others for collaboration, and each collaborator can log via AWS Identity and Access Management (IAM) and/or IAM Identity Center credentials.

OpenSearch application selection

Webpage user interface to visualize your OpenSearch data.

- ☐ Select existing OpenSearch application

- ☒ Create new OpenSearch application

OpenSearch application name

aos-dining-concierge

Workspace selection

Customizable space for your team and use case.

- ☐ Select existing workspace

- ☒ Create new workspace

Workspace name

dining-concierge

The Workspace name must be 3-30 characters, and must start with a lowercase letter. Valid characters are a-z, 0-9, and hyphen (-).

AI Assistant feature

Enable AI-powered assistant features for your OpenSearch application.

- ☐ **Enable Chatbot and Agentic investigation**

Allow users to interact with data through conversational AI interface and autonomous investigation capabilities.

Single sign-on authentication

By default, your dashboard application is authenticated with IAM to manage permissions for AWS resource users. To create a single sign-on experience or to work with SAML-authenticated applications, check the Authenticate with IAM Identity Center box.

- ☐ Authenticate with IAM Identity Center

OpenSearch UI admins management**Permission Settings**

Administrators' permissions includes create, edit and delete Workspaces in an OpenSearch application. Select the users that you want to grant administrators' permissions.

- ☒ Grant administrators' permission to specific user(s)
- ☐ Grant administrators' permission to all users

OpenSearch UI Admins

Select the ARN of IAM principals or name of IDC users

Fine-grained access control

Fine-grained access control provides numerous features to help you keep your data secure. Features include document-



**Master user**

- ☐ Set IAM ARN as master user
- ☒ Create master user

Master username

Master usernames must be between 1 and 64 characters.

Master password

Master password must be at least 8 characters long and contain at least one uppercase letter, one lowercase letter, one number, and one special character.

Confirm master password**► SAML via IAM Federate *optional***

If you are using SAML via IAM Federate to enable single sign-on from your external providers, you can also define Fine-grained access control based on user identity from the external identity providers.

SAML authentication for OpenSearch Dashboards/Kibana

SAML authentication lets you use your existing identity provider for single sign-on for OpenSearch Dashboards/Kibana.

[Learn more](#)

☐ Enable SAML authentication

JWT authentication and authorization - *new*

JSON Web Token (JWT) auth lets you use your existing identity provider for single sign-on for OpenSearch. [Learn](#)

[more](#)

☐ Enable JWT authentication and authorization

Amazon Cognito authentication

Enable to use Amazon Cognito authentication for OpenSearch Dashboards/Kibana. Amazon Cognito supports a variety of identity providers for username-password authentication. [Learn more](#)

☐ Enable Amazon Cognito authentication

Access policy

Access policies control whether a request is accepted or rejected when it reaches the Amazon OpenSearch Service domain. If you specify an account, user, or role in this policy, you must sign your requests. [Learn more](#)

Domain access policy

- ☒ Only use fine-grained access control
Allow open access to the domain.
- ☐ Do not set domain level access policy
All requests to the domain will be denied.
- ☐ Configure domain level access policy

Encryption

You enabled fine-grained access control, which requires HTTPS, node-to-node encryption, and encryption at rest to be enabled.



**Node-to-node encryption**

This setting provides an additional layer of security. Each Amazon OpenSearch domain operates within a secure, dedicated VPC. Node-to-node encryption enables TLS encryption for all communications within that VPC. After you enable node-to-node encryption, you can't disable it. This setting requires Elasticsearch version 6.7 and above.

☒ **Enable encryption of data at rest**

Encryption at rest secures the indexes and automated snapshots associated with the domain. After you enable encryption of data at rest, you can't disable it.

Choose an AWS KMS key

This key will be used to encrypt and decrypt your resources. [Learn more](#)

☒ **Use AWS owned key**

A key that AWS owns and manages for you.

☐ **Choose a different AWS KMS key (advanced)**

Choose a key you have permission to use, or create a new one.

Off-peak window [Info](#)

Off-peak window is a 10-hour time block that you can use to schedule service software updates and auto-tune optimizations. While these updates are designed to be non-disruptive, the service uses the off-peak window to deploy updates at a comparatively lower traffic time, whenever possible. Please note that updates to the domain such as node replacements, or changes that need to be deployed to the domain immediately do not use the off-peak window.

Start time (UTC)**End time (UTC)****Auto-Tune**

Auto-Tune analyzes cluster performance over time and suggests optimizations based on your workload. You can choose to deploy these changes or rollback to the default OpenSearch settings at any time.

[Learn more](#)

i The T2 or T3 instance types do not support Auto-Tune.

Automatic software update☐ **Enable automatic software update**☒ **Apply latest service software with Blue/Green deployments**

When enabled, configuration changes that trigger Blue/Green deployments will also apply the latest service software update. When disabled (default), configuration changes will not automatically update service software.

Deployment strategy**Deployment strategy**

Select a deployment strategy to control how your cluster handles deployments when sufficient capacity is not available at the time of update.

Tags - optional

You can add tags to describe your domain. A tag consists of a case-sensitive key-value pair. For example, you can define a tag with a key-value pair of Environment Name-Development. [Learn More](#)





you can add 50 more tags.

► **Advanced cluster settings** - *optional*