

VIVA VOICE QUESTIONS AND ANSWERS

1. What is database?

A database is a logically coherent collection of data with some inherent meaning, representing some aspect of real world and which is designed, built and populated with data for a specific purpose.

2. What is DBMS?

It is a collection of programs that enables user to create and maintain a database. In other words it is general-purpose software that provides the users with the processes of defining, constructing and manipulating the database for various applications.

3. What is a Database system?

The database and **DBMS** software together is called as Database system.

4. Advantages of DBMS?

- Ø Redundancy is controlled.
- Ø Unauthorised access is restricted.
- Ø Providing multiple user interfaces.
- Ø Enforcing integrity constraints.
- Ø Providing backup and recovery.

5. Disadvantage in File Processing System?

- Ø Data redundancy & inconsistency.
- Ø Difficult in accessing data.
- Ø Data isolation.
- Ø Data integrity.
- Ø Concurrent access is not possible.
- Ø Security Problems.

6. Describe the three levels of data abstraction?

There are three levels of abstraction:

- Ø Physical level: The lowest level of abstraction describes how data are stored.
- Ø Logical level: The next higher level of abstraction, describes what data are stored in database and what relationship among those data.
- Ø View level: The highest level of abstraction describes only part of entire database.

7. Define the "integrity rules"

There are two Integrity rules.

- Ø Entity Integrity: States that "Primary key cannot have NULL value"
- Ø Referential Integrity: States that "Foreign Key can be either a NULL value or should be Primary Key value of other relation.

8. What is extension and intension?

Extension -

It is the number of tuples present in a table at any instance. This is time dependent.

Intension -

It is a constant value that gives the name, structure of table and the constraints laid on it.

9. What is System R? What are its two major subsystems?

System R was designed and developed over a period of 1974-79 at IBM San Jose Research Center. It is a prototype and its purpose was to demonstrate that it is possible to build a Relational System that can be used in a real life environment to solve real life problems, with performance at least comparable to that of existing system.

Its two subsystems are

- Ø Research Storage
- Ø System Relational Data System.

10. How is the data structure of System R different from the relational structure?

Unlike Relational systems in System R

- Ø Domains are not supported
- Ø Enforcement of candidate key uniqueness is optional
- Ø Enforcement of entity integrity is optional
- Ø Referential integrity is not enforced

11. What is Data Independence?

Data independence means that “the application is independent of the storage structure and access strategy of data”. In other words, The ability to modify the schema definition in one level should not affect the schema definition in the next higher level.

Two types of Data Independence:

- Ø Physical Data Independence: Modification in physical level should not affect the logical level.
- Ø Logical Data Independence: Modification in logical level should affect the view level.

NOTE: Logical Data Independence is more difficult to achieve

12. What is a view? How it is related to data independence?

A view may be thought of as a virtual table, that is, a table that does not really exist in its own right but is instead derived from one or more underlying base table. In other words, there is no stored file that directly represents the view instead a definition of view is stored in data dictionary.

Growth and restructuring of base tables is not reflected in views. Thus the view can insulate users from the effects of restructuring and growth in the database. Hence accounts for logical data independence.

13. What is Data Model?

A collection of conceptual tools for describing data, data relationships data semantics and constraints.

14. What is E-R model?

This data model is based on real world that consists of basic objects called entities and of relationship among these objects. Entities are described in a database by a set of attributes.

15. What is Object Oriented model?

This model is based on collection of objects. An object contains values stored in instance variables with in the object. An object also contains bodies of code that operate on the object. These bodies of code are called methods. Objects that contain same types of values and the same methods are grouped together into classes.

16. What is an Entity?

It is a 'thing' in the real world with an independent existence.

17. What is an Entity type?

It is a collection (set) of entities that have same attributes.

18. What is an Entity set?

It is a collection of all entities of particular entity type in the database.

19. What is an Extension of entity type?

The collections of entities of a particular entity type are grouped together into an entity set.

20. What is Weak Entity set?

An entity set may not have sufficient attributes to form a primary key, and its primary key comprises of its partial key and primary key of its parent entity, then it is said to be Weak Entity set.

21. What is an attribute?

It is a particular property, which describes the entity.

22. What is a Relation Schema and a Relation?

A relation Schema denoted by $R(A_1, A_2, \dots, A_n)$ is made up of the relation name R and the list of attributes A_i that it contains. A relation is defined as a set of tuples. Let r be the relation which contains set tuples $(t_1, t_2, t_3, \dots, t_n)$.

Each tuple is an ordered list of n-values $t=(v_1, v_2, \dots, v_n)$.

23. What is degree of a Relation?

It is the number of attribute of its relation schema.

24. What is Relationship?

It is an association among two or more entities.

25. What is Relationship set?

The collection (or set) of similar relationships.

26. What is Relationship type?

Relationship type defines a set of associations or a relationship set among a given set of entity types.

27. What is degree of Relationship type?

It is the number of entity type participating.

28. What is DDL (Data Definition Language)?

A data base schema is specifies by a set of definitions expressed by a special language called DDL.

29. What is VDL (View Definition Language)?

It specifies user views and their mappings to the conceptual schema.

30. What is SDL (Storage Definition Language)?

This language is to specify the internal schema. This language may specify the mapping between two schemas.

31. What is Data Storage - Definition Language?

The storage structures and access methods used by database system are specified by a set of definition in a special type of DDL called data storage-definition language.

32. What is DML (Data Manipulation Language)?

This language that enable user to access or manipulate data as organised by appropriate data model.

Ø Procedural DML or Low level: DML requires a user to specify what data are needed and how to get those data.

Ø Non-Procedural DML or High level: DML requires a user to specify what data are needed without specifying how to get those data.

33. What is DML Compiler?

It translates DML statements in a query language into low-level instruction that the query evaluation engine can understand.

34. What is Query evaluation engine?

It executes low-level instruction generated by compiler.

35. What is DDL Interpreter?

It interprets DDL statements and record them in tables containing metadata.

36. What is Record-at-a-time?

The Low level or Procedural DML can specify and retrieve each record from a set of records. This retrieve of a record is said to be Record-at-a-time.

37. What is Set-at-a-time or Set-oriented?

The High level or Non-procedural DML can specify and retrieve many records in a single DML statement. This retrieve of a record is said to be Set-at-a-time or Set-oriented.

38. What is Relational Algebra?

It is procedural query language. It consists of a set of operations that take one or two relations as input and produce a new relation.

39. What is Relational Calculus?

It is an applied predicate calculus specifically tailored for relational databases proposed by E.F. Codd. E.g. of languages based on it are DSL ALPHA, QUEL.

40. How does Tuple-oriented relational calculus differ from domain-oriented relational calculus

The tuple-oriented calculus uses a tuple variables i.e., variable whose only permitted values are tuples of that relation. E.g. QUEL

The domain-oriented calculus has domain variables i.e., variables that range over the underlying domains instead of over relation. E.g. ILL, DEDUCE.

41. What is normalization?

It is a process of analysing the given relation schemas based on their Functional Dependencies (FDs) and primary key to achieve the properties

Ø Minimizing redundancy

Ø Minimizing insertion, deletion and update anomalies.

42. What is Functional Dependency?

A Functional dependency is denoted by $X \rightarrow Y$ between two sets of attributes X and Y that are subsets of R specifies a constraint on the possible tuple that can form a relation state r of R. The constraint is for any two tuples t1 and t2 in r if $t1[X] = t2[X]$ then they have $t1[Y] = t2[Y]$. This means the value of X component of a tuple uniquely determines the value of component Y.

43. When is a functional dependency F said to be minimal?

Ø Every dependency in F has a single attribute for its right hand side.

Ø We cannot replace any dependency $X \rightarrow A$ in F with a dependency $Y \rightarrow A$ where Y is a proper subset of X and still have a set of dependency that is equivalent to F.

Ø We cannot remove any dependency from F and still have set of dependency that is equivalent to F.

44. What is Multivalued dependency?

Multivalued dependency denoted by $X \twoheadrightarrow Y$ specified on relation schema R, where X and Y are both subsets of R, specifies the following constraint on any relation r of R: if two tuples t1 and t2 exist in r such that $t1[X] = t2[X]$ then t3 and t4 should also exist in r with the following properties

Ø $t3[X] = t4[X] = t1[X] = t2[X]$

Ø $t3[Y] = t1[Y]$ and $t4[Y] = t2[Y]$

Ø $t3[Z] = t2[Z]$ and $t4[Z] = t1[Z]$

where $Z = (R - (X \cup Y))$

45. What is Lossless join property?

It guarantees that the spurious tuple generation does not occur with respect to relation schemas after decomposition.

46. What is 1 NF (Normal Form)?

The domain of attribute must include only atomic (simple, indivisible) values.

47. What is Fully Functional dependency?

It is based on concept of full functional dependency. A functional dependency $X \rightarrow Y$ is full functional dependency if removal of any attribute A from X means that the dependency does not hold any more.

48. What is 2NF?

A relation schema R is in 2NF if it is in 1NF and every non-prime attribute A in R is fully functionally dependent on primary key.

49. What is 3NF?

A relation schema R is in 3NF if it is in 2NF and for every FD $X \rightarrow A$ either of the following is true

Ø X is a Super-key of R.

Ø A is a prime attribute of R.

In other words, if every non prime attribute is non-transitively dependent on primary key.

50. What is BCNF (Boyce-Codd Normal Form)?

A relation schema R is in BCNF if it is in 3NF and satisfies an additional constraint that for every FD X A, X must be a candidate key.

51. What is 4NF?

A relation schema R is said to be in 4NF if for every Multivalued dependency X Y that holds over R, one of following is true

Ø X is subset or equal to (or) XY = R.

Ø X is a super key.

52. What is 5NF?

A Relation schema R is said to be 5NF if for every join dependency {R1, R2, ..., Rn} that holds R, one the following is true

Ø Ri = R for some i.

Ø The join dependency is implied by the set of FD, over R in which the left side is key of R.

53. What is Domain-Key Normal Form?

A relation is said to be in DKNF if all constraints and dependencies that should hold on the the constraint can be enforced by simply enforcing the domain constraint and key constraint on the relation.

54. What are partial, alternate,, artificial, compound and natural key?

Partial Key:

It is a set of attributes that can uniquely identify weak entities and that are related to same owner entity. It is sometime called as Discriminator.

Alternate Key:

All Candidate Keys excluding the Primary Key are known as Alternate Keys.

Artificial Key:

If no obvious key, either stand alone or compound is available, then the last resort is to simply create a key, by assigning a unique number to each record or occurrence. Then this is known as developing an artificial key.

Compound Key:

If no single data element uniquely identifies occurrences within a construct, then combining multiple elements to create a unique identifier for the construct is known as creating a compound key.

Natural Key:

When one of the data elements stored within a construct is utilized as the primary key, then it is called the natural key.

55. What is indexing and what are the different kinds of indexing?

Indexing is a technique for determining how quickly specific data can be found.

Types:

Ø Binary search style indexing

Ø B-Tree indexing

Ø Inverted list indexing

Ø Memory resident table

Ø Table indexing

56. What is system catalog or catalog relation? How is better known as?

A RDBMS maintains a description of all the data that it contains, information about every relation and index that it contains. This information is stored in a collection of relations maintained by the system called metadata. It is also called data dictionary.

57. What is meant by query optimization?

The phase that identifies an efficient execution plan for evaluating a query that has the least estimated cost is

referred to as query optimization.

58. What is join dependency and inclusion dependency?

Join Dependency:

A Join dependency is generalization of Multivalued dependency. A JD $\{R_1, R_2, \dots, R_n\}$ is said to hold over a relation R if $R_1, R_2, R_3, \dots, R_n$ is a lossless-join decomposition of R. There is no set of sound and complete inference rules for JD.

Inclusion Dependency:

An Inclusion Dependency is a statement of the form that some columns of a relation are contained in other columns. A foreign key constraint is an example of inclusion dependency.

59. What is durability in DBMS?

Once the **DBMS** informs the user that a transaction has successfully completed, its effects should persist even if the system crashes before all its changes are reflected on disk. This property is called durability.

60. What do you mean by atomicity and aggregation?

Atomicity:

Either all actions are carried out or none are. Users should not have to worry about the effect of incomplete transactions. **DBMS** ensures this by undoing the actions of incomplete transactions.

Aggregation:

A concept which is used to model a relationship between a collection of entities and relationships. It is used when we need to express a relationship among relationships.

61. What is a Phantom Deadlock?

In distributed deadlock detection, the delay in propagating local information might cause the deadlock detection algorithms to identify deadlocks that do not really exist. Such situations are called phantom deadlocks and they lead to unnecessary aborts.

62. What is a checkpoint and When does it occur?

A Checkpoint is like a snapshot of the **DBMS** state. By taking checkpoints, the **DBMS** can reduce the amount of work to be done during restart in the event of subsequent crashes.

63. What are the different phases of transaction?

Different phases are

Ø Analysis phase

Ø Redo Phase

Ø Undo phase

64. What do you mean by flat file database?

It is a database in which there are no programs or user access languages. It has no cross-file capabilities but is user-friendly and provides user-interface management.

65. What is "transparent DBMS"?

It is one, which keeps its Physical Structure hidden from user.

66. Brief theory of Network, Hierarchical schemas and their properties

Network schema uses a graph data structure to organize records example for such a database management system is CTCS while a hierarchical schema uses a tree data structure example for such a system is IMS.

67. What is a query?

A query with respect to **DBMS** relates to user commands that are used to interact with a data base. The query language can be classified into data definition language and data manipulation language.

68. What do you mean by Correlated subquery?

Subqueries, or nested queries, are used to bring back a set of rows to be used by the parent query. Depending on how the subquery is written, it can be executed once for the parent query or it can be executed once for each row returned by the parent query. If the subquery is executed for each row of the parent, this is called a correlated subquery.

A correlated subquery can be easily identified if it contains any references to the parent subquery columns in its WHERE clause. Columns from the subquery cannot be referenced anywhere else in the parent query. The following example demonstrates a non-correlated subquery.

E.g. Select * From CUST Where '10/03/1990' IN (Select ODATE From ORDER Where CUST.CNUM = ORDER.CNUM)

69. What are the primitive operations common to all record management systems?

Addition, deletion and modification.

70. Name the buffer in which all the commands that are typed in are stored

'Edit' Buffer

71. What are the unary operations in Relational Algebra?

PROJECTION and SELECTION.

72. Are the resulting relations of PRODUCT and JOIN operation the same?

No.

PRODUCT: Concatenation of every row in one relation with every row in another.

JOIN: Concatenation of rows from one relation and related rows from another.

73. What is RDBMS KERNEL?

Two important pieces of RDBMS architecture are the kernel, which is the software, and the data dictionary, which consists of the system-level data structures used by the kernel to manage the database

You might think of an RDBMS as an operating system (or set of subsystems), designed specifically for controlling data access; its primary functions are storing, retrieving, and securing data. An RDBMS maintains its own list of authorized users and their associated privileges; manages memory caches and paging; controls locking for concurrent resource usage; dispatches and schedules user requests; and manages space usage within its table-space structures.

74. Name the sub-systems of a RDBMS

I/O, Security, Language Processing, Process Control, Storage Management, Logging and Recovery, Distribution Control, Transaction Control, Memory Management, Lock Management

75. Which part of the RDBMS takes care of the data dictionary? How

Data dictionary is a set of tables and database objects that is stored in a special area of the database and maintained exclusively by the kernel.

76. What is the job of the information stored in data-dictionary?

The information in the data dictionary validates the existence of the objects, provides access to them, and maps the actual physical storage location.

77. Not only RDBMS takes care of locating data it also

determines an optimal access path to store or retrieve the data

76. How do you communicate with an RDBMS?

You communicate with an RDBMS using Structured Query Language (SQL)

78. Define SQL and state the differences between SQL and other conventional programming Languages

SQL is a nonprocedural language that is designed specifically for data access operations on normalized relational database structures. The primary difference between SQL and other conventional programming languages is that SQL statements specify what data operations should be performed rather than how to perform them.

79. Name the three major set of files on disk that compose a database in Oracle

There are three major sets of files on disk that compose a database. All the files are binary. These are

Ø Database files

Ø Control files

Ø Redo logs

The most important of these are the database files where the actual data resides. The control files and the redo logs support the functioning of the architecture itself.

All three sets of files must be present, open, and available to Oracle for any data on the database to be useable.

Without these files, you cannot access the database, and the database administrator might have to recover some or all of the database using a backup, if there is one.

80. What is an Oracle Instance?

The Oracle system processes, also known as Oracle background processes, provide functions for the user processes—functions that would otherwise be done by the user processes themselves

Oracle database-wide system memory is known as the SGA, the system global area or shared global area. The data and control structures in the SGA are shareable, and all the Oracle background processes and user processes can use them.

The combination of the SGA and the Oracle background processes is known as an Oracle instance

81. What are the four Oracle system processes that must always be up and running for the database to be useable

The four Oracle system processes that must always be up and running for the database to be useable include DBWR (Database Writer), LGWR (Log Writer), SMON (System Monitor), and PMON (Process Monitor).

82. What are database files, control files and log files. How many of these files should a database have at least? Why?

Database Files

The database files hold the actual data and are typically the largest in size. Depending on their sizes, the tables (and other objects) for all the user accounts can go in one database file—but that's not an ideal situation because it does not make the database structure very flexible for controlling access to storage for different users, putting the database on different disk drives, or backing up and restoring just part of the database.

You must have at least one database file but usually, more than one files are used. In terms of accessing and using the data in the tables and other objects, the number (or location) of the files is immaterial.

The database files are fixed in size and never grow bigger than the size at which they were created

Control Files
The control files and redo logs support the rest of the architecture. Any database must have at least one control file, although you typically have more than one to guard against loss. The control file records the name of the database, the date and time it was created, the location of the database and redo logs, and the synchronization information to ensure that all three sets of files are always in step. Every time you add a new database or redo log file to the database, the information is recorded in the control files.

Redo Logs

Any database must have at least two redo logs. These are the journals for the database; the redo logs record all changes to the user objects or system objects. If any type of failure occurs, the changes recorded in the redo logs can be used to bring the database to a consistent state without losing any committed transactions. In the case of non-data loss failure, Oracle can apply the information in the redo logs automatically without intervention from the DBA.

The redo log files are fixed in size and never grow dynamically from the size at which they were created.

83. What is ROWID?

The ROWID is a unique database-wide physical address for every row on every table. Once assigned (when the row is first inserted into the database), it never changes until the row is deleted or the table is dropped.

The ROWID consists of the following three components, the combination of which uniquely identifies the physical storage location of the row.

Ø Oracle database file number, which contains the block with the rows

Ø Oracle block address, which contains the row

Ø The row within the block (because each block can hold many rows)

The ROWID is used internally in indexes as a quick means of retrieving rows with a particular key value.

Application developers also use it in SQL statements as a quick way to access a row once they know the ROWID

84. What is Oracle Block? Can two Oracle Blocks have the same address?

Oracle "formats" the database files into a number of Oracle blocks when they are first created—making it easier for the RDBMS software to manage the files and easier to read data into the memory areas.

The block size should be a multiple of the operating system block size. Regardless of the block size, the entire block is not available for holding data; Oracle takes up some space to manage the contents of the block. This block header

has a minimum size, but it can grow.

These Oracle blocks are the smallest unit of storage. Increasing the Oracle block size can improve performance, but it should be done only when the database is first created.

Each Oracle block is numbered sequentially for each database file starting at 1. Two blocks can have the same block address if they are in different database files.

85. What is database Trigger?

A database trigger is a PL/SQL block that can be defined to automatically execute for insert, update, and delete statements against a table. The trigger can be defined to execute once for the entire statement or once for every row that is inserted, updated, or deleted. For any one table, there are twelve events for which you can define database triggers. A database trigger can call database procedures that are also written in PL/SQL.

86. Name two utilities that Oracle provides, which are used for backup and recovery.

Along with the RDBMS software, Oracle provides two utilities that you can use to back up and restore the database. These utilities are Export and Import.

The Export utility dumps the definitions and data for the specified part of the database to an operating system binary file. The Import utility reads the file produced by an export, recreates the definitions of objects, and inserts the data. If Export and Import are used as a means of backing up and recovering the database, all the changes made to the database cannot be recovered since the export was performed. The best you can do is recover the database to the time when the export was last performed.

87. What are stored-procedures? And what are the advantages of using them.

Stored procedures are database objects that perform a user-defined operation. A stored procedure can have a set of compound SQL statements. A stored procedure executes the SQL commands and returns the result to the client. Stored procedures are used to reduce network traffic.

88. How are exceptions handled in PL/SQL? Give some of the internal exceptions' names.

PL/SQL exception handling is a mechanism for dealing with run-time errors encountered during procedure execution. Use of this mechanism enables execution to continue if the error is not severe enough to cause procedure termination.

The exception handler must be defined within a subprogram specification. Errors cause the program to raise an exception with a transfer of control to the exception-handler block. After the exception handler executes, control returns to the block in which the handler was defined. If there are no more executable statements in the block, control returns to the caller.

User-Defined Exceptions

PL/SQL enables the user to define exception handlers in the declarations area of subprogram specifications. User accomplishes this by naming an exception as in the following example:

```
ot_failure EXCEPTION;
```

In this case, the exception name is `ot_failure`. Code associated with this handler is written in the EXCEPTION specification area as follows:

```
EXCEPTION
```

```
when OT_FAILURE then
```

```
out_status_code := g_out_status_code;
```

```
out_msg := g_out_msg;
```

The following is an example of a subprogram exception:

```
EXCEPTION
```

```
when NO_DATA_FOUND then
```

```
g_out_status_code := 'FAIL';
```

```
RAISE ot_failure;
```

Within this exception is the RAISE statement that transfers control back to the `ot_failure` exception handler. This technique of raising the exception is used to invoke all user-defined exceptions.

System-Defined Exceptions

Exceptions internal to PL/SQL are raised automatically upon error. NO_DATA_FOUND is a system-defined exception. Table below gives a complete list of internal exceptions.

PL/SQL internal exceptions.

PL/SQL internal exceptions.

Exception Name Oracle Error

CURSOR_ALREADY_OPEN ORA-06511

DUP_VAL_ON_INDEX ORA-00001

INVALID_CURSOR ORA-01001

INVALID_NUMBER ORA-01722

LOGIN_DENIED ORA-01017

NO_DATA_FOUND ORA-01403

NOT_LOGGED_ON ORA-01012

PROGRAM_ERROR ORA-06501

STORAGE_ERROR ORA-06500

TIMEOUT_ON_RESOURCE ORA-00051

TOO_MANY_ROWS ORA-01422

TRANSACTION_BACKED_OUT ORA-00061

VALUE_ERROR ORA-06502

ZERO_DIVIDE ORA-01476

In addition to this list of exceptions, there is a catch-all exception named OTHERS that traps all errors for which specific error handling has not been established.

89. Does PL/SQL support "overloading"? Explain

The concept of overloading in PL/SQL relates to the idea that you can define procedures and functions with the same name. PL/SQL does not look only at the referenced name, however, to resolve a procedure or function call. The count and data types of formal parameters are also considered.

PL/SQL also attempts to resolve any procedure or function calls in locally defined packages before looking at globally defined packages or internal functions. To further ensure calling the proper procedure, you can use the dot notation. Prefacing a procedure or function name with the package name fully qualifies any procedure or function reference.

90. Tables derived from the ERD

- a) Are totally unnormalised
- b) Are always in 1NF
- c) Can be further denormalised
- d) May have multi-valued attributes

(b) Are always in 1NF

91. Spurious tuples may occur due to

- i. Bad normalization
 - ii. Theta joins
 - iii. Updating tables from join
- a) i & ii b) ii & iii
c) i & iii d) ii & iii

(a) i & iii because theta joins are joins made on keys that are not primary keys.

92. A B C is a set of attributes. The functional dependency is as follows

AB -> B

AC -> C

C -> B

- a) is in 1NF
- b) is in 2NF
- c) is in 3NF
- d) is in BCNF

(a) is in 1NF since $(AC)^+ = \{ A, B, C \}$ hence AC is the primary key. Since C B is a FD given, where neither C is a Key nor B is a prime attribute, this it is not in 3NF. Further B is not functionally dependent on key AC thus it is not in 2NF. Thus the given FDs is in 1NF.

93. In mapping of ERD to DFD

- a) entities in ERD should correspond to an existing entity/store in DFD
- b) entity in DFD is converted to attributes of an entity in ERD
- c) relations in ERD has 1 to 1 correspondence to processes in DFD
- d) relationships in ERD has 1 to 1 correspondence to flows in DFD

(a) entities in ERD should correspond to an existing entity/store in DFD

94. A dominant entity is the entity

- a) on the N side in a 1 : N relationship
- b) on the 1 side in a 1 : N relationship
- c) on either side in a 1 : 1 relationship
- d) nothing to do with 1 : 1 or 1 : N relationship

(b) on the 1 side in a 1 : N relationship

95. Select 'NORTH', CUSTOMER From CUST_DTLS Where REGION = 'N' Order By CUSTOMER Union Select 'EAST', CUSTOMER From CUST_DTLS Where REGION = 'E' Order By CUSTOMER

The above is

- a) Not an error
- b) Error - the string in single quotes 'NORTH' and 'SOUTH'
- c) Error - the string should be in double quotes
- d) Error - ORDER BY clause

(d) Error - the ORDER BY clause. Since ORDER BY clause cannot be used in UNIONS

96. What is Storage Manager?

It is a program module that provides the interface between the low-level data stored in database, application programs and queries submitted to the system.

97. What is Buffer Manager?

It is a program module, which is responsible for fetching data from disk storage into main memory and deciding what data to be cache in memory.

98. What is Transaction Manager?

It is a program module, which ensures that database, remains in a consistent state despite system failures and concurrent transaction execution proceeds without conflicting.

99. What is File Manager?

It is a program module, which manages the allocation of space on disk storage and data structure used to represent information stored on a disk.

100. What is Authorization and Integrity manager?

It is the program module, which tests for the satisfaction of integrity constraint and checks the authority of user to access data.

101. What are stand-alone procedures?

Procedures that are not part of a package are known as stand-alone because they independently defined. A good example of a stand-alone procedure is one written in a SQL*Forms application. These types of procedures are not available for reference from other Oracle tools. Another limitation of stand-alone procedures is that they are compiled at run time, which slows execution.

102. What are cursors give different types of cursors.

PL/SQL uses cursors for all database information accesses statements. The language supports the use two types of cursors

Ø Implicit

Ø Explicit

103. What is cold backup and hot backup (in case of Oracle)?

Ø Cold Backup:

It is copying the three sets of files (database files, redo logs, and control file) when the instance is shut down. This is a straight file copy, usually from the disk directly to tape. You must shut down the instance to guarantee a consistent copy.

If a cold backup is performed, the only option available in the event of data file loss is restoring all the files from the latest backup. All work performed on the database since the last backup is lost.

Ø Hot Backup:

Some sites (such as worldwide airline reservations systems) cannot shut down the database while making a backup copy of the files. The cold backup is not an available option.

So different means of backing up database must be used — the hot backup. Issue a SQL command to indicate to Oracle, on a tablespace-by-tablespace basis, that the files of the tablespace are to be backed up. The users can continue to make full use of the files, including making changes to the data. Once the user has indicated that he/she wants to back up the tablespace files, he/she can use the operating system to copy those files to the desired backup destination.

The database must be running in ARCHIVELOG mode for the hot backup option.

If a data loss failure does occur, the lost database files can be restored using the hot backup and the online and offline redo logs created since the backup was done. The database is restored to the most consistent state without any loss of committed transactions.

104. What are Armstrong rules? How do we say that they are complete and/or sound

The well-known inference rules for FDs

Ø Reflexive rule :

If Y is subset or equal to X then X Y.

Ø Augmentation rule:

If X Y then XZ YZ.

Ø Transitive rule:

If {X Y, Y Z} then X Z.

Ø Decomposition rule :

If X YZ then X Y.

Ø Union or Additive rule:

If {X Y, X Z} then X YZ.

Ø Pseudo Transitive rule :

If {X Y, WY Z} then WX Z.

Of these the first three are known as Armstrong Rules. They are sound because it is enough if a set of FDs satisfy these three. They are called complete because using these three rules we can generate the rest all inference rules.

105. How can you find the minimal key of relational schema?

Minimal key is one which can identify each tuple of the given relation schema uniquely. For finding the minimal key it is required to find the closure that is the set of all attributes that are dependent on any given set of attributes

under the given set of functional dependency.

Algo. I Determining X^+ , closure for X, given set of FDs F

1. Set $X^+ = X$
2. Set Old $X^+ = X^+$
3. For each FD $Y Z$ in F and if Y belongs to X^+ then add Z to X^+
4. Repeat steps 2 and 3 until Old $X^+ = X^+$

Algo.II Determining minimal K for relation schema R, given set of FDs F

1. Set K to R that is make K a set of all attributes in R
2. For each attribute A in K
 - a. Compute $(K - A)^+$ with respect to F
 - b. If $(K - A)^+ = R$ then set $K = (K - A)^+$

106. What do you understand by dependency preservation?

Given a relation R and a set of FDs F, dependency preservation states that the closure of the union of the projection of F on each decomposed relation R_i is equal to the closure of F. i.e.,

$$((PR_1(F)) \cup \dots \cup (PR_n(F)))^+ = F^+$$

if decomposition is not dependency preserving, then some dependency is lost in the decomposition.

107. What is meant by Proactive, Retroactive and Simultaneous Update.

Proactive Update:

The updates that are applied to database before it becomes effective in real world .

Retroactive Update:

The updates that are applied to database after it becomes effective in real world .

Simultaneous Update:

The updates that are applied to database at the same time when it becomes effective in real world .

108. What are the different types of JOIN operations?

Equi Join: This is the most common type of join which involves only equality comparisons. The disadvantage in this type of join is that there

1. Write a PL/SQL program to restrict the users on Monday not to work on emp table.
2. Write a PL/SQL program to display the details of maximum salaried employee.
3. Create a sequence called Seq starting with 200 and maximum value is 20000 and must jump by 100 and it has to repeat the same set of values.
4. Create view called empdetails which contain the fields empno,ename,job, sal and comm. Also update the view by incrementing the salary where salary is less than 1500.
5. Create the following tables:

College-info

Faculty-info

College-info consists of fields : college-code, college-name, address

Faculty-info consists of fields : college-code, faculty-code, faculty-name, qualification, experience-in-no-of-years, address.

The field college-code is foreign key.

(i) List all those faculty members whose experience is greater than or equal to 10 years and have M. Tech degree.

(ii) List all those faculty members, who have at least 10 years of experience but do not have M. Tech degree.

6. Create the following tables :

Branch (branch-id, branch-name, customer-city, branch-id)

Customer (customer-id, customer-name, customer-city, branch-id)

(a) Create a form to accept the data from the user with appropriate validation checks.

(b) Generate queries to do the following :

(i) List all those customers who live in the same city as the branch in which they have account.

- (ii) List all those customers who have an account in a given branch city.
7. Write a PL/SQL function to test whether the given string is polyndrome or not. Also write a function to generate nth Fibonacci number.
8. Write a PL/SQL package containing the following :
- A procedure for sorting strings.
 - A function to generate factorial of a given number.
9. Write a parameterized cursor to display the details of employees working in a specified department.
10. Demonstrate the control structures in PL/SQL with suitable examples for each.

1. Create the following tables:

College-info

Faculty-info

College-info consists of fields : college-code, college-name, address

Faculty-info consists of fields : college-code, faculty-code, faculty-name, qualification, experience-in-no-of-years, address.

The field college-code is foreign key.

(i) List all those faculty members whose experience is greater than or equal to 10 years and have M. Tech degree.

(ii) List all those faculty members, who have at least 10 years of experience but do not have M. Tech degree.

b. Write a trigger which checks applied batch code before inserting any row in the table batch.

2. Create the following tables :

Branch (branch-id, branch-name, customer-city, branch-id)

Customer (customer-id, customer-name, customer-city, branch-id)

(i) List all those customers who live in the same city as the branch in which they have account.

(ii) List all those customers who have an account in a given branch city.

b. Write a trigger which checks whether specified batch code is of two digits or not.

3. Create the following table with the following and answer the queries.

| SNO | SNAME | CLASS | ADDRESS |
|------|---------|-------|------------|
| ---- | ----- | ----- | ----- |
| 101 | SIRISHA | CSE | PALAKOL |
| 102 | DEVAKI | CSE | NARSAPUR |
| 103 | KUMAR | CAD | BHIMAVARAM |
| 104 | RAVI | VLSI | PALAKOL |

a. List all the details of student whose class is CSE.

b. List all the details of student whose address is PALAKOL.

c. Write a trigger which is not providing any DML operation to user student1 on table entry.

4. Create a table Employee with the following columns.

| Column Name | Data Type | Description |
|-------------|-----------|---------------------------------------|
| EmpId | Integer | |
| EmpName | Varchar | |
| Dept Id | Integer | References DeptId in Department table |
| Designation | Varchar | |
| DOB | Date | |
| Salary | Integer | |
| Gender | Varchar | |

Create a table Department with the following columns

| Column Name | Data Type |
|-------------|-----------|
| DeptId | Integer |
| DeptName | Varchar |
| Location | Varchar |

b. Write a PL/SQL function to test whether a specified batch code is present or not.

5. Write a sql query to insert the details of 7 departments into the department table

| DeptNo | DeptName | Location |
|--------|-----------------------|-----------|
| 10 | Sales | Hyderabad |
| 20 | Marketing | Bombay |
| 30 | Production | Kolkatta |
| 40 | Human Resource | Pune |
| 50 | Purchases | Delhi |
| 60 | Research &Development | Bengaluru |
| 70 | Accounts | Chennai |

b. Write a PL/SQL function to compute net salary of employees department wise.

6. A. Write a sql query to display the details of all the employees with the employee names appearing in upper case and the designation appearing in lower case.

b. Write a sql query to display the details of all the employees along with their Age.

c. Draw an ER diagram for a supermarket.

d. List contents of employee using PL/SQL block.

7.a. Write a sql query to display the details of all the employees who are not managers.

b. Write a sql query to display the details of all the employees in the order of their joining date.

c. Draw an ER diagram for roadway transport company.

d. List contents of employee for a particular department using PL/SQL block.

8.a. Write a sql query to display details of all the employees of the Accounts and Purchases departments.

b. Write a sql query to display the details of all the employees whose salary is greater than Rs. 10,000.

c. List contents of employee having salary greater than or equal to 30000 using PL/SQL block.

9.A. Write a sql query to display the details of all the employees who fall into the manager designation.

b. Write a sql query to display the details of all the departments along with the count of number of employees of each department.

c. List name of department having net salary greater than the specified department.

10.a. Write a sql query to get the details of the employees with maximum and minimum salary

b. Write a sql query to get the details of the employees with maximum and minimum salary of each of the departments.

- c. List the name of the employee whose name is in same department in which Blake works.
- 11.a Write a sql query to display the details of all the employees whose salary lies between Rs. 50,000 and Rs.1,00,000.
- b. Write a sql query to calculate the average salary of an employee in each of the departments.
- c. Delete all rows from employee table using PL/SQL block.
- 12.a. Write a sql query to get the details of the departments along with the average salary of an employee in each department.
- b. Write a sql query to display the different designations in the sales and marketing departments.
- c. Delete all rows from employee for a specified deptno table using PL/SQL block.
- 13.a. Write a query to display the details of all the employees whose salary is greater than the average salary of an employee in the company.
- b. Write a query to display the details of the employees whose salary is lower than the average salary of an employee in the Marketing Department.
- c. Update employee to set salary of a specified employee as salary + 1000.
- 14.a. Write a sql query to display the details of all the employees whose salary is greater than the maximum salary in the Accounts Department.
- b. Write a sql query to display the details of all the employees whose name starts with the letter 'A'
- c. Write a PL/SQL function to test whether a specified employee is present or not.
- 15.a. Write a sql query to display the job with the highest salary and the corresponding department.
- b. Write a sql query to display the details of the employees who earn the lowest salary in each department.
- c. Write a trigger to test whether the joining date is greater than or equal to sysdate or not.
- 16.a. Write a sql query to display the details of all the employees whose age is greater than 40 years.
- b. Write a sql query to display the details of all the employees who have joined in the current year.
- c. Write a trigger before insert on employee not to insert salary greater than or equal to 100000.
- 17.a. Write a sql query to display the details of all the female employees.
- b. Write a sql query to display the details of all the female employees whose salary is greater than Rs. 50,000.
- c. Write a trigger which is not providing any DML operation to user student1 on table entry.
- 18.a. Write a sql query to display the details of all the female employees who would retire in the next year (Assume retirement age of 60 years)
- b. Write a sql query to display the details of all the employees who does not belong to the Accounts and Human Resource department.
- c. Write a trigger to set sal equal to 3000 whenever sal < 2000.
- 19.a. Write a sql query to display the details of all the employees from the place Chennai.
- b. Write a sql query to display the details of all the employees whose name is of length greater than 5 and less than 10.
- c. Write a PL/SQL package containing one function and one procedure of your choice.
- 20.a. Write a sql query to list the details of the employees whose salary is greater than the lowest salary of an employee belonging to Human Resource department.
- b. Write a sql query to list the details of the employees whose salary is lesser than the highest salary of an employee belonging to Purchases department.

- c. Write a PL/SQL package containing two mathematical functions of your choice.
1. Write a trigger which checks applied batch code before inserting any row in the table batch.
2. Write a trigger which checks whether specified batch code is of two digits or not.
3. Write a trigger which is not providing any DML operation to user student1 on table entry.
4. Write a PL/SQL function to test whether a specified batch code is present or not.
5. Write a PL/SQL function to compute net salary of employees department wise.
6. List contents of employee using PL/SQL block.
7. List contents of employee for a particular department using PL/SQL block.
8. List contents of employee having salary greater than or equal to 30000 using PL/SQL block.
9. List name of department having net salary greater than the specified department.
10. List the name of the employee whose name is in same department in which Blake works.
11. Delete all rows from employee table using PL/SQL block.
12. Delete all rows from employee for a specified deptno table using PL/SQL block.
13. Update employee to set salary of a specified employee as salary + 1000.
14. Write a PL/SQL function to test whether a specified employee is present or not.
15. Write a trigger to test whether the joining date is greater than or equal to sysdate or not.
16. Write a trigger before insert on employee not to insert salary greater than or equal to 100000.
17. Write a trigger which is not providing any DML operation to user student1 on table entry.
18. Write a trigger to set sal equal to 3000 whenever sal < 2000.
19. Write a PL/SQL package containing one function and one procedure of your choice.
20. Write a PL/SQL package containing two mathematical functions of your choice.

QUERIES

1. Create the following tables:

College-info

Faculty-info

College-info consists of fields : college-code, college-name, address

Faculty-info consists of fields : college-code, faculty-code, faculty-name, qualification, experience-in-no-of-years, address.

The field college-code is foreign key.

(i) List all those faculty members whose experience is greater than or equal to 10 years and have M. Tech degree.

(ii) List all those faculty members, who have at least 10 years of experience but do not have M. Tech degree.

2. Create the following tables :

Branch (branch-id, branch-name, customer-city, branch-id)

Customer (customer-id, customer-name, customer-city, branch-id)

(i) List all those customers who live in the same city as the branch in which they have account.

(ii) List all those customers who have an account in a given branch city.

3. Create the following table with the following and answer the queries.

| SNO | SNAME | CLASS | ADDRESS |
|------|---------|-------|---------|
| ---- | ----- | ----- | ----- |
| 101 | SIRISHA | CSE | PALAKOL |

| | | | |
|-----|--------|------|------------|
| 102 | DEVAKI | CSE | NARSAPUR |
| 103 | KUMAR | CAD | BHIMAVARAM |
| 104 | RAVI | VLSI | PALAKOL |

- d. List all the details of student whose class is CSE.
- e. List all the details of student whose address is PALAKOL.

4. Create a table Employee with the following columns.

| Column Name | Data Type | Description |
|-------------|-----------|---------------------------------------|
| EmpId | Integer | |
| EmpName | Varchar | |
| Dept Id | Integer | References DeptId in Department table |
| Designation | Varchar | |
| DOB | Date | |
| Salary | Integer | |
| Gender | Varchar | |

Create a table Department with the following columns

| Column Name | Data Type |
|-------------|-----------|
| DeptId | Integer |
| DeptName | Varchar |
| Location | Varchar |

7. Write a sql query to insert the details of 7 departments into the department table

| DeptNo | DeptName | Location |
|--------|-----------------------|-----------|
| 10 | Sales | Hyderabad |
| 20 | Marketing | Bombay |
| 30 | Production | Kolkatta |
| 40 | Human Resource | Pune |
| 50 | Purchases | Delhi |
| 60 | Research &Development | Bengaluru |
| 70 | Accounts | Chennai |

- 8. A. Write a sql query to display the details of all the employees with the employee names appearing in upper case and the designation appearing in lower case.
- f. Write a sql query to display the details of all the employees along with their Age.
- g. Draw an ER diagram for a supermarket.

- 7.a. Write a sql query to display the details of all the employees who are not managers.
- b. Write a sql query to display the details of all the employees in the order of their joining date.
- c. Draw an ER diagram for roadway transport company.

8. A. Write a sql query to display details of all the employees of the Accounts and Purchases departments.
- b. Write a sql query to display the details of all the employees whose salary is greater than Rs. 10,000.
- c. Write a sql query to display the details of all the employees whose salary lies between Rs. 50,000 and Rs.1,00,000.

Select * from employee where sal between 50000 and 100000;

9. A. Write a sql query to display the details of all the employees who fall into the manager designation.
- b. Write a sql query to display the details of all the departments along with the count of number of employees of each department.
- c. Write a sql query to calculate the average salary of an employee in each of the departments.

Select deptid,avg(empid) from dept group by deptid;

10. A. Write a sql query to get the details of the employees with maximum and minimum salary
- b. Write a sql query to get the details of the employees with maximum and minimum salary of each of the departments.
- c. Write a sql query to get the details of the departments along with the average salary of an employee in each department.
- 11.a. Write a sql query to display the different designations in the sales and marketing departments.
- b. Write a query to display the details of all the employees whose salary is greater than the average salary of an employee in the company.
- c. Write a query to display the details of the employees whose salary is lower than the average salary of an employee in the Marketing Department.

- 11.a. Write a sql query to display the details of all the employees whose salary is greater than the maximum salary in the Accounts Department.
- b. Write a sql query to display the details of all the employees whose name starts with the letter 'A'
- c. Write a sql query to display the job with the highest salary and the corresponding department.
- 12.a. Write a sql query to display the details of the employees who earn the lowest salary in each department.
- b. Write a sql query to display the details of all the employees whose age is greater than 40 years.
- c. Write a sql query to display the details of all the employees who have joined in the current year.

13. A. Write a sql query to display the details of all the female employees.
- d. Write a sql query to display the details of all the female employees whose salary is greater than Rs. 50,000.
- c. Write a sql query to display the details of all the female employees who would retire in the next year (Assume retirement age of 60 years)

- 14.a. Write a sql query to display the details of all the employees who does not belong to the Accounts and Human Resource department.
- b. Write a sql query to display the details of all the employees from the place Chennai.
- c. Write a sql query to display the details of all the employees whose name is of length greater than 5 and less than 10.
- 15.a. Write a sql query to list the details of the employees whose salary is greater than the lowest salary of an employee belonging to Human Resource department.
- d. Write a sql query to list the details of the employees whose salary is lesser than the highest salary of an employee belonging to Purchases department.
- e. Write a sql query to display the details of all the employees whose name starts with any of the vowels {a,e,i,o,u} and ends with any of the letters {n,t,i,a,r,s}
- 16.a. Write a sql query to display the details of all the employees whose experience in the company is greater than 5 years.
- b. Write a sql query to update the salary of all the employees whose salary is less than 25,000 by 10%.
- c. Write a sql query to display the details of the department which have average salary greater than the average salary of the Sales Department.
- 17.a. Write a sql query to update the salary of all the employees of the Marketing Department.
- b. Draw an ER diagram for a university.
18. Demonstrate DDL commands with your own example.
19. Demonstrate constrains in oracle with suitable examples on your own tables.
20. a. Demonstrate transaction control language commands.
- b. Demonstrate DCL commands.

1. Create a table Employee with the following columns.

| Column Name | Data Type | Description |
|-------------|-----------|---------------------------------------|
| EmpId | Integer | |
| EmpName | Varchar | |
| Dept Id | Integer | References DeptId in Department table |
| Designation | Varchar | |
| DOB | Date | |
| Salary | Integer | |
| Gender | Varchar | |

2. Create a table Department with the following columns

| Column Name | Data Type |
|-------------|-----------|
| DeptId | Integer |
| DeptName | Varchar |
| Location | Varchar |

3. Write a sql query to insert the details of 7 departments into the department table

| DeptNo | DeptName | Location |
|--------|-----------------------|-----------|
| 10 | Sales | Hyderabad |
| 20 | Marketing | Bombay |
| 30 | Production | Kolkatta |
| 40 | Human Resource | Pune |
| 50 | Purchases | Delhi |
| 60 | Research &Development | Bengaluru |
| 70 | Accounts | Chennai |

4. Write a sql query to insert the details of employees for each of the departments.
5. Write a sql query to insert the details of two new departments.
6. Write a sql query to add a new column to the Employee table

| | |
|----------|------|
| HireDate | Date |
|----------|------|

7. Write a sql query to alter the data type of the column salary to float.

| | |
|--------|-------|
| Salary | Float |
|--------|-------|

8. Write a sql query to display the details of all the departments
9. Write a sql query to display the details of all the employees.
10. Write a sql query to display the details of all the employees along with the information of departments.
11. Write a sql query to display the details of all the employees with the employee names appearing in upper case and the designation appearing in lower case.
12. Write a sql query to display the details of all the employees along with their Age.
13. Write a sql query to display the details of all the employees who are not managers.
14. Write a sql query to display the details of all the employees in the order of their joining date.
15. Write a sql query to display details of all the employees of the Accounts and Purchases departments.
16. Write a sql query to display the details of all the employees whose salary is greater than Rs. 10,000.
17. Write a sql query to display the details of all the employees whose salary lies between Rs. 50,000 and Rs.1,00,000.
18. Write a sql query to display the details of all the employees who fall into the manager designation.
19. Write a sql query to display the details of all the departments along with the count of number of employees of each department.
20. Write a sql query to calculate the average salary of an employee in each of the departments.
21. Write a sql query to get the details of the employees with maximum and minimum salary
22. Write a sql query to get the details of the employees with maximum and minimum salary of each of the departments.
23. Write a sql query to get the details of the departments along with the average salary of an employee in each department.

24. Write a sql query to display the different designations in the sales and marketing departments.
25. Write a query to display the details of all the employees whose salary is greater than the average salary of an employee in the company.
26. Write a query to display the details of the employees whose salary is lower than the average salary of an employee in the Marketing Department.
27. Write a sql query to display the details of all the employees whose salary is greater than the maximum salary in the Accounts Department.
28. Write a sql query to display the details of all the employees whose name starts with the letter 'A'.
29. Write a sql query to display the job with the highest salary and the corresponding department.
30. Write a sql query to display the list of employees who belong to the same departments as a particular employee 'X'.
31. Write a sql query to display the details of the employees who earn the lowest salary in each department.
32. Write a sql query to display the details of all the employees whose age is greater than 40 years.
33. Write a sql query to display the details of all the employees who have joined in the current year.
34. Write a sql query to display the details of all the female employees.
35. Write a sql query to display the details of all the female employees whose salary is greater than Rs. 50,000.
36. Write a sql query to display the details of all the female employees who would retire in the next year (Assume retirement age of 60 years)
37. Write a sql query to display the details of all the employees who does not belong to the Accounts and Human Resource department.
38. Write a sql query to display the details of all the employees from the place Chennai.
39. Write a sql query to display the details of all the employees whose name is of length greater than 5 and less than 10.
40. Write a sql query to list the details of the employees whose salary is greater than the lowest salary of an employee belonging to Human Resource department.
41. Write a sql query to list the details of the employees whose salary is lesser than the highest salary of an employee belonging to Purchases department.
42. Write a sql query to display the details of all the employees whose name starts with any of the vowels {a,e,i,o,u} and ends with any of the letters {n,t,i,a,r,s}
43. Write a sql query to display the details of all the employees whose experience in the company is greater than 5 years.
44. Write a sql query to update the salary of all the employees whose salary is less than 25,000 by 10%.
45. Write a sql query to display the details of the department which have average salary greater than the average salary of the Sales Department.
46. Write a sql query to update the salary of all the employees of the Marketing Department.
47. Write a sql query to find the difference between the highest and the lowest salary in each department.

48. Write a sql query to add a column commission to the Employee table of data type float.
49. Write a sql query to update the value of commission based on the salary of the employee.

| Salary range (in Rs.) | commission |
|--------------------------|------------|
| < 10,000 | 5% |
| 10,000 – 50,000 | 10% |
| > 50,000 | 15% |

50. Write a sql query to find out the number of bonus shares for which an employee is eligible where the company has declared bonus based the years of experience in the company by the following scheme

| Experience (in years) | Bonus Shares |
|--------------------------|--------------|
| < 1 | Nil |
| 1- 3 | 100 |
| 3-5 | 200 |