

REQUERIMIENTOS TÉCNICOS

IMPRESORA 3D BAMBU LAB A1 COMBO CON AMS LITE – MULTICOLOR O EQUIVALENTE

Impresora 3D Bambu Lab A1 junto al AMS LITE para impresión multimaterial

Volumen de construcción (ancho x profundidad x alto)	256 x 256 x 256 mm ³
Boquilla	Acero templado de 4 mm incluido
Hotend	Full metal
Temperatura máxima del Hotend	300 °C
Diámetro de la boquilla	0.4 mm incluida, opcionales: 0.2mm, 0.6mm, 0.8mm
Diámetro del filamento	1.75 mm
Filamento compatible	PLA, PETG, TPU, PVA
Compatibilidad de superficie de placa de construcción	Placa PEI texturizada.
Temperatura máxima de la placa de construcción	100 °C
Velocidad máxima	500 mm/s
Aceleración máxima del cabezal de la herramienta	10 m/s ²
Cámara	Baja Frecuencia hasta 1080P Compatible Timelapse
Sensor de final de filamento	Sí
Odometría de filamentos	Sí
Recuperación tras corte eléctrico	Sí
Sensor de enredo de filamento	Sí
Dimensiones físicas	A1: 385 x 410 x 430 mm ³ , Tamaño del paquete : 552 x 410 x 430 mm ³ 8,3 kg , Peso bruto 11,7 kg A1 Combo: Tamaño del paquete 546 x 536 x 420 mm ³ (incluido) 14,3 kg
Requisitos eléctricos	100-240 VCA, 50/60 horas, 1000 W a 220 V, 350 W a 100 V

REFERENCIAL:

Bambu Lab A1 Technical Specification

Body

Build Volume:	256*256*256 mm ³
Chassis:	Steel + Extruded Aluminum

ToolHead

Hot End:	All-Metal
Extruder Gears:	Hardened Steel
Nozzle:	Stainless Steel
Max Hot End Temperature:	300 °C
Nozzle Diameter (Included):	0.4 mm
Nozzle Diameter (Optional):	0.2 mm, 0.6 mm, 0.8 mm
Filament Cutter:	Yes
Filament Diameter:	1.75 mm

Heatbed

Compatible Build Plate:	Bambu Textured PEI Plate Bambu Smooth PEI Plate Bambu High Temperature Plate (Smooth PEI) Bambu Cool Plate
Max Build PlateTemperature	100 °C

Speed

Max Speed of Toolhead:	5000mm/s
Max Acceleration of Toolhead:	10000mm/s ²
Max Hot End Flow:	28 mm ³ /s @ABS (Model: 150*150 mm single wall; Material: Bambu ABS; Temperature: 280 °C)

Cooling

Part Cooling Fan:	Closed Loop Control
Hot End Fan:	Closed Loop Control

Supported Filament

	Not Recommended
PLA, PETG, TPU, PVA:	Ideal
ABS, ASA, PC, PA, PET, Carbon/Glass Fiber Reinforced Polymer:	

Sensors

Monitoring Camera:	Low Rate Camera (up to 1080P) Timelapse Supported
Filament Run Out Sensor:	Yes
Filament Odometry:	Yes
Power Loss Recover:	Yes
Filament Tangle Sensor:	Yes

Physical Dimensions

Dimensions:	385*410*430mm ³
Net Weight :	8.3 kg

Electrical Parameters

Input Voltage:	100-240 VAC, 50/60 Hz
Max Power:	1300W@220V, 350W@110V

Electronics

Display:	3.5 inches 320*240 IPS Touch Screen
Connectivity:	Wi-Fi, Bambu-Bus
Storage:	Micro SD Card
Control Interface:	Touch Screen, APP, PC Application
Motion Controller:	Dual-Core Cortex M4

Software

Slicer:	Bambu Studio Support third party slicers which export standard Gcode such as Superslicer, Prusaslicer and Cura, but certain advanced features may not be supported.
Slicer Supported OS:	MacOS, Windows

Wi-Fi

Frequency Range:	2412 MHz - 2472 MHz (CE) 2412 MHz - 2462 MHz (FCC) 2400 MHz - 2483.5 MHz (SRRC)
Transmitter Power (EIRP):	≤ 21.5 dBm (FCC) ≤ 20 dBm (CE/SRRC)
Protocol:	IEEE 802.11 b/g/n