Blastoid API

Concept

The **Blastoid API** is featured in Quick Launch for ReText.

Key features include:

- Rico File Download
- HTML Scraper
- JSON Scraper Results
- JSOM Scraper Results

The primary use case is to examine (scrape) HTML SCRIPT elements. Though it also supports any element with an ID value.

The main **Entry Point**, which doubles as an **Accessor Object**, is `blastoid()`. This function accepts a single ID value as an argument. It then locates the object and reads its content.

Content is based on the object's HTML `nodeName` property.

The ID is used as a filename. This and the content are passed to the `rico()` method. The overall action is to export an HTML element as Plain Text.

Members

Name	Type	Purpose
options	Object	Blob Options for rico
jsom	Method	Scrape Elements as JSOM
json	Method	Scrape Elements as JSON
mods	Method	Scrape Elements as Core Table
read	Method	Read Element’s Content
rico	Method	Save Plain Text File

Related Links

- This Document
- **Published eBook**
  - Morpheus
  - Omega
- **Quick Links**
  - Omega
- **Morpheus**
  - Home Page
  - Snek
  - Owl System Test
- **LAN Hosts**
  - Omega ReText Notes
- **Project Tools**
  - Project Notes
  - Gemini Chats
- **Related Projects**
  - HUD Editor
  - Chatter
  - Tonto Editor