

CAN Communications Protocol

V1.0

1. Version revision record

Serial Num	Description	Date	Version	Author
1.	Initial version	2019.06.11	V1.0	

1.Physical layer

1.1 UART

1. physical interface	CAN
2. baud rate	250K

2.Communication format

2.1 Basic timing

All messages are sent by the host, all slaves receive messages to determine whether the slave address matches, only in the case of slave address match allowed to return data to the host.

2.2 Address assignment

Module	Address
BMS master	0x01
Bluetooth APP	0x80
GPRS	0x20
Upper computer	0x40

2.3 CAN Communication Format

2.3.1 PC send

CAN ID (4 Bytes)	Data
Priority + Data ID + BMS Address +PC Address 0x18100140	8 Bytes

2.3.2 The slave responds to the host command

CAN ID (4 Bytes)	Data
Priority + Data ID + PC Address +BMS Address 0x18104001	8 Bytes

3.Communications content information

Data Message	Data ID	UPPER-BMS	Note Remark
SOC of total voltage current	0x90	Send	Byte0~Byte7: Reserved
		Received	Byte0~Byte1:Cumulative total voltage (0.1 V) Byte2~Byte3:Gather total voltage (0.1 V) Byte4~Byte5:Current (30000 Offset ,0.1A) Byte6~Byte7:SOC (0.1%)
Maximum & Minimum voltage	0x91	Send	Byte0~Byte7: Reserved
		Received	Byte0~Byte1:Maximum cell voltage value (mV) Byte2:No of cell with Maximum voltage Byte3~byte4: Minimum cell voltage value (mV) Byte5:No of cell with Minimum voltage
Maximum & Minimum temperature	0x92	Send	Byte0~Byte7: Reserved
		Received	Byte0: Maximum temperature value (40 Offset ,°C) Byte1: Maximum temperature cell No Byte2: Minimum temperature value (40 Offset ,°C) Byte3: Minimum temperature cell No
Charge & discharge MOS status	0x93	Send	Byte0~Byte7: Reserved
		Received	Byte0:State (0 stationary 1 charge 2 discharge) Byte1:Charge MOS state Byte2:Discharge MOS status Byte3:BMS life (0~255 cycles) Byte4~Byte7:Remain capacity (mAH)
Status information 1	0x94	Send	Byte0~Byte7: Reserved
		Received	Byte0:No of battery string Byte1: No of Temperature Byte2: Charger status (0 disconnect 1 access) Byte3: Load status (0 disconnect 1 access) Byte4: Bit 0:DI1state Bit 1:DI2state Bit 2:DI3state Bit 3:DI4state Bit 4:DO1state Bit 5:DO2state Bit 6:DO3state Bit 7:DO4state Byte 5~Byte 7: Reserved
Cell voltage 1~48	0x95	Send	Byte0~Byte7: Reserved

		Received	<p>The voltage of each monomer is 2 byte, according to the actual number of cell, the maximum 96 byte, is sent in 16 frames</p> <p>Byte0:frame number, starting from 0,0xFF invalid</p> <p>Byte1~byte6:Cell voltage (1 mV)</p> <p>Byte7: Reserved</p>
Cell temperature 1~16	0x96	Send	Byte0~Byte7: Reserved
		Received	<p>Each temperature accounts for 1 byte, according to the actual number of temperature send, the maximum 21 byte, send in 3 frames</p> <p>Byte0:frame number, starting at 0</p> <p>Byte1~byte7:cell temperature(40 Offset ,°C)</p>
Cell balance State 1~48	0x97	Send	Byte0~Byte7: Reserved
		Received	<p>0: Closed 1: Open</p> <p>Bit0: Cell 1 balance state</p> <p>...</p> <p>Bit47:Cell 48 balance state</p> <p>Bit48~Bit63: reserved</p>
Battery failure status	0x98	Send	Byte0~Byte7: Reserved
		Received	<p>0->No error 1->Error</p> <p>Byte 0</p> <p>Bit 0: Cell volt high level 1</p> <p>Bit 1: Cell volt high level 2</p> <p>Bit 2: Cell volt low level 1</p> <p>Bit 3: Cell volt low level 2</p> <p>Bit 4: Sum volt high level 1</p> <p>Bit 5: Sum volt high level 2</p> <p>Bit 6: Sum volt low level 1</p> <p>Bit 7: Sum volt low level 2</p> <p>Byte 1</p> <p>Bit 0: Chg temp high level 1</p> <p>Bit 1: Chg temp high level 2</p> <p>Bit 2: Chg temp low level 1</p> <p>Bit 3: Chg temp low level 2</p> <p>Bit 4: Dischg temp high level 1</p> <p>Bit 5: Dischg temp high level 2</p> <p>Bit 6: Dischg temp low level 1</p> <p>Bit 7: Dischg temp low level 2</p> <p>Byte 2</p> <p>Bit 0: Chg overcurrent level 1</p> <p>Bit 1: Chg overcurrent level 2</p> <p>Bit 2: Dischg overcurrent level 1</p> <p>Bit 3: Dischg overcurrent level 2</p> <p>Bit 4: SOC high level 1</p>

		<p> Bit 5: SOC high level 2 Bit 6: SOC Low level 1 Bit 7: SOC Low level 2 Byte 3 Bit 0: Diff volt level 1 Bit 1: Diff volt level 2 Bit 2: Diff temp level 1 Bit 3: Diff temp level 2 Bit 4~Bit7:Reserved Byte 4 Bit 0: Chg MOS temp high alarm Bit 1: Dischg MOS temp high alarm Bit 2: Chg MOS temp sensor err Bit 3: Dischg MOS temp sensor err Bit 4: Chg MOS adhesion err Bit 5: Dischg MOS adhesion err Bit 6: Chg MOS open circuit err Bit 7: Discrg MOS open circuit err Byte 5 Bit 0: AFE collect chip err Bit 1: Voltage collect dropped Bit 2: Cell temp sensor err Bit 3: EEPROM err Bit 4: RTC err Bit 5: Precharge failure Bit 6: Communication failure Bit 7: Internal communication failure Byte6 Bit 0: Current module fault Bit 1: Sum voltage detect fault Bit 2: Short circuit protect fault Bit 3: Low volt forbidden chg fault Bit4-Bit7: Reserved Byte7: Fault code </p>
--	--	---