



CSCI 3302

Introduction to Robotics

Alessandro Roncone

aroncone@colorado.edu




Lab 2

Odometry


Agenda

- Review from Last Lab
- Introduce Lab 2

Last Time




Reactive Behaviors



State Machines

Today: Odometry




Odometer:
Integrates velocity

Example from last lab: when do I know I turned 180 degrees?

Question: *What variable is missing to fully define the robot's pose on the plane?*


Today: Odometry



Odometer:
Integrates velocity


Example from last lab: when do I know I turned 180 degrees?

Lab Setup



- Which direction is the robot driving in the world coordinate frame?
- What unit is the robot's wheel-speed?
- How many meters is this per second?
- What is its pose after one complete tour?

Lab Setup





- Which direction is the robot driving in the world coordinate frame? *Along positive Z*
- What unit is the robot's wheel-speed? *Rad/s*
- How many meters is this per second? *Radius * Rad/s*
- What is its pose after one complete tour? *(0,0,0)*


How can I find out how fast the robot is?




Angular and forward speed




Forward Kinematics of a Mobile Robot



Superposition of velocities



Forward Kinematics of a Mobile Robot




$$\dot{x}_I = \cos(\theta) \dot{x}_R - \sin(\theta) \dot{y}_R$$

$$\dot{y}_I = \sin(\theta) \dot{x}_R + \cos(\theta) \dot{y}_R$$

$$\dot{\theta}_I = \dot{\theta}_R$$

$$\begin{pmatrix} \dot{x}_I \\ \dot{y}_I \\ \dot{\theta} \end{pmatrix} = \begin{pmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} \frac{r\dot{\phi}_l}{2} + \frac{r\dot{\phi}_r}{2} \\ 0 \\ \frac{\dot{\phi}_r r}{d} - \frac{\dot{\phi}_l r}{d} \end{pmatrix}$$

Your coordinate system



How can we compute position?

$$\begin{pmatrix} x_I(T) \\ y_I(T) \\ \theta(T) \end{pmatrix} = \boxed{\quad} \begin{pmatrix} \dot{x}_I(t) \\ \dot{y}_I(t) \\ \dot{\theta}(t) \end{pmatrix} \boxed{\quad}$$

How can we compute position?

$$\begin{pmatrix} x_I(T) \\ y_I(T) \\ \theta(T) \end{pmatrix} = \int_0^T \begin{pmatrix} \dot{x}_I(t) \\ \dot{y}_I(t) \\ \dot{\theta}(t) \end{pmatrix} dt \approx \sum_{k=0}^{k=T} \begin{pmatrix} \Delta x_I(k) \\ \Delta y_I(k) \\ \Delta \theta(k) \end{pmatrix} \Delta t$$



`int(robot.getBasicTimeStep())`

From linear algebra/diff equations to code

$$\begin{pmatrix} \dot{x}_I \\ \dot{y}_I \\ \dot{\theta} \end{pmatrix} = \begin{pmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} \frac{r\dot{\phi}_l}{2} + \frac{r\dot{\phi}_r}{2} \\ 0 \\ \frac{\dot{\phi}_r r}{d} - \frac{\dot{\phi}_l r}{d} \end{pmatrix}$$



1. Robot never moves sideways

$$\begin{pmatrix} \dot{x}_I \\ \dot{y}_I \\ \dot{\theta} \end{pmatrix} = \begin{pmatrix} \cos(\theta) & 0 \\ \sin(\theta) & 0 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} \frac{r\dot{\phi}_l}{2} + \frac{r\dot{\phi}_r}{2} \\ \frac{\dot{\phi}_r r}{d} - \frac{\dot{\phi}_l r}{d} \end{pmatrix}$$

2. Multiply matrices

$$\dot{x}_I = \cos(\theta) \left(\frac{r\dot{\phi}_l}{2} + \frac{r\dot{\phi}_r}{2} \right)$$

$$\dot{y}_I = \sin(\theta) \left(\frac{r\dot{\phi}_l}{2} + \frac{r\dot{\phi}_r}{2} \right)$$

$$\dot{\theta} = \frac{\dot{\phi}_r r}{d} - \frac{\dot{\phi}_l r}{d}$$

3. Integrate

$$\begin{pmatrix} x_I(T) \\ y_I(T) \\ \theta(T) \end{pmatrix} += \begin{pmatrix} \Delta x_I(k) \\ \Delta y_I(k) \\ \Delta \theta(k) \end{pmatrix} \Delta t$$

Sources of Error

Deterministic


- Unequal wheel diameter
- Wheel contact point variation

Non-deterministic

- Variable friction
- Measurement noise

Addressed with
calibration

Code Suggestions



- Start implementing line following. Do NOT move forward before line following is not robust.
- Use an if/elif chain to check which state your system is in.
- Don't ever use time.sleep() or estimate the elapsed time, instead skip steps in the loop and call robot_step()




```
current_state = 'STATE_1'  
while robot.step(TIME_STEP) != -1:  
    if current_state == 'STATE_1':  
        pass  
    elif current_state == 'STATE_2':  
        pass
```

Need Help? Send a chat message!

Group programming IDEs: www.codeshare.io | <http://collabedit.com/>

FAQs:

- What's due at the end of today?
 - Nothing, this is a 2-week lab. Due Tuesday 2/11 at 11:59pm.
- What do I turn in?
 - ONE person needs to turn in the lab report and code per group.
- We're done! Can we leave?
 - Yep. Lab is meant to provide an interactive problem-solving time. If you complete the work early, you are free to go!



Questions?