Сорока-Белобока кашу варила,
Деток кормила:

- Этому дала, - Этому дала,

querySelectorAll() ⇒ [🖐, ✋]
NodeList

[🖐 , ✋].forEach(🥣);

```
>> document.querySelectorAll('button');
<- ▼ NodeList(3) [ button#red ⬡ , button#blue ⬡ , button#green ⬡ ]
      ▶ 0: <button id="red"> ⬡
      ▶ 1: <button id="blue"> ⬡
      ▶ 2: <button id="green"> ⬡
        length: 3
      ▶ <prototype>: NodeListPrototype { item: item(), keys: keys(), values: values(), … }
```

```
document.querySelectorAll('button').forEach(function(button) {
    button.onclick = function() {
        document.querySelector('#hello').style.color =
            button.dataset.color;
}; });
```

Red | Blue | Green

When the page is done loading

```
<script>
    document.addEventListener('DOMContentLoaded', function() {
```

I'm going to document.querySelectorAll, looking for all of the buttons

```
    document.querySelectorAll('.color-change').forEach(
        function(button) {
```

looked for things of the particular class

```
button.onclick = function() {
document.querySelector('#hello').style.color = button.dataset.color;
        };
    });
    });
</script>
```

─── **HTML** ───
```
<button class="color-change" data-color="red">Red</button>
    <button class="color-change" data-color="blue">Blue</button>
    <button class="color-change" data-color="green">Green</button>
```

```
<button class="color-change"
data-color="red">Red</button>
```

function that takes as input, the button | It's first going to pass in as input the first button [Red]
then the second button [Blue]
then the third button [Green]

```
function(button) {
        button.onclick = function() {
```

```
document.querySelector('#hello').
    style.color =
        button.dataset.color;
    };
```

function() {…}

```
function(but) {
but.onclick =
    function() {…}
        }
```

() => {…}

```
but => {
    but.onclick =
        () => {…}
    }
```

```
<head>
    <script>
    document.addEventListener('DOMContentLoaded', () => {
        document.querySelector('#color-change').onchange = function() {
            document.querySelector('#hello').style.color = this.value;
        };
    });
    </script>
</head>
  <body>
    <h1 id="hello">Hello!</h1>
    <select id="color-change">
      <option value="red">Red</option>
      <option value="blue">Blue</option>
      <option value="green">Green</option>
    </select>
</body>
```

Hello!

Red ▾
Black
Red
Blue
Green