

This document was generated on 07/14/2014

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 95009-7661

Status: Active

Overview: Modular Plugs - Jacks

**Description:** Modular Jack, Right Angle, 6/6, Panel Stops, Palladium Nickel (PdNi)

**Documents:** 

3D Model Test Summary STR-1422 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-95009-001 (PDF)

**Agency Certification** 

UL E107635

General

Product Family Modular Jacks/Plugs

Series 95009
Comments Flush Mount
Component Type PCB Jack
Magnetic No

Overview <u>Modular Plugs - Jacks</u>

Performance Category 3
Power over Ethernet (PoE) N/A
Product Name RJ11

UPC 884982793804

**Physical** 

Color - ResinBlackDurability (mating cycles max)2,500Flammability94V-0Inverted / Top LatchNoJack Height16.00mmLightpipes/LEDsNone

Material - Metal Brass
Material - Plating Mating Palladium Nickel

Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 2.720/g

Orientation Right Angle (Side Entry)

PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 1.57mm
Packaging Type Tray
Panel Mount With Flange
Pitch - Mating Interface 1.02mm
Pitch - Termination Interface 1.27mm

Pitch - Termination Interface

Plating min - Mating

Plating min - Termination

Ports

Positions / Loaded Contacts

Surface Mount Compatible (SMC)

1.270µm

1.905µm


6/6

No

Temperature Range - Operating -40°C to +80°C Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A

## **Electrical**



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

<u>95009</u>Series

Mates With FCC 68 Plugs

Current - Maximum per Contact 1.5A
Shielded No
Voltage - Maximum 125V DC

**Material Info** 

**Reference - Drawing Numbers** 

Product Specification PS-95009-001
Sales Drawing SDA-95009-F
Test Summary STR-1422

This document was generated on 07/14/2014

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION