# Publication Validation Report (pub-check): CSAF v2.1 CSD01 (corpus)

**Not publishable: 1 blocker, 14 warnings**

The document cannot be published until each blocker below is fixed.

## Blockers: fix these

| Where | What is wrong | How to fix it |
|---|---|---|
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 13 | The public review metadata file is missing, empty or cannot be opened.<br>Found: csd01 underwent a TC public review (Tier 1 (a comment-resolution-log for this revision is already live)) but the live stage directory https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/ does not carry the required companion file csaf-v2.1-csd01-public-review-metadata.html. Naming Directives v1.7 s5.2: 'Project Administration will publish an additional "public review metadata" file in the directory with the CSD or CND'; TC Handbook Naming: 'Work products undergoing public review must include a companion metadata file.' | Include the public review metadata file for this draft in the package. |

## 14 warnings: worth checking, but they do not stop publication

| Where | What is wrong | How to fix it |
|---|---|---|
| Not tied to one line | There is a horizontal line between the OASIS logo and the title on the cover page.<br>Found: Horizontal rule between the OASIS logo and the title: the publication CSS treats <hr/> as a page break, which opens the PDF with a blank page. Harmless in other renderers; remove if publishing through the OASIS HTML-to-PDF path. | Delete the horizontal line (--- in Markdown, <hr> in HTML) between the logo and the title. |
| Not tied to one line | The date of the document does not match between its formats, or the copyright year does not match the document date.<br>Found: Copyright year 2022 does not match the document date year 2025. | Use the same date in the Markdown, the HTML and the PDF, and make the copyright year the year of that date. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 63 | A link in the Markdown is written in a way that displays badly in the HTML or PDF.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/aggregator.json | Write a web address on its own as <https://...>, or give the link real text, as in [link text](https://...). Put a space after an address that ends a sentence. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 64 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/csaf.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 65 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/meta.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 66 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/provider.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 486 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://www.oasis-open.org/committees/csaf/ipr.php | As above. |

| Where | What is wrong | How to fix it |
|---|---|---|
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 3795 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://www.first.org/cvss/cvss-v2.0.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 3798 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://www.first.org/cvss/cvss-v3.0.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 3799 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://www.first.org/cvss/cvss-v3.1.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 3802 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://www.first.org/cvss/cvss-v4.0.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 3805 | Same as above.<br>Found: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://certcc.github.io/SSVC/data/schema/v1/Decision_Point_Value_Selection-1-0-1.schema.json | As above. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf | The PDF table of contents has no page numbers, or a page number is wrong.<br>Found: The PDF's table of contents gives no page number for 356 of its 356 entries: a reader of the PDF cannot find a section by it. | Rebuild the PDF so the table of contents shows the page on which each section starts. |
| examples/csaf/v2.1/csd01/csaf-v2.1-csd01.md line 13 | A draft with this label is already published on docs.oasis-open.org.<br>Found: Stage /csd01/ is already published at https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/: a NEW submission for v2.1 must use the next revision number instead. Ignore this warning if you are re-checking the published package itself. | Use the next draft number (for example csd02 instead of csd01) for this publication. |

6 notes for information only, with nothing to change, are in the tables below.

## Report details

| | |
|---|---|
| Target | `examples/csaf/v2.1/csd01` |
| Validation date | 2026-10-28 |
| Tool | oasis_pub_check.py (OASIS-Docs/publication-assurance) |
| Coverage | 186 individual checks across 62 check classes, all run |
| Blockers | 1 |
| Checker exit code | 1 |

**NOT publication-ready: 1 blocker(s). 51 of 60 evaluated check classes fully clean; 2 not evaluated; findings: 1 blocker, 14 warning, 6 informational.**

## Check-by-Check Results

Every check class the tool carries is listed, whether or not it raised a finding. Conditions is the number of individual verifications inside the class.

| # | Result | Check class | Cond. | Findings |
|---|---|---|---|---|
| 1 | PASS | artifact-naming | 1 | none |
| 2 | PASS | asset-refs | 1 | none |
| 3 | PASS | authors | 4 | none |
| 4 | PASS | boilerplate-dup | 1 | none |
| 5 | PASS (2 of 3 evaluated) | case | 3 | none |
| 6 | PASS | comment-resolution-log | 2 | none |
| 7 | PASS | conformance-structure | 9 | none |
| 8 | INFO | content-labels | 1 | INFO: Appendix/Annex heading 'Appendix A. Acknowledgments <a id='acknowledgments'></a>' (markdown line 11935) carries no content-type statement. Advisory only: say under its title whether it is part of the conformance requirements, for example with the OASIS template's '(This appendix does not form an integral part of this Specification and is informational.)'; Conformance Requirements for Specifications v1.0, 7.3: 'normative and informative sections SHALL be evident and, if necessary, labeled accordingly'.<br>INFO: Appendix/Annex heading 'Appendix B. Revision History <a id='revision-history'></a>' (markdown line 12061) carries no content-type statement. Advisory only: say under its title whether it is part of the conformance requirements, for example with the OASIS template's '(This appendix does not form an integral part of this Specification and is informational.)'; Conformance Requirements for Specifications v1.0, 7.3: 'normative and informative sections SHALL be evident and, if necessary, labeled accordingly'.<br>INFO: Document-wide blanket example content-type statement found (no unlabeled example heading needed it): "All examples in this document are informative" |
| 9 | WARN | cover-hr | 1 | WARN: Horizontal rule between the OASIS logo and the title: the publication CSS treats <hr/> as a page break, which opens the PDF with a blank page. Harmless in other renderers; remove if publishing through the OASIS HTML-to-PDF path. |
| 10 | WARN | date-sync | 2 | WARN: Copyright year 2022 does not match the document date year 2025. |
| 11 | PASS (2 of 3 evaluated) | dead-lists | 3 | none |
| 12 | PASS | double-slash | 1 | none |
| 13 | PASS | extension-conformance | 1 | none |
| 14 | PASS | extension-count | 4 | none |
| 15 | PASS | fence-collapse | 1 | none |
| 16 | PASS | filenames | 6 | none |
| 17 | PASS (8 of 11 evaluated) | front-matter | 11 | none |
| 18 | NA | generator | 1 | NA: DOCX-render condition; this package carries no Word source |
| 19 | PASS | html-anchors | 3 | none |
| 20 | PASS | html-code-sync | 2 | none |
| 21 | PASS | html-residue | 4 | none |

| # | Result | Check class | Cond. | Findings |
|---|---|---|---|---|
| 22 | PASS | html-title | 2 | none |
| 23 | PASS | image-policy | 11 | none |
| 24 | PASS | junk-files | 2 | none |
| 25 | PASS | link-mismatch | 2 | none |
| 26 | PASS | logo | 1 | none |
| 27 | INFO (0 of 3 evaluated) | manifest | 3 | INFO: No manifest.json in the package. Emit one (--emit-manifest or your own tool) and intake verification becomes automatic. |
| 28 | WARN | md-links | 2 | WARN: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/aggregator.json<br>WARN: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/csaf.json<br>WARN: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/meta.json<br>WARN: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/provider.json<br>WARN: Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://www.oasis-open.org/committees/csaf/ipr.php<br>... and 5 more findings of this class (full list in the JSON record) |
| 29 | PASS | member-uri | 1 | none |
| 30 | PASS | multi-part-naming | 8 | none |
| 31 | PASS | name-chars | 4 | none |
| 32 | PASS | normdef-refs | 2 | none |
| 33 | PASS | ns-segment | 2 | none |
| 34 | NA | odt-integrity | 6 | NA: ODT-source condition; this package carries no ODT source |
| 35 | PASS | package-refs | 2 | none |
| 36 | PASS | pdf-cover | 2 | none |
| 37 | INFO (0 of 2 evaluated) | pdf-fonts | 2 | INFO: Package declares no local font authority (no font-family in its HTML/CSS); font check skipped. |
| 38 | PASS | pdf-legibility | 2 | none |
| 39 | PASS | pdf-sync | 6 | none |
| 40 | WARN | pdf-toc-pages | 2 | WARN: The PDF's table of contents gives no page number for 356 of its 356 entries: a reader of the PDF cannot find a section by it. |
| 41 | PASS (1 of 2 evaluated) | previous-stage | 2 | none |
| 42 | BLOCKER | public-review-metadata | 4 | BLOCKER: csd01 underwent a TC public review (Tier 1 (a comment-resolution-log for this revision is already live)) but the live stage directory https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/ does not carry the required companion file csaf-v2.1-csd01-public-review-metadata.html. Naming Directives v1.7 s5.2: 'Project Administration will publish an additional "public review metadata" file in the directory with the CSD or CND'; TC Handbook Naming: 'Work products undergoing public review must include a companion metadata file.' |
| 43 | PASS | ref-rfc | 2 | none |
| 44 | PASS | references-split | 2 | none |

| # | Result | Check class | Cond. | Findings |
|---|---|---|---|---|
| 45 | PASS | residue | 4 | none |
| 46 | WARN | revision-collision | 2 | WARN: Stage /csd01/ is already published at https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/: a NEW submission for v2.1 must use the next revision number instead. Ignore this warning if you are re-checking the published package itself.<br>INFO: Published stages already live under https://docs.oasis-open.org/csaf/csaf/v2.1/: csd01, csd02, csd03, csd04. |
| 47 | PASS | rfc-keywords | 2 | none |
| 48 | PASS | schema-id | 5 | none |
| 49 | PASS | stage-name | 4 | none |
| 50 | PASS | stage-token | 3 | none |
| 51 | PASS | stage-uri-live | 1 | none |
| 52 | PASS | symlinks | 1 | none |
| 53 | PASS | template | 3 | none |
| 54 | PASS | template-css | 2 | none |
| 55 | PASS | title-oasis-prefix | 1 | none |
| 56 | PASS | title-version | 3 | none |
| 57 | PASS (6 of 9 evaluated) | uri-alias | 9 | none |
| 58 | PASS | uri-chars | 1 | none |
| 59 | PASS | version-naming | 3 | none |
| 60 | PASS | version-refs | 1 | none |
| 61 | PASS | vml-fallback | 1 | none |
| 62 | PASS | xml-namespace | 6 | none |

## All Individual Conditions: Observed vs Expected

Every one of the 186 individual conditions, with the value the check pulled from this package and what it was compared against. NA rows state why the condition does not apply to this package.

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 1 | PASS | stage-name | Stage directory name, and an erratNN parent directory, carry a two-digit number | stage_directory: csd01 | valid stage prefixes must carry exactly two digits (csd01, never bare csd or csd1); an Errata directory is /errata01/ (the OASIS Naming Directives v1.7 Section 4) |
| 2 | PASS | stage-name | A package staged for publication is not a Working Draft | stage_directory: csd01 | wd: Working Drafts are unpublished and may use any naming (the OASIS Naming Directives v1.7 5.2 note); docs.oasis-open.org has no wd location (dmlex/v1.1/wd01 returns 404) |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 3 | PASS | stage-name | Stage token is not a retired abbreviation | stage_directory: csd01 | retired token set (csprd, cnprd, cos, csdpr, cndpr) per Naming Directives v1.7 |
| 4 | PASS | stage-name | Stage token (and an Errata parent directory) is a recognized current stage, in lower case, and os carries no revision number | stage_directory: csd01 | valid stage set: wd, csd, cs, cnd, cn, os, ps, psd, pn, pnd, errata; lower case, and 'The os stage abbreviation is never used with a revision number' (the OASIS Naming Directives v1.7 5.2) |
| 5 | PASS | version-naming | Version directory matches the vN.N(.N) convention | version_directory: v2.1; delivery_stem: csaf-v2.1-csd01 | the Naming Directives version-segment pattern vN.N(.N), e.g. v1.0, v2.0.1 |
| 6 | PASS | version-naming | Version embedded in the delivery filename agrees with the version directory | version_directory: v2.1; delivery_stem: csaf-v2.1-csd01 | the version directory the package publishes under |
| 7 | PASS | version-naming | Delivery filename embeds the version segment | version_directory: v2.1; delivery_stem: csaf-v2.1-csd01 | the Naming Directives filename shape <base>-<version>-<stage> |
| 8 | WARN | revision-collision | The submitted stage does not already exist on the live site | Stage /csd01/ is already published at https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/: a NEW submission for v2.1 must use the next revision number instead. Ignore this warning if you are re-checking the published package itself. | expected non-200 for a NEW submission; an existing stage means the revision must increment |
| 9 | PASS | revision-collision | The live-site collision check is not silently skipped when the cover gives no This-stage base URL | this_stage_url: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/; http_status: 200 | a base URL under this package's own /version/stage/ directory; without one the check reports NOT EVALUATED |
| 10 | PASS | filenames | The stage directory contains delivery items at all | stems: csaf-v2.1-csd01; delivery_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; formats_present: html, md, pdf; required_formats: html, md, pdf | at least one delivery item (md/docx/odt/html/pdf) must be present |
| 11 | PASS | filenames | All delivery items share one basename, and the stage directory and package zip hold only that document | stems: csaf-v2.1-csd01; delivery_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; formats_present: html, md, pdf; required_formats: html, md, pdf | exactly one distinct stem across md/docx/odt/html/pdf; another [WP-abbrev]-[version]-[stage] identifier, or a zip named for one, is a second package |
| 12 | PASS | filenames | Delivery filename carries no working token | stems: csaf-v2.1-csd01; delivery_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; formats_present: html, md, pdf; required_formats: html, md, pdf | forbidden working tokens: draft, tmp, rc (files are named for the published stage) |
| 13 | PASS | filenames | Delivery filename ends in the stage suffix | stems: csaf-v2.1-csd01; delivery_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; formats_present: html, md, pdf; required_formats: html, md, pdf | the stage directory name as a -<stage> suffix, or -erratanN-<stage> inside an Errata directory |
| 14 | PASS | filenames | All required delivery formats are present | stems: csaf-v2.1-csd01; delivery_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; formats_present: html, md, pdf; required_formats: html, md, pdf | the track's required set: html+pdf plus the authoritative source (md, docx, or odt) |
| 15 | PASS | filenames | An authoritative source artifact travels with the renderings | stems: csaf-v2.1-csd01; delivery_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; formats_present: html, md, pdf; required_formats: html, md, pdf | at least one authoritative source (.md, .docx, or .odt) expected beside HTML/PDF |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 16 | PASS | `stage-uri-live` | Every Previous-stage and Latest-stage URI the cover declares actually retrieves | previous_stage_urls: (none); latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf; stage_uris_fetched: 3; latest_created_by_this_publication: (none) | a definitive 404/410 from the published site (transport failures and non-404 errors stay INFO) |
| 17 | PASS | `front-matter` | Markdown front matter carries a This-stage URL block | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | at least one URL must be declared |
| 18 | PASS | `front-matter` | Every stage URL is under docs.oasis-open.org | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | the canonical site prefix https://docs.oasis-open.org/ |
| 19 | PASS | `front-matter` | This-stage URLs carry the version and stage path segments | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | the package's /<version>/ and /<stage>/ path segments |
| 20 | PASS | `front-matter` | Every This-stage URL points at a file included in the package | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | the set of delivery filenames actually in the package |
| 21 | PASS | `front-matter` | The This-stage block lists all three artifacts (md, html, pdf) | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | the full delivery set: .md, .html, .pdf |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 22 | PASS | front-matter | Latest-stage URLs point at the persistent version root | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | must NOT contain the /<stage>/ segment (latest is the version-root path) |
| 23 | PASS | front-matter | Latest-stage URLs are under the package's version directory | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | the package's /<version>/ path segment |
| 24 | PASS | version-refs | A docs.oasis-open.org link to another version of this work product is intended | own_work_product_urls_compared: 22; other_versions_cited_in_references: (none) | the package's own version; another version of this work product cited elsewhere is a stale-draft tell |
| 25 | PASS | front-matter | No Latest-labelled line cites a stage-pinned URL for this spec | this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | the persistent version-root form (no /<stage>/ segment) |
| 26 | PASS | uri-chars | No underscore appears in a This/Latest-stage document URI | cover_uris_scanned: 6 | Naming Directives v1.7 s3: '_' is barred from any filename or directory name used in a document URI |
| 27 | PASS | member-uri | No OASIS member-only (Kavi) URI is cited in the package | member_only_uris: (none) | Naming Directives v1.7 s6.6: member-only (password-protected) Kavi references must not appear in public TC documents |
| 28 | NA | front-matter | HTML cover carries a This-version URL block | NA: DOCX-render condition; this package carries no Word source | at least one URL must be present |
| 29 | NA | front-matter | Cover This-version URLs carry the version and stage segments | NA: DOCX-render condition; this package carries no Word source | the package's /<version>/ and /<stage>/ path segments |
| 30 | NA | front-matter | Cover Latest-version URLs point at the persistent version root | NA: DOCX-render condition; this package carries no Word source | must NOT contain the /<stage>/ segment |
| 31 | PASS | residue | No editor TODO markers left in prose | scanned: html, markdown | the patterns TODO(...) and TODO: must not occur |
| 32 | PASS | residue | No bare 'tbd' placeholder sections | scanned: html, markdown | no line consisting solely of 'tbd' |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 33 | PASS | residue | No template editor-instruction text left in the published prose | scanned: html, markdown | the OASIS Board-approved work product templates, which state that 'All template instructions ... need to be deleted prior to publication'; an imperative to remove/delete something 'before publication' or 'prior to publication' surviving in the prose means an instruction block reached publication |
| 34 | PASS | residue | No 'Will be filled in' placeholders (early-stage tolerated, must resolve before CS) | scanned: html, markdown | the template placeholder 'Will be filled in' (after an opening bracket, or opening a line, list item, quote, table cell or element) must not occur; the phrase inside a sentence is prose |
| 35 | PASS | html-title | HTML title carries no working residue | title: Common Security Advisory Framework Version 2.1 | must not end in tmp, draft, or wip |
| 36 | PASS | html-title | HTML title is a plausible document title | title: Common Security Advisory Framework Version 2.1 | a full spec title (at least 8 characters) |
| 37 | PASS | html-residue | No stale pandoc title-block header in the HTML | title_block_headers: 0; runner_paths: 0; markdown_caption_or_attribute_text: 0 | the <header id="title-block-header"> element must be absent (lint D2) |
| 38 | PASS | html-residue | No CI runner paths in HTML hrefs or srcs | title_block_headers: 0; runner_paths: 0; markdown_caption_or_attribute_text: 0 | the /home/runner/ path prefix must not occur (lint D3) |
| 39 | PASS | html-residue | No visible text block of the HTML ends with a pandoc attribute block printed as text | title_block_headers: 0; runner_paths: 0; markdown_caption_or_attribute_text: 0 | a block whose text ends with '{#id}' or '{#id .class ...}' (a leaked caption 'Table: ...{#id}', or a heading's id) is Markdown the renderer did not read; the id it names is missing from the HTML (CSAF v2.1 csd03: 5 table captions). Caption words alone, '{{#...', and a URI template such as /files{#path} pass |
| 40 | PASS | html-residue | The document title appears in exactly one H1 | title_block_headers: 0; runner_paths: 0; markdown_caption_or_attribute_text: 0 | exactly 1 (more renders the title twice on the PDF cover, lint D1) |
| 41 | PASS | html-anchors | Every internal fragment link resolves to an anchor | internal_links: 391; anchors: 1281; unresolved: 0; non_web_scheme_links: (none) | every referenced fragment must exist as an id or <a name> |
| 42 | PASS | html-anchors | No link's href is a cross-reference written without its '#' | internal_links: 391; anchors: 1281; unresolved: 0; non_web_scheme_links: (none) | an href beginning with a pandoc-crossref prefix (tab:, tbl:, fig:, sec:, eq:, lst:), or one that is itself an id of the document, is a link that goes nowhere (CSAF v2.1 csd03: href="tab:tlp-labels-across-csaf-versions"); any other scheme (did:, isbn:, urn:, ...) or relative path passes |
| 43 | PASS | html-anchors | The HTML carries a linked table of contents | internal_links: 391; anchors: 1281; unresolved: 0; non_web_scheme_links: (none) | at least one expected (a spec HTML without any is missing its TOC links) |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 44 | WARN x10 | md-links | No dual `[url](url)` links in the markdown | Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/aggregator.json \| Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/csaf.json \| Dual link [url](url); write the URL in angle brackets, <https://...>, which renders as a link in both the HTML and the PDF, or give it real anchor text: https://docs.oasis-open.org/csaf/csaf/v2.1/schema/meta.json \| ... and 7 more (full list in the JSON record) | text and target being the same URL calls for an angle-bracket autolink `<https://...>` (a link in both the HTML and the PDF) or real anchor text |
| 45 | PASS | md-links | No bare URL runs into '.\' without a space | links_scanned: 208 | the safe form '. \' (otherwise pandoc pulls the backslash, and any period before it, into the href) |
| 46 | PASS | fence-collapse | No opening code fence carries trailing text in its info string | fences_scanned: 970; trailing_text_fences: 0; rendered_as_code_in_html: 0 | a bare language token or curly-attribute form; trailing text collapses the block under pandoc's markdown reader (lint D6). BLOCKER when the package has no HTML, or the HTML does not carry the block as a <pre> block; a block the HTML does carry is noted once as INFO, with no action needed. The remedy offered is the note as an HTML comment on its own line above the fence, which pandoc, gfm and commonmark all render |
| 47 | PASS | image-policy | No empty img src attributes | img_tags: 1; image_payload_bytes: 12402 | src must be non-empty |
| 48 | PASS | image-policy | No absolute-path image sources | img_tags: 1; image_payload_bytes: 12402 | a leading / resolves outside the package on publication |
| 49 | PASS | image-policy | No path-traversal image sources | img_tags: 1; image_payload_bytes: 12402 | the path must not contain .. segments |
| 50 | PASS | image-policy | No responsive srcset image constructs | img_tags: 1; image_payload_bytes: 12402 | the publication pipeline's self-containment policy refuses srcset |
| 51 | PASS | image-policy | No image lays out wider than the printable width of the PDF page | img_tags: 1; image_payload_bytes: 12402 | 643px (A4 less 20mm side margins at 96px/in) unless the package's CSS caps images; a wider figure runs off the page or shrinks every page |
| 52 | PASS | image-policy | No <picture> elements | img_tags: 1; image_payload_bytes: 12402 | the publication pipeline's self-containment policy refuses <picture> |
| 53 | PASS | image-policy | Every image file is under the per-image size cap | img_tags: 1; image_payload_bytes: 12402 | the pipeline's 2MB per-image refusal cap |
| 54 | PASS | image-policy | No SVG carries script content | img_tags: 1; image_payload_bytes: 12402 | <script> elements are active content, refused on docs.oasis-open.org |
| 55 | PASS | image-policy | No SVG carries inline event handlers | img_tags: 1; image_payload_bytes: 12402 | on*= attributes are active content, refused |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 56 | PASS | image-policy | No SVG references external image or use targets | img_tags: 1; image_payload_bytes: 12402 | external <image>/<use> hrefs break self-containment |
| 57 | PASS | image-policy | Total image payload is under the cumulative cap | img_tags: 1; image_payload_bytes: 12402 | the pipeline's 5MB cumulative inlining cap |
| 58 | PASS | pdf-cover | The document title appears exactly once on the PDF cover page | title: Common Security Advisory Framework Version 2.1; cover_page_occurrences: 1; runner_path_in_pdf: False | exactly 1 (more means stale title-block residue baked into the render, assertion A1) |
| 59 | PASS | pdf-cover | No CI runner path anywhere in the PDF text | title: Common Security Advisory Framework Version 2.1; cover_page_occurrences: 1; runner_path_in_pdf: False | the /home/runner/ path must not occur (assertion A2) |
| 60 | PASS | schema-id | Every .json file in the package parses as JSON | json_files: 4; expected_id_root: https://docs.oasis-open.org/csaf/csaf/v2.1/ | must parse without error |
| 61 | PASS | schema-id | A flattened $id under the version root is a conscious convention | json_files: 4; expected_id_root: https://docs.oasis-open.org/csaf/csaf/v2.1/ | the file's publish path; a version-root flattened $id (CSAF v2.0 style) needs a copy at that location |
| 62 | PASS | schema-id | Each schema's $id agrees with where the file publishes | json_files: 4; expected_id_root: https://docs.oasis-open.org/csaf/csaf/v2.1/ | the canonical latest-version URL derived from the package path |
| 63 | PASS | schema-id | Schema-internal self-references agree with the declared $id | json_files: 4; expected_id_root: https://docs.oasis-open.org/csaf/csaf/v2.1/ | the schema's own declared $id |
| 64 | PASS | schema-id | The schema $id checks are not silently skipped when the cover gives no This-stage base URL | json_files: 4; expected_id_root: https://docs.oasis-open.org/csaf/csaf/v2.1/ | a base URL under this package's own /version/stage/ directory; without one the check reports NOT EVALUATED |
| 65 | PASS | pdf-sync | The PDF This-stage URL cross-check is not silently skipped when the cover gives no This-stage base URL | pdftotext: present; this_stage_base_in_pdf: True; other_versions_excused: v2.0 | a base URL under this package's own /version/stage/ directory; without one the check reports NOT EVALUATED |
| 66 | PASS | pdf-sync | The PDF cross-check toolchain is available | pdftotext: present; this_stage_base_in_pdf: True; other_versions_excused: v2.0 | pdftotext present; absent means the PDF front-matter cross-check is skipped here and runs at intake |
| 67 | PASS | pdf-sync | pdftotext executes against the PDF | pdftotext: present; this_stage_base_in_pdf: True; other_versions_excused: v2.0 | a clean execution |
| 68 | PASS | pdf-sync | The PDF is machine-readable | pdftotext: present; this_stage_base_in_pdf: True; other_versions_excused: v2.0 | exit 0 |
| 69 | PASS | pdf-sync | The PDF front matter carries the canonical this-stage URL | pdftotext: present; this_stage_base_in_pdf: True; other_versions_excused: v2.0 | the this-stage base URL declared by the package front matter |
| 70 | PASS | pdf-sync | The PDF cites no unexpected other version of this spec | pdftotext: present; this_stage_base_in_pdf: True; other_versions_excused: v2.0 | the package's own version (other versions excused inside the Previous stage and Related work blocks, anything else confirmed) |
| 71 | PASS | template | All required template front-matter sections are present | sections_found: Abstract, Chair(s), Citation format, Editor(s), Latest stage/version, Notices, Previous stage/version, Status, Technical Committee / Open Project, This stage/version; conformance_section: True | the template's required set: This/Previous/Latest stage, Technical Committee, Chairs, Editors, Abstract |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 72 | PASS | template | Front-matter sections appear in template order | sections_found: Abstract, Chair(s), Citation format, Editor(s), Latest stage/version, Notices, Previous stage/version, Status, Technical Committee / Open Project, This stage/version; conformance_section: True | the canonical template ordering |
| 73 | PASS | template | A Conformance section exists | sections_found: Abstract, Chair(s), Citation format, Editor(s), Latest stage/version, Notices, Previous stage/version, Status, Technical Committee / Open Project, This stage/version; conformance_section: True | the TC Process requirement: every Standards Track Work Product carries conformance clauses |
| 74 | PASS | template-css | A non-canonical stylesheet keeps the template font family | stylesheet_links: 1; inline_style_blocks: 1 | the template look: Liberation Sans / Arial / Helvetica |
| 75 | PASS | template-css | The HTML carries a stylesheet | stylesheet_links: 1; inline_style_blocks: 1 | at least one styling source must be present |
| 76 | PASS | package-refs | The cited-file check is not silently skipped when the cover gives no This-stage base URL | own_stage_citations_checked: 8 | a base URL under this package's own /version/stage/ directory; without one the check reports NOT EVALUATED |
| 77 | PASS | package-refs | Every file the document cites under its own stage path is included in the package | own_stage_citations_checked: 8 | the cited relative path must exist as a file in the package |
| 78 | PASS | link-mismatch | Visible URL text and its link target agree | html_url_text_anchors: 112; shown_target_pairs: 10 | shown and target must be the same URL (a disagreement is a rename artifact) |
| 79 | PASS | link-mismatch | Anchor text that displays a URL agrees with the anchor's href | html_url_text_anchors: 112; shown_target_pairs: 10 | the displayed URL and the href must name the same resource (scheme, www., and trailing-slash differences and ellipsis display-truncation excepted); readers cite what they see |
| 80 | PASS | ref-rfc | An [RFCnnnn] references entry's URL cites the same RFC number as its label | markdown_rfc_reference_entries: 0; html_rfc_reference_entries: 0 | the RFC number in the entry's own label; a disagreement means the label or the linked document is stale |
| 81 | PASS | ref-rfc | An [RFCnnnn] references entry's body text cites the same RFC number as its label and URL | markdown_rfc_reference_entries: 0; html_rfc_reference_entries: 0 | the RFC number in the entry's label and URL (numbers drift when a reference is upgraded to a successor RFC and the prose is not) |
| 82 | PASS | boilerplate-dup | The template's 'send comments' status paragraph appears exactly once | markdown_comments_paragraphs: 1; html_comments_paragraphs: 1 | exactly one occurrence per the Board-approved template (a duplicate rides in on a stale template merge and truncates the sentence it collides with) |
| 83 | PASS | double-slash | No relative link path contains a double slash | double_slash_paths: 0 | single slashes only (the CDN 404s a double slash even where browsers tolerate it) |
| 84 | WARN | cover-hr | No horizontal rule between the OASIS logo and the title | Horizontal rule between the OASIS logo and the title: the publication CSS treats <hr/> as a page break, which opens the PDF with a blank page. Harmless in other renderers; remove if publishing through the OASIS HTML-to-PDF path. | no --- / *** / ___ rule after the logo (the publication CSS renders it as a PDF page break) |
| 85 | NA | pdf-fonts | pdffonts executes against the PDF | NA: pdffonts unavailable or the package declares no font authority | a clean execution |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 86 | NA | pdf-fonts | The PDF's embedded fonts are declared by the package's own CSS | NA: pdffonts unavailable or the package declares no font authority | the font families declared in the package's HTML/CSS (its own typography authority) |
| 87 | PASS | pdf-legibility | pdftotext -bbox executes against the PDF | median_word_height_pt: 12.5; declared_body_pt: 12; declared_by: markdown-styles-v1.7.3.css; words: 59411 | a clean execution |
| 88 | PASS | pdf-legibility | The PDF's body text prints at no less than 85% of the body size the package declares | median_word_height_pt: 12.5; declared_body_pt: 12; declared_by: markdown-styles-v1.7.3.css; words: 59411 | 85% of the declared body size; skipped for landscape PDFs and PDFs from Word, LibreOffice, TeX, Typst, FOP or Acrobat |
| 89 | PASS | html-code-sync | Each fenced code block of the Markdown source is published in the HTML with the same whitespace | markdown_fenced_blocks: 485; not_compared: 15; html_pre_blocks: 500 | the same block with its tabs intact; a block whose only change is tabs expanded to spaces (the pipeline's pandoc did this to DMLex v1.0 OS, Sep 2026) is this WARN, any other change the BLOCKER |
| 90 | PASS | html-code-sync | Each fenced code block of the Markdown source appears in the HTML with the same characters | markdown_fenced_blocks: 485; not_compared: 15; html_pre_blocks: 500 | the HTML's <pre> blocks: every Markdown block must match one not already matched, character for character apart from whitespace at line ends |
| 91 | WARN | pdf-toc-pages | The PDF's table of contents gives a page number for its entries | The PDF's table of contents gives no page number for 356 of its 356 entries: a reader of the PDF cannot find a section by it. | at least half of the entries numbered; a contents list of fewer than five entries is not graded |
| 92 | PASS | pdf-toc-pages | The page a contents entry gives is the page its heading is printed on | contents_entries: 356; with_page_numbers: 0 | the entry's title on that page, after the constant offset most entries agree on (printed labels may differ from the PDF page index); more than 2, or a fifth of the sample, missing is reported |
| 93 | NA | manifest | manifest.json parses as JSON | NA: no manifest.json in the package (noted as informational) | must parse without error |
| 94 | NA | manifest | Every manifest item exists in the package | NA: no manifest.json in the package (noted as informational) | the package file tree |
| 95 | NA | manifest | Every manifest sha256 matches the file's actual digest | NA: no manifest.json in the package (noted as informational) | the digest recorded in the manifest |
| 96 | PASS | junk-files | No working directories inside the package | files_walked: 8 | forbidden set: __MACOSX, .git, .venv, venv, node_modules |
| 97 | PASS | junk-files | No OS junk or editor backup files in the package | files_walked: 8 | forbidden: .DS_Store, Thumbs.db, desktop.ini, and ~ / .bak / .orig / .swp suffixes |
| 98 | PASS | case | Every filename in the package is lowercase | md_docs_urls_scanned: 27; mixed_case_files: (none) | its lowercase form (the publication origin is case-sensitive; the canonical logo filename is exempt) |
| 99 | PASS | case | Every self-referential docs.oasis-open.org URL path is lowercase (markdown source) | md_docs_urls_scanned: 27; mixed_case_files: (none) | its lowercase form (case-sensitive origin; /templates/ paths exempt) |
| 100 | NA | case | Every self-referential docs.oasis-open.org URL path is lowercase (HTML render) | NA: evaluated on the markdown-source row for this package | its lowercase form (case-sensitive origin; /templates/ paths exempt) |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 101 | NA | odt-integrity | The ODT source opens as a ZIP archive | NA: ODT-source condition; this package carries no ODT source | a readable OpenDocument container |
| 102 | NA | odt-integrity | The ODT archive carries a mimetype member | NA: ODT-source condition; this package carries no ODT source | the OpenDocument package requirement of a mimetype entry |
| 103 | NA | odt-integrity | The declared mimetype is an OpenDocument type | NA: ODT-source condition; this package carries no ODT source | the application/vnd.oasis.opendocument.* family |
| 104 | NA | odt-integrity | The ODT archive carries the document body (content.xml) | NA: ODT-source condition; this package carries no ODT source | the OpenDocument package requirement of a content.xml body |
| 105 | NA | odt-integrity | The ODT document body parses as XML | NA: ODT-source condition; this package carries no ODT source | well-formed XML |
| 106 | NA | odt-integrity | The ODT carries no embedded macros or scripts | NA: ODT-source condition; this package carries no ODT source | the host's active-content policy (none permitted, same as SVG scripts) |
| 107 | PASS | symlinks | No symlink points at itself or an ancestor directory | symlinks_found: 0 | must not equal or contain its own directory (deploys materialize symlinks into unbounded recursion) |
| 108 | PASS | dead-lists | No reference to a lists.oasis-open.org mailing address (markdown source) | md_lists_addresses: (none) | the dead-infrastructure rule: that mail host silently fails; comments route via Higher Logic |
| 109 | NA | dead-lists | No reference to a lists.oasis-open.org mailing address (HTML render) | NA: evaluated on the markdown-source row for this package | the dead-infrastructure rule: that mail host silently fails; comments route via Higher Logic |
| 110 | PASS | dead-lists | Links into the retired list archives are flagged for verification | md_lists_addresses: (none) | each must be individually verified while the archive infrastructure is retired |
| 111 | PASS | rfc-keywords | Normative key words are backed by an RFC 2119 citation | normative_keywords_present: True; rfc2119_cited: True; rfc8174_cited: True | an RFC 2119 citation must be present when key words are used |
| 112 | PASS | rfc-keywords | RFC 2119 citation is paired with RFC 8174 | normative_keywords_present: True; rfc2119_cited: True; rfc8174_cited: True | the current template cites both 2119 and 8174 (uppercase-only clarification) |
| 113 | PASS | logo | The cover logo is the canonical OASIS logo | logo_sources: https://docs.oasis-open.org/templates/OASISLogo-v3.0.png | https://docs.oasis-open.org/templates/OASISLogo-v3.0.png |
| 114 | PASS | previous-stage | A stage past 01 cites its previous stage | pulled: the URLs in the markdown's Previous-stage block; no violating instance found | at least one docs.oasis-open.org URL required when the revision number exceeds 01 |
| 115 | NA | previous-stage | A stage past 01 cites its previous stage on the HTML cover | NA: DOCX-render condition; this package carries no Word source | at least one docs.oasis-open.org URL required when the revision number exceeds 01 |
| 116 | PASS | date-sync | The markdown front-matter date appears in the HTML | document_date: 28 May 2025; copyright_year: 2022 | the rendered HTML text (absence means the HTML came from a different revision) |
| 117 | WARN | date-sync | The copyright year matches the document date year | Copyright year 2022 does not match the document date year 2025. | the year of the front-matter document date |
| 118 | NA | generator | A DOCX-native render was produced by Microsoft Word | NA: DOCX-render condition; this package carries no Word source | must contain 'Microsoft Word' (a LibreOffice render differs in kind from the TC's precedent) |
| 119 | PASS | vml-fallback | Every VML image has an <![if !vml]> img fallback | vml_images: 0; img_fallbacks: 0 | fallback count must cover VML count (the invisible-cover-logo class) |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 120 | PASS | asset-refs | Every relative src/href the HTML references is included in the package | relative_refs_checked: 1; missing: 0 | the package file tree; a missing target 404s on publication |
| 121 | PASS | conformance-structure | At least one Conformance heading is a genuine top-level numbered section (not nested deeper than the document's modal top-level depth, and not under an Annex/Appendix ancestor) | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | The TC Handbook page 'Conformance Clauses': 'a separate, top-level numbered section of the work product (not a subsection buried elsewhere)'; BLOCKER at cs/os (WARN at wd/csd, or when the modal-depth signal itself is low-confidence) |
| 122 | PASS | conformance-structure | Each conformance profile scope yields at least one extracted clause identifier | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | The TC Handbook page 'Work Product Requirements': 'a set of numbered conformance clauses to which any implementation must adhere'; BLOCKER at cs/os, WARN at wd/csd; an empty Conformance section is reported at either tier |
| 123 | PASS | conformance-structure | No clause identifier repeats within the same profile scope | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | The TC Handbook page 'Conformance Clauses': 'individually numbered conformance clauses ... so that implementers and Statements of Use can cite specific clauses by number'; BLOCKER at cs/os, WARN at wd/csd |
| 124 | PASS | conformance-structure | Every (profile, clause number) pair in the previous stage is still present in this stage (append-only extension is fine; removal/renumbering, including a whole profile silently disappearing, is flagged) | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | The TC Handbook page 'Work Product Requirements' 'Key principles': 'Clause numbering must be unique and stable across revisions'. Guidelines-sourced (recommended, not mandatory) so WARN-tier informational, never BLOCKER, and never fired for the CS->OS transition (that gets the zero-tolerance override instead); profile names and clause text are compared with curly quotes, apostrophes and Unicode dashes folded to ASCII, so straightening a quote changes nothing |
| 125 | PASS | conformance-structure | A (profile, clause number) pair missing from this stage does not reappear under a DIFFERENT number in the same profile with the same content (a disguised renumber-via-delete-and-re-add) | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | the same Guidelines stability principle as 'removed/renumbered'; WARN-tier informational; profile names and clause text are compared with curly quotes, apostrophes and Unicode dashes folded to ASCII, so straightening a quote changes nothing |
| 126 | PASS | conformance-structure | At the CS->OS transition, the current (profile, clause id) key set is a byte-for-byte match to the approved-CS key set, scoped per profile, so a whole profile silently dropped while a surviving profile happens to reuse its bare clause numbers is still caught | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | The TC Handbook page 'Conformance Clauses' 'OASIS Standard os': 'Conformance clauses are preserved unchanged from the approved Committee Specification' (TC Process 2.9): zero tolerance, always BLOCKER |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 127 | PASS | conformance-structure | A clause whose (profile, number) key is unchanged at CS->OS is flagged for manual confirmation when its content hash changed | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | The TC Handbook page 'Work Product Requirements' 'Allowed changes during publication': coordinated non-material changes are permitted (TC Process 2.2.4); not itself a zero-tolerance failure, so WARN/manual-review, never an automatic BLOCKER; profile names and clause text are compared with curly quotes, apostrophes and Unicode dashes folded to ASCII, so straightening a quote changes nothing |
| 128 | PASS | conformance-structure | At the CS->OS transition, the approved-CS baseline artifact must be resolvable to verify clause-set preservation at all | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | TC Process 2.9's preservation obligation cannot be verified for a Standards Track OS approval if the CS baseline is unreachable, so it is elevated to BLOCKER rather than reported as a silent WARN |
| 129 | PASS | conformance-structure | A general (non-CS->OS) stability diff that could not resolve its previous-stage artifact says so in the report | stage_prefix: csd; headings_scanned: 373; conformance_candidates: 27; modal_top_level: 1; modal_confidence: high; profiles_found: 9; clauses_extracted: 25; stability: no-op (first publication) | the general stability check is WARN-tier informational; an unresolvable prior artifact (first publication is a separate, silent no-op) still surfaces the gap as a WARN |
| 130 | PASS | references-split | A bare 'References' heading carrying 2+ direct reference entries is split into separately labeled Normative/Informative child headings (or is too small a sample, 0 or 1 entries, to judge) | stage_prefix: csd; stage_track: standards; references_headings_found: 0 | The TC Handbook page 'Work Product Quality Checklist' editorial quality checklist bullet: 'normative references listed separately from informative references' (WARN: staff-maintained best-practice checklist, not a TC Process must/shall clause) |
| 131 | PASS | references-split | No reference-entry ID appears under both a Normative References heading and an Informative References heading anywhere in the document | stage_prefix: csd; stage_track: standards; references_headings_found: 0 | the two ID sets must not intersect; a shared ID is a labeling inconsistency or editorial duplication (the TC Handbook page 'Work Product Quality Checklist' same checklist bullet) |
| 132 | PASS | content-labels | Every Examples/Illustrative-Examples/Sample-<noun> heading carries a structural content-type label (heading suffix, first-sentence lead/predicate, labeled ancestor heading, or document-wide blanket statement) | track: markdown; headings_scanned: 373; example_candidates: 0; example_unlabeled: 0; appendix_candidates: 6; appendix_unlabeled: 2; blanket_statement_classes: example | The TC Handbook page 'Conformance Clauses' 'Normative versus non-normative content': Examples content is classified non-normative and 'should be clearly labelled' |
| 133 | PASS | stage-token | Previous-stage URL stage token is not a retired abbreviation | doc_stage_token: csd; this_stage_block: present (not independently evaluated); previous_stage_status: N/A (first instance); latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf; result: PASS -- Previous-stage tokens match/legacy-clean or N/A, Latest-stage filenames carry no stage token | retired token set (csprd, cnprd, cos, csdpr, cndpr) per Naming Directives v1.7; WARN with a legacy-URI verification caveat since a pre-2024 Previous-stage URI may permanently retain a retired token (the OASIS Naming Directives v1.7 6.3 Resource Permanence) |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 134 | PASS | stage-token | Previous-stage URL stage token matches the document's own current csd/cnd stage abbreviation or the track's approved-stage counterpart | doc_stage_token: csd; this_stage_block: present (not independently evaluated); previous_stage_status: N/A (first instance); latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf; result: PASS -- Previous-stage tokens match/legacy-clean or N/A, Latest-stage filenames carry no stage token | the document's own current stage token, or the track's approved-stage set (csd: cs/os/errata; cnd: cn) when the block links a previous VERSION at its own approved stage (the TC Handbook page 'Public Review': the cover page URIs 'should all reflect the csd stage abbreviation') |
| 135 | PASS | stage-token | Latest-stage URL's filename embeds no stage-abbreviation/revision token at all | doc_stage_token: csd; this_stage_block: present (not independently evaluated); previous_stage_status: N/A (first instance); latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf; result: PASS -- Previous-stage tokens match/legacy-clean or N/A, Latest-stage filenames carry no stage token | The OASIS Naming Directives v1.7 6.2: the Latest-stage locator URI 'does not contain the path component [stage-abbrev] [revisionNumber] or stage identifier in the filename', an absolute prohibition independent of whether the token matches the current stage |
| 136 | PASS | title-version | The rendered cover-page title incorporates the package's own Version identifier | stage: csd01; track: standards; pkg_version: 2.1; title_source: HTML <title>/<h1>; title_text: Common Security Advisory Framework Version 2.1; version_tokens_found: 1 | The OASIS Naming Directives v1.7 5.1: 'A Version identifier must also be incorporated into a Work Product name/title' |
| 137 | PASS | title-version | The Version cited in the title agrees with the package's own Version identifier | stage: csd01; track: standards; pkg_version: 2.1; title_source: HTML <title>/<h1>; title_text: Common Security Advisory Framework Version 2.1; version_tokens_found: 1 | the package's own Version identifier (the version directory segment, with a leading 'v' stripped per the OASIS Naming Directives v1.7 Section 4's [version-id] grammar) |
| 138 | PASS | title-version | The title's Version token is composed as '<name/identifier> Version <number>' with no forbidden punctuation before it and only a sanctioned continuation after it (a '. Part N: <part title>' suffix; on a package whose own stage directory or immediate parent is named erratanN, also an 'Errata NN' or 'Plus Errata NN' suffix whose number matches the package's own errata number, per the OASIS Naming Directives v1.7 Section 4's separate Errata construction) | stage: csd01; track: standards; pkg_version: 2.1; title_source: HTML <title>/<h1>; title_text: Common Security Advisory Framework Version 2.1; version_tokens_found: 1 | The OASIS Naming Directives v1.7 Section 7: MUST for Standards Track (csd/cs/os/errata) -> BLOCKER; SHOULD for Non-Standards Track (cnd/cn) -> WARN with the 'reasonable grounds for alternate constructions' exception; WARN also for any stage token outside the six Section-5.2-enumerated tokens (track unresolved, no corpus citation, never escalated to BLOCKER on an uncited classification) |
| 139 | PASS | title-oasis-prefix | The Work Product title (the <h1> identified by _h1_title_match_info's 'exact' or 'singular-related-fallback' classification) does not begin with the word 'OASIS' | title_source: Common Security Advisory Framework Version 2.1; track: standards; track_confidence: confirmed; title_match: exact | The OASIS Naming Directives v1.7 s7: 'Preferably, a title should not begin with the name "OASIS" except on the recommendation of Project Administration for special cases.' Section 7's lead sentence track-scopes this to BLOCKER (Standards Track, must-observe) / WARN (Non-Standards Track, should-follow with an additional alternate-construction escape valve). |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 140 | PASS | authors | A Technical Report/Technical Report Draft names its Authors on the cover page (heading or title-block byline) | work_product_type: committee specification draft | TC Handbook, Technical Reports: 'A Technical Report has one or more named Authors ... recorded on the cover page' |
| 141 | PASS | authors | The Authors heading/byline is not empty or placeholder-only (tbd/n/a/none), including list/task/blockquote-dressed variants | work_product_type: committee specification draft | at least one non-placeholder named entry must remain |
| 142 | PASS | authors | A Technical Report Draft's Authors section is not left on the registry's own tolerated 'Will be filled in' placeholder indefinitely (WARN while still a TRD) | work_product_type: committee specification draft | the existing residue-check precedent (check='residue') tolerating 'Will be filled in' pre-CS, scoped here to the Authors record of an in-progress Technical Report Draft |
| 143 | PASS | authors | An approved (non-draft) Technical Report's Authors section is resolved, not still the 'Will be filled in' placeholder | work_product_type: committee specification draft | the TRD-stage 'will be filled in' tolerance does not survive Full Majority Vote approval to the final Technical Report |
| 144 | PASS | name-chars | No underscore in an identifying (document-URI-bearing) package name | names_scanned: 12; identifying_stage: csd01; identifying_version: v2.1; multi_part_dirs: (none); junk_dirs_skipped: (none) | STRICT allowlist [A-Za-z0-9.-]. Naming Directives v1.7 s3: an UNDERSCORE 'must never be used in a filename or directory name that is used in a document URI' |
| 145 | PASS | name-chars | No character outside the sixty-four permitted characters in an identifying package name | names_scanned: 12; identifying_stage: csd01; identifying_version: v2.1; multi_part_dirs: (none); junk_dirs_skipped: (none) | STRICT allowlist [A-Za-z0-9.-]. Naming Directives v1.7 s3: 'TCs must use only the sixty-four characters from among alphanumerics [A-Za-z0-9] and the two punctuation characters ... PERIOD ... and ... HYPHEN' |
| 146 | PASS | name-chars | No character outside the sixty-four permitted characters plus UNDERSCORE in a supporting (non-identifying) package name | names_scanned: 12; identifying_stage: csd01; identifying_version: v2.1; multi_part_dirs: (none); junk_dirs_skipped: (none) | BASE allowlist [A-Za-z0-9._-]. Naming Directives v1.7 s3 base 'must use only' clause, with UNDERSCORE included per the conditional tolerance |
| 147 | PASS | name-chars | An identifying (document-URI-bearing) package name is non-empty | names_scanned: 12; identifying_stage: csd01; identifying_version: v2.1; multi_part_dirs: (none); junk_dirs_skipped: (none) | STRICT test ^[A-Za-z0-9.-]+$: the '+' quantifier requires at least one character, so an empty identifying name trivially fails the sixty-four-permitted-character allowlist; mirrors how check_stage_name's and check_version_naming's own fullmatch patterns already reject an empty stage/version token without any special-casing |
| 148 | PASS | extension-count | A stage-directory-root delivery item (the established document-identifier stem plus one packaged format) carries at least one file extension | tier_a_files_checked: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; tier_a_severity: BLOCKER; tier_b_files_checked: 5; tier_b_flagged: (none) | Naming Directives v1.7 s4: 'A single file(name) extension must be used in each filename except for a recognized set of extensionless filenames in common use.' BLOCKER at published stages, WARN at wd (s5.2 Note: working drafts 'may use any file naming pattern preferred by the TC'); wd-stage match is case-folded. |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 149 | PASS | extension-count | A stage-directory-root delivery item carries exactly one file extension after the stem (or one blessed compound: tar.gz/tar.bz2/tar.xz, and only when that compound is the WHOLE remaining suffix) | tier_a_files_checked: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; tier_a_severity: BLOCKER; tier_b_files_checked: 5; tier_b_flagged: (none) | Naming Directives v1.7 s4's single-extension rule, structurally against the same stem boundary the 'filenames' check already validates. BLOCKER at published stages, WARN at wd. |
| 150 | PASS | extension-count | A non-delivery-item (Tier B) file with zero dots is one of the three literally recognized extensionless names | tier_a_files_checked: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; tier_a_severity: BLOCKER; tier_b_files_checked: 5; tier_b_flagged: (none) | Naming Directives v1.7 s9: 'Exceptions to the rule that every filename must include a file extension include: CATALOG or catalog, README, ChangeLog.' Non-blocking WARN per s4's Applicability carve-out for non-identification-pattern files. |
| 151 | PASS | extension-count | A non-delivery-item (Tier B) dotted filename's penultimate segment does not look like a known extension token (or the trailing pair is a blessed compound) | tier_a_files_checked: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; tier_a_severity: BLOCKER; tier_b_files_checked: 5; tier_b_flagged: (none) | A disclosed, non-exhaustive known-extension-token vocabulary (not an IANA-derived classification); flagged only as a non-blocking heuristic pattern-match advisory per s4's Applicability carve-out for non-identification-pattern files (schemas, images, WSDLs, XML/JSON artifacts). |
| 152 | PASS | extension-conformance | Every root principal/stage-identifying filename and every Multi-Part named-part filename uses an extension that matches a common OASIS publication rendering format | principal_files: csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf; named_part_files: (none) | a curated allowlist of common OASIS document/publication rendering-format extensions (txt, md, html, htm, pdf, doc, docx, odt, ods, odp, xls, xlsx, ppt, pptx, rtf, xml, json, epub), per Naming Directives Section 4 'File extensions should conform to industry best practice, matching well-known IANA MIME Media Types'; filenames on the Section 9 extensionless allowlist (CATALOG, catalog, README, ChangeLog) are exempt |
| 153 | PASS | artifact-naming | A non-document-identifier artifact's own filename does not embed a stage+revision token | supporting_files_scanned: 5; stage_revision_matches: 0 | Naming Directives s4: 'it is considered inadvisable to incorporate instance-specific [stage][revision] data for any release in filenames other than in the document identifier files ... thus mySchema.xsd but NOT mySchema-csd02.xsd'; TCs are advised to use named subdirectories and retain stable/identical filenames per s5.2/5.3's stage-abbreviation and two-digit-revision definitions |
| 154 | PASS | multi-part-naming | Every Multi-Part Work Product part filename embeds the identical WP-abbrev token | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | the set of distinct WP-abbrev tokens across all matched part filenames must collapse to exactly one value, per TC Process 2.2.3's single Work Product name and the Handbook's Multi-part work products restatement |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 155 | PASS | multi-part-naming | Every Multi-Part Work Product part filename embeds the identical version-id token | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | the set of distinct version-id tokens across all matched part filenames must collapse to exactly one value, per TC Process 2.2.3's single Work Product version number and the Handbook's Multi-part work products restatement |
| 156 | PASS | multi-part-naming | No bare CORE.ext delivery filename coexists with genuine part files | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | The OASIS Naming Directives v1.7 s4: the single-part bare-CORE filename rule does not apply once the package is multi-part |
| 157 | PASS | multi-part-naming | Every non-canonical delivery filename sharing the package core carries a well-formed -part<N>-<name> segment | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | Naming Directives v1.7 s4 multi-part filename grammar: literal lowercase 'part' + Arabic numeral + hyphen + partName, positioned before the extension |
| 158 | PASS | multi-part-naming | A part file discovered inside an Option-1 URI part-subdirectory agrees with that subdirectory's own [partNumber]-[partName] segment | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | The OASIS Naming Directives v1.7 s6.1 (Option 1): the subdirectory segment and the filename's part identifier must name the same part |
| 159 | PASS | multi-part-naming | Each part number maps to exactly one partName across every format variant and discovery location | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | Naming Directives v1.7 s4: partNumber identifies one distinct separately-titled prose part, not two |
| 160 | PASS | multi-part-naming | Part numbering for a multi-part package begins at 1 | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | The OASIS Naming Directives v1.7 s4: partNumber begins with the number '1' (for Part 1) |
| 161 | PASS | multi-part-naming | Part numbering for a multi-part package is contiguous with no gaps | part_subdirs_scanned: (none); part_subdirs_unreadable: (none); matched_part_grammar_files: (none); part_grammar_files: 0; distinct_parts: 0; naming20_entries_scanned: 3; naming20_cores_resolved: csaf-v2.1-csd01; naming20_core: csaf-v2.1-csd01; naming20_distinct_tails: | The OASIS Naming Directives v1.7 s4: partNumber increases monotonically (2, 3, 4, ...) for other parts, i.e. the exact sequence [1, 2, ..., N] |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 162 | BLOCKER | public-review-metadata | A live, published csd/cnd stage directory confirmed (by tiered evidence) and successfully scanned to have undergone TC public review carries the required public-review-metadata companion file | csd01 underwent a TC public review (Tier 1 (a comment-resolution-log for this revision is already live)) but the live stage directory https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/ does not carry the required companion file csaf-v2.1-csd01-public-review-metadata.html. Naming Directives v1.7 s5.2: 'Project Administration will publish an additional "public review metadata" file in the directory with the CSD or CND'; TC Handbook Naming: 'Work products undergoing public review must include a companion metadata file.' | the exact, case-sensitive filename [WP-abbrev]-[version-id]-[stage-abbrev][revisionNumber]-public-review-metadata.html (the OASIS Naming Directives v1.7 5.2; the TC Handbook page 'Naming & URIs' 'Public-review metadata filename (new in v1.7)') |
| 163 | PASS | public-review-metadata | A present public-review-metadata companion file is non-empty | stage_directory_url: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/; http_status: 200; live_filenames: csaf-v2.1-csd01-comment-resolution-log.md, csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf, csaf-v2.1-csd01.zip | The OASIS Naming Directives v1.7 5.2: the file 'provides a publication history of the Work Product' (content validation itself is out of scope for this check; only non-zero size is tested here) |
| 164 | PASS | public-review-metadata | A public-review-metadata companion file listed in the live directory is actually reachable so its content can be evaluated | stage_directory_url: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/; http_status: 200; live_filenames: csaf-v2.1-csd01-comment-resolution-log.md, csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf, csaf-v2.1-csd01.zip | a listing entry alone is not proof of a readable file; an unreachable listed file stays an open advisory rather than a silent, unreviewed pass |
| 165 | PASS | public-review-metadata | The public-review-metadata check on a csd/cnd is not silently skipped when the cover gives no This-stage base URL | stage_directory_url: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/; http_status: 200; live_filenames: csaf-v2.1-csd01-comment-resolution-log.md, csaf-v2.1-csd01.html, csaf-v2.1-csd01.md, csaf-v2.1-csd01.pdf, csaf-v2.1-csd01.zip | a base URL under this package's own /version/stage/ directory; without one the check reports NOT EVALUATED |
| 166 | PASS | comment-resolution-log | A file resembling a comment-resolution-log, if present in a CSD/CND stage directory that itself carries a public-review-metadata file, carries the exact basename Naming Directives prescribes | public_review_metadata_expected: csaf-v2.1-csd01-public-review-metadata.html; public_review_metadata_present: False; siblings_scanned: 3 | the expected basename [stem]-comment-resolution-log against the OASIS Naming Directives v1.7 s5.2's filename pattern for a produced comment resolution log |
| 167 | PASS | comment-resolution-log | Where in-package evidence (a later-stage sibling directory) shows a CSD/CND public review has demonstrably concluded, a comment-resolution-log basename match was sought and not found | public_review_metadata_expected: csaf-v2.1-csd01-public-review-metadata.html; public_review_metadata_present: False; siblings_scanned: 3 | The OASIS Technical Committee (TC) Process s2.6/s2.7 (comment disposition is required to be posted to the TC's e-mail lists; the downstream approval ballot may only commence once every comment is resolved) against the TC Handbook page 'Public Review"s 'best practice, not a normative filing mandate' framing for HOW that record is kept |
| 168 | PASS | normdef-refs | Every candidate normative-definition file (schema/grammar/code plain-text file, excluding example/sample/test-case/non-normative and pipeline/asset directories) is referenced from the Work Product | candidates: schema/aggregator.json, schema/csaf.json, schema/meta.json, schema/provider.json; orphans: 0; ambiguous_basename_only: 0 | TC Process 2.2.5: 'Each text file must be referenced from the Work Product; and'. Standards Track (csd, cs, os, errata) only |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 169 | PASS | normdef-refs | A basename-only match among candidate files sharing that basename in different directories is flagged for confirmation rather than silently satisfying the requirement for every tied file | candidates: schema/aggregator.json, schema/csaf.json, schema/meta.json, schema/provider.json; orphans: 0; ambiguous_basename_only: 0 | TC Process 2.2.5's reference requirement; an ambiguous basename-only match does not unambiguously resolve which file was referenced |
| 170 | PASS | uri-alias | No live META-refresh element in any delivered HTML file | prong_a_html_files_scanned: 1; prong_b_files_hashed: 8; prong_b_duplicate_buckets: 0; prong_b_unreadable_entries_skipped: 0; prong_c_md_block_urls_scanned: 6; prong_c_md_anchor_links_scanned: 553; prong_c_md_bare_urls_scanned: 95 | Naming Directives v1.7 s6.5(a): unauthorized URI aliasing via META-refresh elements is barred |
| 171 | PASS | uri-alias | No stage-root delivery file or manifest-cited file (by exact package-relative path) shares byte-identical content with another package-relative path | prong_a_html_files_scanned: 1; prong_b_files_hashed: 8; prong_b_duplicate_buckets: 0; prong_b_unreadable_entries_skipped: 0; prong_c_md_block_urls_scanned: 6; prong_c_md_anchor_links_scanned: 553; prong_c_md_bare_urls_scanned: 95 | Naming Directives v1.7 s6.5(b): preparing files with identical content under two different filenames within a published instance is barred |
| 172 | PASS | uri-alias | An ancillary (non-delivery, non-manifest-cited) duplicate is flagged for review, not treated as a s6.5(b) aliasing risk | prong_a_html_files_scanned: 1; prong_b_files_hashed: 8; prong_b_duplicate_buckets: 0; prong_b_unreadable_entries_skipped: 0; prong_c_md_block_urls_scanned: 6; prong_c_md_anchor_links_scanned: 553; prong_c_md_bare_urls_scanned: 95 | the package's own delivery-item paths and manifest.json authoritative/delivery-role paths |
| 173 | PASS | uri-alias | The markdown Previous-stage block cites no redirect/URL-shortening domain | prong_a_html_files_scanned: 1; prong_b_files_hashed: 8; prong_b_duplicate_buckets: 0; prong_b_unreadable_entries_skipped: 0; prong_c_md_block_urls_scanned: 6; prong_c_md_anchor_links_scanned: 553; prong_c_md_bare_urls_scanned: 95 | the seed redirect-service domain list (tinyurl.com, bit.ly, goo.gl, ow.ly, t.co, is.gd, buff.ly, rebrand.ly, tiny.cc, cutt.ly, shorturl.at, rb.gy, purl.oclc.org) |
| 174 | NA | uri-alias | The DOCX-native rendered cover's This/Previous/Latest-version fields cite no redirect/URL-shortening domain | NA: DOCX-render condition; this package carries no Word source | the seed redirect-service domain list |
| 175 | PASS | uri-alias | Plain-prose anchor text that names oasis-open.org does not link to a redirect/URL-shortening domain (markdown source) | prong_a_html_files_scanned: 1; prong_b_files_hashed: 8; prong_b_duplicate_buckets: 0; prong_b_unreadable_entries_skipped: 0; prong_c_md_block_urls_scanned: 6; prong_c_md_anchor_links_scanned: 553; prong_c_md_bare_urls_scanned: 95 | the seed redirect-service domain list, checked against the anchor text literally containing 'oasis-open.org' |
| 176 | NA | uri-alias | Plain-prose anchor text that names oasis-open.org does not link to a redirect/URL-shortening domain (HTML render) | NA: evaluated on the markdown-source row for this package | the seed redirect-service domain list, checked against the anchor text literally containing 'oasis-open.org' |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 177 | PASS | uri-alias | A bare URL's enclosing sentence that names oasis-open.org does not point at a redirect/URL-shortening domain (markdown source) | prong_a_html_files_scanned: 1; prong_b_files_hashed: 8; prong_b_duplicate_buckets: 0; prong_b_unreadable_entries_skipped: 0; prong_c_md_block_urls_scanned: 6; prong_c_md_anchor_links_scanned: 553; prong_c_md_bare_urls_scanned: 95 | the seed redirect-service domain list, checked against the sentence window literally containing 'oasis-open.org' |
| 178 | NA | uri-alias | A bare URL's enclosing sentence that names oasis-open.org does not point at a redirect/URL-shortening domain (HTML render) | NA: evaluated on the markdown-source row for this package | the seed redirect-service domain list, checked against the sentence window literally containing 'oasis-open.org' |
| 179 | PASS | xml-namespace | The XML namespace checks are not silently skipped when the cover gives no This-stage base URL | schema_files_scanned: 0; schema_files_excluded: 0; tc_shortname: csaf | a base URL under this package's own /version/stage/ directory; without one the check reports NOT EVALUATED |
| 180 | PASS | xml-namespace | An http(s) namespace's tail matches the docs.oasis-open.org/[tc-shortname]/ns/xxxx pattern | schema_files_scanned: 0; schema_files_excluded: 0; tc_shortname: csaf | Naming Directives s8 pattern http(s)://docs.oasis-open.org/[tc-shortname]/ns/xxxx, xxxx restricted to the s3 sixty-four-character set plus internal '/', terminating in '/', '#', or alphanumeric; BLOCKER when the tc-shortname has no pattern-grandfather allowlist entry |
| 181 | PASS | xml-namespace | A pattern-mismatched namespace's tc-shortname is a confirmed-approved pre-2012 pattern grandfather | schema_files_scanned: 0; schema_files_excluded: 0; tc_shortname: csaf | Naming Directives v1.2 s9: pre-2012 practice 'may be grandfathered, if approved by Project Administration': WARN when listed but approval is not machine-confirmable at check time |
| 182 | PASS | xml-namespace | The same namespace tail is declared under one scheme only, package-wide | schema_files_scanned: 0; schema_files_excluded: 0; tc_shortname: csaf | Naming Directives s8: 'While either "http" or "https" may be used ... they are not interchangeable. One or the other must be used consistently.' |
| 183 | PASS | xml-namespace | A urn:-scheme declared namespace's TC is on the URN-grandfather allowlist | schema_files_scanned: 0; schema_files_excluded: 0; tc_shortname: csaf | Naming Directives s8: URN-based namespaces 'must not be declared otherwise', permitted only for TCs that already used the feature (or Maintenance Activity TCs), approved by Project Administration |
| 184 | PASS | xml-namespace | A RELAX NG grammar declares only one namespace, on its root grammar/element node | schema_files_scanned: 0; schema_files_excluded: 0; tc_shortname: csaf | this check only validates the root-level self-declared namespace; a differing non-root ns is flagged for manual review rather than silently dropped |

| # | Result | Check | Condition verified | Value pulled (observed) | Compared against |
|---|---|---|---|---|---|
| 185 | PASS | `ns-segment` | This-stage and Latest-stage cover URIs do not reuse the reserved /ns/ path segment | cover_uris_scanned: 6; this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; previous_stage_urls: (none); latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | The TC Handbook page 'Naming & URIs': '/ns/ ... is for namespace identifiers, not for retrievable documents. Do not use /ns/ in the URI of a document you intend to publish as a retrievable resource' |
| 186 | PASS | `ns-segment` | Previous-stage cover URI does not reuse the reserved /ns/ path segment (non-blocking, manual-review if it does: an immutable inherited citation) | cover_uris_scanned: 6; this_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csd01/csaf-v2.1-csd01.pdf; previous_stage_urls: (none); latest_stage_urls: https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.html, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.md, https://docs.oasis-open.org/csaf/csaf/v2.1/csaf-v2.1.pdf | The TC Handbook page 'Naming & URIs''s /ns/ reservation rule, applied to an already-published prior-stage citation the current package cannot alter |