

jsDropList

description

jsDropList is a replacement for browser built-in select tags and is stylable with CSS. The reason for this is to have the exact same look on every platform, to be able to size the dropdown list with the text and to have a better handling for the values.

instanciation

The element is instatiated with:

new jsDropList(parent, id, options)

The parent parameter is a string with the id of the parent element or a jQuery object of said parent element. The id parameter is the HTML id, the element will be given. The options are explained on the next page.

instanciation example

```
var DL01Options = {
  onChange:      changeCallback,
  onUndo:        undoCallback,
  onRedo:        redoCallback,
  onRedoClear:   redoClearCallback,
  values:        [{
                    value:      'A',
                    label:      'A'
                  }, {
                    value:      'B',
                    label:      'B'
                  }
                ],
  order:         'label',
  cssCollapsed:  {
                    'font-size': '16px',
                    'margin-left': '20px'
                  },
  cssExpanded:   {
                    'font-size': '14px',
                    'background-color': '#DDD',
                    border: '1px solid black'
                  },
  initialValue:  'A',
  dataId:        'optionsAB',
  readOnly:      false
}
var dropList01 = new jsDropList('dropList01', DL01Options);
```

options description

onChange:	callback function when value changes. It will send 4 parameters: param 1 => id of the sender param 2 => current value of the dropList param 3 => dirty flag indicating if changes have been made since original value param 4 => dataId
onUndo:	callback when undo has been triggered param 1 => id of the group param 2 => current length of the undo list
onRedo:	callback when redo has been triggered param 1 => id of the group param 2 => current length of the redo list
onRedoClear:	callback when all redoLists should be cleared, because new changes occurred param 1 => id of the group
choices:	an array of objects describing the choices to be created every object must have the following data: value: the value of this choice (unique inside the list) label: html string of the label (may include image tag)
order:	the order for the choices: either 'label' or 'value' which defines the key by which will be sorted. If not indicated, no ordering will take place
cssCollapsed	an object of key/value pairs that is applied as CSS rules to the element in its collapsed state
cssExpanded	an object of key/value pairs that is applied as CSS rules to the element in its expanded state
listTitle:	title of the list when there is no selection, default is "Bitte wähle:"
noChoiceTitle:	title of the list when no select items are available, default is "Keine Auswahl vorhanden!"
initialValue:	the value the list should have after creation (preselection)
dataId:	a string identifying what the data represents (e.g. name of database field) this will be sent back in the onChange event and helps identify the data being sent default is empty string
readOnly:	boolean that defines if the elements can be modified

methods

addChoices(choices)

when additional choices need to be added at runtime, this method will merge the new choices with those already present in the list. The parameter is an array of objects just like the **choices** option defined at creation time. After merging, the choices must be ordered if an order was defined at creation

removeChoices(values)

removes the indicated choices from list (*values* is an array of values to remove)

getValue()

manual trigger of the **onChange** handler

reset(v)

sets a new value for the list. The parameter is the same as when set at creation with the **initialValue** option. In addition the undo and redo lists will be reset

lock()

sets list to read only mode

unlock()

removes read only mode

undo()

triggers the undo handler: the last change (if any) is rolled back.

redo()

triggers the redo handler: the last undone change will be redone.

clearUndoList()

clears all undo and redo steps registered.

clearRedoList()

clears all redo steps registered, but leaves undo steps untouched.

setDataId(dataId)

sets a new dataId for this group

getDataId()

fetches the dataId for this group