

jsMultipleChoice

description

jsMultipleChoice is a replacement for browser built-in checkboxes and radio buttons and uses its own graphics. The reason for this is to have the exact same look on every platform, to be able to size the checkboxes and radio buttons with the text and to have a better handling for the values.

instanciation

The element is instatiated with:

new jsMultipleChoice(id, options)

The id parameter is an id for the complete group. The options are explained on the next page.

instanciation example

```
var cbGroup01Options = {
  type: 'cb', //checkboxes
  onChange: changeCallback,
  onUndo: undoCallback,
  onRedo: redoCallback,
  onRedoClear: redoClearCallback,
  elements: [{
    elementParent: 'table01',
    value: 'A',
    labelParent: 'table01',
    label: 'A'
  }, {
    elementParent: 'table01',
    value: 'B',
    labelParent: 'table01',
    label: 'B'
  }],
  elPrefix: '<tr><td>',
  elPostfix: '</td>',
  lbPrefix: '<td>',
  lbPostfix: '</td></tr>',
  order: 'elementFirst',
  height: '20px',
  initialValue: ['A', 'B'],
  dataId: 'optionsAB',
  readOnly: false
}
var cbGroup01 = new jsMultipleChoice('cbGroup01', cbGroup01Options);
```

options description

type:	'cb' for checkboxes and 'rb' for radiobuttons [mandatory]
onChange:	callback function when value changes. It will send 4 parameters: param 1 => id of the group param 2 => current value of the group (as array of values for checkbox groups) param 3 => dirty flag indicating if changes have been made since original value param 4 => dataId
onUndo:	callback when undo has been triggered param 1 => id of the group param 2 => current length of the undo list
onRedo:	callback when redo has been triggered param 1 => id of the group param 2 => current length of the redo list
onRedoClear:	callback when all redoLists should be cleared, because new changes occurred param 1 => id of the group
elements:	an array of objects describing the elements to be created every element must have the following data: elementParent: parent id where element is to be created value: the value of this element (unique inside the group) labelParent: parent id where the label is created label: html string of the label (may include image tag)
elPrefix:	a string to be added before the element on creation (e.g.: '<p>') default is an empty string
elPostfix:	a string to be added in after the element on creation (e.g.: ' ') default is an empty string
lbPrefix:	a string to be added before the label on creation (e.g.: ' ') default is an empty string
lbPostfix:	a string to be added after the label on creation (e.g.: '</p>') default is an empty string
order:	the creation order for the elements: either 'elementFirst' (default) or 'labelFirst'
height:	css string or integer for the height of the element (integer to be interpreted as pixels) default is '20px'
initialValue:	the value the group should have after creation (preselection) radio groups just get a string matching the value of one button checkbox groups get an array of values each of which matches a checkbox default is empty string resp. empty array
dataId:	a string identifying what the data represents (e.g. name of database field) this will be sent back in the onChange event and helps identify the data being sent default is empty string
readOnly:	boolean that defines if the elements can be modified

methods

addElement(elementParent, value, labelParent, label)

if elements are not defined at creation time, this function allows to add them one by one. The parameters are the same as when created at creation time with the **elements** option.

getValue()

manual trigger of the **onChange** handler.

reset(v)

sets a new value for the group. The parameter is the same as when set at creation with the **initialValue** option. In addition the undo and redo lists will be reset.

lock()

sets group to read only mode.

unlock()

removes read only mode.

setHeight()

modifies the height of all checkboxes or radio buttons in the group. The parameter is the same as when set at creation with the **height** option.

undo()

triggers the undo handler: the last change (if any) is rolled back.

redo()

triggers the redo handler: the last undone change will be redone.

clearUndoList()

clears all undo and redo steps registered.

clearRedoList()

clears all redo steps registered, but leaves undo steps untouched.

updateLabel(v, newLabel)

updates the label of the element with value **v** with the HTML string **newLabel**.

setDataId(dataId)

sets a new dataId for this group

getDataId()

fetches the dataId for this group