

# CMPSC 465: LECTURE XV

## Dijkstra's Algorithm

Ke Chen

October 03, 2025

## Shortest path on weighted graphs

In many applications, having weights on edges is useful.

The edge weights could represent distances, cost, time, etc.

**Second scenario** Find shortest paths on weighted graphs.

**Idea** Suppose all the weights are **positive integers**, we can add **dummy nodes** to represent edge weights.

## Shortest path on weighted graphs



In many applications, having weights on edges is useful.

The edge weights could represent distances, cost, time, etc.

**Second scenario** Find shortest paths on weighted graphs.

**Idea** Suppose all the weights are **positive integers**, we can add **dummy nodes** to represent edge weights.

**Example**



# Don't watch the pot, just take a nap

Problem with this approach?

# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?

# Don't watch the pot, just take a nap



Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.

# Don't watch the pot, just take a nap

Problem with this approach?



- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.



# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.





- ▶ Suppose that every second we discover one new layer.



# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.





- ▶ Suppose that every second we discover one new layer.

# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.



- ▶ Suppose that every second we discover one new layer.







# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.





- ▶ Suppose that every second we discover one new layer.
- ▶ For the first 99 seconds, we are waiting for the dummy nodes we don't care about.
- ▶ We could set alarm clocks and go take a nap.



# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.





- ▶ Suppose that every second we discover one new layer.
- ▶ For the first 99 seconds, we are waiting for the dummy nodes we don't care about.
- ▶ We could set **alarm clocks** and go take a nap.

# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.





- ▶ Suppose that every second we discover one new layer.
- ▶ For the first 99 seconds, we are waiting for the dummy nodes we don't care about.
- ▶ We could set alarm clocks and go take a nap.



# Don't watch the pot, just take a nap

Problem with this approach?

- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.





- ▶ Suppose that every second we discover one new layer.
- ▶ For the first 99 seconds, we are waiting for the dummy nodes we don't care about.
- ▶ We could set **alarm clocks** and go take a nap.

# Don't watch the pot, just take a nap

Problem with this approach?


- ▶ What about non-integer weights? Negative weights?
- ▶ The graph size can increase exponentially.



- ▶ Suppose that every second we discover one new layer.
- ▶ For the first 99 seconds, we are waiting for the dummy nodes we don't care about.
- ▶ We could set alarm clocks and go take a nap.
- ▶ These are the estimated upper bounds for arrival time.


## Another example

Time: (initial)




## Another example

Time: 0




## Another example

Time: 0




## Another example

Time: 0




## Another example

Time: 0



## Another example


Time: 2






## Another example

Time: 2




## Another example

Time: 2




## Another example

Time: 2




## Another example

Time: 2




## Another example

Time: 3




## Another example

Time: 3




## Another example

Time: 3



## Another example


Time: 3






## Another example

Time: 5



## Another example

Time: 6



## Dijkstra's algorithm

**Input:** A graph  $G = (V, E, \ell)$  where  $\ell : E \rightarrow \mathbb{N}$  maps edges to weights, a starting vertex  $s$

**Output:** Shortest paths from  $s$  to any other vertex

Dijkstra( $G, s$ )

```
// dist has length  $|V|$ , for the alarm clocks
```

```
foreach  $v \in V$  do
```

```
└  $dist[v] = \infty$ 
```

```
 $dist[s] = 0$ 
```

```
repeat  $|V|$  times do
```

```
└ Find the vertex  $v$  with the smallest time among those  
  whose alarms have not rung yet
```

```
    foreach  $(v, w) \in E$  do
```

```
        if  $dist[w] > dist[v] + \ell(v, w)$  then
```

```
            └  $dist[w] = dist[v] + \ell(v, w)$ 
```

# Dijkstra's algorithm

**Input:** A graph  $G = (V, E, \ell)$  where  $\ell : E \rightarrow \mathbb{N}$  maps edges to weights, a starting vertex  $s$

**Output:** Shortest paths from  $s$  to any other vertex

Dijkstra( $G, s$ )

```
// dist has length  $|V|$ , for the alarm clocks
```

```
foreach  $v \in V$  do
```

```
└  $dist[v] = \infty$ 
```

```
 $dist[s] = 0$ 
```

```
repeat  $|V|$  times do
```

```
└ Find the vertex  $v$  with the smallest time among those  
  whose alarms have not rung yet
```

```
  foreach  $(v, w) \in E$  do
```

```
    if  $dist[w] > dist[v] + \ell(v, w)$  then
```

```
      └  $dist[w] = dist[v] + \ell(v, w)$ 
```

$O(|V|^2)$  with naive implementation, we'll see how to improve later.

# Correctness of Dijkstra's algorithm

**Lemma** If at time  $T$  the alarm clock for vertex  $v$  rings for the first time, the shortest path from  $s$  to  $v$  has weight  $T$ .

# Correctness of Dijkstra's algorithm

**Lemma** If at time  $T$  the alarm clock for vertex  $v$  rings for the first time, the shortest path from  $s$  to  $v$  has weight  $T$ .

*Proof.* Let  $R$  be the set of vertices whose alarm have already gone off. We aim to prove by induction that the claim holds for each vertex  $v \in R$ .

# Correctness of Dijkstra's algorithm

**Lemma** If at time  $T$  the alarm clock for vertex  $v$  rings for the first time, the shortest path from  $s$  to  $v$  has weight  $T$ .

*Proof.* Let  $R$  be the set of vertices whose alarm have already gone off. We aim to prove by induction that the claim holds for each vertex  $v \in R$ .

Base case: At time  $T = 0$ ,  $R = \{s\}$  and  $dist[s] = 0$ .

# Correctness of Dijkstra's algorithm

**Lemma** If at time  $T$  the alarm clock for vertex  $v$  rings for the first time, the shortest path from  $s$  to  $v$  has weight  $T$ .

*Proof.* Let  $R$  be the set of vertices whose alarm have already gone off. We aim to prove by induction that the claim holds for each vertex  $v \in R$ .

Base case: At time  $T = 0$ ,  $R = \{s\}$  and  $dist[s] = 0$ .

Suppose the alarm of  $v$  goes off first at time  $T$ . This means:

- ▶  $T = dist[v] = \min_{w \notin R} dist[w]$
- ▶  $v$  will now be added to  $R$
- ▶  $dist[v] = dist[u] + \ell(u, v)$  for some  $u \in R$ .




## Correctness of Dijkstra's algorithm

Suppose the alarm of  $v$  goes off first at time  $T$ . This means:

- ▶  $T = \text{dist}[v] = \min_{w \notin R} \text{dist}[w]$
- ▶  $v$  will now be added to  $R$
- ▶  $\text{dist}[v] = \text{dist}[u] + \ell(u, v)$  for some  $u \in R$ .

Assume, for contradiction, that there is a **shorter path** from  $s$  to  $v$ :




## Correctness of Dijkstra's algorithm

Suppose the alarm of  $v$  goes off first at time  $T$ . This means:

- ▶  $T = \text{dist}[v] = \min_{w \notin R} \text{dist}[w]$
- ▶  $v$  will now be added to  $R$
- ▶  $\text{dist}[v] = \text{dist}[u] + \ell(u, v)$  for some  $u \in R$ .

Assume, for contradiction, that there is a **shorter path** from  $s$  to  $v$ :



$$\text{len}(\text{red path}) \geq \text{dist}[x] + \ell(x, y) \geq \text{dist}[y] \geq \text{dist}[v] = \text{len}(\text{blue path}).$$

## Speed up our implementation of Dijkstra

We need to find, in each iteration of the outer loop, the vertex with the minimum alarm time.

# Speed up our implementation of Dijkstra

We need to find, in each iteration of the outer loop, the vertex with the minimum alarm time.

This can be done using a min-heap:

- ▶ Store key-value pairs (alarm time, vertex) in the heap.

# Speed up our implementation of Dijkstra

We need to find, in each iteration of the outer loop, the vertex with the minimum alarm time.

This can be done using a min-heap:

- ▶ Store key-value pairs (alarm time, vertex) in the heap.
- ▶ Call DecreaseKey if an alarm needs update.

# Speed up our implementation of Dijkstra

We need to find, in each iteration of the outer loop, the vertex with the minimum alarm time.

This can be done using a min-heap:

- ▶ Store key-value pairs (alarm time, vertex) in the heap.
- ▶ Call DecreaseKey if an alarm needs update.
- ▶ Each vertex also needs to know its index in the heap.