

CMPSC 465: LECTURE III

Sorting algorithms

Ke Chen

September 03, 2025

Sorting problem

Input: A sequence of n numbers a_1, a_2, \dots, a_n .

Output: A reordering (permutation) of the input sequence a'_1, a'_2, \dots, a'_n such that $a'_1 \leq a'_2 \leq \dots \leq a'_n$.

Example:

Input: 8, 1, 9, 2, 8, 4, 6, 5

Output: 1, 2, 4, 5, 6, 8, 8, 9


InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

Input: 8 1 9 2 8 4 6 5

InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

Input:  8 1 9 2 8 4 6 5

InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

1st iteration:

1

8

9

2

8

4


6

5

InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

2nd iteration: 1 8 9 2 8 4 6 5



The diagram illustrates the 2nd iteration of Insertion Sort. The sequence of numbers is 1, 8, 9, 2, 8, 4, 6, 5. The first three numbers (1, 8, 9) are enclosed in green circles, representing the 'partially sorted sequence'. The remaining numbers (2, 8, 4, 6, 5) are in black text. An arrow points from the 9 to the 8, indicating that the 9 is being shifted to the right to make space for the 8.

InsertionSort


Idea: repeatedly insert the next number to the partially sorted sequence.

3rd iteration: 1 8 9 2 8 4 6 5

InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

3rd iteration: 1 8 2 9 8 4 6 5



InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

3rd iteration: 

InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

4th iteration: 1 2 8 9 8 4 6 5



InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

4th iteration: 1 2 8 8 9 4 6 5



InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

5th iteration:



InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.


6th iteration:



InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

7th iteration:



InsertionSort

Idea: repeatedly insert the next number to the partially sorted sequence.

7th iteration:

1

2

4

5

6

8

8

9

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Correctness?

Loop invariant (property that is true after each iteration):

after the k -th iteration, $A[1..k]$ is sorted.

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Correctness?

Loop invariant (property that is true after each iteration):

after the k -th iteration, $A[1..k]$ is sorted.

Proof by induction: $A[1]$ is sorted (base case).

If $A[1..k - 1]$ is sorted, after inserting $A[k]$, $A[1..k]$ is sorted.

Consequently, $A[1..n]$ is sorted when the algorithm finishes. \square

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Time complexity?

while-loop: $O(n)$ time

for-loop: $O(n)$ rounds, $O(n)$ time each, in total $O(n^2)$.

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Time complexity?

while-loop: $O(n)$ time

for-loop: $O(n)$ rounds, $O(n)$ time each, in total $O(n^2)$.

A more careful analysis: the i -th round takes $O(i)$ time.

In total: $O(1) + O(2) + \dots + O(n)$

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Time complexity?

while-loop: $O(n)$ time

for-loop: $O(n)$ rounds, $O(n)$ time each, in total $O(n^2)$.

A more careful analysis: the i -th round takes $O(i)$ time.

In total: $O(1) + O(2) + \dots + O(n)$

$= O(1 + 2 + \dots + n) = O(n(n + 1)/2) = O(n^2)$.

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Space complexity?

Only uses $O(1)$ additional space beyond the n cells for the input data.

InsertionSort

InsertionSort($A[1..n]$)

for $i = 1$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Can we do better?

InsertionSort

InsertionSort($A[1..n]$)

for $i = \textcolor{red}{1}$ ² **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

$A[j] = key$

$j = j - 1$

Can we do better?

Yes? We can do some optimization ...

InsertionSort

InsertionSort($A[1..n]$)

for $i = \overset{2}{\cancel{1}}$ **to** n **do**

$key = A[i]$

$j = i - 1$

while $j > 0$ **and** $A[j] > key$ **do**

$A[j + 1] = A[j]$

~~$A[j] = key$~~

$j = j - 1$

$A[j + 1] = key$

Can we do better?

Yes? We can do some optimization ...

InsertionSort

InsertionSort($A[1..n]$)

```
for  $i = 1$  to  $n$  do
     $key = A[i]$ 
     $j = i - 1$ 
    while  $j > 0$  and  $A[j] > key$  do
         $A[j + 1] = A[j]$ 
         $A[j] = key$ 
         $j = j - 1$ 
     $A[j + 1] = key$ 
```

Can we do better?

Yes? We can do some optimization ...

No. If $A[1..n]$ is given in decreasing order, we need at least $1 + 2 + \dots + n - 1 = n(n - 1)/2 = \Omega(n^2)$ comparisons. So the worst-case running time of InsertionSort is $\Theta(n^2)$.

InsertionSort

InsertionSort($A[1..n]$)

```
for  $i = 1$  to  $n$  do
     $key = A[i]$ 
     $j = i - 1$ 
    while  $j > 0$  and  $A[j] > key$  do
         $A[j + 1] = A[j]$ 
         $A[j] = key$ 
         $j = j - 1$ 
     $A[j + 1] = key$ 
```

Can we do better?

Yes? We can do some optimization ...

No. If $A[1..n]$ is given in decreasing order, we need at least $1 + 2 + \dots + n - 1 = n(n - 1)/2 = \Omega(n^2)$ comparisons. So the worst-case running time of InsertionSort is $\Theta(n^2)$.

Maybe with a different sorting algorithm?

MergeSort

Input: 8,1,9,2,8,4,6,5

Idea: divide and conquer

- 1 Split input in halves: 8,1,9,2 and 8,4,6,5
- 2 Sort each half: 1,2,8,9 and 4,5,6,8
- 3 Merge two sorted halves: 1,2,4,5,6,8,8,9

MergeSort

Input: 8,1,9,2,8,4,6,5

Idea: divide and conquer

- 1 Split input in halves: 8,1,9,2 and 8,4,6,5
- 2 Sort each half: 1,2,8,9 and 4,5,6,8
- 3 Merge two sorted halves: 1,2,4,5,6,8,8,9

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort

Input: 8,1,9,2,8,4,6,5

Idea: divide and conquer

- 1 Split input in halves: 8,1,9,2 and 8,4,6,5
- 2 Sort each half: 1,2,8,9 and 4,5,6,8
- 3 Merge two sorted halves: 1,2,4,5,6,8,8,9

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
  return Merge( $B_L, B_R$ )
```

How to do Merge?

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

B_L : 1 2 8 9



B_R : 4 5 6 8



Output :

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

B_L : 1 2 8 9



B_R : 4 5 6 8



Output : 1

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

B_L : 1 2 8 9



B_R : 4 5 6 8



Output : 1 2

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

$B_L :$	1	2	8	9
			↑	
$B_R :$	4	5	6	8
		↑		
Output :	1	2	4	

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

$B_L :$	1	2	8	9
			↑	
$B_R :$	4	5	6	8
			↑	
Output :	1	2	4	5

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

$B_L :$	1	2	8	9	
			↑		
$B_R :$	4	5	6	8	
				↑	
Output :	1	2	4	5	6

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

$B_L :$	1	2	8	9		
				↑		
$B_R :$	4	5	6	8		
				↑		
Output :	1	2	4	5	6	8

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

$B_L :$	1	2	8	9				
				↑				
$B_R :$	4	5	6	8				
					↑			
Output :	1	2	4	5	6	8	8	

Merge two sorted arrays

Idea: should take advantage of the fact that both B_L and B_R are already sorted.

$B_L :$	1	2	8	9				
					↑			
$B_R :$	4	5	6	8				
					↑			
Output :	1	2	4	5	6	8	8	9

Merge two sorted arrays

Merge($X[1..k]$, $Y[1..\ell]$)

if X is empty **then return** Y

if Y is empty **then return** X

if $X[1] \leq Y[1]$ **then**

return $[X[1], \text{Merge}(X[2..k], Y)]$

else

return $[Y[1], \text{Merge}(X, Y[2..\ell])]$

Merge two sorted arrays

Merge($X[1..k]$, $Y[1..\ell]$)

```
if  $X$  is empty then return  $Y$ 
if  $Y$  is empty then return  $X$ 
if  $X[1] \leq Y[1]$  then
  return  $[X[1], \text{Merge}(X[2..k], Y)]$ 
else
  return  $[Y[1], \text{Merge}(X, Y[2..\ell])]$ 
```

Correctness?

- ▶ Since X and Y are both sorted, if $X[1] \leq Y[1]$, $X[1]$ is a smallest element.
- ▶ By induction, $\text{Merge}(X[2..k], Y)$ produces a sorted array.
- ▶ After prepending $X[1]$, the result remains sorted.
- ▶ Similar for $X[1] > Y[1]$.

Merge two sorted arrays

Merge($X[1..k]$, $Y[1..\ell]$)

if X is empty **then return** Y

if Y is empty **then return** X

if $X[1] \leq Y[1]$ **then**

return $[X[1], \text{Merge}(X[2..k], Y)]$

else

return $[Y[1], \text{Merge}(X, Y[2..\ell])]$

Time complexity?

Each round adds a new element to the output in constant time:

$O(k + \ell)$.

Merge two sorted arrays

Merge($X[1..k]$, $Y[1..\ell]$)

if X is empty **then return** Y

if Y is empty **then return** X

if $X[1] \leq Y[1]$ **then**

return $[X[1], \text{Merge}(X[2..k], Y)]$

else

return $[Y[1], \text{Merge}(X, Y[2..\ell])]$

Time complexity?

Each round adds a new element to the output in constant time:
 $O(k + \ell)$.

Exercise: Show that for all $k, \ell \geq 1$, there are two sorted arrays of sizes k and ℓ , respectively, such that merging them requires $k + \ell - 1$ comparisons. Hence the above upper bound is tight.

Merge two sorted arrays

Merge($X[1..k]$, $Y[1..\ell]$)

if X is empty **then return** Y

if Y is empty **then return** X

if $X[1] \leq Y[1]$ **then**

return $[X[1], \text{Merge}(X[2..k], Y)]$

else

return $[Y[1], \text{Merge}(X, Y[2..\ell])]$

Time complexity?

Each round adds a new element to the output in constant time:
 $O(k + \ell)$.

Exercise: Show that for all $k, \ell \geq 1$, there are two sorted arrays of sizes k and ℓ , respectively, such that merging them requires $k + \ell - 1$ comparisons. Hence the above upper bound is tight.

Space complexity?

Uses $O(k + \ell)$ extra space for the output.

Merge two sorted arrays

Merge($X[1..k]$, $Y[1..\ell]$)

if X is empty **then return** Y

if Y is empty **then return** X

if $X[1] \leq Y[1]$ **then**

return $[X[1], \text{Merge}(X[2..k], Y)]$

else

return $[Y[1], \text{Merge}(X, Y[2..\ell])]$

Can we do better?

Time bound is tight: $\Theta(k + \ell)$.

Space complexity can be improved to $O(\min\{k, \ell\})$. (Exercise)

MergeSort

MergeSort($A[1..n]$)

if $n == 1$ **then return** A

$B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$

$B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$

return Merge(B_L, B_R)

MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

Correctness?

Proof.

By induction on the size of the input n . (What is the base case?)

Suppose MergeSort correctly sorts arrays of size up to $n - 1$.

Then the two recursive calls produce sorted arrays.

Since we have shown Merge is correct, the final result is sorted.

So MergeSort works correctly on arrays of size n .

By induction, MergeSort is correct for all finite input sizes. \square

MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action

Input:


8, 1, 9, 2, 8, 4, 6, 5

MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
 $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
 $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
 $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
 $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
 $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
 $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
 $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
 $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action




MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
 $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
 $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

MergeSort in action



MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

Time complexity?

Let $T(n)$ be the running time of MergeSort on an input of size n .

We have:

$$T(n) =$$

MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil]) \leftarrow$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

Time complexity?

Let $T(n)$ be the running time of MergeSort on an input of size n .

We have:

$$T(n) = T(\lceil n/2 \rceil) +$$

MergeSort

MergeSort($A[1..n]$)

if $n == 1$ **then return** A

$B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$

$B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$ ←

return Merge(B_L, B_R)

Time complexity?

Let $T(n)$ be the running time of MergeSort on an input of size n .

We have:

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) +$$

MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ ) ←
```

Time complexity?

Let $T(n)$ be the running time of MergeSort on an input of size n .

We have:

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) + \Theta(n).$$

MergeSort

MergeSort($A[1..n]$)

```
if  $n == 1$  then return  $A$   
   $B_L = \text{MergeSort}(A[1..\lceil n/2 \rceil])$   
   $B_R = \text{MergeSort}(A[\lceil n/2 \rceil + 1..n])$   
return Merge( $B_L, B_R$ )
```

Time complexity?

Let $T(n)$ be the running time of MergeSort on an input of size n .

We have:

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) + \Theta(n).$$

How to solve for $T(n)$?

Solving recurrences

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) + \Theta(n).$$

Simplification: assume n is a power of 2 so we can ignore floors and ceilings.

Solving recurrences

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) + \Theta(n).$$

Simplification: assume n is a power of 2 so we can ignore floors and ceilings.

$$T(n) = 2T(n/2) + \Theta(n).$$

Solving recurrences

$$T(n) = T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor) + \Theta(n).$$

Simplification: assume n is a power of 2 so we can ignore floors and ceilings.

$$T(n) = 2T(n/2) + \Theta(n).$$

Solve by substitution

- ▶ Make a guess, e.g., $T(n) = O(n \log n)$.
- ▶ Try to prove the guess by induction.

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n \log n)$.

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n \log n)$.

In order to prove our guess, we need to show that

$$T(n) \leq c \cdot n \log n \text{ for some constant } c.$$

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n \log n)$.

In order to prove our guess, we need to show that

$$T(n) \leq c \cdot n \log n \text{ for some constant } c.$$

Assume this is true for all $m < n$, in particular, for $m = n/2$.

Substituting into the recurrence gives

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n \log n)$.

In order to prove our guess, we need to show that

$$T(n) \leq c \cdot n \log n \text{ for some constant } c.$$

Assume this is true for all $m < n$, in particular, for $m = n/2$.

Substituting into the recurrence gives

$$\begin{aligned} T(n) &= 2T(n/2) + \Theta(n) \\ &\leq 2c \cdot (n/2) \log(n/2) + O(n) \\ &= 2c \cdot (n/2) \log n - 2c \cdot n/2 + O(n) \\ &\leq c \cdot n \log n - c \cdot n + c' \cdot n \\ &= c \cdot n \log n - (c - c') \cdot n \\ &\leq c \cdot n \log n. \end{aligned}$$

The last step holds as long as we choose $c \geq c'$.

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n)$.

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n)$.

Need to show that $T(n) \leq c \cdot n$ for some constant c .

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n)$.

Need to show that $T(n) \leq c \cdot n$ for some constant c .

Assume this is true for all $m < n$, in particular, for $m = n/2$.

Substituting into the recurrence gives

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n)$.

Need to show that $T(n) \leq c \cdot n$ for some constant c .

Assume this is true for all $m < n$, in particular, for $m = n/2$.

Substituting into the recurrence gives

$$\begin{aligned} T(n) &= 2T(n/2) + \Theta(n) \\ &\leq 2c \cdot n/2 + O(n) \\ &\leq 2c \cdot n/2 + c' \cdot n \\ &= (c + c')n \end{aligned}$$

Solving recurrences by substitution

$$T(n) = 2T(n/2) + \Theta(n).$$

Let's guess $T(n) = O(n)$.

Need to show that $T(n) \leq c \cdot n$ for some constant c .

Assume this is true for all $m < n$, in particular, for $m = n/2$.

Substituting into the recurrence gives

$$\begin{aligned} T(n) &= 2T(n/2) + \Theta(n) \\ &\leq 2c \cdot n/2 + O(n) \\ &\leq 2c \cdot n/2 + c' \cdot n \\ &= (c + c')n > c \cdot n \end{aligned}$$