herdr Cheat Sheet

01 Start and stop (in your terminal)

`herdr`	Start herdr, or reattach to the session already running. Run it from your project folder.
`herdr --session work`	Use a separate named session. Most people only need the default one.
`herdr session list`	List sessions. **session stop** and **session delete** clean them up.
`herdr status`	Client and server status, including versions.
`herdr --remote host`	Attach to herdr on another machine over SSH.
`herdr integration install claude`	Lets herdr resume Claude Code conversations after a server restart.
`herdr server stop`	Stop the server and every process in its panes, agents included.
`herdr update`	Install the latest version. Homebrew installs update through brew instead.

02 The prefix key

`ctrl+b`	The prefix. Press it, let go, then press the action key. **prefix+c** means ctrl+b, then c.
`prefix+?`	Show every active binding. Press / to filter the list.
`prefix+q`	Detach. Everything keeps running. Run **herdr** to come back.
`prefix+s`	Open settings.
`prefix+shift+r`	Reload config.toml after you edit it.
`prefix+o`	Jump to the pane behind the latest notification.

You can skip the keys entirely. Click to focus, drag borders to resize, right-click for menus, drag to select and copy.

03 Panes

`prefix+v`	Split right.
`prefix+minus`	Split down.
`prefix+h/j/k/l`	Move focus left, down, up, or right.
`prefix+tab`	Cycle to the next pane. Add shift to go back.
`prefix+shift+h/j/k/l`	Swap the pane with its neighbor in that direction.
`prefix+z`	Zoom the pane to fill the tab. Press again to restore the layout.
`prefix+r`	Resize mode: size the pane from the keyboard.
`prefix+x`	Close the pane.
`prefix+shift+p`	Rename the pane.
`prefix+e`	Open the pane's scrollback in your editor.
`prefix+[`	Copy mode. See section 08.

04 Tabs

`prefix+c`	New tab. herdr asks for a name first.
`prefix+n / p`	Next or previous tab.
`prefix+1..9`	Jump to a tab by number.
`prefix+shift+t`	Rename the tab.
`prefix+shift+x`	Close the tab.

05 Workspaces and the sidebar

`prefix+w`	Workspace navigation. Up and Down change workspace, h/j/k/l move between panes, Esc leaves.
`prefix+g`	Goto picker: every agent and terminal, grouped by workspace. See section 07.
`prefix+shift+n`	New workspace.
`prefix+shift+g`	New workspace on a new git worktree, a separate checkout of the repo.
`prefix+shift+w`	Rename the workspace.
`prefix+shift+d`	Close the workspace. herdr asks first.
`prefix+b`	Show or hide the sidebar.

How herdr is organized

Session: the background server. Panes live here and survive closing the terminal window.
Workspace: one per project or task. The sidebar sums up the agents inside it.
Tab: a layout inside a workspace, such as agents, logs, or server.
Pane: a real terminal. Split it right or down.
Agent: Claude Code or another coding tool that herdr spots running in a pane.

Habits that save you

Give each repo its own workspace, and name it.
Detach with **prefix+q** instead of closing things. Agents keep working while you're away.
Watch the sidebar for **blocked** agents. They are waiting on you.
Running a second agent on the same repo? Give it its own worktree so the two don't edit the same files.

06 Agent states in the sidebar

`working`	Busy on a task.
`blocked`	Stopped at an approval or a question. Go read it and answer.
`done`	Finished, and you haven't looked yet.
`idle`	At its prompt and ready for the next task.
`unknown`	herdr sees an agent but can't tell its state. Don't assume it finished.

herdr recognizes Claude Code, Codex, Gemini, Cursor, Copilot, OpenCode, and others. State looks wrong? Run `herdr agent explain <pane>`.

07 Goto picker (prefix+g)

`/`	Search names, agent kinds, tabs, branches, and paths.
`j/k`	Move up and down the list. Arrow keys work too.
`Left / Right`	Jump to the previous or next workspace.
`b w i d`	Show only blocked, working, idle, or done agents.
`a`	Show all terminals again.
`Enter`	Go to the selected pane.
`Esc`	Close the picker.

Where things live

`~/.config/herdr/config.toml`: settings and keys.
`~/.config/herdr/herdr.log`: logs, next to the client and server logs.
`~/.herdr/worktrees`: where new worktrees go.
`herdr.dev/tui/docs`: full documentation.

08 Copy mode (prefix+[)

`h/j/k/l`	Move the cursor. w, b, and e move by word.
`PageUp / Down`	Scroll a page. ctrl+u and ctrl+d scroll half a page.
`/ or ?`	Search forward or back. n and N repeat the search.
`v or Space`	Start a selection.
`y or Enter`	Copy the selection and leave.
`q or Esc`	Leave without copying.

The pane keeps running while you're in copy mode. Dragging with the mouse copies without entering it.

09 Configure

`~/.config/herdr/config.toml`	Your settings file. herdr runs fine without one.
`herdr --default-config`	Print every option with comments. Copy the lines you want.
`prefix = "ctrl+a"`	Change the prefix. Goes under **[keys]**. Every binding can change.
`name = "dracula"`	Pick a theme under **[theme]**: catppuccin, tokyo-night, nord, gruvbox, and more.
`herdr config check`	Check config.toml for mistakes.
`herdr server reload-config`	Apply your edits to the running server.
`herdr config reset-keys`	Back up config.toml and remove your custom keys.

10 Drive herdr from the command line

`herdr agent list`	Every agent and its state.
`herdr pane split --current --direction right --no-focus`	Open a pane beside this one. Focus stays where it is.
`herdr agent start rev --kind claude --pane w1:p2`	Start Claude Code in pane w1:p2 and name it rev.
`herdr agent prompt rev "review the diff" --wait`	Send rev a prompt and wait until it finishes or needs you.
`herdr agent wait rev --until blocked`	Wait until rev needs your input.
`herdr agent read rev --lines 120`	Read rev's recent output.
`herdr pane run w1:p2 "npm test"`	Run a command in another pane.
`herdr worktree create --branch fix`	New git worktree with a workspace of its own.

These work from inside a herdr pane and reply in JSON. Pane IDs look like w1:p2; get them from `herdr pane list`.

Be careful

herdr server stop and closing a workspace end every process in those panes.
herdr refuses to launch inside one of its own panes. Detach first.
Running tmux inside herdr? Both use ctrl+b, so change one prefix.
A blocked agent is asking permission. Read what it wants before you approve.