

OCORA

Open CCS On-board Reference Architecture

Problem Statements

Gamma Release

This OCORA work is licensed under the dual licensing Terms EUPL 1.2 (Commission Implementing Decision (EU) 2017/863 of 18 May 2017) and the terms and condition of the Attributions- ShareAlike 3.0 Unported license or its national version (in particular CC-BY -SA 3.0 DE).





Document ID: OCORA-30-002-Gamma

Version: 1.10

Date: 04.12.2020

Status: Final



Revision history

Version	Change Description	Name (Initials)	Date of change
0.01	First Proposal for Gamma Release	RM	2020-10-29
0.02	Improved Proposal for Gamma Release	RM	2020-11-04
1.00	DRAFT for Gamma Release	RM	2020-11-25
1.10	final for Gamma Release	RM	2020-12-04

Table of contents

1	Introd	Introduction		
	1.1	Document context and purpose	3	
	1.2	Why should I read this document?		
2	Probl	Problem Statements		
3	OCOF	RA Actions	5	

Table of figures

Figure 1 - OCORA Actions5







References

The following references are used in this document:

- [1] OCORA-10-001-Gamma Release Notes
- [2] OCORA-30-001-Gamma Introduction to OCORA
- [3] OCORA-40-001-Gamma System Architecture
- [4] OCORA-40-004-Gamma Computing Platform Whitepaper
- [5] OCORA-90-002-Gamma Glossary

1 Introduction

1.1 Document context and purpose

This document is published as part of the OCORA Gamma release, together with the documents listed in the Release Notes [1]. It is the second release of this document and it is still in a preliminary state. It is to be understood as a state-of-the-art update of the OCORA Beta release problem statement document.

The focus of this document has shifted from short-term objectives (focusing on the change requests for the upcoming TSI Release in 2022) in the Beta release to problem statements and their derived business objectives for CCS On-board in general.

1.2 Why should I read this document?

This document is addressed to experts in the CCS domain and to any other person, interested in the OCORA concepts for CCS on-board. The reader will gain insights regarding the current problems and derived business objectives for the next generation of CCS On-board solutions.

Before reading this document, it is recommended to read the Release Notes [1] and the Introduction to OCORA [2]. The reader should also be aware of the Glossary [5].

The content provided in this document can be seen as the foundation for the Architecture [3], the Computing Platform [4], and the foreseen work in upcoming OCORA Releases related to a more detailed requirement engineering phase.







2 Problem Statements

The scope of the following problem statements is focusing on CCS On-board in general. In order to develop/compile the problem statements RUs have collected issues on current ETCS On-board solutions. In addition, foreseeable challenges such as the game changer developments have been considered in order to determine the gap between the existing and the future solutions.

Current ETCS On-board solutions:

- 1. are based on the TSI specifications ensuring interoperability, but the **subset specifications** are incomplete and ambiguous. Therefore, interoperability¹ is not a given.
- 2. are more expensive² than technologically justifiable. This seems to be a result of high integration engineering and certification efforts, as well as small batch sizes and high project risks.
- 3. are difficult to be integrated into existing vehicles.
- 4. are difficult and time consuming to adapt/change/update/upgrade:
 - o In the case of patching in non SIL area (e.g. cyber- security patching)
 - o In the case of error correction in SIL area
 - o In the case of baseline upgrade (e.g. ETCS baseline 2 to 3)
 - In the case of functional enrichment (ex. base for game changer introduction is not a given)
- 5. do **not respect different**, **non-overlapping life cycles** (e.g. vehicle vs. CCS vs. connectivity)
- 6. are difficult to maintain (e.g. maintenance, monitoring, diagnose possibilities very limited)
- 7. are **lacking built-in cyber security**, since this is a newer topic, especially in combination with 4 + 6.
- 8. are **performing below expected availability and reliability** (from overall ETCS system perspective).

In addition:

- The benefit of ETCS On-board only pays off, if the ERTMS rollout progresses in Europe on large scale.
- The ETCS On-board functions as such also need some improvements (e.g. braking curve, odometry accuracy, etc.) to serve current operational needs.
- Difficult, expensive and time consuming ETCS On-board fitments in general, are delaying national deployment plans, impacting trackside investments, and postponing ERTMS rollouts.

² More expensive in invest/CAPEX and operation/OPEX. OCORA always focus total cost of ownership, hence the full life cycle.





¹ Here "interoperability" addresses not only the interaction between vehicle and trackside CCS equipment. But also, same behavior / interchangeability of on-board equipment from different suppliers on one trackside installation and same behavior of one on-board installation on trackside installations from different suppliers.



3 OCORA Actions

The following list aligns high level Business Objectives to identified action fields. It is expected that the list will grow in future mainly in the dimension of identified action fields. Nevertheless, over time, additional Business Objectives could emerge as well.

Business Objectives:	OCORA Actions:
Ensure easier Access	Perform formal functional modelling on selected subsets together with the industry to improve and complete TSI subset specifications
to Interoperability	Establish common test center / reference system facilities including trackside and on-board end to end testing, off production.
	Establish modular safety by design in line with current standards
Reduction of one-off	Automate generic and specific safety case documentation and process
efforts increase	Address existing fleet while introducing a standardized gateway
standardization	Perform investigation in Acceptance of global standards
	Separate SIL from NonSIL functionality
	Define, and promote OCORA as common tendering base
From Project to Prod- uct , increase batch	Encapsulate all vehicle specific configuration and adaptation in the functional vehicle adapter, FVA
size	Introduce a common bus technology to standardize peripheral device interfaces
	Introduce a common open architecture and identify a balanced amount of building blocks
Introduce Modularity	Structure EVC monolith into functional blocks, separate ETCS core from other functions
and precisely defined Interfaces to ensure	Allow both, designs with a deployment on multiple hardware, as well as multiple functionalities on the same hardware platform
Upgradeability	Promote standardized interfaces between building blocks on all OSI layers to allow for plug-and-play like replaceability/upgradeability
	Elaborate test methods and set requirements to ensure exchangeability
	Introduce remote maintenance, monitoring and diagnostics to reduce operational cost and improve reaction / correction time
Improve Product Ma- turity (maintenance, monitoring, diagnose,	Follow a stepwise approach, use gained upgradeability to serve individual migration strategies and set the basis for a faster ERTMS rollout in Europe
performance)	Collect and analyse performance issues of whole ETCS system, define steps to improve these
	Introduce state-of-the-art (cyber-) security by design

Figure 1 - OCORA Actions



