

Audit of the DENS-SMV Project

By OCamlPro

August 20, 2021

Table of Major and Critical Issues

Critical issue: Administrative Take-over in <code>Demiurge.constructor</code>	12
Major issue: No initialization check performed in <code>Demiurge.constructor</code>	12
Critical issue: No permission check in <code>Demiurge.getTotalDistributedCb</code>	15
Critical issue: No value check in <code>Demiurge.getTotalDistributedCb</code>	15
Critical issue: Unlimited voting rights in <code>Padawan.vote</code>	27
Major issue: Infinite locking of deposits in <code>Padawan.vote</code>	27
Critical issue: Division by 0 in <code>Proposal._softMajority</code>	36
Major issue: Overflow in <code>Proposal._tryEarlyComplete</code>	37

Contents

1	Introduction	5
1.0.1	Location	5
1.0.2	End Date	5
2	Overview	6
3	Contract Base	7
3.1	Constant Definitions	7
3.2	Modifier Definitions	8
3.2.1	Modifier signed	8
3.2.2	Modifier accept	8
3.2.3	Modifier onlyContract	9
3.2.4	Modifier onlyMe	9
4	Contract Demiurge	10
4.1	Contract Inheritance	11
4.2	Constant Definitions	11
4.3	Variable Definitions	11
4.4	Modifier Definitions	12
4.4.1	Modifier checksEmpty	12
4.4.2	Modifier onlyStore	12
4.5	Constructor Definitions	12
4.5.1	Constructor	12
4.6	Public Method Definitions	13
4.6.1	Function deployPadawan	13
4.6.2	Function deployReserveProposal	13
4.6.3	Function getStats	14
4.6.4	Function getStored	14
4.6.5	Function getTotalDistributedCb	15
4.6.6	Function updateAddr	15
4.6.7	Function updateCode	15
4.7	Internal Method Definitions	16
4.7.1	Function _allCheckPassed	16
4.7.2	Function _beforeProposalDeploy	16

4.7.3	Function <code>_createChecks</code>	16
4.7.4	Function <code>_deployProposals</code>	17
4.7.5	Function <code>_passCheck</code>	17
5	Contract <code>DemiurgeStore</code>	18
5.1	Overview	18
5.2	General Minor-level Remarks	18
5.3	Public Functions	19
5.3.1	Function <code>queryAddr</code>	19
5.3.2	Function <code>queryCode</code>	19
5.3.3	Function <code>setDensRootAddr</code>	19
5.3.4	Function <code>setFaucetAddr</code>	19
5.3.5	Function <code>setPadawanCode</code>	20
5.3.6	Function <code>setProposalCode</code>	20
5.3.7	Function <code>setTokenRootAddr</code>	20
6	Contract <code>Padawan</code>	21
6.1	Overview	22
6.2	Static Variable Definitions	22
6.3	Variable Definitions	22
6.4	Modifier Definitions	22
6.4.1	Modifier <code>onlyOwner</code>	22
6.4.2	Modifier <code>onlyTokenRoot</code>	23
6.5	Constructor Definitions	23
6.5.1	Constructor	23
6.6	Public Method Definitions	23
6.6.1	Function <code>confirmVote</code>	23
6.6.2	Function <code>depositTokens</code>	24
6.6.3	Function <code>getActiveProposals</code>	24
6.6.4	Function <code>getAddresses</code>	24
6.6.5	Function <code>getAll</code>	24
6.6.6	Function <code>getTipAccount</code>	25
6.6.7	Function <code>getVoteInfo</code>	25
6.6.8	Function <code>onGetBalance</code>	25
6.6.9	Function <code>onTokenWalletDeploy</code>	25
6.6.10	Function <code>reclaimDeposit</code>	25
6.6.11	Function <code>rejectVote</code>	26
6.6.12	Function <code>updateStatus</code>	26
6.6.13	Function <code>vote</code>	27
6.7	Internal Method Definitions	28
6.7.1	Function <code>_createTokenAccount</code>	28
6.7.2	Function <code>_unlockDeposit</code>	28
6.7.3	Function <code>_updateLockedVotes</code>	28

7	Contract PadawanResolver	29
7.1	Overview	29
7.2	Variable Definitions	29
7.3	Public Method Definitions	29
7.3.1	Function resolvePadawan	29
7.4	Internal Method Definitions	30
7.4.1	Function _buildPadawanState	30
8	Contract Proposal	31
8.1	Overview	31
8.2	Static Variable Definitions	32
8.3	Variable Definitions	32
8.4	Constructor Definitions	32
8.4.1	Constructor	32
8.5	Public Method Definitions	33
8.5.1	Function getAll	33
8.5.2	Function getCurrentVotes	33
8.5.3	Function getInfo	33
8.5.4	Function getVotingResults	33
8.5.5	Function queryStatus	34
8.5.6	Function vote	34
8.5.7	Function wrapUp	35
8.6	Internal Method Definitions	35
8.6.1	Function _buildPadawanState	35
8.6.2	Function _calculateVotes	35
8.6.3	Function _changeState	35
8.6.4	Function _finalize	36
8.6.5	Function _softMajority	36
8.6.6	Function _tryEarlyComplete	37
8.6.7	Function _wrapUp	37
9	Contract ProposalResolver	38
9.1	Overview	38
9.2	Variable Definitions	38
9.3	Public Method Definitions	38
9.3.1	Function resolveProposal	38
9.4	Internal Method Definitions	39
9.4.1	Function _buildProposalState	39

Chapter 1

Overview

The Location section should be read as: The source code is available at <https://github.com/RSquad/dens-smv> at branch master with hash code equal to fbdfe4bca3c372b02cacf9788b4ad37112d0da2c and <https://github.com/RSquad/BFTG> (SMV part only) at branch master with hash code equal to 7c6ec7d811bcc1f228a3499ab19f6d20652ca94b

Chapter 2

Contract Base

In file `Base.sol`

2.1 Constant Definitions

```
8  uint16 constant ERROR_DIFFERENT_CALLER = 211;
10 uint64 constant START_BALANCE          = 3 ton;
11 uint64 constant DEPLOYER_FEE           = 0.1 ton;
12 uint64 constant PROCESS_FEE            = 0.3 ton;
13 uint64 constant VOTE_FEE                = 1 ton;
14 uint64 constant DEPLOY_FEE              = START_BALANCE +
    DEPLOYER_FEE;
15 uint64 constant DEPLOY_PAY              = DEPLOY_FEE + PROCESS_FEE;
16 uint64 constant DEPLOY_PROPOSAL_FEE    = 5 ton;
17 uint64 constant DEPLOY_PROPOSAL_PAY    = DEPLOY_PROPOSAL_FEE +
    PROCESS_FEE;
18 uint64 constant DEPOSIT_TONS_FEE        = 1 ton;
19 uint64 constant DEPOSIT_TONS_PAY        = DEPOSIT_TONS_FEE +
    PROCESS_FEE;
20 uint64 constant DEPOSIT_TOKENS_FEE      = 0.5 ton +
    DEPOSIT_TONS_FEE;
21 uint64 constant DEPOSIT_TOKENS_PAY      = DEPOSIT_TOKENS_FEE +
    PROCESS_FEE;
```

```

22  uint64 constant TOKEN_ACCOUNT_FEE    = 2 ton;
23  uint64 constant TOKEN_ACCOUNT_PAY    = TOKEN_ACCOUNT_FEE +
    PROCESS_FEE;
24  uint64 constant QUERY_STATUS_FEE     = 0.02 ton;
25  uint64 constant QUERY_STATUS_PAY     = QUERY_STATUS_FEE +
    DEF_RESPONSE_VALUE;
27  uint64 constant DEF_RESPONSE_VALUE   = 0.03 ton;
28  uint64 constant DEF_COMPUTE_VALUE    = 0.2 ton;

```

2.2 Modifier Definitions

2.2.1 Modifier signed

```

30  modifier signed {
31      require(msg.pubkey() == tvn.pubkey(), Errors.INVALID_CALLER
    );
32      tvn.accept();
33      -;
34  }

```

2.2.2 Modifier accept

- Minor issue: this modifier is dangerous in general, although not used in this project, because a function using it is easier to target to drain the balance of the contract. It should be removed.

```

36  modifier accept {
37      tvn.accept();
38      -;
39  }

```

2.2.3 Modifier onlyContract

```

41  modifier onlyContract() {
42      require(msg.sender != address(0), Errors.ONLY_CONTRACT);
43      -;
44  }

```

2.2.4 Modifier onlyMe

```

46  modifier onlyMe {
47      require(msg.sender == address(this), ERROR_DIFFERENT_CALLER
    );
48      -;
49  }

```


Chapter 3

Contract Demiurge

Contents

3.1	Constant Definitions	7
3.2	Modifier Definitions	8
3.2.1	Modifier signed	8
3.2.2	Modifier accept	8
3.2.3	Modifier onlyContract	9
3.2.4	Modifier onlyMe	9

In file `Demiurge.sol`

The `Demiurge` contract acts as a central hub to create user contracts and proposal contracts.x

3.1 Contract Inheritance

Base	
PadawanResolver	
ProposalResolver	
IDemiurgeStoreCb	
IFaucetCb	

3.2 Constant Definitions

- OK

```
30  uint8 constant CHECK_PROPOSAL = 1;
31  uint8 constant CHECK_PADAWAN = 2;
33  uint128 constant TOTAL_EMISSION = 21000000;
```

3.3 Variable Definitions

- OK

```

35     uint32 _deployedPadawansCounter = 0;
36     uint32 _deployedProposalsCounter = 0;
37     uint16 _version = 3;
39     address _addrStore;
40     address _addrDensRoot;
41     address _addrTokenRoot;
42     address _addrFaucet;
44     uint8 _checkList;
46    NewProposal[] public _newProposals;
47     uint8 public _getBalancePendings = 0;
48     uint128 public _totalVotes = 0;

```

3.4 Modifier Definitions

3.4.1 Modifier checksEmpty

- Minor issue: this modifier is not used. It should be removed.

```

66     modifier checksEmpty() {
67         require(_allCheckPassed(), Errors.NOT_ALL_CHECKS_PASSED);
68         tvn.accept();
69         -;
70     }

```

3.4.2 Modifier onlyStore

- OK

```

72     modifier onlyStore() {
73         require(msg.sender == _addrStore);
74         tvn.accept();
75         -;
76     }

```

3.5 Constructor Definitions

3.5.1 Constructor

Critical issue: Administrative Take-over in `Demiurge.constructor`

- No test is performed to verify the sender in the case `msg.sender != address(0)`. An attacker could use it to deploy the contract himself for another user, providing its own `addrStore`, i.e. with his own code for most contracts.

Major issue: No initialization check performed in `Demiurge.constructor`

- The `_createChecks` function gives the false feeling the checks are performed for initialization of the Padawan and Proposal codes. However, the checks are not performed in the functions where they would be required. No attempt is done to perform the same checks for addresses.
- Minor issue (readability): a number is used as an error, a constant should be defined instead.
- Minor issue (duplicate code): the check `addrStore != address(0)` is performed twice, the second one is useless.

```

82     constructor(address addrStore) public {
83         if (msg.sender == address(0)) {
84             require(msg.pubkey() == tvn.pubkey(), 101);
85         }
86         require(addrStore != address(0), Errors.
87             STORE_SHOULD_BE_NOT_NULL);
88         tvn.accept();
89
90         if (addrStore != address(0)) {
91             _addrStore = addrStore;
92             DemiurgeStore(_addrStore).queryCode{value: 0.2 ton,
93                 bounce: true}(ContractType.Proposal);
94             DemiurgeStore(_addrStore).queryCode{value: 0.2 ton,
95                 bounce: true}(ContractType.Padawan);
96             DemiurgeStore(_addrStore).queryAddr{value: 0.2 ton,
97                 bounce: true}(ContractAddr.DensRoot);
98             DemiurgeStore(_addrStore).queryAddr{value: 0.2 ton,
99                 bounce: true}(ContractAddr.TokenRoot);
100             DemiurgeStore(_addrStore).queryAddr{value: 0.2 ton,
101                 bounce: true}(ContractAddr.Faucet);
102         }
103
104         _createChecks();
105     }

```

3.6 Public Method Definitions

3.6.1 Function deployPadawan

- Minor issue: the function should check that the code of the Padawan contract was correctly initialized.

```

103     function deployPadawan(address owner) external onlyContract {
104         require(msg.value >= DEPLOY_FEE + 2 ton);
105         require(owner != address(0));
106         TvmCell state = _buildPadawanState(owner);
107         new Padawan{stateInit: state, value: START_BALANCE + 2 ton
108             }(_addrTokenRoot);
109     }

```

3.6.2 Function deployReserveProposal

- Minor issue: this function should check that `_codePadawan` and `_codeProposal` have been correctly initialized
- Minor issue: there is no need to store `_codePadawan` in the proposal struct as it is already a global variable.

```

112     function deployReserveProposal(
113         string title,
114         ReserveProposalSpecific specific
115     ) external onlyContract {
116         require(msg.value >= DEPLOY_PROPOSAL_FEE);
117         TvmBuilder b;
118         b.store(specific);
119         TvmCell cellSpecific = b.toCell();
120
121        NewProposal _newProposal =NewProposal(
122             0,
123             _addrDensRoot,
124             ProposalType.Reserve,
125             cellSpecific,
126             _codePadawan,
127             _buildProposalState(title)
128         );
129         _newProposals.push(_newProposal);
130
131         _beforeProposalDeploy(uint8(_newProposals.length - 1));
132     }

```

3.6.3 Function getStats

- OK

```

214     function getStats() public view returns (uint16 version, uint32
        deployedPadawansCounter, uint32 deployedProposalsCounter)
        {
215         version = _version;
216         deployedPadawansCounter = _deployedPadawansCounter;
217         deployedProposalsCounter = _deployedProposalsCounter;
218     }

```

3.6.4 Function getStored

- OK

```

198     function getStored() public view returns (
199         TvmCell codePadawan,
200         TvmCell codeProposal,
201         address addrStore,
202         address addrDensRoot,
203         address addrTokenRoot,
204         address addrFaucet
205     ) {
206         codePadawan = _codePadawan;
207         codeProposal = _codeProposal;
208         addrStore = _addrStore;
209         addrDensRoot = _addrDensRoot;
210         addrTokenRoot = _addrTokenRoot;
211         addrFaucet = _addrFaucet;
212     }

```

3.6.5 Function getTotalDistributedCb

- | |
|--|
| Critical issue: No permission check in Demiurge.getTotalDistributedCb |
| Anybody can send this message. An attacker could use it to force the deployment of all proposals with a wrong number of total votes. |
- | |
|--|
| Critical issue: No value check in Demiurge.getTotalDistributedCb |
| This function is in charge of deploying all pending proposals. It should check that the sender gave enough value to perform these deployments before the end of the action phase. Otherwise, the action phase may succeed, all proposal will be removed from the array of proposals, but the deployments will fail by lack of gas. |
- Minor issue: this function should send back the remaining gas not consumed to its called, especially if the caller gave a lot of gas to account for the deployments of multiple proposals.

```

148     function getTotalDistributedCb(
149         uint128 totalDistributed
150     ) public override {
151         _totalVotes = totalDistributed;

```

```

152     _getBalancePendings -= 1;
153     _deployProposals();
154 }

```

3.6.6 Function updateAddr

- Minor issue: add `_passCheck` for addresses too.

```

174     function updateAddr(ContractAddr kind, address addr) external
175         override onlyStore {
176         require(addr != address(0));
177         if (kind == ContractAddr.DensRoot) {
178             _addrDensRoot = addr;
179         } else if (kind == ContractAddr.TokenRoot) {
180             _addrTokenRoot = addr;
181         } else if (kind == ContractAddr.Faucet) {
182             _addrFaucet = addr;
183         }
184     }

```

3.6.7 Function updateCode

- OK

```

185     function updateCode(ContractType kind, TvmCell code) external
186         override onlyStore {
187         tvn.accept();
188         if (kind == ContractType.Proposal) {
189             _codeProposal = code;
190             _passCheck(CHECK_PROPOSAL);
191         } else if (kind == ContractType.Padawan) {
192             _codePadawan = code;
193             _passCheck(CHECK_PADAWAN);
194         }
195     }

```

3.7 Internal Method Definitions

3.7.1 Function _allCheckPassed

- OK

```

62     function _allCheckPassed() private view inline returns (bool) {
63         return (_checkList == 0);
64     }

```

3.7.2 Function `_beforeProposalDeploy`

- OK

```

134     function _beforeProposalDeploy(
135         uint8 i
136     ) private {
137         uint256 hashState = tvn.hash(_newProposals[i].state);
138         address addrProposal = address.makeAddrStd(0, hashState);
139         IClient(_addrDensRoot).onProposalDeploy
140             {value: 1 ton, bounce: true}
141             (addrProposal, _newProposals[i].proposalType,
142              _newProposals[i].specific);
143
144         IFaucet(_addrFaucet).getTotalDistributed
145             {value: 0.2 ton, flag: 1, bounce: false}();
146         _getBalancePendings += 1;
147     }

```

3.7.3 Function `_createChecks`

- OK

```

54     function _createChecks() private inline {
55         _checkList = CHECK_PADAWAN | CHECK_PROPOSAL;
56     }

```

3.7.4 Function `_deployProposals`

- OK

```

156     function _deployProposals() private {
157         if(_getBalancePendings == 0) {
158             for(uint8 i = 0; i < _newProposals.length; i++) {
159                 new Proposal {stateInit: _newProposals[i].state,
160                             value: START_BALANCE}(
161                     _totalVotes,
162                     _newProposals[i].addrClient,
163                     _newProposals[i].proposalType,
164                     _newProposals[i].specific,
165                     _newProposals[i].codePadawan
166                 );
167                 _deployedProposalsCounter++;
168             }
169             delete _newProposals;
170         }
171     }

```

3.7.5 Function `_passCheck`

- OK

```
58     function _passCheck(uint8 check) private inline {  
59         _checkList &= ~check;  
60     }
```


Chapter 4

Contract DemiurgeStore

Contents

4.1	Contract Inheritance	11
4.2	Constant Definitions	11
4.3	Variable Definitions	11
4.4	Modifier Definitions	12
4.4.1	Modifier checksEmpty	12
4.4.2	Modifier onlyStore	12
4.5	Constructor Definitions	12
4.5.1	Constructor	12
4.6	Public Method Definitions	13
4.6.1	Function deployPadawan	13
4.6.2	Function deployReserveProposal	13
4.6.3	Function getStats	14
4.6.4	Function getStored	14
4.6.5	Function getTotalDistributedCb	15
4.6.6	Function updateAddr	15
4.6.7	Function updateCode	15
4.7	Internal Method Definitions	16
4.7.1	Function _allCheckPassed	16
4.7.2	Function _beforeProposalDeploy	16
4.7.3	Function _createChecks	16
4.7.4	Function _deployProposals	17
4.7.5	Function _passCheck	17

4.1 Overview

In file `DemiurgeStore.sol`

This contract is used to store “global” values for the whole infrastructure, such as the code of the contracts to be deployed and the addresses of some contracts.

4.2 General Minor-level Remarks

In general, the infrastructure would be safer if this contract would be implemented in two phases:

- In the Initialization phase, the contract is waiting for all the `setXXX` methods to be called to initialize all the fields. A bitmap can be used to keep the current initialization state. Any attempt to user a `getXXX` method should fail.
- In the Post-Initialization phase, the contract accepts to reply to `getXXX` methods, but `setXXX` methods are disabled.

There is also an inconsistency between the getters and setters: getters are generic (they take a `kind` as argument), whereas setters are specific (there is a different one for every `kind`).

4.3 Public Functions

4.3.1 Function `queryAddr`

- Minor issue: a `require` could be added to fail if `kind` is not a well-known `kind`.

```

43     function queryAddr(ContractAddr kind) public view {
44         address addr = _addrs[uint8(kind)];
45         IDemiurgeStoreCb(msg.sender).updateAddr{value: 0, flag: 64,
46             bounce: false}(kind, addr);

```

4.3.2 Function `queryCode`

- Minor issue: a `require` could be added to fail if `kind` is not a well-known `kind`.

```

38     function queryCode(ContractType kind) public view {
39         TvmCell code = _codes[uint8(kind)];
40         IDemiurgeStoreCb(msg.sender).updateCode{value: 0, flag: 64,
41             bounce: false}(kind, code);

```

4.3.3 Function setDensRootAddr

- OK

```

21     function setDensRootAddr(address addr) public signed {
22         require(addr != address(0));
23         _addrs[uint8(ContractAddr.DensRoot)] = addr;
24     }

```

4.3.4 Function setFaucetAddr

- OK

```

29     function setFaucetAddr(address addr) public signed {
30         require(addr != address(0));
31         _addrs[uint8(ContractAddr.Faucet)] = addr;
32     }

```

4.3.5 Function setPadawanCode

- Minor issue: the infrastructure would probably be safer if the expected code hash is hardcoded in the source code, and check through a `require`

```

14     function setPadawanCode(TvmCell code) public signed {
15         _codes[uint8(ContractType.Padawan)] = code;
16     }

```

4.3.6 Function setProposalCode

- Minor issue: the infrastructure would probably be safer if the expected code hash is hardcoded in the source code, and check through a `require`

```

17     function setProposalCode(TvmCell code) public signed {
18         _codes[uint8(ContractType.Proposal)] = code;
19     }

```

4.3.7 Function setTokenRootAddr

- OK

```

25     function setTokenRootAddr(address addr) public signed {
26         require(addr != address(0));
27         _addrs[uint8(ContractAddr.TokenRoot)] = addr;
28     }

```

Chapter 5

Contract Padawan

Contents

5.1	Overview	18
5.2	General Minor-level Remarks	18
5.3	Public Functions	19
5.3.1	Function queryAddr	19
5.3.2	Function queryCode	19
5.3.3	Function setDensRootAddr	19
5.3.4	Function setFaucetAddr	19
5.3.5	Function setPadawanCode	20
5.3.6	Function setProposalCode	20
5.3.7	Function setTokenRootAddr	20

5.1 Overview

In file `Padawan.sol`

This contract is used by a user to collect his voting rights (within a token wallet), and vote for proposals. Voting rights can be added, and reclaimed if not currently used.

5.2 Static Variable Definitions

- OK

```
18     address static _deployer;
```

```
19     address static _owner;
```

5.3 Variable Definitions

- Minor issue: there is no function to clean `_activeProposals`, i.e. to remove proposals that are ended. Currently, it is possible to use `reclaimDeposit` with argument 0 to do that. It would be better to introduce a `cleanProposals` function for that purpose.

```

21     address _addrTokenRoot;
23     TipAccount _tipAccount;
24     address _returnTo;
26     mapping(address => uint32) _activeProposals;
28     uint32 _requestedVotes;
29     uint32 _totalVotes;
30     uint32 _lockedVotes;

```

5.4 Modifier Definitions

5.4.1 Modifier onlyOwner

- OK

```

34     modifier onlyOwner() {
35         require(msg.sender == _owner, Errors.
36             NOT_AUTHORIZED_CONTRACT);
37     }

```

5.4.2 Modifier onlyTokenRoot

- OK

```

39     modifier onlyTokenRoot() {
40         require(msg.sender == _addrTokenRoot, Errors.INVALID_CALLER
41             );
42     }

```

5.5 Constructor Definitions

5.5.1 Constructor

- OK

```

46     constructor(address addrTokenRoot) public onlyContract {
47         require(_deployer == msg.sender, Errors.ONLY_DEPLOYER);
48         _addrTokenRoot = addrTokenRoot;
49         _createTokenAccount();
50     }

```

5.6 Public Method Definitions

5.6.1 Function confirmVote

- Minor issue: there is no real reason to call `_updateLockedVotes` here, as it could be called in `reclaimDeposit` instead. Indeed, `_lockedVotes` is only used when the deposit is reclaimed, so it will save the cost of the recomputation if the user votes for many proposals without reclaiming his tokens.

```

74     function confirmVote(uint32 votesCount) external onlyContract {
75         // TODO: better to check is it proposal or not
76         optional(uint32) optActiveProposal = _activeProposals.fetch
77             (msg.sender);
78         require(optActiveProposal.hasValue());
79         _activeProposals[msg.sender] += votesCount;
80         _updateLockedVotes();
81         _owner.transfer(0, false, 64);
82     }
83
84

```

5.6.2 Function depositTokens

- OK

```

172     function depositTokens() external onlyOwner view {
173         require(msg.value >= DEPOSIT_TOKENS_FEE, Errors.
174             MSG_VALUE_TOO_LOW);
175         require(_tipAccount.addr != address(0), Errors.
176             ACCOUNT_DOES_NOT_EXIST);
177         ITokenWallet(_tipAccount.addr).getBalance_InternalOwner
178             {value: 0, flag: 64, bounce: true}
179             (tvm.functionId(onGetBalance));
180     }

```

5.6.3 Function getActiveProposals

- OK

```
228     function getActiveProposals() public view returns (mapping(  
229         address => uint32) activeProposals) {  
230         activeProposals = _activeProposals;  
    }
```

5.6.4 Function getAddresses

- OK

```
224     function getAddresses() public view returns (address  
225         ownerAddress) {  
226         ownerAddress = _owner;  
    }
```

5.6.5 Function getAll

- OK

```
207     function getAll() external view returns (TipAccount tipAccount,  
208         uint32 reqVotes, uint32 totalVotes, uint32 lockedVotes) {  
209         tipAccount = _tipAccount;  
210         reqVotes = _requestedVotes;  
211         totalVotes = _totalVotes;  
212         lockedVotes = _lockedVotes;  
    }
```

5.6.6 Function getTipAccount

- OK

```
214     function getTipAccount() external view returns (TipAccount  
215         tipAccount) {  
216         tipAccount = _tipAccount;  
    }
```

5.6.7 Function getVoteInfo

- OK

```
218     function getVoteInfo() external view returns (uint32 reqVotes,  
219         uint32 totalVotes, uint32 lockedVotes) {  
220         reqVotes = _requestedVotes;  
221         totalVotes = _totalVotes;  
222         lockedVotes = _lockedVotes;  
    }
```

5.6.8 Function onGetBalance

- OK

```

181     function onGetBalance(uint128 balance) public onlyContract {
182         require(_tipAccount.addr == msg.sender, Errors.
            NOT_AUTHORIZED_CONTRACT);
183         _tipAccount.balance = balance;
184         _totalVotes = uint32(balance);
185         _owner.transfer(0, false, 64);
186     }

```

5.6.9 Function onTokenWalletDeploy

- OK

```

192     function onTokenWalletDeploy(address ownerAddress) public
        onlyTokenRoot {
193         _tipAccount = TipAccount(ownerAddress, 0);
194         _owner.transfer(0, false, 64);
195     }

```

5.6.10 Function reclaimDeposit

- Minor issue: the user might want to use votes=0 to cancel a withdrawal. In this case, this function should skip sending all `queryStatus` messages, unless the goal is to clean the `_activeProposals` mapping (we advise to create a function for that purpose).
- Minor issue: there is no reason to send `queryStatus` messages if the `_unlockDeposit` function was called, i.e. if the reclaim was already successful

```

103     function reclaimDeposit(uint32 votes, address returnTo)
        external onlyOwner {
104         require(msg.value >= 3 ton, Errors.MSG_VALUE_TOO_LOW);
105         require(votes <= _totalVotes, Errors.NOT_ENOUGH_VOTES);
106         require(returnTo != address(0));
107         _returnTo = returnTo;
108         _requestedVotes = votes;
109
110         if (_requestedVotes <= _totalVotes - _lockedVotes) {
111             _unlockDeposit();
112         } else {
113             _requestedVotes = 0;
114         }
115
116         optional(address, uint32) optActiveProposal =
            _activeProposals.min();
117         while (optActiveProposal.hasValue()) {
118             (address addrActiveProposal,) = optActiveProposal.get()
            ;

```



```

119         IProposal(addrActiveProposal).queryStatus
120         {value: QUERY_STATUS_FEE, bounce: true, flag: 1}
121         ();
122         optActiveProposal = _activeProposals.next(
123             addrActiveProposal);
124     }

```

5.6.11 Function rejectVote

- OK

```

87     function rejectVote(uint32 votesCount, uint16 errorCode)
88         external onlyContract {
89             votesCount; errorCode;
90
91             // TODO: better to check is it proposal or not
92             optional(uint32) optActiveProposal = _activeProposals.fetch(
93                 msg.sender);
94             require(optActiveProposal.hasValue());
95             uint32 activeProposalVotes = optActiveProposal.get();
96             if (activeProposalVotes == 0) {
97                 delete _activeProposals[msg.sender];
98             }
99             _owner.transfer(0, false, 64);

```

5.6.12 Function updateStatus

- OK

```

127     function updateStatus(ProposalState state) external
128         onlyContract {
129         optional(uint32) optActiveProposal = _activeProposals.fetch(
130             msg.sender);
131         require(optActiveProposal.hasValue());
132         tvn.accept();
133
134         if (state >= ProposalState.Ended) {
135             delete _activeProposals[msg.sender];
136             _updateLockedVotes();
137         }
138
139         if (_requestedVotes != 0 && _requestedVotes <= _totalVotes
140             - _lockedVotes) {
141             _unlockDeposit();
142         }

```

5.6.13 Function vote

Critical issue: Unlimited voting rights in Padawan.vote

- An attacker can call this method several times in the same round and in consecutive rounds to vote several times for the same proposal, until the Padawan.confirmVote message is received. Fix: voting rights should be immediately decreased instead of waiting for confirmVote.

Major issue: Infinite locking of deposits in Padawan.vote

- An attacker could send a faked proposal address to a user to make him vote for a non-existing proposal. It can generate a little increase in storage, but if the fix of the critical issue above is done, it could also lock the deposits forever, as the corresponding contract will never end and unlock the deposits. Fix: this method should take the title of the proposal in argument, computes the address of the proposal, and the contract should correctly deal with bounced messages.

```

55  function vote(address proposal, bool choice, uint32 votes)
56      external onlyOwner {
57          require(msg.value >= VOTE_FEE, Errors.MSG_VALUE_TOO_LOW);
58          optional(uint32) optActiveProposal = _activeProposals.fetch
59              (proposal);
60
61          uint32 activeProposalVotes = optActiveProposal.hasValue() ?
62              optActiveProposal.get() : 0;
63          uint32 availableVotes = _totalVotes - activeProposalVotes;
64          require(votes <= availableVotes, Errors.NOT_ENOUGH_VOTES);
65
66          // TODO: better to remove
67          if (activeProposalVotes == 0) {
68              _activeProposals[proposal] = 0;
69          }
70
71          IProposal(proposal).vote
72              {value: 0, flag: 64, bounce: true}
73              (_owner, choice, votes);
74      }

```

5.7 Internal Method Definitions

5.7.1 Function _createTokenAccount

- OK

```

197  function _createTokenAccount() private view {
198      ITokenRoot(_addrTokenRoot).deployEmptyWallet
199          {value: 2 ton, flag: 1, bounce: true}
200          (tvm.functionId(onTokenWalletDeploy), 0, 0, address(
201              this).value, 1 ton);
202  }

```

5.7.2 Function `_unlockDeposit`

- Minor issue: this function should skip sending a message if `_requestedVotes` is 0.

```
146     function _unlockDeposit() private {
147         ITokenWallet(_tipAccount.addr).transfer
148             {value: 0.1 ton + 0.1 ton}
149             (_returnTo, _requestedVotes, 0.1 ton);
150         _totalVotes -= _requestedVotes;
151         _requestedVotes = 0;
152         _returnTo = address(0);
153     }
```

5.7.3 Function `_updateLockedVotes`

- OK

```
155     function _updateLockedVotes() private inline {
156         optional(address, uint32) optActiveProposal =
157             _activeProposals.min();
158         uint32 lockedVotes;
159         while (optActiveProposal.hasValue()) {
160             (address addr, uint32 votes) = optActiveProposal.get();
161             if (votes > lockedVotes) {
162                 lockedVotes = votes;
163             }
164             optActiveProposal = _activeProposals.next(addr);
165         }
166         _lockedVotes = lockedVotes;
167     }
```

Chapter 6

Contract PadawanResolver

Contents

6.1	Overview	22
6.2	Static Variable Definitions	22
6.3	Variable Definitions	22
6.4	Modifier Definitions	22
6.4.1	Modifier onlyOwner	22
6.4.2	Modifier onlyTokenRoot	23
6.5	Constructor Definitions	23
6.5.1	Constructor	23
6.6	Public Method Definitions	23
6.6.1	Function confirmVote	23
6.6.2	Function depositTokens	24
6.6.3	Function getActiveProposals	24
6.6.4	Function getAddresses	24
6.6.5	Function getAll	24
6.6.6	Function getTipAccount	25
6.6.7	Function getVoteInfo	25
6.6.8	Function onGetBalance	25
6.6.9	Function onTokenWalletDeploy	25
6.6.10	Function reclaimDeposit	25
6.6.11	Function rejectVote	26
6.6.12	Function updateStatus	26
6.6.13	Function vote	27
6.7	Internal Method Definitions	28
6.7.1	Function _createTokenAccount	28
6.7.2	Function _unlockDeposit	28
6.7.3	Function _updateLockedVotes	28

6.1 Overview

In file `PadawanResolver.sol`

This contract is inherited by contracts that need to deploy `Padawan` contract and verify that an address belongs to a deployed `Padawan` contract.

6.2 Variable Definitions

- OK

```
8   TvmCell _codePadawan;
```

6.3 Public Method Definitions

6.3.1 Function `resolvePadawan`

- OK

```
10   function resolvePadawan(address owner) public view returns (
11       address addrPadawan) {
12       TvmCell state = _buildPadawanState(owner);
13       uint256 hashState = tvn.hash(state);
14       addrPadawan = address.makeAddrStd(0, hashState);
15   }
```

6.4 Internal Method Definitions

6.4.1 Function `_buildPadawanState`

- Minor issue: the state built in this function uses `address(this)` as one of the static variables for the contract. Yet, this contract is bound to be inherited by different contracts (here, at least `Demiurge` and `Proposal`), i.e. computed addresses will be different for different contracts. Instead, the value of the `_deployer` variable should be made explicit to the caller, by passing it as an argument of the function.
- Minor issue: this function should fail (**require**) if the `_codePadawan` variable has not yet been initialized. A global boolean could be used for that, set in an internal function initializing both global variables.

```
16   function _buildPadawanState(address owner) internal virtual
17       view returns (TvmCell) {
18       return tvn.buildStateInit({
19           contr: Padawan,
20           varInit: {_deployer: address(this), _owner: owner},
```

```
20         code: _codePadawan  
21     });  
22 }
```

Chapter 7

Contract Proposal

Contents

7.1 Overview	29
7.2 Variable Definitions	29
7.3 Public Method Definitions	29
7.3.1 Function <code>resolvePadawan</code>	29
7.4 Internal Method Definitions	30
7.4.1 Function <code>_buildPadawanState</code>	30

7.1 Overview

In file `Proposal.sol`

This contract is used to collect the votes for a particular proposal. Votes are sent by `Padawan` contracts.

7.2 Static Variable Definitions

- OK

```
13     address static _deployer;
```

```
14     string static _title;
```

7.3 Variable Definitions

- OK

```
16     address public _addrClient;
```

```

18 ProposalInfo public _proposalInfo;
20 ProposalResults _results;
21 VoteCountModel _voteCountModel;

```

7.4 Constructor Definitions

7.4.1 Constructor

- Minor issue: there is a limitation to 16 kB for deploy messages. For this constructor, the deploy message contains the code of **Proposal**, the title and the code of **Padawan**. Thus, it might become a problem in the future. There is already a mechanism in the infrastructure to download codes from the **DemiurgeStore**, this contract should take advantage of it.
- Minor issue: the `_voteCountModel` variable is initialized to **SoftMajority** in this constructor, but it is not used anywhere. Consider removing it if no future use.

```

25 constructor(
26     uint128 totalVotes,
27     address addrClient,
28     ProposalType proposalType,
29     TvmCell specific,
30     TvmCell codePadawan
31 ) public {
32     require(_deployer == msg.sender);
33
34     _addrClient = addrClient;
35
36     _proposalInfo.title = _title;
37     _proposalInfo.start = uint32(now);
38     _proposalInfo.end = uint32(now + 60 * 60 * 24 * 7);
39     _proposalInfo.proposalType = proposalType;
40     _proposalInfo.specific = specific;
41     _proposalInfo.state = ProposalState.New;
42     _proposalInfo.totalVotes = totalVotes;
43
44     _codePadawan = codePadawan;
45
46     _voteCountModel = VoteCountModel.SoftMajority;
47 }

```

7.5 Public Method Definitions

7.5.1 Function getAll

- OK


```

168     function getAll() public view override returns (ProposalInfo
169         info) {
170         info = _proposalInfo;
171     }

```

7.5.2 Function getCurrentVotes

- OK

```

181     function getCurrentVotes() external override view returns (
182         uint32 votesFor, uint32 votesAgainst) {
183         return (_proposalInfo.votesFor, _proposalInfo.votesAgainst)
184     }

```

7.5.3 Function getInfo

- OK

```

177     function getInfo() public view returns (ProposalInfo info) {
178         info = _proposalInfo;
179     }

```

7.5.4 Function getVotingResults

- OK

```

172     function getVotingResults() public view returns (
173         ProposalResults vr) {
174         require(_proposalInfo.state > ProposalState.Ended, Errors.
175             VOTING_HAS_NOT_ENDED);
176         vr = _results;
177     }

```

7.5.5 Function queryStatus

- Minor issue: a `require` should check that the message contains enough value to send the message.

```

162     function queryStatus() external override {
163         IPadawan(msg.sender).updateStatus(_proposalInfo.state);
164     }

```

7.5.6 Function vote

- Minor issue: a **require** should check that the message contains enough value to send back the reply;
- Minor issue: given that the constructor initializes `_proposalInfo.start` to `now`, it is impossible for this function to return the `VOTING_NOT_STARTED` error.
- Minor issue: the transaction could be aborted if a `onProposalPassed` message is sent by `_finalize` (in `_wrapUp`), together with `rejectVote` or `confirmVote` messages, because of the flag 64. Need to test what happens if two messages are sent by the same transaction, with one of them containing the flag 64.

```

55 function vote(address addrPadawanOwner, bool choice, uint32
    votesCount) external override {
56     address addrPadawan = resolvePadawan(addrPadawanOwner);
57     uint16 errorCode = 0;
58
59     if (addrPadawan != msg.sender) {
60         errorCode = Errors.NOT_AUTHORIZED_CONTRACT;
61     } else if (now < _proposalInfo.start) {
62         errorCode = Errors.VOTING_NOT_STARTED;
63     } else if (now > _proposalInfo.end) {
64         errorCode = Errors.VOTING_HAS_ENDED;
65     }
66
67     if (errorCode > 0) {
68         IPadawan(msg.sender).rejectVote{value: 0, flag: 64,
        bounce: true}(votesCount, errorCode);
69     } else {
70         IPadawan(msg.sender).confirmVote{value: 0, flag: 64,
        bounce: true}(votesCount);
71         if (choice) {
72             _proposalInfo.votesFor += votesCount;
73         } else {
74             _proposalInfo.votesAgainst += votesCount;
75         }
76     }
77
78     _wrapUp();
79 }

```

7.5.7 Function wrapUp

- OK

```

49 function wrapUp() external override {
50     _wrapUp();
51     msg.sender.transfer(0, false, 64);
52 }

```

7.6 Internal Method Definitions

7.6.1 Function `_buildPadawanState`

- Minor issue (code repetition): instead of defining this function, the same function in `PadawanResolver` should take the `deployer` in argument.

```

154     function _buildPadawanState(address owner) internal view
155         override returns (TvmCell) {
156         return tvm.buildStateInit({
157             contr: Padawan,
158             varInit: {_deployer: _deployer, _owner: owner},
159             code: _codePadawan
160         });
161     }

```

7.6.2 Function `_calculateVotes`

- OK

```

132     function _calculateVotes(
133         uint32 yes,
134         uint32 no
135     ) private view returns (bool) {
136         bool passed = false;
137         passed = _softMajority(yes, no);
138         return passed;
139     }

```

7.6.3 Function `_changeState`

- OK

```

150     function _changeState(ProposalState state) private inline {
151         _proposalInfo.state = state;
152     }

```

7.6.4 Function `_finalize`

- Minor issue: a `require` should check that the message contains enough value to send the `onProposalPassed` message. This check could be moved earlier in methods calling `_finalize`

```

81     function _finalize(bool passed) private {
82         _results = ProposalResults(
83             uint32(0),
84             passed,
85             _proposalInfo.votesFor,
86             _proposalInfo.votesAgainst,

```

```

87         _proposalInfo.totalVotes,
88         _voteCountModel,
89         uint32(now)
90     );
91
92     ProposalState state = passed ? ProposalState.Passed :
93         ProposalState.NotPassed;
94
95     _changeState(state);
96
97     IClient(address(_addrClient)).onProposalPassed{value: 1 ton
98         } (_proposalInfo);
99
100     emit ProposalFinalized(_results);
101 }

```

7.6.5 Function _softMajority

Critical issue: Division by 0 in Proposal._softMajority

- If totalVotes=1, this function fails with division by 0. Fix: the function should check that totalVotes>1, and add special cases for totalVotes=1 and totalVotes=0
- Minor issue (readability): use returns (bool passed) to avoid the need to define a temporary variable and to return it.

```

141 function _softMajority(
142     uint32 yes,
143     uint32 no
144 ) private view returns (bool) {
145     bool passed = false;
146     passed = yes >= 1 + (_proposalInfo.totalVotes / 10) + (no *
147         ((_proposalInfo.totalVotes / 2) - (_proposalInfo.
148             totalVotes / 10))) / (_proposalInfo.totalVotes / 2);
149     return passed;
150 }

```

7.6.6 Function _tryEarlyComplete

Major issue: Overflow in Proposal._tryEarlyComplete

- If vote counts are expected to be in the full uint32 range, yes*2 and no*2 can overflow. Fix: use uint64 for parameters.
- Minor issue (readability): use returns (bool completed, bool passed) to avoid the need to define temporary variables and to return them.

```

101 function _tryEarlyComplete(
102     uint32 yes,
103     uint32 no
104 ) private view returns (bool, bool) {
105     (bool completed, bool passed) = (false, false);

```

```

106     if (yes * 2 > _proposalInfo.totalVotes) {
107         completed = true;
108         passed = true;
109     } else if (no * 2 >= _proposalInfo.totalVotes) {
110         completed = true;
111         passed = false;
112     }
113     return (completed, passed);
114 }

```

7.6.7 Function `_wrapUp`

- Minor issue: the function could immediately check if the state is above `Ended` to avoid recomputing again when the state cannot change anymore;
- Minor issue: there is no need to call `_changeState` before calling `_finalize`, as `_finalize` always calls `_changeState` and will thus override the state written in this function;

```

116 function _wrapUp() private {
117     (bool completed, bool passed) = (false, false);
118
119     if (now > _proposalInfo.end) {
120         completed = true;
121         passed = _calculateVotes(_proposalInfo.votesFor,
122                                 _proposalInfo.votesAgainst);
123     } else {
124         (completed, passed) = _tryEarlyComplete(_proposalInfo.
125                                                 votesFor, _proposalInfo.votesAgainst);
126     }
127
128     if (completed) {
129         _changeState(ProposalState.Ended);
130         _finalize(passed);
131     }
132 }

```

Chapter 8

Contract ProposalResolver

Contents

8.1	Overview	31
8.2	Static Variable Definitions	32
8.3	Variable Definitions	32
8.4	Constructor Definitions	32
8.4.1	Constructor	32
8.5	Public Method Definitions	33
8.5.1	Function getAll	33
8.5.2	Function getCurrentVotes	33
8.5.3	Function getInfo	33
8.5.4	Function getVotingResults	33
8.5.5	Function queryStatus	34
8.5.6	Function vote	34
8.5.7	Function wrapUp	35
8.6	Internal Method Definitions	35
8.6.1	Function _buildPadawanState	35
8.6.2	Function _calculateVotes	35
8.6.3	Function _changeState	35
8.6.4	Function _finalize	36
8.6.5	Function _softMajority	36
8.6.6	Function _tryEarlyComplete	37
8.6.7	Function _wrapUp	37

8.1 Overview

In file `ProposalResolver.sol`

This contract is inherited by contracts that need to deploy `Proposal` contract and verify that an address belongs to a deployed `Proposal` contract.

8.2 Variable Definitions

- OK

```
6 TvmCell _codeProposal;
```

8.3 Public Method Definitions

8.3.1 Function resolveProposal

- OK

```
8 function resolveProposal(string title) public view returns (
9     address addrProposal) {
10     TvmCell state = _buildProposalState(title);
11     uint256 hashState = tvm.hash(state);
12     addrProposal = address.makeAddrStd(0, hashState);
13 }
```

8.4 Internal Method Definitions

8.4.1 Function _buildProposalState

- Minor issue: the state built in this function uses `address(this)` as one of the static variables for the contract. Yet, this contract is bound to be inherited by different contracts (although here, only `Demiurge` uses it), i.e. computed addresses will be different for different contracts. Instead, the value of the `_deployer` variable should be made explicit to the caller, by passing it as an argument of the function.
- Minor issue: this function should fail (`require`) if the `_codeProposal` variable has not yet been initialized. A global boolean could be used for that, set in an internal function initializing both global variables.

```
14 function _buildProposalState(string title) internal view
15     returns (TvmCell) {
16     return tvm.buildStateInit({
17         contr: Proposal,
18         varInit: {_deployer: address(this), _title: title},
19         code: _codeProposal
20     });
21 }
```