

MachLe - Résumé Olivier D'Ancona

Evaluation Metrics

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

$$Precision = \frac{TP}{TP + FP}$$

$$Recall = \frac{TP}{TP + FN}$$

$$Specificity = \frac{TN + FP}{TN + FP}$$

$$Fscore = \frac{2 \cdot Precision \cdot Recall}{Precision + Recall}$$

Activation Functions

$$\text{Sigmoid} : \frac{1}{1 + e^{-x}}$$

$$\text{Hyperbolic tangent} : \frac{e^x - e^{-x}}{e^x + e^{-x}}$$

$$\text{Relu} : \begin{cases} 0 & \text{si } x < 0 \\ x & \text{si } x \geq 0 \end{cases}$$

$$\text{Gaussian} : e^{-x^2}$$

$$\text{Softmax} : \frac{e^{z_j}}{\sum_{k=1}^K e^{z_k}}$$

Neural Network

Structure

Biais : b , An extra weight that can be learned using a learning algorithm. The purpose is to replace threshold.

Input : I , Input vector

Weights : W , Vector of weights

Learning algorithm

1. Randomly initialize weights
2. Compute the neuron's output for a given input vector X
3. Update weights : $W_j(t+1) = W_j(t) + \eta(\hat{y}_i - y)x$ with η the learning rate and \hat{y}_i the desired output.
4. Repeat steps 2 and 3 for the number of epochs you need or until the error is smaller than a threshold.

KNN for classification and regression

Complexity : $O(knd)$

Choose a value for k :

Linear Regression

Soit un tableau de données :

$x = \text{Soap(g)}$, $y = \text{Height(cm)}$, $x \cdot y$, x^2

$$X = [1, \text{Soap}]$$

$$X^T X = \begin{bmatrix} n & \sum x_i \\ \sum x_i & \sum x_i^2 \end{bmatrix} = \begin{bmatrix} 7 & 38.5 \\ 38.5 & 218.95 \end{bmatrix}$$

$$X^T y = \begin{bmatrix} \sum y_i \\ \sum x_i y_i \end{bmatrix} = \begin{bmatrix} 348 \\ 1975 \end{bmatrix}$$

$$\hat{\theta} = (X^T X)^{-1} X^T y = \begin{bmatrix} -2.67 \\ 9.51 \end{bmatrix}$$

Inverse d'une matrice 2x2 :

$$\begin{bmatrix} a & b \\ c & d \end{bmatrix}^{-1} = \frac{1}{ad - bc} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix}$$

System engineering / Data preparation / Tuning

Logistic regression / Overfitting

SVM

Clustering

Decision Trees

Convolutional Neural Networks

Recurrent Neural Networks

Dimensionality Reduction

Reinforcement Learning

Bayesian networks / GMM / Statistical learning

Computational Complexity of ML Algorithms

Algorithm	Assumption	Train Time/Space	Inference Time/Space
KNN (Brute Force)	Similar things exist in close proximity	$O(knd) / O(nd)$	$O(knd) / O(nd)$
KNN (KD Tree)	Similar things exist in close proximity	$O(nd \log(n)) / O(nd)$	$O(k \log(n)d) / O(nd)$
Naive Bayes	Features are conditionally independent	$O(ndc) / O(dc)$	$O(dc) / O(dc)$
Logistic Regression	Classes are linearly separable	$O(nd) / O(nd)$	$O(d) / O(d)$
Linear Regression	Linear relationship between variables	$O(nd) / O(nd)$	$O(d) / O(d)$
SVM	Classes are linearly separable	$O(n^2d^2) / O(nd)$	$O(kd) / O(kd)$
Decision Tree	Feature selection by information gain	$O(n \log(n)d) / O(\text{nodes})$	$O(\log(n)) / O(\text{nodes})$
Random Forest	Low bias and variance trees	$O(kn \log(n)d) / O(\text{nodes} \times k)$	$O(k \log(n)) / O(\text{nodes} \times k)$
GBDT	High bias, low variance trees	$O(Mn \log(n)d) / O(\text{nodes} \times M + \gamma_m)$	$O(M \log(n)) / O(\text{nodes} \times M + \gamma_m)$