



The diagram illustrates the CH340C USB-to-serial converter module. The top portion shows the physical module with its pin headers and a USB cable connected. The bottom portion shows the internal circuit, including a USB-to-UART bridge chip (CH340C), a 3.3V regulator, and two LEDs (Q1 and Q2) connected to the TX and RX pins.

[illegible]

1.54/2.13/2.7-~2.9 inch

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

2

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

3

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

4

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

5

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

6

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

7

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

8

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

9

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

10

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

11

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

12

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

13

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	1

14

Pin	Signal	IO	Level
1	GND	0	0
2	INT	1	1
3	RST	1	1
4	VDD	1	1
5	ICL	1	1
6	ICL	1	



Date		
Name	Telephone	E-mail address
A2		
Group	2002/03/11	Sheet 01