

# Modes of Transfer in Computer Organization

In Computer Organization, data transfer between the CPU, memory, and I/O devices can occur in different ways. These are called modes of transfer. The choice of mode depends on speed requirements, device capability, and CPU involvement.

## **1. Programmed I/O (Polling)**

- CPU repeatedly checks the status of the I/O device.
- Simple but wastes CPU time because it keeps waiting.
- Example: Keyboard input where CPU checks each key press.

## **2. Interrupt-Driven I/O**

- CPU continues execution until the device interrupts when ready.
- Efficient compared to polling as CPU is not kept busy.
- Example: Printer notifying CPU when ready for next data.

## **3. Direct Memory Access (DMA)**

- A separate DMA controller transfers data directly between I/O and memory.
- CPU is free for other tasks, improving performance.
- Best suited for high-speed data transfer like disk or graphics.

## **4. Memory-Mapped I/O**

- I/O devices are assigned unique memory addresses.
- CPU communicates with devices using normal read/write instructions.
- Easy to program but reduces memory address space.

## **5. Isolated I/O (Port-Mapped I/O)**

- I/O devices use a separate address space.
- Special instructions (IN, OUT) are used.
- Keeps memory and I/O separate, but requires different instructions.

**Conclusion:** Each transfer mode has its advantages and disadvantages. - Programmed I/O is simple but inefficient. - Interrupt-driven I/O improves efficiency. - DMA is the fastest and best for bulk transfers. - Memory-mapped and isolated I/O differ in addressing method.