

Package ‘BrokenAdaptiveRidge’

April 5, 2023

Type Package

Title Broken adaptive ridge extensions to Cyclop

Version 1.0.0

Date 2023-04-05

Maintainer Marc A. Suchard <msuchard@ucla.edu>

Description Approximates best-subset selection (L0) regression with an iteratively adaptive Ridge (L2) penalty. This package uses Cyclops for an efficient implementation.

License Apache License 2.0

VignetteBuilder knitr

Depends R (>= 3.2.2),
Cyclops (>= 3.0.0)

Imports futile.logger,
bit64

Suggests testthat,
survival,
knitr,
rmarkdown

Encoding UTF-8

RoxygenNote 7.1.2

R topics documented:

createBarPrior	1
createFastBarPrior	2

Index	4
--------------	----------

createBarPrior	<i>Create a BAR Cyclops prior object</i>
----------------	--

Description

createBarPrior creates a BAR Cyclops prior object for use with [fitCyclopsModel](#).

Usage

```
createBarPrior(
  penalty = "bic",
  exclude = c(),
  forceIntercept = FALSE,
  fitBestSubset = FALSE,
  initialRidgeVariance = 10000,
  tolerance = 1e-08,
  maxIterations = 10000,
  threshold = 1e-06,
  delta = 0
)
```

Arguments

penalty	Specifies the BAR penalty; possible values are 'BIC' or 'AIC' or a numeric value
exclude	A vector of numbers or covariateId names to exclude from prior
forceIntercept	Logical: Force intercept coefficient into regularization
fitBestSubset	Logical: Fit final subset with no regularization
initialRidgeVariance	Numeric: variance used for algorithm initiation
tolerance	Numeric: maximum abs change in coefficient estimates from successive iterations to achieve convergence
maxIterations	Numeric: maxium iterations to achieve convergence
threshold	Numeric: absolute threshold at which to force coefficient to 0
delta	Numeric: change from 2 in ridge norm dimension

Value

A BAR Cyclops prior object of class inheriting from "cyclopsPrior" for use with `fitCyclopsModel`.

Examples

```
prior <- createBarPrior(penalty = "bic")
```

createFastBarPrior	<i>Create a fastBAR Cyclops prior object</i>
--------------------	--

Description

`createFastBarPrior` creates a fastBAR Cyclops prior object for use with [fitCyclopsModel](#).

Usage

```
createFastBarPrior(  
  penalty = 0,  
  exclude = c(),  
  forceIntercept = FALSE,  
  fitBestSubset = FALSE,  
  initialRidgeVariance = 10000,  
  tolerance = 1e-08,  
  maxIterations = 10000,  
  threshold = 1e-06  
)
```

Arguments

penalty	Specifies the BAR penalty
exclude	A vector of numbers or covariateId names to exclude from prior
forceIntercept	Logical: Force intercept coefficient into regularization
fitBestSubset	Logical: Fit final subset with no regularization
initialRidgeVariance	Numeric: variance used for algorithm initiation
tolerance	Numeric: maximum abs change in coefficient estimates from successive iterations to achieve convergence
maxIterations	Numeric: maximum iterations to achieve convergence
threshold	Numeric: absolute threshold at which to force coefficient to 0

Value

A BAR Cyclops prior object of class inheriting from "cyclopsPrior" for use with fitCyclopsModel.

Examples

```
nobs = 500; ncovs = 100  
prior <- createFastBarPrior(penalty = log(ncovs), initialRidgeVariance = 1 / log(ncovs))
```

Index

`createBarPrior`, [1](#)
`createFastBarPrior`, [2](#)
`fitCyclopsModel`, [1](#), [2](#)