

# Package ‘CaseControl’

July 15, 2016

**Type** Package

**Title** Case-Control

**Version** 0.0.5

**Date** 2016-06-29

**Author** Martijn Schuemie

**Maintainer** Martijn Schuemie <schuemie@ohdsi.org>

**Description** CaseControl is an R package for performing (nested) matched case-control analyses in an observational database in the OMOP Common Data Model.

**VignetteBuilder** knitr

**Depends** R (>= 3.2.2),  
Cyclops (>= 1.2.0),  
DatabaseConnector (>= 1.3.0),  
survival,  
FeatureExtraction (>= 1.0.1)

**Imports** RJDBC,  
SqlRender (>= 1.1.1),  
bit,  
ff,  
ffbase (>= 0.12.1),  
Rcpp (>= 0.11.2),  
OhdsiRTools (>= 1.1.1),  
plyr

**Suggests** testthat,  
knitr,  
rmarkdown,  
EmpiricalCalibration

**License** Apache License 2.0

**LinkingTo** Rcpp

**NeedsCompilation** yes

**RoxygenNote** 5.0.1

## R topics documented:

CaseControl . . . . .	<a href="#">2</a>
createCaseControlData . . . . .	<a href="#">2</a>

createCcAnalysis . . . . .	3
createCreateCaseControlDataArgs . . . . .	4
createExposureOutcomeNestingCohort . . . . .	5
createFitCaseControlModelArgs . . . . .	6
createGetDbCaseDataArgs . . . . .	6
createGetDbExposureDataArgs . . . . .	7
createSelectControlsArgs . . . . .	8
fitCaseControlModel . . . . .	9
getAttritionTable . . . . .	10
getDbCaseData . . . . .	10
getDbExposureData . . . . .	11
insertDbPopulation . . . . .	12
loadCaseControlsExposure . . . . .	13
loadCaseData . . . . .	14
loadCcAnalysisList . . . . .	14
loadExposureOutcomeNestingCohortList . . . . .	15
runCcAnalyses . . . . .	15
saveCaseControlsExposure . . . . .	17
saveCaseData . . . . .	18
saveCcAnalysisList . . . . .	18
saveExposureOutcomeNestingCohortList . . . . .	19
selectControls . . . . .	19
summarizeCcAnalyses . . . . .	20

## Index 22

---

CaseControl	<i>CaseControl</i>
-------------	--------------------

---

### Description

CaseControl

---

createCaseControlData	<i>Create case-control data</i>
-----------------------	---------------------------------

---

### Description

Create case-control data

### Usage

```
createCaseControlData(caseControlsExposure, exposureId,
  firstExposureOnly = FALSE, riskWindowStart = 0, riskWindowEnd = 0)
```

## Arguments

caseControlsExposure	An object of type caseControlsExposure as created using the <a href="#">getDbExposureData</a> function.
exposureId	The identifier of the exposure.
firstExposureOnly	Should only the first exposure per subject be included?
riskWindowStart	The start of the risk window (in days) relative to the index date. This number should be non-positive.
riskWindowEnd	The end of the risk window (in days) relative to the index date. This number should be non-positive.

## Details

For each case and control, assesses whether exposure takes place within the risk window. The output can be directly used in a conditional logistic regression.

## Value

A data frame with these columns:

**personId** The person ID  
**indexDate** The index date  
**isCase** Is the person a case or a control?  
**stratumId** The ID linking cases and controls in a matched set  
**exposed** Was the subject exposed during the risk window?

---

createCcAnalysis	<i>Create a case-control analysis specification</i>
------------------	---

---

## Description

Create a case-control analysis specification

## Usage

```
createCcAnalysis(analysisId = 1, description = "", exposureType = NULL,
  outcomeType = NULL, nestingCohortType = NULL, getDbCaseDataArgs,
  selectControlsArgs, getDbExposureDataArgs, createCaseControlDataArgs,
  fitCaseControlModelArgs)
```

## Arguments

analysisId	An integer that will be used later to refer to this specific set of analysis choices.
description	A short description of the analysis.
exposureType	If more than one exposure is provided for each exposureOutcomeNestingCohort, this field should be used to select the specific exposure to use in this analysis.
outcomeType	If more than one outcome is provided for each exposureOutcomeNestingCohort, this field should be used to select the specific outcome to use in this analysis.
nestingCohortType	If more than one nesting cohort is provided for each exposureOutcomeNestingCohort, this field should be used to select the specific nesting cohort to use in this analysis.
getDbCaseDataArgs	An object representing the arguments to be used when calling the <a href="#">createGetDbCaseDataArgs</a> function.
selectControlsArgs	An object representing the arguments to be used when calling the <a href="#">createSelectControlsArgs</a> function.
getDbExposureDataArgs	An object representing the arguments to be used when calling the <a href="#">createGetDbExposureDataArgs</a> function.
createCaseControlDataArgs	An object representing the arguments to be used when calling the <a href="#">createCreateCaseControlDataArgs</a> function.
fitCaseControlModelArgs	An object representing the arguments to be used when calling the <a href="#">createFitCaseControlModelArgs</a> function.

## Details

Create a set of analysis choices, to be used with the [runCcAnalyses](#) function.

---

createCreateCaseControlDataArgs

*Create a parameter object for the function createCaseControlData*

---

## Description

Create a parameter object for the function createCaseControlData

## Usage

```
createCreateCaseControlDataArgs(firstExposureOnly = FALSE,
  riskWindowStart = 0, riskWindowEnd = 0)
```

**Arguments**

firstExposureOnly	Should only the first exposure per subject be included?
riskWindowStart	The start of the risk window (in days) relative to the index date. This number should be non-positive.
riskWindowEnd	The end of the risk window (in days) relative to the index date. This number should be non-positive.

**Details**

Create an object defining the parameter values.

---

createExposureOutcomeNestingCohort  
*Create exposure-outcome-nesting-cohort combinations.*

---

**Description**

Create exposure-outcome-nesting-cohort combinations.

**Usage**

```
createExposureOutcomeNestingCohort(exposureId, outcomeId,
  nestingCohortId = NULL)
```

**Arguments**

exposureId	A concept ID indentifying the target drug in the exposure table. If multiple strategies for picking the exposure will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the #' exposureType parameter in the <a href="#">createCcAnalysis</a> function.
outcomeId	A concept ID indentifying the outcome in the outcome table. If multiple strategies for picking the outcome will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the outcomeType parameter in the <a href="#">createCcAnalysis</a> function.
nestingCohortId	A concept ID indentifying the nesting cohort in the nesting cohort table. If multiple strategies for picking the nesting cohort will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the nestingCohortType parameter in the <a href="#">createCcAnalysis</a> function.

**Details**

Create a set of hypotheses of interest, to be used with the [runCcAnalyses](#) function.

---

```
createFitCaseControlModelArgs
```

*Create a parameter object for the function fitCaseControlModel*

---

## Description

Create a parameter object for the function fitCaseControlModel

## Usage

```
createFitCaseControlModelArgs(useCovariates = FALSE,
  excludeCovariateIds = c(), includeCovariateIds = c(),
  prior = createPrior("laplace", useCrossValidation = TRUE),
  control = createControl(cvType = "auto", startingVariance = 0.01, tolerance
    = 2e-07, cvRepetitions = 10, selectorType = "byPid", noiseLevel = "quiet"))
```

## Arguments

useCovariates	Whether to use the covariates in the caseControlsExposure.
excludeCovariateIds	Exclude these covariates from the model.
includeCovariateIds	Include only these covariates in the model.
prior	The prior used to fit the model. See createPrior for details.
control	The control object used to control the cross-validation used to determine the hyperparameters of the prior (if applicable). See createControl for details.

## Details

Create an object defining the parameter values.

---

```
createGetDbCaseDataArgs
```

*Create a parameter object for the function getDbCaseData*

---

## Description

Create a parameter object for the function getDbCaseData

## Usage

```
createGetDbCaseDataArgs(useNestingCohort = FALSE,
  useObservationEndAsNestingEndDate = TRUE, getVisits = TRUE,
  studyStartDate = "", studyEndDate = "")
```

**Arguments**

useNestingCohort	Should the study be nested in a cohort (e.g. people with a specific indication)? If not, the study will be nested in the general population.
useObservationEndAsNestingEndDate	When using a nesting cohort, should the observation period end date be used instead of the cohort end date?
getVisits	Get data on visits? This is needed when matching on visit date is requested later on.
studyStartDate	A calendar date specifying the minimum date where data is used. Date format is 'yyyymmdd'.
studyEndDate	A calendar date specifying the maximum date where data is used. Date format is 'yyyymmdd'.

**Details**

Create an object defining the parameter values.

---

```
createGetDbExposureDataArgs
```

*Create a parameter object for the function getDbExposureData*

---

**Description**

Create a parameter object for the function getDbExposureData

**Usage**

```
createGetDbExposureDataArgs(covariateSettings = NULL)
```

**Arguments**

covariateSettings	An object of type covariateSettings as created using the createCovariateSettings function in the FeatureExtraction package. If NULL then no covariate data is retrieved.
-------------------	--

**Details**

Create an object defining the parameter values.

---

```
createSelectControlsArgs
```

*Create a parameter object for the function selectControls*

---

## Description

Create a parameter object for the function selectControls

## Usage

```
createSelectControlsArgs(firstOutcomeOnly = TRUE, washoutPeriod = 180,
  controlsPerCase = 2, matchOnAge = TRUE, ageCaliper = 2,
  matchOnGender = TRUE, matchOnProvider = FALSE, matchOnVisitDate = FALSE,
  visitDateCaliper = 30, removedUnmatchedCases = TRUE)
```

## Arguments

firstOutcomeOnly	Use the first outcome per person?
washoutPeriod	Minimum required numbers of days of observation for inclusion as either case or control.
controlsPerCase	Maximum number of controls to select per case.
matchOnAge	Match on age?
ageCaliper	Maximum difference (in years) in age when matching on age.
matchOnGender	Match on gender?
matchOnProvider	Match on provider (as specified in the person table)?
matchOnVisitDate	Should the index date of the control be changed to the nearest visit date?
visitDateCaliper	Maximum difference (in days) between the index date and the visit date when matching on visit date.
removedUnmatchedCases	Should cases with no matched controls be removed?

## Details

Create an object defining the parameter values.



---

fitCaseControlModel	<i>Fit the case-control model</i>
---------------------	-----------------------------------

---

## Description

Fit the case-control model

## Usage

```
fitCaseControlModel(caseControlData, useCovariates = FALSE,  
  excludeCovariateIds = c(), includeCovariateIds = c(),  
  caseControlsExposure = NULL, prior = createPrior("laplace",  
  useCrossValidation = TRUE), control = createControl(cvType = "auto",  
  startingVariance = 0.01, tolerance = 2e-07, cvRepetitions = 10, selectorType =  
  "byPid", noiseLevel = "quiet"))
```

## Arguments

caseControlData	A data frame as generated by the <a href="#">createCaseControlData</a> function.
useCovariates	Whether to use the covariates in the caseControlsExposure.
excludeCovariateIds	Exclude these covariates from the model.
includeCovariateIds	Include only these covariates in the model.
caseControlsExposure	An object of type caseControlsExposure as created using the <a href="#">getDbExposureData</a> function.
prior	The prior used to fit the model. See <a href="#">createPrior</a> for details.
control	The control object used to control the cross-validation used to determine the hyperparameters of the prior (if applicable). See <a href="#">createControl</a> for details.

## Details

Fits the model using a conditional logistic regression.

## Value

An object of type outcomeModel.

---

getAttritionTable	<i>Get the attrition table for a population</i>
-------------------	---

---

**Description**

Get the attrition table for a population

**Usage**

```
getAttritionTable(caseControls)
```

**Arguments**

caseControls     A data frame of cases and controls as generated by the function [selectControls](#).

**Value**

A data frame specifying the number of cases and events after various steps of filtering.

---

getDbCaseData	<i>Load case data from the database</i>
---------------	---

---

**Description**

Load all data about the cases and nesting cohort from the database.

**Usage**

```
getDbCaseData(connectionDetails, cdmDatabaseSchema,
  oracleTempSchema = cdmDatabaseSchema,
  outcomeDatabaseSchema = cdmDatabaseSchema, outcomeTable = "condition_era",
  outcomeIds = c(), useNestingCohort = FALSE,
  nestingCohortDatabaseSchema = cdmDatabaseSchema,
  nestingCohortTable = "cohort", nestingCohortId,
  useObservationEndAsNestingEndDate = TRUE, getVisits = TRUE,
  studyStartDate = "", studyEndDate = "")
```

**Arguments**

connectionDetails

An R object of type ConnectionDetails created using the function createConnectionDetails in the DatabaseConnector package.

cdmDatabaseSchema

The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm\_instance.dbo'.

oracleTempSchema

A schema where temp tables can be created in Oracle.

outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If outcomeTable = CONDITION_ERA, outcomeDatabaseSchema is not used. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable is not CONDITION_OCCURRENCE or CONDITION_ERA, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
outcomeIds	A list of ids used to define outcomes. If outcomeTable = CONDITION_OCCURRENCE, the list is a set of ancestor CONCEPT_IDs, and all occurrences of all descendant concepts will be selected. If outcomeTable <> CONDITION_OCCURRENCE, the list contains records found in COHORT_DEFINITION_ID field.
useNestingCohort	Should the study be nested in a cohort (e.g. people with a specific indication)? If not, the study will be nested in the general population.
nestingCohortDatabaseSchema	The name of the database schema that is the location where the nesting cohort is defined.
nestingCohortTable	Name of the table holding the nesting cohort. This table should have the same structure as the cohort table.
nestingCohortId	A cohort definition ID identifying the records in the nestingCohortTable to use as nesting cohort
useObservationEndAsNestingEndDate	When using a nesting cohort, should the observation period end date be used instead of the cohort end date?
getVisits	Get data on visits? This is needed when matching on visit date is requested later on.
studyStartDate	A calendar date specifying the minimum date where data is used. Date format is 'yyyymmdd'.
studyEndDate	A calendar date specifying the maximum date where data is used. Date format is 'yyyymmdd'.

**Value**

Returns an object of type caseData, containing information on the cases, the nesting cohort, and optionally visits. Information about multiple outcomes can be captured at once for efficiency reasons. The generic summary() function has been implemented for this object.

---

getDbExposureData	<i>Get exposure data for cases and controls from a database</i>
-------------------	---

---

**Description**

Get exposure data for cases and controls from a database

**Usage**

```
getDbExposureData(caseControls, connectionDetails, oracleTempSchema = NULL,
  exposureDatabaseSchema, exposureTable = "drug_era", exposureIds = c(),
  cdmDatabaseSchema = exposureDatabaseSchema, covariateSettings = NULL)
```

**Arguments**

- caseControls** A data frame as generated by the [selectControls](#) function.
- connectionDetails** An R object of type `connectionDetails` created using the function `createConnectionDetails` in the `DatabaseConnector` package.
- oracleTempSchema** A schema where temp tables can be created in Oracle.
- exposureDatabaseSchema** The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If `exposureTable = DRUG_ERA`, `exposureDatabaseSchema` is not used but assumed to be `cdmSchema`. Requires read permissions to this database.
- exposureTable** The tablename that contains the exposure cohorts. If `exposureTable <> drug_era`, then expectation is `exposureTable` has format of COHORT table: `cohort_definition_id`, `subject_id`, `cohort_start_date`, `cohort_end_date`.
- exposureIds** A list of identifiers to define the exposures of interest. If `exposureTable = drug_era`, `exposureIds` should be `concept_id`. If `exposureTable <> drug_era`, `exposureIds` is used to select the `cohort_definition_id` in the cohort-like table. If no `exposureIds` are provided, all drugs or cohorts in the `exposureTable` are included as exposures.
- cdmDatabaseSchema** Needed when constructing covariates: the name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example `'cdm_instance.dbo'`.
- covariateSettings** An object of type `covariateSettings` as created using the `createCovariateSettings` function in the `FeatureExtraction` package. If `NULL` then no covariate data is retrieved.

---

<code>insertDbPopulation</code>	<i>Insert cases and controls into a database</i>
---------------------------------	--

---

**Description**

Insert cases and controls into a database

**Usage**

```
insertDbPopulation(caseControls, cohortIds = c(1, 0), connectionDetails,
  cohortDatabaseSchema, cohortTable = "cohort", createTable = FALSE,
  dropTableIfExists = TRUE)
```

**Arguments**

caseControls	A data frame as generated by the <a href="#">selectControls</a> function.
cohortIds	The IDs to be used for the cohorts of cases and controls, respectively.
connectionDetails	An R object of type <code>connectionDetails</code> created using the function <code>createConnectionDetails</code> in the <code>DatabaseConnector</code> package.
cohortDatabaseSchema	The name of the database schema where the data will be written. Requires write permissions to this database. On SQL Server, this should specify both the database and the schema, so for example <code>'cdm_instance.dbo'</code> .
cohortTable	The name of the table in the database schema where the data will be written.
createTable	Should a new table be created? If not, the data will be inserted into an existing table.
dropTableIfExists	If <code>createTable = TRUE</code> and the table already exists it will be overwritten.

**Details**

Inserts cases and controls into a database. The table in the database will have the same structure as the 'cohort' table in the Common Data Model.

---

loadCaseControlsExposure

*Load the caseControlsExposure data from a folder*

---

**Description**

loadCaseControlsExposure loads an object of type `caseControlsExposure` from a folder in the file system.

**Usage**

```
loadCaseControlsExposure(folder, readOnly = TRUE)
```

**Arguments**

folder	The name of the folder containing the data.
readOnly	If true, the data is opened read only.

**Details**

The data will be written to a set of files in the folder specified by the user.

**Value**

An object of class `caseControlsExposure`.

---

loadCaseData	<i>Load the case data from a folder</i>
--------------	---

---

**Description**

loadCaseData loads an object of type caseData from a folder in the file system.

**Usage**

```
loadCaseData(folder, readOnly = TRUE)
```

**Arguments**

folder	The name of the folder containing the data.
readOnly	If true, the data is opened read only.

**Details**

The data will be written to a set of files in the folder specified by the user.

**Value**

An object of class caseData.

---

loadCcAnalysisList	<i>Load a list of ccAnalysis from file</i>
--------------------	--

---

**Description**

Load a list of objects of type ccAnalysis from file. The file is in JSON format.

**Usage**

```
loadCcAnalysisList(file)
```

**Arguments**

file	The name of the file
------	----------------------

**Value**

A list of objects of type ccAnalysis.

---

loadExposureOutcomeNestingCohortList	<i>Load a list of exposureOutcomeNestingCohort from file</i>
--------------------------------------	--

---

**Description**

Load a list of objects of type exposureOutcomeNestingCohort from file. The file is in JSON format.

**Usage**

```
loadExposureOutcomeNestingCohortList(file)
```

**Arguments**

file	The name of the file
------	----------------------

**Value**

A list of objects of type drugComparatorOutcome.

---

runCcAnalyses	<i>Run a list of analyses</i>
---------------	-------------------------------

---

**Description**

Run a list of analyses

**Usage**

```
runCcAnalyses(connectionDetails, cdmDatabaseSchema,
  oracleTempSchema = cdmDatabaseSchema,
  exposureDatabaseSchema = cdmDatabaseSchema, exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema, outcomeTable = "condition_era",
  nestingCohortDatabaseSchema = cdmDatabaseSchema,
  nestingCohortTable = "condition_era", outputFolder = "./CcOutput",
  ccAnalysisList, exposureOutcomeNestingCohortList, getDbCaseDataThreads = 1,
  selectControlsThreads = 1, getDbExposureDataThreads = 1,
  createCaseControlDataThreads = 1, fitCaseControlModelThreads = 1,
  cvThreads = 1)
```

**Arguments**

connectionDetails	An R object of type ConnectionDetails created using the function createConnectionDetails in the DatabaseConnector package.
cdmDatabaseSchema	The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.

oracleTempSchema	A schema where temp tables can be created in Oracle.
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used but assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> drug_era, then expectation is exposureTable has format of COHORT table: cohort_definition_id, subject_id, cohort_start_date, cohort_end_date.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If outcomeTable = CONDITION_ERA, outcomeDatabaseSchema is not used. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable is not CONDITION_OCCURRENCE or CONDITION_ERA, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
nestingCohortDatabaseSchema	The name of the database schema that is the location where the nesting cohort is defined.
nestingCohortTable	Name of the table holding the nesting cohort. This table should have the same structure as the cohort table.
outputFolder	Name of the folder where all the outputs will written to.
ccAnalysisList	A list of objects of type ccAnalysis as created using the <a href="#">createCcAnalysis</a> function.
exposureOutcomeNestingCohortList	A list of objects of type exposureOutcomeNestingCohort as created using the <a href="#">createExposureOutcomeNestingCohort</a> function.
getDbCaseDataThreads	The number of parallel threads to use for building the caseData objects.
selectControlsThreads	The number of parallel threads to use for selecting controls.
getDbExposureDataThreads	The number of parallel threads to use for fetchign data on exposures for cases and controls.
createCaseControlDataThreads	The number of parallel threads to use for creating case and control data including exposure status indicators
fitCaseControlModelThreads	The number of parallel threads to use for fitting the models.
cvThreads	The number of parallel threads used for the cross-validation to determine the hyper-parameter when fitting the model.

## Details

Run a list of analyses for the exposure-outcome-nesting cohorts of interest. This function will run all specified analyses against all hypotheses of interest, meaning that the total number of outcome models is 'length(ccAnalysisList) \* length(exposureOutcomeNestingCohortList)' (if all analyses



specify an outcome model should be fitted). When you provide several analyses it will determine whether any of the analyses have anything in common, and will take advantage of this fact. For example, if we specify several analyses that only differ in the way the outcome model is fitted, then this function will extract the data and fit the propensity model only once, and re-use this in all the analysis.

### Value

A data frame with the following columns:

analysisId	The unique identifier for a set of analysis choices.
exposureId	The ID of the target drug.
outcomeId	The ID of the outcome.
ccDataFolder	The folder where the ccData object is stored.
ccEraDataFolder	The folder where the ccEraData object is stored.
ccModelFile	The file where the fitted SCCS model is stored.

---

saveCaseControlsExposure

*Save the caseControlsExposure data to folder*

---

### Description

saveCaseControlsExposure saves an object of type caseControlsExposure to folder.

### Usage

```
saveCaseControlsExposure(caseControlsExposure, folder)
```

### Arguments

caseControlsExposure	An object of type caseControlsExposure as generated using <a href="#">getDbExposureData</a> .
folder	The name of the folder where the data will be written. The folder should not yet exist.

### Details

The data will be written to a set of files in the specified folder.

---

saveCaseData	<i>Save the case data to folder</i>
--------------	-------------------------------------

---

**Description**

saveCaseData saves an object of type caseData to folder.

**Usage**

```
saveCaseData(caseData, folder)
```

**Arguments**

caseData	An object of type caseData as generated using <a href="#">getDbCaseData</a> .
folder	The name of the folder where the data will be written. The folder should not yet exist.

**Details**

The data will be written to a set of files in the specified folder.

---

saveCcAnalysisList	<i>Save a list of ccAnalysis to file</i>
--------------------	--

---

**Description**

Write a list of objects of type ccAnalysis to file. The file is in JSON format.

**Usage**

```
saveCcAnalysisList(ccAnalysisList, file)
```

**Arguments**

ccAnalysisList	The ccAnalysis list to be written to file
file	The name of the file where the results will be written

---

```
saveExposureOutcomeNestingCohortList
```

*Save a list of drugComparatorOutcome to file*

---

### Description

Write a list of objects of type exposureOutcomeNestingCohort to file. The file is in JSON format.

### Usage

```
saveExposureOutcomeNestingCohortList(exposureOutcomeNestingCohortList, file)
```

### Arguments

exposureOutcomeNestingCohortList	The exposureOutcomeNestingCohort list to be written to file
file	The name of the file where the results will be written

---

selectControls	<i>Select matched controls per case</i>
----------------	---

---

### Description

Select matched controls per case

### Usage

```
selectControls(caseData, outcomeId, firstOutcomeOnly = TRUE,
  washoutPeriod = 180, controlsPerCase = 2, matchOnAge = TRUE,
  ageCaliper = 2, matchOnGender = TRUE, matchOnProvider = FALSE,
  matchOnVisitDate = FALSE, visitDateCaliper = 30,
  matchOnTimeInCohort = FALSE, daysInCohortCaliper = 30,
  removedUnmatchedCases = TRUE)
```

### Arguments

caseData	An object of type caseData as generated using the <a href="#">getDbCaseData</a> function.
outcomeId	The outcome ID of the cases for which we need to pick controls.
firstOutcomeOnly	Use the first outcome per person?
washoutPeriod	Minimum required numbers of days of observation for inclusion as either case or control.
controlsPerCase	Maximum number of controls to select per case.
matchOnAge	Match on age?
ageCaliper	Maximum difference (in years) in age when matching on age.
matchOnGender	Match on gender?

matchOnProvider	Match on provider (as specified in the person table)?
matchOnVisitDate	Should the index date of the control be changed to the nearest visit date?
visitDateCaliper	Maximum difference (in days) between the index date and the visit date when matching on visit date.
matchOnTimeInCohort	Match on time in nesting cohort? When not using nesting, this is interpreted as time observed prior to index.
daysInCohortCaliper	Maximum difference (in days) in time in cohort.
removedUnmatchedCases	Should cases with no matched controls be removed?

### Details

Select controls per case. Controls are matched on calendar time and the criteria defined in the arguments. Controls are randomly sampled to the required number.

### Value

A data frame with these columns:

- personId** The person ID
- indexDate** The index date
- isCase** Is the person a case or a control?
- stratumId** The ID linking cases and controls in a matched set

---

summarizeCcAnalyses	<i>Create a summary report of the analyses</i>
---------------------	--

---

### Description

Create a summary report of the analyses

### Usage

```
summarizeCcAnalyses(outcomeReference)
```

### Arguments

- outcomeReference**  
A data.frame as created by the [runCcAnalyses](#) function.

**Value**

A data frame with the following columns:

analysisId	The unique identifier for a set of analysis choices.
targetId	The ID of the target drug.
comparatorId	The ID of the comparator group.
indicationConceptIds	The ID(s) of indications in which to nest to study.
outcomeId	The ID of the outcome.
rr	The estimated effect size.
ci95lb	The lower bound of the 95 percent confidence interval.
ci95ub	The upper bound of the 95 percent confidence interval.
treated	The number of subjects in the treated group (after any trimming and matching).
comparator	The number of subjects in the comparator group (after any trimming and matching).
eventsTreated	The number of outcomes in the treated group (after any trimming and matching).
eventsComparator	The number of outcomes in the comparator group (after any trimming and matching).
logRr	The log of the estimated relative risk.
seLogRr	The standard error of the log of the estimated relative risk.

# Index

CaseControl, [2](#)  
CaseControl-package (CaseControl), [2](#)  
createCaseControlData, [2](#), [9](#)  
createCcAnalysis, [3](#), [5](#), [16](#)  
createControl, [9](#)  
createCreateCaseControlDataArgs, [4](#), [4](#)  
createExposureOutcomeNestingCohort, [5](#),  
[16](#)  
createFitCaseControlModelArgs, [4](#), [6](#)  
createGetDbCaseDataArgs, [4](#), [6](#)  
createGetDbExposureDataArgs, [4](#), [7](#)  
createPrior, [9](#)  
createSelectControlsArgs, [4](#), [8](#)  
  
fitCaseControlModel, [9](#)  
  
getAttritionTable, [10](#)  
getDbCaseData, [10](#), [18](#), [19](#)  
getDbExposureData, [3](#), [9](#), [11](#), [17](#)  
  
insertDbPopulation, [12](#)  
  
loadCaseControlsExposure, [13](#)  
loadCaseData, [14](#)  
loadCcAnalysisList, [14](#)  
loadExposureOutcomeNestingCohortList,  
[15](#)  
  
runCcAnalyses, [4](#), [5](#), [15](#), [20](#)  
  
saveCaseControlsExposure, [17](#)  
saveCaseData, [18](#)  
saveCcAnalysisList, [18](#)  
saveExposureOutcomeNestingCohortList,  
[19](#)  
selectControls, [10](#), [12](#), [13](#), [19](#)  
summarizeCcAnalyses, [20](#)