

# Package ‘CaseControl’

April 19, 2017

**Type** Package

**Title** Case-Control

**Version** 1.3.0

**Date** 2017-04-19

**Author** Martijn Schuemie

**Maintainer** Martijn Schuemie <schuemie@ohdsi.org>

**Description** CaseControl is an R package for performing (nested) matched case-control analyses in an observational database in the OMOP Common Data Model.

**VignetteBuilder** knitr

**Depends** R (>= 3.2.2),  
Cyclops (>= 1.2.0),  
DatabaseConnector (>= 1.3.0),  
survival,  
FeatureExtraction (>= 1.0.1)

**Imports** RJDBC,  
SqlRender (>= 1.1.1),  
bit,  
ff,  
ffbase (>= 0.12.1),  
Rcpp (>= 0.11.2),  
OhdsiRTools (>= 1.1.1),  
plyr

**Suggests** testthat,  
knitr,  
rmarkdown,  
EmpiricalCalibration

**License** Apache License 2.0

**LinkingTo** Rcpp

**NeedsCompilation** yes

**RoxygenNote** 6.0.1

## R topics documented:

CaseControl . . . . .	<a href="#">2</a>
computeMdr . . . . .	<a href="#">2</a>

createCaseControlData . . . . .	3
createCcAnalysis . . . . .	4
createCreateCaseControlDataArgs . . . . .	5
createExposureOutcomeNestingCohort . . . . .	6
createFitCaseControlModelArgs . . . . .	6
createGetDbCaseDataArgs . . . . .	7
createGetDbExposureDataArgs . . . . .	8
createSelectControlsArgs . . . . .	8
fitCaseControlModel . . . . .	9
getAttritionTable . . . . .	10
getDbCaseData . . . . .	11
getDbExposureData . . . . .	12
insertDbPopulation . . . . .	13
loadCaseControlsExposure . . . . .	14
loadCaseData . . . . .	15
loadCcAnalysisList . . . . .	15
loadExposureOutcomeNestingCohortList . . . . .	16
runCcAnalyses . . . . .	16
saveCaseControlsExposure . . . . .	18
saveCaseData . . . . .	19
saveCcAnalysisList . . . . .	19
saveExposureOutcomeNestingCohortList . . . . .	20
selectControls . . . . .	20
summarizeCcAnalyses . . . . .	22

## Index 23

---

CaseControl	<i>CaseControl</i>
-------------	--------------------

---

### Description

CaseControl

---

computeMdr	<i>Compute the minimum detectable relative risk</i>
------------	---

---

### Description

Compute the minimum detectable relative risk

### Usage

```
computeMdr(caseControlData, alpha = 0.05, power = 0.8, twoSided = TRUE)
```

**Arguments**

caseControlData	A data frame describing the cases and controls as created using the <a href="#">createCaseControlData</a> function. This should at least have these columns: isCase, exposed.
alpha	Type I error.
power	1 - beta, where beta is the type II error.
twoSided	Consider a two-sided test?

**Details**

Compute the minimum detectable relative risk (MDRR) for a given study population, using the actual observed sample size and number of exposed controls. Computations by Miettinen (1969) and Rothman and Boice (1979) are used. Based on and verified using Ken Rothman's EpiSheet.

**Value**

A data frame with the MDRR and some counts.

**References**

- Miettinen OS (1969) Individual matching in the case of all or none responses. *Biometrics*, 25, 339-354.
- Rothman KJ, Boice JD (1979) *Epidemiologic Analysis with a Programmable Calculator*. NIH Publication No.79-1649.

---

createCaseControlData *Create case-control data*

---

**Description**

Create case-control data

**Usage**

```
createCaseControlData(caseControlsExposure, exposureId,
  firstExposureOnly = FALSE, riskWindowStart = 0, riskWindowEnd = 0)
```

**Arguments**

caseControlsExposure	An object of type caseControlsExposure as created using the <a href="#">getDbExposureData</a> function.
exposureId	The identifier of the exposure.
firstExposureOnly	Should only the first exposure per subject be included?
riskWindowStart	The start of the risk window (in days) relative to the index date. This number should be non-positive.
riskWindowEnd	The end of the risk window (in days) relative to the index date. This number should be non-positive.

## Details

For each case and control, assesses whether exposure takes place within the risk window. The output can be directly used in a conditional logistic regression.

## Value

A data frame with these columns:

**personId** The person ID

**indexDate** The index date

**isCase** Is the person a case or a control?

**stratumId** The ID linking cases and controls in a matched set

**exposed** Was the subject exposed during the risk window?

---

createCcAnalysis	Create a case-control analysis specification
------------------	--

---

## Description

Create a case-control analysis specification

## Usage

```
createCcAnalysis(analysisId = 1, description = "", exposureType = NULL,
  outcomeType = NULL, nestingCohortType = NULL, getDbCaseDataArgs,
  selectControlsArgs, getDbExposureDataArgs, createCaseControlDataArgs,
  fitCaseControlModelArgs)
```

## Arguments

**analysisId** An integer that will be used later to refer to this specific set of analysis choices.

**description** A short description of the analysis.

**exposureType** If more than one exposure is provided for each exposureOutcomeNestingCohort, this field should be used to select the specific exposure to use in this analysis.

**outcomeType** If more than one outcome is provided for each exposureOutcomeNestingCohort, this field should be used to select the specific outcome to use in this analysis.

**nestingCohortType**

If more than one nesting cohort is provided for each exposureOutcomeNestingCohort, this field should be used to select the specific nesting cohort to use in this analysis.

**getDbCaseDataArgs**

An object representing the arguments to be used when calling the [createGetDbCaseDataArgs](#) function.

**selectControlsArgs**

An object representing the arguments to be used when calling the [createSelectControlsArgs](#) function.

getDbExposureDataArgs

An object representing the arguments to be used when calling the [createGetDbExposureDataArgs](#) function.

createCaseControlDataArgs

An object representing the arguments to be used when calling the [createCreateCaseControlDataArgs](#) function.

fitCaseControlModelArgs

An object representing the arguments to be used when calling the [createFitCaseControlModelArgs](#) function.

## Details

Create a set of analysis choices, to be used with the [runCcAnalyses](#) function.

---

createCreateCaseControlDataArgs

*Create a parameter object for the function createCaseControlData*

---

## Description

Create a parameter object for the function createCaseControlData

## Usage

```
createCreateCaseControlDataArgs(firstExposureOnly = FALSE,
  riskWindowStart = 0, riskWindowEnd = 0)
```

## Arguments

firstExposureOnly

Should only the first exposure per subject be included?

riskWindowStart

The start of the risk window (in days) relative to the index date. This number should be non-positive.

riskWindowEnd

The end of the risk window (in days) relative to the index date. This number should be non-positive.

## Details

Create an object defining the parameter values.

---

```
createExposureOutcomeNestingCohort
```

*Create exposure-outcome-nesting-cohort combinations.*

---

### Description

Create exposure-outcome-nesting-cohort combinations.

### Usage

```
createExposureOutcomeNestingCohort(exposureId, outcomeId,
  nestingCohortId = NULL)
```

### Arguments

exposureId	A concept ID indentifying the target drug in the exposure table. If multiple strategies for picking the exposure will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the #' exposureType parameter in the <a href="#">createCcAnalysis</a> function.
outcomeId	A concept ID indentifying the outcome in the outcome table. If multiple strategies for picking the outcome will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the outcomeType parameter in the <a href="#">createCcAnalysis</a> function.
nestingCohortId	A concept ID indentifying the nesting cohort in the nesting cohort table. If multiple strategies for picking the nesting cohort will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the nestingCohortType parameter in the <a href="#">createCcAnalysis</a> function.

### Details

Create a set of hypotheses of interest, to be used with the [runCcAnalyses](#) function.

---

```
createFitCaseControlModelArgs
```

*Create a parameter object for the function fitCaseControlModel*

---

### Description

Create a parameter object for the function fitCaseControlModel

### Usage

```
createFitCaseControlModelArgs(useCovariates = FALSE,
  excludeCovariateIds = c(), includeCovariateIds = c(),
  prior = createPrior("laplace", useCrossValidation = TRUE),
  control = createControl(cvType = "auto", startingVariance = 0.01, tolerance
    = 2e-07, cvRepetitions = 10, selectorType = "byPid", noiseLevel = "quiet"))
```

**Arguments**

useCovariates	Whether to use the covariates in the caseControlsExposure.
excludeCovariateIds	Exclude these covariates from the model.
includeCovariateIds	Include only these covariates in the model.
prior	The prior used to fit the model. See createPrior for details.
control	The control object used to control the cross-validation used to determine the hyperparameters of the prior (if applicable). See createControl for details.

**Details**

Create an object defining the parameter values.

---

```
createGetDbCaseDataArgs
```

*Create a parameter object for the function getDbCaseData*

---

**Description**

Create a parameter object for the function getDbCaseData

**Usage**

```
createGetDbCaseDataArgs(useNestingCohort = FALSE,
  useObservationEndAsNestingEndDate = TRUE, getVisits = TRUE,
  studyStartDate = "", studyEndDate = "")
```

**Arguments**

useNestingCohort	Should the study be nested in a cohort (e.g. people with a specific indication)? If not, the study will be nested in the general population.
useObservationEndAsNestingEndDate	When using a nesting cohort, should the observation period end date be used instead of the cohort end date?
getVisits	Get data on visits? This is needed when matching on visit date is requested later on.
studyStartDate	A calendar date specifying the minimum date where data is used. Date format is 'yyyymmdd'.
studyEndDate	A calendar date specifying the maximum date where data is used. Date format is 'yyyymmdd'.

**Details**

Create an object defining the parameter values.

---

```
createGetDbExposureDataArgs
```

*Create a parameter object for the function getDbExposureData*

---

### Description

Create a parameter object for the function getDbExposureData

### Usage

```
createGetDbExposureDataArgs(covariateSettings = NULL)
```

### Arguments

covariateSettings

An object of type covariateSettings as created using the createCovariateSettings function in the FeatureExtraction package. If NULL then no covariate data is retrieved.

### Details

Create an object defining the parameter values.

---

```
createSelectControlsArgs
```

*Create a parameter object for the function selectControls*

---

### Description

Create a parameter object for the function selectControls

### Usage

```
createSelectControlsArgs(firstOutcomeOnly = TRUE, washoutPeriod = 180,
  controlsPerCase = 2, matchOnAge = TRUE, ageCaliper = 2,
  matchOnGender = TRUE, matchOnProvider = FALSE, matchOnCareSite = FALSE,
  matchOnVisitDate = FALSE, visitDateCaliper = 30,
  matchOnTimeInCohort = FALSE, daysInCohortCaliper = 30, minAge = NULL,
  maxAge = NULL, removedUnmatchedCases = TRUE)
```

### Arguments

firstOutcomeOnly

Use the first outcome per person?

washoutPeriod Minimum required numbers of days of observation for inclusion as either case or control.

controlsPerCase

Maximum number of controls to select per case.

matchOnAge

Match on age?



ageCaliper	Maximum difference (in years) in age when matching on age.
matchOnGender	Match on gender?
matchOnProvider	Match on provider (as specified in the person table)?
matchOnCareSite	Match on care site (as specified in the person table)?
matchOnVisitDate	Should the index date of the control be changed to the nearest visitdate?
visitDateCaliper	Maximum difference (in days) between the index date and the visitdate when matching on visit date.
matchOnTimeInCohort	Match on time in nesting cohort? When not using nesting, this is interpreted as time observed prior to index.
daysInCohortCaliper	Maximum difference (in days) in time in cohort.
minAge	Minimum age at which patient time will be included in the analysis. Note that information prior to the min age is still used to determine exposure status after the minimum age (e.g. when a prescription was started just prior to reaching the minimum age). Also, outcomes occurring before the minimum age is reached will be considered as prior outcomes when using first outcomes only. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.
maxAge	Maximum age at which patient time will be included in the analysis. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.
removedUnmatchedCases	Should cases with no matched controls be removed?

## Details

Create an object defining the parameter values.

---

fitCaseControlModel	<i>Fit the case-control model</i>
---------------------	-----------------------------------

---

## Description

Fit the case-control model

## Usage

```
fitCaseControlModel(caseControlData, useCovariates = FALSE,
  excludeCovariateIds = c(), includeCovariateIds = c(),
  caseControlsExposure = NULL, prior = createPrior("laplace",
  useCrossValidation = TRUE), control = createControl(cvType = "auto",
  startingVariance = 0.01, tolerance = 2e-07, cvRepetitions = 10, selectorType =
  "byPid", noiseLevel = "quiet"))
```

**Arguments**

- `caseControlData`      A data frame as generated by the [createCaseControlData](#) function.
- `useCovariates`      Whether to use the covariates in the caseControlsExposure.
- `excludeCovariateIds`      Exclude these covariates from the model.
- `includeCovariateIds`      Include only these covariates in the model.
- `caseControlsExposure`      An object of type caseControlsExposure as created using the [getDbExposureData](#) function.
- `prior`      The prior used to fit the model. See [createPrior](#) for details.
- `control`      The control object used to control the cross-validation used to determine the hyperparameters of the prior (if applicable). See [createControl](#) for details.

**Details**

Fits the model using a conditional logistic regression.

**Value**

An object of type outcomeModel.

---

<code>getAttritionTable</code>	<i>Get the attrition table for a population</i>
--------------------------------	---

---

**Description**

Get the attrition table for a population

**Usage**

```
getAttritionTable(caseControls)
```

**Arguments**

- `caseControls`      A data frame of cases and controls as generated by the function [selectControls](#).

**Value**

A data frame specifying the number of cases and events after various steps of filtering.

---

getDbCaseData	<i>Load case data from the database</i>
---------------	---

---

## Description

Load all data about the cases and nesting cohort from the database.

## Usage

```
getDbCaseData(connectionDetails, cdmDatabaseSchema,
  oracleTempSchema = cdmDatabaseSchema,
  outcomeDatabaseSchema = cdmDatabaseSchema, outcomeTable = "condition_era",
  outcomeIds = c(), useNestingCohort = FALSE,
  nestingCohortDatabaseSchema = cdmDatabaseSchema,
  nestingCohortTable = "cohort", nestingCohortId = NULL,
  useObservationEndAsNestingEndDate = TRUE, getVisits = TRUE,
  getExposures = FALSE, exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era", exposureIds = c(), studyStartDate = "",
  studyEndDate = "")
```

## Arguments

connectionDetails	An R object of type ConnectionDetails created using the function createConnectionDetails in the DatabaseConnector package.
cdmDatabaseSchema	The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.
oracleTempSchema	A schema where temp tables can be created in Oracle.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If outcomeTable = CONDITION_ERA, outcomeDatabaseSchema is not used. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable is not CONDITION_OCCURRENCE or CONDITION_ERA, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
outcomeIds	A list of ids used to define outcomes. If outcomeTable = CONDITION_OCCURRENCE, the list is a set of ancestor CONCEPT_IDs, and all occurrences of all descendant concepts will be selected. If outcomeTable <> CONDITION_OCCURRENCE, the list contains records found in COHORT_DEFINITION_ID field.
useNestingCohort	Should the study be nested in a cohort (e.g. people with a specific indication)? If not, the study will be nested in the general population.
nestingCohortDatabaseSchema	The name of the database schema that is the location where the nesting cohort is defined.

nestingCohortTable	Name of the table holding the nesting cohort. This table should have the same structure as the cohort table.
nestingCohortId	A cohort definition ID identifying the records in the nestingCohortTable to use as nesting cohort.
useObservationEndAsNestingEndDate	When using a nesting cohort, should the observation period end date be used instead of the cohort end date?
getVisits	Get data on visits? This is needed when matching on visit date is requested later on.
getExposures	Should data on exposures be fetched? All exposure information for the nesting cohort will be retrieved, which may be time-consuming. Usually it is more efficient to fetch exposure data only for the cases and controls, as can be done using the <a href="#">getDbExposureData</a> function.
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used but assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
exposureIds	A list of identifiers to define the exposures of interest. If exposureTable = DRUG_ERA, exposureIds should be CONCEPT_ID. If exposureTable <> DRUG_ERA, exposureIds is used to select the cohort_concept_id in the cohort-like table. If no exposureIds are provided, all drugs or cohorts in the exposureTable are included as exposures.
studyStartDate	A calendar date specifying the minimum date where data is used. Date format is 'yyyymmdd'.
studyEndDate	A calendar date specifying the maximum date where data is used. Date format is 'yyyymmdd'.

### Value

Returns an object of type caseData, containing information on the cases, the nesting cohort, and optionally visits. Information about multiple outcomes can be captured at once for efficiency reasons. The generic summary() function has been implemented for this object.

---

getDbExposureData	<i>Get exposure data for cases and controls from a database</i>
-------------------	---

---

### Description

Get exposure data for cases and controls from a database

**Usage**

```
getDbExposureData(caseControls, connectionDetails, oracleTempSchema = NULL,
  exposureDatabaseSchema, exposureTable = "drug_era", exposureIds = c(),
  cdmDatabaseSchema = exposureDatabaseSchema, covariateSettings = NULL,
  caseData = NULL)
```

**Arguments**

- caseControls** A data frame as generated by the [selectControls](#) function.
- connectionDetails** An R object of type `connectionDetails` created using the function `createConnectionDetails` in the `DatabaseConnector` package.
- oracleTempSchema** A schema where temp tables can be created in Oracle.
- exposureDatabaseSchema** The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If `exposureTable = DRUG_ERA`, `exposureDatabaseSchema` is not used but assumed to be `cdmSchema`. Requires read permissions to this database.
- exposureTable** The tablename that contains the exposure cohorts. If `exposureTable <> drug_era`, then expectation is `exposureTable` has format of COHORT table: `cohort_definition_id`, `subject_id`, `cohort_start_date`, `cohort_end_date`.
- exposureIds** A list of identifiers to define the exposures of interest. If `exposureTable = drug_era`, `exposureIds` should be `concept_id`. If `exposureTable <> drug_era`, `exposureIds` is used to select the `cohort_definition_id` in the cohort-like table. If no `exposureIds` are provided, all drugs or cohorts in the `exposureTable` are included as exposures.
- cdmDatabaseSchema** Needed when constructing covariates: the name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example `'cdm_instance.dbo'`.
- covariateSettings** An object of type `covariateSettings` as created using the `createCovariateSettings` function in the `FeatureExtraction` package. If `NULL` then no covariate data is retrieved.
- caseData** An object of type `caseData` as generated using the [getDbCaseData](#) function. If `caseData` is provided and contains the exposure data (see `getExposures` in the [getDbCaseData](#) function, and if no covariates need to be constructed (`covariateSettings = NULL`), then the no connection to the database is used to create the exposure data. This may be much more efficient in some situations.

---

<code>insertDbPopulation</code>	<i>Insert cases and controls into a database</i>
---------------------------------	--

---

**Description**

Insert cases and controls into a database

**Usage**

```
insertDbPopulation(caseControls, cohortIds = c(1, 0), connectionDetails,
  cohortDatabaseSchema, cohortTable = "cohort", createTable = FALSE,
  dropTableIfExists = TRUE)
```

**Arguments**

caseControls	A data frame as generated by the <a href="#">selectControls</a> function.
cohortIds	The IDs to be used for the cohorts of cases and controls, respectively.
connectionDetails	An R object of type <code>connectionDetails</code> created using the function <code>createConnectionDetails</code> in the <code>DatabaseConnector</code> package.
cohortDatabaseSchema	The name of the database schema where the data will be written. Requires write permissions to this database. On SQL Server, this should specify both the database and the schema, so for example <code>'cdm_instance.dbo'</code> .
cohortTable	The name of the table in the database schema where the data will be written.
createTable	Should a new table be created? If not, the data will be inserted into an existing table.
dropTableIfExists	If <code>createTable = TRUE</code> and the table already exists it will be overwritten.

**Details**

Inserts cases and controls into a database. The table in the database will have the same structure as the 'cohort' table in the Common Data Model.

---

loadCaseControlsExposure

*Load the caseControlsExposure data from a folder*

---

**Description**

loadCaseControlsExposure loads an object of type `caseControlsExposure` from a folder in the file system.

**Usage**

```
loadCaseControlsExposure(folder, readOnly = TRUE)
```

**Arguments**

folder	The name of the folder containing the data.
readOnly	If true, the data is opened read only.

**Details**

The data will be written to a set of files in the folder specified by the user.

**Value**

An object of class caseControlsExposure.

---

loadCaseData	<i>Load the case data from a folder</i>
--------------	---

---

**Description**

loadCaseData loads an object of type caseData from a folder in the file system.

**Usage**

```
loadCaseData(folder, readOnly = TRUE)
```

**Arguments**

folder	The name of the folder containing the data.
readOnly	If true, the data is opened read only.

**Details**

The data will be written to a set of files in the folder specified by the user.

**Value**

An object of class caseData.

---

loadCcAnalysisList	<i>Load a list of ccAnalysis from file</i>
--------------------	--

---

**Description**

Load a list of objects of type ccAnalysis from file. The file is in JSON format.

**Usage**

```
loadCcAnalysisList(file)
```

**Arguments**

file	The name of the file
------	----------------------

**Value**

A list of objects of type ccAnalysis.

---

```
loadExposureOutcomeNestingCohortList
```

*Load a list of exposureOutcomeNestingCohort from file*

---

### Description

Load a list of objects of type exposureOutcomeNestingCohort from file. The file is in JSON format.

### Usage

```
loadExposureOutcomeNestingCohortList(file)
```

### Arguments

file	The name of the file
------	----------------------

### Value

A list of objects of type drugComparatorOutcome.

---

```
runCcAnalyses
```

*Run a list of analyses*

---

### Description

Run a list of analyses

### Usage

```
runCcAnalyses(connectionDetails, cdmDatabaseSchema,
  oracleTempSchema = cdmDatabaseSchema,
  exposureDatabaseSchema = cdmDatabaseSchema, exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema, outcomeTable = "condition_era",
  nestingCohortDatabaseSchema = cdmDatabaseSchema,
  nestingCohortTable = "condition_era", outputFolder = "./CcOutput",
  ccAnalysisList, exposureOutcomeNestingCohortList,
  prefetchExposureData = FALSE, getDbCaseDataThreads = 1,
  selectControlsThreads = 1, getDbExposureDataThreads = 1,
  createCaseControlDataThreads = 1, fitCaseControlModelThreads = 1,
  cvThreads = 1)
```

### Arguments

connectionDetails

An R object of type ConnectionDetails created using the function createConnectionDetails in the DatabaseConnector package.



cdmDatabaseSchema	The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm_instance.dbo'.
oracleTempSchema	A schema where temp tables can be created in Oracle.
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used but assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> drug_era, then expectation is exposureTable has format of COHORT table: cohort_definition_id, subject_id, cohort_start_date, cohort_end_date.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If outcomeTable = CONDITION_ERA, outcomeDatabaseSchema is not used. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable is not CONDITION_OCCURRENCE or CONDITION_ERA, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
nestingCohortDatabaseSchema	The name of the database schema that is the location where the nesting cohort is defined.
nestingCohortTable	Name of the table holding the nesting cohort. This table should have the same structure as the cohort table.
outputFolder	Name of the folder where all the outputs will be written to.
ccAnalysisList	A list of objects of type ccAnalysis as created using the <a href="#">createCcAnalysis</a> function.
exposureOutcomeNestingCohortList	A list of objects of type exposureOutcomeNestingCohort as created using the <a href="#">createExposureOutcomeNestingCohort</a> function.
prefetchExposureData	Should exposure data for the entire nesting cohort be fetched at the beginning, or should exposure data be fetched later specifically for a set of cases and controls. Prefetching can be faster when there are many outcomes but only few exposures. Prefetching does not speed up performance when covariates also need to be constructed.
getDbCaseDataThreads	The number of parallel threads to use for building the caseData objects.
selectControlsThreads	The number of parallel threads to use for selecting controls.
getDbExposureDataThreads	The number of parallel threads to use for fetching data on exposures for cases and controls.
createCaseControlDataThreads	The number of parallel threads to use for creating case and control data including exposure status indicators

fitCaseControlModelThreads

The number of parallel threads to use for fitting the models.

cvThreads

The number of parallel threads used for the cross-validation to determine the hyper-parameter when fitting the model.

## Details

Run a list of analyses for the exposure-outcome-nesting cohorts of interest. This function will run all specified analyses against all hypotheses of interest, meaning that the total number of outcome models is 'length(ccAnalysisList) \* length(exposureOutcomeNestingCohortList)' (if all analyses specify an outcome model should be fitted). When you provide several analyses it will determine whether any of the analyses have anything in common, and will take advantage of this fact. For example, if we specify several analyses that only differ in the way the outcome model is fitted, then this function will extract the data and fit the propensity model only once, and re-use this in all the analysis.

## Value

A data frame with the following columns:

analysisId	The unique identifier for a set of analysis choices.
exposureId	The ID of the target drug.
outcomeId	The ID of the outcome.
ccDataFolder	The folder where the ccData object is stored.
ccEraDataFolder	The folder where the ccEraData object is stored.
ccModelFile	The file where the fitted SCCS model is stored.

---

saveCaseControlsExposure

*Save the caseControlsExposure data to folder*

---

## Description

saveCaseControlsExposure saves an object of type caseControlsExposure to folder.

## Usage

```
saveCaseControlsExposure(caseControlsExposure, folder)
```

## Arguments

caseControlsExposure

An object of type caseControlsExposure as generated using [getDbExposureData](#).

folder

The name of the folder where the data will be written. The folder should not yet exist.

## Details

The data will be written to a set of files in the specified folder.

---

saveCaseData	<i>Save the case data to folder</i>
--------------	-------------------------------------

---

### Description

saveCaseData saves an object of type caseData to folder.

### Usage

```
saveCaseData(caseData, folder)
```

### Arguments

caseData	An object of type caseData as generated using <a href="#">getDbCaseData</a> .
folder	The name of the folder where the data will be written. The folder should not yet exist.

### Details

The data will be written to a set of files in the specified folder.

---

saveCcAnalysisList	<i>Save a list of ccAnalysis to file</i>
--------------------	--

---

### Description

Write a list of objects of type ccAnalysis to file. The file is in JSON format.

### Usage

```
saveCcAnalysisList(ccAnalysisList, file)
```

### Arguments

ccAnalysisList	The ccAnalysis list to be written to file
file	The name of the file where the results will be written

---

```
saveExposureOutcomeNestingCohortList
    Save a list of drugComparatorOutcome to file
```

---

### Description

Write a list of objects of type exposureOutcomeNestingCohort to file. The file is in JSON format.

### Usage

```
saveExposureOutcomeNestingCohortList(exposureOutcomeNestingCohortList, file)
```

### Arguments

exposureOutcomeNestingCohortList	The exposureOutcomeNestingCohort list to be written to file
file	The name of the file where the results will be written

---

```
selectControls    Select matched controls per case
```

---

### Description

Select matched controls per case

### Usage

```
selectControls(caseData, outcomeId, firstOutcomeOnly = TRUE,
  washoutPeriod = 180, controlsPerCase = 2, matchOnAge = TRUE,
  ageCaliper = 2, matchOnGender = TRUE, matchOnProvider = FALSE,
  matchOnCareSite = FALSE, matchOnVisitDate = FALSE,
  visitDateCaliper = 30, matchOnTimeInCohort = FALSE,
  daysInCohortCaliper = 30, minAge = NULL, maxAge = NULL,
  removedUnmatchedCases = TRUE)
```

### Arguments

caseData	An object of type caseData as generated using the <a href="#">getDbCaseData</a> function.
outcomeId	The outcome ID of the cases for which we need to pick controls.
firstOutcomeOnly	Use the first outcome per person?
washoutPeriod	Minimum required numbers of days of observation for inclusion as either case or control.
controlsPerCase	Maximum number of controls to select per case.
matchOnAge	Match on age?
ageCaliper	Maximum difference (in years) in age when matching on age.

matchOnGender	Match on gender?
matchOnProvider	Match on provider (as specified in the person table)?
matchOnCareSite	Match on care site (as specified in the person table)?
matchOnVisitDate	Should the index date of the control be changed to the nearest visit date?
visitDateCaliper	Maximum difference (in days) between the index date and the visit date when matching on visit date.
matchOnTimeInCohort	Match on time in nesting cohort? When not using nesting, this is interpreted as time observed prior to index.
daysInCohortCaliper	Maximum difference (in days) in time in cohort.
minAge	Minimum age at which patient time will be included in the analysis. Note that information prior to the min age is still used to determine exposure status after the minimum age (e.g. when a prescription was started just prior to reaching the minimum age). Also, outcomes occurring before the minimum age is reached will be considered as prior outcomes when using first outcomes only. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.
maxAge	Maximum age at which patient time will be included in the analysis. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.
removedUnmatchedCases	Should cases with no matched controls be removed?

## Details

Select controls per case. Controls are matched on calendar time and the criteria defined in the arguments. Controls are randomly sampled to the required number.

## Value

A data frame with these columns:

**personId** The person ID

**indexDate** The index date

**isCase** Is the person a case or a control?

**stratumId** The ID linking cases and controls in a matched set

---

summarizeCcAnalyses	<i>Create a summary report of the analyses</i>
---------------------	--

---

## Description

Create a summary report of the analyses

## Usage

```
summarizeCcAnalyses(outcomeReference)
```

## Arguments

outcomeReference

A data.frame as created by the [runCcAnalyses](#) function.

## Value

A data frame with the following columns:

analysisId	The unique identifier for a set of analysis choices.
targetId	The ID of the target drug.
comparatorId	The ID of the comparator group.
indicationConceptIds	The ID(s) of indications in which to nest to study.
outcomeId	The ID of the outcome.
rr	The estimated effect size.
ci95lb	The lower bound of the 95 percent confidence interval.
ci95ub	The upper bound of the 95 percent confidence interval.
treated	The number of subjects in the treated group (after any trimming and matching).
comparator	The number of subjects in the comparator group (after any trimming and matching).
eventsTreated	The number of outcomes in the treated group (after any trimming and matching).
eventsComparator	The number of outcomes in the comparator group (after any trimming and matching).
logRr	The log of the estimated relative risk.
seLogRr	The standard error of the log of the estimated relative risk.

# Index

CaseControl, [2](#)  
CaseControl-package (CaseControl), [2](#)  
computeMdr, [2](#)  
createCaseControlData, [3](#), [3](#), [10](#)  
createCcAnalysis, [4](#), [6](#), [17](#)  
createControl, [10](#)  
createCreateCaseControlDataArgs, [5](#), [5](#)  
createExposureOutcomeNestingCohort, [6](#),  
[17](#)  
createFitCaseControlModelArgs, [5](#), [6](#)  
createGetDbCaseDataArgs, [4](#), [7](#)  
createGetDbExposureDataArgs, [5](#), [8](#)  
createPrior, [10](#)  
createSelectControlsArgs, [4](#), [8](#)  
  
fitCaseControlModel, [9](#)  
  
getAttritionTable, [10](#)  
getDbCaseData, [11](#), [13](#), [19](#), [20](#)  
getDbExposureData, [3](#), [10](#), [12](#), [12](#), [18](#)  
  
insertDbPopulation, [13](#)  
  
loadCaseControlsExposure, [14](#)  
loadCaseData, [15](#)  
loadCcAnalysisList, [15](#)  
loadExposureOutcomeNestingCohortList,  
[16](#)  
  
runCcAnalyses, [5](#), [6](#), [16](#), [22](#)  
  
saveCaseControlsExposure, [18](#)  
saveCaseData, [19](#)  
saveCcAnalysisList, [19](#)  
saveExposureOutcomeNestingCohortList,  
[20](#)  
selectControls, [10](#), [13](#), [14](#), [20](#)  
summarizeCcAnalyses, [22](#)