

Package ‘CohortPrevalence’

December 12, 2025

Title Standardized Prevalence Calculator for OMOP/OHDSI Ecosystem

Version 0.0.2

Description This package calculates prevalence of a condition in a population.

License Apache License

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Imports cli,
crayon,
fs,
purrr,
SqlRender,
snakecase,
DatabaseConnector,
dplyr,
glue,
readr,
tibble,
tidyr,
here,
methods

Additional_repositories <https://OHDSI.github.io/drat>

Suggests knitr,
rmarkdown

VignetteBuilder knitr

R topics documented:

createCohortPrevalenceAnalysis	2
createDenominatorType	3
createLookBackOptions	4
createPopulationCohort	4
createPrevalenceCohort	5
createSpanPrevalence	5
createYearlyPrevalence	6
exportPrevalenceQuery	6

exportPrevalenceResults	7
generateMultiplePrevalence	7
generateSinglePrevalence	8

Index	9
--------------	----------

createCohortPrevalenceAnalysis

Create a CohortPrevalenceAnalysis object

Description

Constructs an CohortPrevalenceAnalysis object with the specified settings.

Usage

```
createCohortPrevalenceAnalysis(
  analysisId,
  prevalentCohort,
  periodOfInterest,
  lookBackOptions,
  numeratorType,
  denominatorType,
  minimumObservationLength = 0L,
  useOnlyFirstObservationPeriod = FALSE,
  multiplier = 100000L,
  strata = NULL,
  populationCohort = NULL
)
```

Arguments

analysisId	Unique integer analysisId to identify the analysis (required).
prevalentCohort	A PrevalenceCohort object specifying the cohort of interest (required).
periodOfInterest	A PeriodOfInterest object (required).
numeratorType	Character string specifying numerator type. Must be one of: <ul style="list-style-type: none"> "pn1": Patients who have been observed to have the condition of interest on the first day of the period of interest or within the lookback time "pn2": patients who have been observed to have the condition of interest at any time in the period of interest or within the lookback time
denominatorType	A DenominatorType object (required).
useOnlyFirstObservationPeriod	Logical: TRUE to restrict analysis to the first observation period (optional).
multiplier	Integer specifying prevalence multiplier (optional).
strata	Character string. Must be one, or some of: "age", "gender", "race" (optional).

populationCohort	A CohortPopulation object specifying the population of interest on which to compute prevalence.
lookBackDays	Integer used for specifying length of lookback (required).
minimumObservationLength:	Integer specifying minimum observation length (optional).
lookbackOptions	A LookBackOption object (required).

Value

A CohortPrevalenceAnalysis R6 object.

createDenominatorType *Create a DenominatorType object*

Description

Constructs an DenominatorType object for denominator choice.

Usage

```
createDenominatorType(denomType, sufficientDays = NULL)
```

Arguments

denomType	Character string specifying denominator type. Must be one of: <ul style="list-style-type: none"> "pd1": Patients who have been observed on the first day of the period of interest "pd2": Patients who contribute all observable person-days in the period of interest. "pd3": Patients who contribute at least 1 day in the period of interest. "pd4": Patients who contribute sufficient time in the period of interest based on at least n observable person-days in the period of interest.
sufficientDays	Integer: For denominator choice "pd4", the number of minimum observable days patients must be observed.

Value

A DenominatorType R6 object.

`createLookBackOptions` *Create a LookBackOptions object*

Description

Constructs an LookBackOptions object with the specified settings.

Usage

```
createLookBackOptions(lookBackDays = 99999L, useObservedTimeOnly = FALSE)
```

Arguments

`lookBackDays` An integer number of days for the lookback period.

`useObservedTimeOnly`

Logical: TRUE restricts the lookback period to only using observed periods.

Value

A LookBackOptions R6 object.

`createPopulationCohort`

Create a population cohort CohortInfo object

Description

Constructs an CohortInfo object for population of interest.

Usage

```
createPopulationCohort(cohortId, cohortName)
```

Arguments

`cohortId` Integer: the cohort ID within the database results schema of interest.

`cohortName` Character string specifying a name for the cohort.

Value

A CohortInfo R6 object.

`createPrevalenceCohort`*Create a prevalence cohort CohortInfo object*

Description

Constructs an CohortInfo object for target cohort of interest

Usage

```
createPrevalenceCohort(cohortId, cohortName)
```

Arguments

<code>cohortId</code>	Integer: the cohort ID within the database results schema of interest.
<code>cohortName</code>	Character string specifying a name for the cohort.

Value

A CohortInfo R6 object.

`createSpanPrevalence` *Create a PeriodOfInterest object*

Description

Constructs an PeriodOfInterest object for span prevalence analyses.

Usage

```
createSpanPrevalence(startDates, endDates)
```

Arguments

<code>startYears</code>	A numeric vector of start years of interest.
<code>endYears</code>	A numeric vector of end years of interest.

Value

A PeriodOfInterest R6 object.

```
createYearlyPrevalence
```

Create a PeriodOfInterest object

Description

Constructs an `PeriodOfInterest` object for yearly prevalence analyses.

Usage

```
createYearlyPrevalence(range)
```

Arguments

`range` A numeric vector of years of interest.

Value

A `PeriodOfInterest` R6 object.

```
exportPrevalenceQuery    Export Prevalence Query
```

Description

Exports the full SQL query of a `CohortPrevalenceAnalysis` analysis.

Usage

```
exportPrevalenceQuery(
  prevalenceAnalysisClass,
  executionSettings,
  outputFolder = NULL
)
```

Arguments

`prevalenceAnalysisClass` A `CohortPrevalenceAnalysis` R6 object with analysis settings (required).

`outputFolder` Character string specifying the path to the folder where the output files will be saved. If left `NULL`, will default to current working directory (optional).

`exportPrevalenceResults`*Export Prevalence Query*

Description

Saves the results of a CohortPrevalenceAnalysis analysis as a .csv.

Usage

```
exportPrevalenceResults(results, outputFolder = NULL)
```

Arguments

<code>results</code>	Dataframe: Result of a generateSinglePrevalence analysis.
<code>outputFolder</code>	Character string specifying the path to the folder where the output files will be saved. If left NULL, will default to current working directory (optional).

`generateMultiplePrevalence`*Run Multiple Prevalence Analyses*

Description

Runs multiple prevalence analysis with a list of specified CohortPrevalenceAnalysis settings

Usage

```
generateMultiplePrevalence(prevalenceAnalysisList, executionSettings)
```

Arguments

<code>prevalenceAnalysisList</code>	A list CohortPrevalenceAnalysis R6 object with analysis settings.
<code>executionSettings</code>	An executionSettings R6 object with connection and schema details.

Value

A results dataframe with prevalence rates and strata per analysis id.

`generateSinglePrevalence`*Run Single Prevalence Analysis*

Description

Runs a single prevalence analysis with specified CohortPrevalenceAnalysis settings

Usage

```
generateSinglePrevalence(prevalenceAnalysisClass, executionSettings)
```

Arguments

`prevalenceAnalysisClass`

A CohortPrevalenceAnalysis R6 object with analysis settings.

`executionSettings`

An executionSettings R6 object with connection and schema details.

Value

A results dataframe with prevalence rates and strata.

Index

`createCohortPrevalenceAnalysis`, [2](#)
`createDenominatorType`, [3](#)
`createLookBackOptions`, [4](#)
`createPopulationCohort`, [4](#)
`createPrevalenceCohort`, [5](#)
`createSpanPrevalence`, [5](#)
`createYearlyPrevalence`, [6](#)

`exportPrevalenceQuery`, [6](#)
`exportPrevalenceResults`, [7](#)

`generateMultiplePrevalence`, [7](#)
`generateSinglePrevalence`, [8](#)