

Package ‘ConceptSetDiagnostics’

July 21, 2022

Type Package

Title Concept Set Diagnostics

Version 0.0.1

Author Gowtham Rao [aut, cre]

Date 2022-07-21

Maintainer Gowtham Rao <rao@ohdsi.org>

Description A package to work with OMOP concepts and cohort concept sets.

Depends DatabaseConnector (>= 5.0.0),
dplyr,
R (>= 4.0.0)

Imports checkmate,
CirceR,
purrr,
RJSONIO,
rlang,
scales,
SqlRender,
stringr,
stringdist,
tidyr

Suggests readr,
remotes,
rmarkdown,
knitr,
testthat,
withr

Remotes ohdsi/CirceR,
ohdsi/SqlRender

License Apache License (>= 2)

RoxygenNote 7.2.0

Encoding UTF-8

Language en-US

R topics documented:

convertConceptSetDataFrameToExpression	2
convertConceptSetExpressionToDataFrame	3
extractConceptSetsInCohortDefinition	4
extractConceptSetsInCohortDefinitionSet	5
findOrphanConcepts	5
getConceptAncestor	6
getConceptDescendant	7
getConceptIdDetails	8
getConceptPrevalenceCounts	8
getConceptRelationship	9
getConceptSynonym	10
getDomain	11
getDrugIngredients	11
getExcludedConceptsInConceptSetExpression	12
getMappedSourceConcepts	13
getMappedStandardConcepts	14
getMedraRelationship	15
getRecommendedSource	15
getRecommendedStandard	16
getRelationship	17
getVocabulary	18
getVocabularyVersion	18
mapMedraToSnomedViaVocabulary	19
optimizeConceptSetExpression	20
performStringSearchForConcepts	21
resolveConceptSetExpression	21
resolveConceptSetsInCohortExpression	22
Index	24

convertConceptSetDataFrameToExpression

Convert concept set expression in a data frame format convert to R (list) expression

Description

Convert concept set expression in a data frame format convert to R (list) expression

Usage

```
convertConceptSetDataFrameToExpression(
  conceptSetExpressionDataFrame,
  selectAllDescendants = FALSE,
  updateVocabularyFields = FALSE,
  connectionDetails = NULL,
  connection = NULL,
  vocabularyDatabaseSchema = NULL
)
```

Arguments

- `conceptSetExpressionDataFrame`
Concept set expression in data frame format with required fields `conceptId`. If `includeMapped`, `isExcluded` or `includeDescendants` are missing value or is not existent - it is assumed to be FALSE. All column names should be in camelCase format.
- `selectAllDescendants`
Do you want to over ride the concept set expression by add select descendants for concept ids in concept set expression.
- `updateVocabularyFields`
Do you want to update the details about concepts from the vocabulary tables such as domain, vocabulary, concept name? If yes, then connection or connectionDetails to a remote db with OMOP vocabulary tables is needed.
- `connectionDetails`
An object of type `connectionDetails` as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.
- `connection`
An object of type `connection` as created using the [connect](#) function in the DatabaseConnector package. Can be left NULL if `connectionDetails` is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
- `vocabularyDatabaseSchema`
The schema name of containing the vocabulary tables.

Value

Returns a R list object

```
convertConceptSetExpressionToDataFrame
```

convert a concept set expression R list object into a data frame object

Description

convert a concept set expression R list object into a data frame object

Usage

```
convertConceptSetExpressionToDataFrame(  
  conceptSetExpression,  
  updateVocabularyFields = FALSE,  
  connection = NULL,  
  connectionDetails = NULL,  
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),  
  vocabularyDatabaseSchema = NULL  
)
```

Arguments

- conceptSetExpression**
An R-object (list) with expression of the concept set.
- updateVocabularyFields**
Do you want to update the details about concepts from the vocabulary tables such as domain, vocabulary, concept name? If yes, then connection or connectionDetails to a remote db with OMOP vocabulary tables is needed.
- connection**
An object of type connection as created using the [connect](#) function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
- connectionDetails**
An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.
- tempEmulationSchema**
Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
- vocabularyDatabaseSchema**
The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

extractConceptSetsInCohortDefinition
Extract concept set expressions from cohort definition expression.

Description

Given a cohort expression, this function extracts the concept set expressions from cohort definition expression.

Usage

```
extractConceptSetsInCohortDefinition(cohortExpression)
```

Arguments

- cohortExpression**
A R-object (list) that represents cohort definition expression. This is derived from cohort expression json using `RJSONIO::fromJSON(content = json, digits = 23)`. Note: it is important to use `digits = 23`, otherwise numerical precision may be lost for large integer values like conceptId's in cohort definition. The cohort expression JSON is commonly generated using OHDSI tools like Atlas or CapR.

Value

Returns a tibble data frame.

```
extractConceptSetsInCohortDefinitionSet
```

Extract concept sets from cohort definition set

Description

given a cohort definition set (data frame with cohortId, json), this function extracts the concept set json and sql for all cohorts, compares concept sets across cohort definitions, assigns unique id.

Usage

```
extractConceptSetsInCohortDefinitionSet(cohortDefinitionSet)
```

Arguments

cohortDefinitionSet

The cohortDefinitionSet argument must be a data frame with at least the following columns.

cohortId The cohort Id is the id used to identify a cohort definition. This is required to be unique. It is usually used to create file names.

cohortName The full name of the cohort.

json The JSON cohort definition for the cohort.

sql The SQL of the cohort definition rendered from the cohort json.

Value

Returns a tibble data frame.

```
findOrphanConcepts
```

Get all the domain id(s) in the vocabulary schema.

Description

Get all the domain id(s) in the vocabulary schema.

Usage

```
findOrphanConcepts(
  connectionDetails = NULL,
  connection = NULL,
  cdmDatabaseSchema,
  vocabularyDatabaseSchema = cdmDatabaseSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  conceptIds
)
```

Arguments

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
cdmDatabaseSchema	Schema name where your patient-level data in OMOP CDM format resides. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
conceptIds	an array of conceptIds that are used as reference to search for orphan concepts

Value

Returns a tibble data frame.

getConceptAncestor	<i>get concept ancestor</i>
--------------------	-----------------------------

Description

given an array of conceptIds, get their ancestor and descendants.

Usage

```
getConceptAncestor(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getConceptDescendant	<i>get concept descendant</i>
----------------------	-------------------------------

Description

given an array of conceptIds, get their descendants.

Usage

```
getConceptDescendant(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getConceptIdDetails *get concept id details*

Description

given an array of conceptIds, get their details

Usage

```
getConceptIdDetails(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary",
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

Value

Returns a tibble data frame.

getConceptPrevalenceCounts
 get concept id count

Description

Get the count for an array of concept id(s) from concept prevalence table.

Usage

```

getConceptPrevalenceCounts(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  conceptPrevalenceSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)

```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
conceptPrevalenceSchema	The schema name that has the concept prevalence table. The following tables are expected to be present. recommender_set, cp_master, recommended_blacklist.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

Value

Returns a tibble data frame.

```
getConceptRelationship
```

given a list of conceptIds, get their relationship

Description

given a list of conceptIds, get their relationship

Usage

```

getConceptRelationship(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)

```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getConceptSynonym	<i>given a list of conceptIds, get their synonyms</i>
-------------------	---

Description

given a list of conceptIds, get their synonyms

Usage

```
getConceptSynonym(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

getDomain

Get all the domain id(s) in the vocabulary schema.

Description

Get all the domain id(s) in the vocabulary schema.

Usage

```
getDomain(
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

connection An object of type connection as created using the [connect](#) function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

connectionDetails An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

vocabularyDatabaseSchema The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getDrugIngredients

Get ingredient information

Description

Given an array of drug concept ids, returns their ingredients

Usage

```
getDrugIngredients(
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  conceptIds,
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

- | | |
|--------------------------|--|
| connection | An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes. |
| connectionDetails | An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided. |
| tempEmulationSchema | Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created. |
| conceptIds | An array of concept ids to find ingredients for |
| vocabularyDatabaseSchema | The schema name of containing the vocabulary tables. |

Value

Returns a tibble data frame.

getExcludedConceptsInConceptSetExpression

Given a concept set expression, get the resolved concepts

Description

Given a concept set expression, get the resolved concepts

Usage

```
getExcludedConceptsInConceptSetExpression(
  conceptSetExpression,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptSetExpression	An R-object (list) with expression of the concept set.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getMappedSourceConcepts

given a list of conceptIds, get their mapped

Description

Given a concept set expression, get the resolved concepts

Usage

```
getMappedSourceConcepts(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getMappedStandardConcepts

given a list of conceptIds, get their mapped

Description

given a list of conceptIds, get their mapped

Usage

```
getMappedStandardConcepts(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

getMedraRelationship *get MedDRA relationship*

Description

given an array of conceptIds belonging to MedDRA vocabulary get its full MedDRA relationship

Usage

```
getMedraRelationship(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a a list of tibble data frames conceptId, socConceptId, socConceptName, HLTConceptId, HltConceptName, HlgtConceptId, hlgtConceptName, ptConceptId, ptConceptName, lltConceptId, lltConceptName

getRecommendedSource *given a list of non standard conceptIds, get recommended conceptIds*

Description

given a list of non standard conceptIds, get recommended conceptIds

Usage

```
getRecommendedSource(
  conceptIds,
  vocabularyDatabaseSchema = "vocabulary",
  connection = NULL,
  connectionDetails = NULL,
  conceptPrevalenceSchema = "concept_prevalence",
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)
```

Arguments

conceptIds	An array of Concept ids.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
conceptPrevalenceSchema	The schema name that has the concept prevalence table. The following tables are expected to be present. recommender_set, cp_master, recommended_blacklist.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

```
getRecommendedStandard
```

given a list of standard conceptIds, get recommended concepts.

Description

given a list of standard conceptIds, get recommended concepts.

Usage

```
getRecommendedStandard(
  conceptIds,
  vocabularyDatabaseSchema,
  connection = NULL,
  connectionDetails = NULL,
  conceptPrevalenceSchema = "concept_prevalence",
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)
```


Arguments

conceptIds	An array of Concept ids.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
conceptPrevalenceSchema	The schema name that has the concept prevalence table. The following tables are expected to be present. recommender_set, cp_master, recommended_blacklist.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

getRelationship	<i>get all relationship id from vocabulary tables in vocabulary schema.</i>
-----------------	---

Description

get all relationship id from vocabulary tables in vocabulary schema.

Usage

```
getRelationship(
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

getVocabulary	<i>Get vocabulary id(s) in vocabulary tables in vocabulary schema.</i>
---------------	--

Description

Get vocabulary id(s) in vocabulary tables in vocabulary schema.

Usage

```
getVocabulary(  
    connection = NULL,  
    connectionDetails = NULL,  
    vocabularyDatabaseSchema = "vocabulary"  
)
```

Arguments

connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

getVocabularyVersion	<i>Get vocabulary version.</i>
----------------------	--------------------------------

Description

Get vocabulary version.

Usage

```
getVocabularyVersion(  
    connection = NULL,  
    connectionDetails = NULL,  
    vocabularyDatabaseSchema = "vocabulary"  
)
```

Arguments

connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

```
mapMedraToSnomedViaVocabulary
      map MedDRA to SNOMED
```

Description

given an array of conceptIds belonging to MedDRA vocabulary get its equivalent SNOMED ranked using a combination of OMOP vocabulary mapping, lexical string matching and concept prevalence counts

Usage

```
mapMedraToSnomedViaVocabulary(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame

`optimizeConceptSetExpression`

given a concept set expression, get optimized concept set expression

Description

given a concept set expression, get optimized concept set expression

Usage

```
optimizeConceptSetExpression(  
  conceptSetExpression,  
  vocabularyDatabaseSchema = "vocabulary",  
  connection = NULL,  
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),  
  connectionDetails = NULL  
)
```

Arguments

`conceptSetExpression`

An R-object (list) with expression of the concept set.

`vocabularyDatabaseSchema`

The schema name of containing the vocabulary tables.

`connection`

An object of type `connection` as created using the [connect](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connectionDetails` is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

`tempEmulationSchema`

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

`connectionDetails`

An object of type `connectionDetails` as created using the [createConnectionDetails](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connection` is provided.

`performStringSearchForConcepts`*Get concepts that match a string search*

Description

Get concepts that match a string search

Usage

```
performStringSearchForConcepts(  
    searchString,  
    vocabularyDatabaseSchema = "vocabulary",  
    connection = NULL,  
    connectionDetails = NULL  
)
```

Arguments

`searchString` A phrase (can be multiple words) to search for.

`vocabularyDatabaseSchema` The schema name of containing the vocabulary tables.

`connection` An object of type `connection` as created using the [connect](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connectionDetails` is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

`connectionDetails` An object of type `connectionDetails` as created using the [createConnectionDetails](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connection` is provided.

`resolveConceptSetExpression`*Given a concept set expression, get the resolved concepts*

Description

Given a concept set expression, get the resolved concepts

Usage

```
resolveConceptSetExpression(  
    conceptSetExpression,  
    connection = NULL,  
    connectionDetails = NULL,  
    vocabularyDatabaseSchema = "vocabulary"  
)
```

Arguments

conceptSetExpression	An R-object (list) with expression of the concept set.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

Value

Returns a tibble data frame.

```
resolveConceptSetsInCohortExpression
```

Given a cohort definition expression, get the resolved concepts for all concept sets

Description

Given a cohort definition expression, get the resolved concepts for all concept sets

Usage

```
resolveConceptSetsInCohortExpression(
  cohortExpression,
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary"
)
```

Arguments

cohortExpression	A R-object (list) that represents cohort definition expression. This is derived from cohort expression json using <code>RJSONIO::fromJSON(content = json, digits = 23)</code> . Note: it is important to use <code>digits = 23</code> , otherwise numerical precision may be lost for large integer values like conceptId's in cohort definition. The cohort expression JSON is commonly generated using OHDSI tools like Atlas or CapR.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

connectionDetails

An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

Index

connect, [3](#), [4](#), [6–22](#)
convertConceptSetDataFrameToExpression,
 [2](#)
convertConceptSetExpressionToDataFrame,
 [3](#)
createConnectionDetails, [3](#), [4](#), [6–23](#)

extractConceptSetsInCohortDefinition,
 [4](#)
extractConceptSetsInCohortDefinitionSet,
 [5](#)

findOrphanConcepts, [5](#)

getConceptAncestor, [6](#)
getConceptDescendant, [7](#)
getConceptIdDetails, [8](#)
getConceptPrevalenceCounts, [8](#)
getConceptRelationship, [9](#)
getConceptSynonym, [10](#)
getDomain, [11](#)
getDrugIngredients, [11](#)
getExcludedConceptsInConceptSetExpression,
 [12](#)
getMappedSourceConcepts, [13](#)
getMappedStandardConcepts, [14](#)
getMedraRelationship, [15](#)
getRecommendedSource, [15](#)
getRecommendedStandard, [16](#)
getRelationship, [17](#)
getVocabulary, [18](#)
getVocabularyVersion, [18](#)

mapMedraToSnomedViaVocabulary, [19](#)

optimizeConceptSetExpression, [20](#)

performStringSearchForConcepts, [21](#)

resolveConceptSetExpression, [21](#)
resolveConceptSetsInCohortExpression,
 [22](#)