

# Package ‘ConceptSetDiagnostics’

July 20, 2022

**Type** Package

**Title** Concept Set Diagnostics

**Version** 0.0.1

**Author** Gowtham Rao [aut, cre]

**Maintainer** Gowtham Rao <rao@ohdsi.org>

**Description** A package for design diagnostics.

**Depends** DatabaseConnector (>= 5.0.0),  
dplyr,  
R (>= 4.0.0)

**Imports** checkmate,  
CirceR,  
purrr,  
RJSONIO,  
rlang,  
scales,  
SqlRender,  
stringr,  
stringdist,  
tidyr

**Suggests** remotes,  
rmarkdown,  
knitr,  
testthat,  
withr

**Remotes** ohdsi/CirceR,  
ohdsi/SqlRender

**License** Apache License (>= 2)

**RoxygenNote** 7.2.0

**Encoding** UTF-8

**Language** en-US

## R topics documented:

convertConceptSetDataFrameToExpression	2
convertConceptSetExpressionToDataFrame	3

extractConceptSetsInCohortDefinition . . . . .	4
extractConceptSetsInCohortDefinitionSet . . . . .	5
getConceptAncestor . . . . .	5
getConceptDescendant . . . . .	6
getConceptIdDetails . . . . .	7
getConceptPrevalenceCounts . . . . .	8
getConceptRelationship . . . . .	9
getConceptSynonym . . . . .	9
getDomain . . . . .	10
getDrugIngredients . . . . .	11
getExcludedConceptsInConceptSetExpression . . . . .	12
getMappedSourceConcepts . . . . .	12
getMappedStandardConcepts . . . . .	13
getMedraRelationship . . . . .	14
getRelationship . . . . .	15
getVocabulary . . . . .	16
getVocabularyVersion . . . . .	16
mapMedraToSnomedViaVocabulary . . . . .	17
optimizeConceptSetExpression . . . . .	18
performStringSearchForConcepts . . . . .	19
resolveConceptSetExpression . . . . .	19
resolveConceptSetsInCohortExpression . . . . .	20

## Index 22

---

### convertConceptSetDataFrameToExpression

*Convert concept set expression in a data frame format convert to R (list) expression*

---

### Description

Convert concept set expression in a data frame format convert to R (list) expression

### Usage

```
convertConceptSetDataFrameToExpression(
  conceptSetExpressionDataFrame,
  selectAllDescendants = FALSE,
  updateVocabularyFields = FALSE,
  connectionDetails = NULL,
  connection = NULL,
  vocabularyDatabaseSchema = NULL
)
```

### Arguments

conceptSetExpressionDataFrame

Concept set expression in data frame format with required fields conceptId. If includeMapped, isExcluded or includeDescendants are missing value or is not existent - it is assumed to be FALSE. All column names should be in camelCase format.

selectAllDescendants	Do you want to over ride the concept set expression by add select descendants for concept ids in concept set expression.
updateVocabularyFields	Do you want to update the details about concepts from the vocabulary tables such as domain, vocabulary, concept name? If yes, then connection or connectionDetails to a remote db with OMOP vocabulary tables is needed.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

**Value**

Returns a R list object

---

convertConceptSetExpressionToDataFrame

*convert a concept set expression R list object into a data frame object*

---

**Description**

convert a concept set expression R list object into a data frame object

**Usage**

```
convertConceptSetExpressionToDataFrame(
  conceptSetExpression,
  updateVocabularyFields = FALSE,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = NULL
)
```

**Arguments**

conceptSetExpression

An R-object (list) with expression of the concept set.

updateVocabularyFields

Do you want to update the details about concepts from the vocabulary tables such as domain, vocabulary, concept name? If yes, then connection or connectionDetails to a remote db with OMOP vocabulary tables is needed.

connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

### Value

Returns a tibble data frame.

---

extractConceptSetsInCohortDefinition

*Extract concept set expressions from cohort definition expression.*

---

### Description

Given a cohort expression, this function extracts the concept set expressions from cohort definition expression.

### Usage

```
extractConceptSetsInCohortDefinition(cohortExpression)
```

### Arguments

**cohortExpression**  
A R-object (list) that represents cohort definition expression. This is derived from cohort expression json using `RJSONIO::fromJSON(content = json, digits = 23)`. Note: it is important to use `digits = 23`, otherwise numerical precision may be lost for large integer values like `conceptId`'s in cohort definition. The cohort expression JSON is commonly generated using OHDSI tools like Atlas or CapR.

### Value

Returns a tibble data frame.

---

```
extractConceptSetsInCohortDefinitionSet
```

*Extract concept sets from cohort definition set*

---

## Description

given a cohort definition set (data frame with cohortId, json), this function extracts the concept set json and sql for all cohorts, compares concept sets across cohort definitions, assigns unique id.

## Usage

```
extractConceptSetsInCohortDefinitionSet(cohortDefinitionSet)
```

## Arguments

**cohortDefinitionSet**

The cohortDefinitionSet argument must be a data frame with at least the following columns.

**cohortId** The cohort Id is the id used to identify a cohort definition. This is required to be unique. It is usually used to create file names.

**cohortName** The full name of the cohort.

**json** The JSON cohort definition for the cohort.

**sql** The SQL of the cohort definition rendered from the cohort json.

## Value

Returns a tibble data frame.

---

```
getConceptAncestor      get concept ancestor
```

---

## Description

given an array of conceptIds, get their ancestor and descendants.

## Usage

```
getConceptAncestor(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

**Value**

Returns a tibble data frame.

---

getConceptDescendant	<i>get concept descendant</i>
----------------------	-------------------------------

---

**Description**

given an array of conceptIds, get their descendants.

**Usage**

```
getConceptDescendant(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

## Value

Returns a tibble data frame.

---

getConceptIdDetails	<i>get concept id details</i>
---------------------	-------------------------------

---

## Description

given an array of conceptIds, get their details

## Usage

```
getConceptIdDetails(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary",
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)
```

## Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

## Value

Returns a tibble data frame.

---

```
getConceptPrevalenceCounts  
    get concept id count
```

---

## Description

Get the count for an array of concept id(s) from concept prevalence table.

## Usage

```
getConceptPrevalenceCounts(  
  conceptIds,  
  connection = NULL,  
  connectionDetails = NULL,  
  conceptPrevalenceTable,  
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")  
)
```

## Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
conceptPrevalenceTable	A reference table (can be schemaName.tableName) that holds the concept prevalence data. The required fields are concept_id, rc, drc, dbc, ddbc. In case of error, cocneptPrevalence is silently ignored.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

## Value

Returns a tibble data frame.



---

getConceptRelationship

*given a list of conceptIds, get their relationship*


---

### Description

given a list of conceptIds, get their relationship

### Usage

```
getConceptRelationship(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

### Arguments

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

### Value

Returns a tibble data frame.

---

getConceptSynonym

*given a list of conceptIds, get their synonyms*


---

### Description

given a list of conceptIds, get their synonyms

**Usage**

```

getConceptSynonym(
    conceptIds,
    connection = NULL,
    connectionDetails = NULL,
    tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
    vocabularyDatabaseSchema = "vocabulary"
)

```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

---

getDomain

---

*Get all the domain id(s) in the vocabulary schema.*


---

**Description**

Get all the domain id(s) in the vocabulary schema.

**Usage**

```

getDomain(
    connection = NULL,
    connectionDetails = NULL,
    vocabularyDatabaseSchema = "vocabulary"
)

```

**Arguments**

connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
------------	--

connectionDetails

An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

## Value

Returns a tibble data frame.

---

getDrugIngredients	<i>Get ingredient information</i>
--------------------	-----------------------------------

---

## Description

Given an array of drug concept ids, returns their ingredients

## Usage

```
getDrugIngredients(
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  conceptIds,
  vocabularyDatabaseSchema = "vocabulary"
)
```

## Arguments

connection      An object of type connection as created using the [connect](#) function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

connectionDetails

An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

conceptIds      An array of concept ids to find ingredients for

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

## Value

Returns a tibble data frame.

---

```
getExcludedConceptsInConceptSetExpression
```

*Given a concept set expression, get the resolved concepts*

---

### Description

Given a concept set expression, get the resolved concepts

### Usage

```
getExcludedConceptsInConceptSetExpression(
  conceptSetExpression,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

### Arguments

conceptSetExpression	An R-object (list) with expression of the concept set.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

### Value

Returns a tibble data frame.

---

```
getMappedSourceConcepts
```

*given a list of conceptIds, get their mapped*

---

### Description

Given a concept set expression, get the resolved concepts

**Usage**

```
getMappedSourceConcepts(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

**Value**

Returns a tibble data frame.

---

```
getMappedStandardConcepts
```

*given a list of conceptIds, get their mapped*

---

**Description**

given a list of conceptIds, get their mapped

**Usage**

```
getMappedStandardConcepts(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

**Value**

Returns a tibble data frame.

---

getMedraRelationship	<i>get MedDRA relationship</i>
----------------------	--------------------------------

---

**Description**

given an array of conceptIds belonging to MedDRA vocabulary get its full MedDRA relationship

**Usage**

```
getMedraRelationship(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

## Value

Returns a a list of tibble data frames conceptId, socConceptId, socConceptName, HLTConceptId, HltConceptName, HlgtConceptId, hlgtConceptName, ptConceptId, ptConceptName, lltConceptId, lltConceptName

---

getRelationship	<i>get all relationship id from vocabulary tables in vocabulary schema.</i>
-----------------	---

---

## Description

get all relationship id from vocabulary tables in vocabulary schema.

## Usage

```
getRelationship(
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary"
)
```

## Arguments

**connection** An object of type connection as created using the [connect](#) function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

**connectionDetails**

An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

**vocabularyDatabaseSchema**

The schema name of containing the vocabulary tables.

---

getVocabulary	<i>Get vocabulary id(s) in vocabulary tables in vocabulary schema.</i>
---------------	--

---

### Description

Get vocabulary id(s) in vocabulary tables in vocabulary schema.

### Usage

```
getVocabulary(  
    connection = NULL,  
    connectionDetails = NULL,  
    vocabularyDatabaseSchema = "vocabulary"  
)
```

### Arguments

connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

---

getVocabularyVersion	<i>Get vocabulary version.</i>
----------------------	--------------------------------

---

### Description

Get vocabulary version.

### Usage

```
getVocabularyVersion(  
    connection = NULL,  
    connectionDetails = NULL,  
    vocabularyDatabaseSchema = "vocabulary"  
)
```



**Arguments**

connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

---

```
mapMedraToSnomedViaVocabulary
      map MedDRA to SNOMED
```

---

**Description**

given an array of conceptIds belonging to MedDRA vocabulary get its equivalent SNOMED ranked using a combination of OMOP vocabulary mapping, lexical string matching and concept prevalence counts

**Usage**

```
mapMedraToSnomedViaVocabulary(
  conceptIds,
  connection = NULL,
  connectionDetails = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

conceptIds	An array of Concept ids.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

**Value**

Returns a tibble data frame

---

`optimizeConceptSetExpression`

*given a concept set expression, get optimized concept set expression*

---

**Description**

given a concept set expression, get optimized concept set expression

**Usage**

```
optimizeConceptSetExpression(  
  conceptSetExpression,  
  vocabularyDatabaseSchema = "vocabulary",  
  connection = NULL,  
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),  
  connectionDetails = NULL  
)
```

**Arguments**

`conceptSetExpression`

An R-object (list) with expression of the concept set.

`vocabularyDatabaseSchema`

The schema name of containing the vocabulary tables.

`connection`

An object of type `connection` as created using the [connect](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connectionDetails` is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

`tempEmulationSchema`

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

`connectionDetails`

An object of type `connectionDetails` as created using the [createConnectionDetails](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connection` is provided.

---

`performStringSearchForConcepts`*Get concepts that match a string search*

---

**Description**

Get concepts that match a string search

**Usage**

```
performStringSearchForConcepts(  
    searchString,  
    vocabularyDatabaseSchema = "vocabulary",  
    connection = NULL,  
    connectionDetails = NULL  
)
```

**Arguments**

`searchString` A phrase (can be multiple words) to search for.

`vocabularyDatabaseSchema` The schema name of containing the vocabulary tables.

`connection` An object of type `connection` as created using the [connect](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connectionDetails` is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

`connectionDetails` An object of type `connectionDetails` as created using the [createConnectionDetails](#) function in the `DatabaseConnector` package. Can be left `NULL` if `connection` is provided.

---

`resolveConceptSetExpression`*Given a concept set expression, get the resolved concepts*

---

**Description**

Given a concept set expression, get the resolved concepts

**Usage**

```
resolveConceptSetExpression(  
    conceptSetExpression,  
    connection = NULL,  
    connectionDetails = NULL,  
    vocabularyDatabaseSchema = "vocabulary"  
)
```

**Arguments**

conceptSetExpression	An R-object (list) with expression of the concept set.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package. Can be left NULL if connection is provided.
vocabularyDatabaseSchema	The schema name of containing the vocabulary tables.

**Value**

Returns a tibble data frame.

---

```
resolveConceptSetsInCohortExpression
```

*Given a cohort definition expression, get the resolved concepts for all concept sets*

---

**Description**

Given a cohort definition expression, get the resolved concepts for all concept sets

**Usage**

```
resolveConceptSetsInCohortExpression(
  cohortExpression,
  connection = NULL,
  connectionDetails = NULL,
  vocabularyDatabaseSchema = "vocabulary"
)
```

**Arguments**

cohortExpression	A R-object (list) that represents cohort definition expression. This is derived from cohort expression json using <code>RJSONIO::fromJSON(content = json, digits = 23)</code> . Note: it is important to use <code>digits = 23</code> , otherwise numerical precision may be lost for large integer values like conceptId's in cohort definition. The cohort expression JSON is commonly generated using OHDSI tools like Atlas or CapR.
connection	An object of type connection as created using the <a href="#">connect</a> function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

connectionDetails

An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

vocabularyDatabaseSchema

The schema name of containing the vocabulary tables.

# Index

connect, [3](#), [4](#), [6–20](#)  
convertConceptSetDataFrameToExpression,  
    [2](#)  
convertConceptSetExpressionToDataFrame,  
    [3](#)  
createConnectionDetails, [3](#), [4](#), [6–21](#)  
  
extractConceptSetsInCohortDefinition,  
    [4](#)  
extractConceptSetsInCohortDefinitionSet,  
    [5](#)  
  
getConceptAncestor, [5](#)  
getConceptDescendant, [6](#)  
getConceptIdDetails, [7](#)  
getConceptPrevalenceCounts, [8](#)  
getConceptRelationship, [9](#)  
getConceptSynonym, [9](#)  
getDomain, [10](#)  
getDrugIngredients, [11](#)  
getExcludedConceptsInConceptSetExpression,  
    [12](#)  
getMappedSourceConcepts, [12](#)  
getMappedStandardConcepts, [13](#)  
getMedraRelationship, [14](#)  
getRelationship, [15](#)  
getVocabulary, [16](#)  
getVocabularyVersion, [16](#)  
  
mapMedraToSnomedViaVocabulary, [17](#)  
  
optimizeConceptSetExpression, [18](#)  
  
performStringSearchForConcepts, [19](#)  
  
resolveConceptSetExpression, [19](#)  
resolveConceptSetsInCohortExpression,  
    [20](#)