

# Package ‘OhdsiRTools’

January 18, 2017

**Type** Package

**Title** Tools for Maintaining OHDSI R Packages

**Version** 1.2.0

**Date** 2017-1-18

**Author** Martijn J. Schuemie [aut, cre],  
Marc A. Suchard [aut],

**Maintainer** Martijn J. Schuemie <schuemie@ohdsi.org>

**Description** Format and check syntax of R code and packages following the OHDSI  
R style guidelines. Support for parallel computation.

**License** Apache License 2.0

**Depends** R (>= 3.1.0)

**Imports** devtools,  
codetools,  
formatR,  
snow,  
RJSONIO,  
RCurl,  
XML,  
jsonlite,  
methods,  
utils

**Suggests** testthat

**NeedsCompilation** no

**RoxygenNote** 5.0.1

## R topics documented:

checkUsagePackage . . . . .	2
clusterApply . . . . .	3
clusterRequire . . . . .	4
convertArgsToList . . . . .	4
createArgFunction . . . . .	5
excludeFromList . . . . .	5
formatRFile . . . . .	6
formatRFolder . . . . .	6
formatRText . . . . .	7

insertCirceDefinitionInPackage . . . . .	7
loadSettingsFromJson . . . . .	8
makeCluster . . . . .	8
matchInList . . . . .	9
OhdsiRTools . . . . .	9
prettyPrint . . . . .	10
restoreEnvironment . . . . .	10
saveSettingsToJson . . . . .	11
selectFromList . . . . .	11
stopCluster . . . . .	12
takeEnvironmentSnapshot . . . . .	12
updateCopyrightYearFile . . . . .	13
updateCopyrightYearFolder . . . . .	13
<b>Index</b>	<b>14</b>

---

checkUsagePackage	<i>Check all code in a package</i>
-------------------	------------------------------------

---

## Description

Check all code in a package

## Usage

```
checkUsagePackage(package, ignoreHiddenFunctions = TRUE,
  suppressBindingKeywords = c("ggplot2", "ffwhich", "subset.ffdf", "glm"))
```

## Arguments

package	The name of the package to check.
ignoreHiddenFunctions	Ignore functions for which the definition cannot be retrieved?
suppressBindingKeywords	A set of keywords that are indicative of non-standard evaluation.

## Details

This function uses the codetools package to check the code from problems. Heuristics are used to eliminate false positives due to non-standard evaluation.

---

clusterApply	<i>Apply a function to a list using the cluster</i>
--------------	---

---

## Description

Apply a function to a list using the cluster

## Usage

```
clusterApply(cluster, x, fun, ..., stopOnError = FALSE, progressBar = TRUE,  
             divideFfMemory = TRUE, setFfTempDir = TRUE)
```

## Arguments

cluster	The cluster of threads to run the function.
x	The list on which the function will be applied.
fun	The function to apply. Note that the context in which the function is specified matters (see details).
...	Additional parameters for the function.
stopOnError	Stop when one of the threads reports an error? If FALSE, all errors will be reported at the end.
progressBar	Show a progress bar?
divideFfMemory	When TRUE, the memory available for processing ff and ffdf objects will be equally divided over the threads.
setFfTempDir	When TRUE, the ffTempDir option will be copied to each thread.

## Details

The function will be executed on each element of x in the threads of the cluster. If there are more elements than threads, the elements will be queued. The progress bar will show the number of elements that have been completed. It can sometimes be important to realize that the context in which a function is created is also transmitted to the worker node. If a function is defined inside another function, and that outer function is called with a large argument, that argument will be transmitted to the worker node each time the function is executed. It can therefore make sense to define the function to be called at the package level rather than inside a function, to save overhead.

## Value

A list with the result of the function on each item in x.

---

clusterRequire	<i>Require a package in the cluster</i>
----------------	---

---

**Description**

Require a package in the cluster

**Usage**

```
clusterRequire(cluster, package)
```

**Arguments**

cluster	The cluster object.
package	The name of the package to load in all nodes.

---

convertArgsToList	<i>Deprecated: Convert arguments used in call to a list</i>
-------------------	---

---

**Description**

Deprecated: Convert arguments used in call to a list

**Usage**

```
convertArgsToList(matchCall, resultClass = "list")
```

**Arguments**

matchCall	The result of <code>match.call()</code> .
resultClass	The class of the resulting object.

**Details**

Takes the argument values (both default and user-specified) and store them in a list. This function is deprecated because it fails when used in a function that is called using `::`.

**Value**

An object of the class specified in `resultClass`.

**Examples**

```
myFun <- function(x = 1, y = 2) {  
  return(convertArgsToList(match.call()))  
}
```

---

createArgFunction	Create an argument function
-------------------	-----------------------------

---

**Description**

Create an argument function

**Usage**

```
createArgFunction(functionName, excludeArgs = c(), includeArgs = NULL,  
  addArgs = list(), rCode = c(), newName)
```

**Arguments**

functionName	The name of the function for which we want to create an args function.
excludeArgs	Exclude these arguments from appearing in the args function.
includeArgs	Include these arguments in the args function.
addArgs	Add these arguments to the args functions. Defined as a list with format name = default.
rCode	A character vector representing the R code where the new function should be appended to.
newName	The name of the new function. If not specified, the new name will be automatically derived from the old name.

**Details**

This function can be used to create a function that has (almost) the same interface as the specified function, and the output of this function will be a list of argument values.

**Value**

A character vector with the R code including the new function.

**Examples**

```
createArgFunction("read.csv", addArgs = list(exposureId = "exposureId"))
```

---

excludeFromList	Exclude variables from a list of objects of the same type
-----------------	---

---

**Description**

Exclude variables from a list of objects of the same type

**Usage**

```
excludeFromList(x, exclude)
```

**Arguments**

x	A list of objects of the same type.
exclude	A character vector of names of variables to exclude.

---

formatRFile	<i>Format an R file</i>
-------------	-------------------------

---

**Description**

Format an R file

**Usage**

```
formatRFile(file, width.cutoff = 100)
```

**Arguments**

file	The path to the file.
width.cutoff	Number of characters that each line should be limited to.

---

formatRFolder	<i>Format all R files in a folder</i>
---------------	---------------------------------------

---

**Description**

Format all R files in a folder

**Usage**

```
formatRFolder(path = ".", recursive = TRUE, skipAutogenerated = TRUE, ...)
```

**Arguments**

path	Path to the folder containing the files to format. Only files with the .R extension will be formatted.
recursive	Include all subfolders?
skipAutogenerated	Skip autogenerated files such as RcppExports.R?
...	Parameters to be passed on the the formatRFile function

**Examples**

```
## Not run:
formatRFolder()

## End(Not run)
```

---

`formatRText`*Format R code*

---

**Description**

Format R code

**Usage**

```
formatRText(text, width.cutoff = 100)
```

**Arguments**

<code>text</code>	A character vector with the R code to be formatted.
<code>width.cutoff</code>	Number of characters that each line should be limited to.

**Value**

A character vector with formatted R code.

---

`insertCirceDefinitionInPackage`*Load a Circe definition and insert it into this package*

---

**Description**

Load a Circe definition and insert it into this package

**Usage**

```
insertCirceDefinitionInPackage(definitionId, name = NULL,  
  baseUrl = "http://hix.jnj.com:8080/WebAPI")
```

**Arguments**

<code>definitionId</code>	The number indicating which Circe definition to fetch.
<code>name</code>	The name that will be used for the json and SQL files. If not provided, the name in Circe will be used, but this may not lead to valid file names.
<code>baseUrl</code>	The base URL for the WebApi instance.

**Details**

Load a Circe definition from a WebApi instance and insert it into this package. This will fetch the json object and store it in the 'inst/circe' folder, and fetch the template SQL and store it in the 'inst/sql/sql\_server' folder. Both folders will be created if they don't exist.

**Examples**

```
## Not run:
# This will create 'inst/circe/Angioedema.json' and 'inst/sql/sql_server/Angioedema.sql':

insertCirceDefinitionInPackage(2132, "Angioedema")

## End(Not run)
```

---

loadSettingsFromJson	<i>Load a settings object from a JSON file</i>
----------------------	--

---

**Description**

Load a settings object from a JSON file

**Usage**

```
loadSettingsFromJson(fileName)
```

**Arguments**

fileName	Name of the JSON file to load.
----------	--------------------------------

**Details**

Load a settings object from a JSON file, restoring object classes and attributes.

**Value**

An R object as specified by the JSON.

---

makeCluster	<i>Create a cluster of nodes for parallel computation</i>
-------------	---

---

**Description**

Create a cluster of nodes for parallel computation

**Usage**

```
makeCluster(numberOfThreads, singleThreadToMain = TRUE)
```

**Arguments**

numberOfThreads	Number of parallel threads.
singleThreadToMain	If numberOfThreads is 1, should we fall back to running the process in the main thread?



**Value**

An object representing the cluster.

---

matchInList	<i>In a list of object of the same type, find those that match the input</i>
-------------	--

---

**Description**

In a list of object of the same type, find those that match the input

**Usage**

```
matchInList(x, toMatch)
```

**Arguments**

x	A list of objects of the same type.
toMatch	The object to match.

**Details**

Typically, toMatch will contain a subset of the variables that are in the objects in the list. Any object matching all variables in toMatch will be included in the result.

**Value**

A list of objects that match the toMatch object.

---

OhdsiRTools	<i>OhdsiRTools</i>
-------------	--------------------

---

**Description**

OhdsiRTools

---

prettyPrint	<i>Print a list of objects</i>
-------------	--------------------------------

---

**Description**

Print a list of objects

**Usage**

```
prettyPrint(object)
```

**Arguments**

object	The list to print.
--------	--------------------

**Details**

Will print nested lists using indentation.

---

restoreEnvironment	<i>Restore the R environment to a snapshot</i>
--------------------	--

---

**Description**

Restore the R environment to a snapshot

**Usage**

```
restoreEnvironment(snapshot, stopOnWrongRVersion = FALSE)
```

**Arguments**

snapshot	The snapshot data frame as generated using the <a href="#">takeEnvironmentSnapshot</a> function.
stopOnWrongRVersion	Should the function stop when the wrong version of R is installed? Else just a warning will be thrown when the version doesn't match.

**Details**

This function restores the R environment to a previous snapshot, meaning all the packages will be restored to the versions they were at at the time of the snapshot. Note: on Windows you will very likely need to have RTools installed to build the various packages.

**Examples**

```
## Not run:
snapshot <- takeEnvironmentSnapshot("OhdsiRTools")
write.csv(snapshot, "snapshot.csv")

# 5 years later

snapshot <- read.csv("snapshot.csv")
restoreEnvironment(snapshot)

## End(Not run)
```

---

saveSettingsToJson	<i>Save a settings object as JSON file</i>
--------------------	--

---

**Description**

Save a settings object as JSON file

**Usage**

```
saveSettingsToJson(object, fileName)
```

**Arguments**

object	R object to be saved.
fileName	File name where the object should be saved.

**Details**

Save a setting object as a JSON file, using pretty formatting and preserving object classes and attributes.

---

selectFromList	<i>Select variables from a list of objects of the same type</i>
----------------	---

---

**Description**

Select variables from a list of objects of the same type

**Usage**

```
selectFromList(x, select)
```

**Arguments**

x	A list of objects of the same type.
select	A character vector of names of variables to select.

---

stopCluster	<i>Stop the cluster</i>
-------------	-------------------------

---

**Description**

Stop the cluster

**Usage**

```
stopCluster(cluster)
```

**Arguments**

cluster	The cluster to stop
---------	---------------------

---

takeEnvironmentSnapshot	<i>Take a snapshot of the R environment</i>
-------------------------	---

---

**Description**

Take a snapshot of the R environment

**Usage**

```
takeEnvironmentSnapshot(rootPackage)
```

**Arguments**

rootPackage	The name of the root package
-------------	------------------------------

**Details**

This function records all versions used in the R environment that are used by one root package. This can be used for example to restore the environment to the state it was when a particular study package was run using the [restoreEnvironment](#) function.

**Value**

A data frame listing all the dependencies of the root package and their version numbers, in the order in which they should be installed.

**Examples**

```
snapshot <- takeEnvironmentSnapshot("OhdsiRTools")
snapshot
```

---

`updateCopyrightYearFile`*Update the copyright year in a R or SQL file*

---

**Description**

Update the copyright year in a R or SQL file

**Usage**

```
updateCopyrightYearFile(file)
```

**Arguments**

<code>file</code>	The path to the file.
-------------------	-----------------------

---

`updateCopyrightYearFolder`*Update the copyright year in all R and SQL files in a folder*

---

**Description**

Update the copyright year in all R and SQL files in a folder

**Usage**

```
updateCopyrightYearFolder(path = ".", recursive = TRUE)
```

**Arguments**

<code>path</code>	Path to the folder containing the files to update. Only files with the .R and .SQL extension will be updated.
<code>recursive</code>	Include all subfolders?

**Examples**

```
## Not run:  
updateCopyrightYearFolder()  
  
## End(Not run)
```

# Index

checkUsagePackage, [2](#)  
clusterApply, [3](#)  
clusterRequire, [4](#)  
convertArgsToList, [4](#)  
createArgFunction, [5](#)  
  
excludeFromList, [5](#)  
  
formatRFile, [6](#)  
formatRFolder, [6](#)  
formatRText, [7](#)  
  
insertCirceDefinitionInPackage, [7](#)  
  
loadSettingsFromJson, [8](#)  
  
makeCluster, [8](#)  
matchInList, [9](#)  
  
OhdsiRTools, [9](#)  
OhdsiRTools-package (OhdsiRTools), [9](#)  
  
prettyPrint, [10](#)  
  
restoreEnvironment, [10](#), [12](#)  
  
saveSettingsToJson, [11](#)  
selectFromList, [11](#)  
stopCluster, [12](#)  
  
takeEnvironmentSnapshot, [10](#), [12](#)  
  
updateCopyrightYearFile, [13](#)  
updateCopyrightYearFolder, [13](#)