

Package ‘OhdsiSharing’

February 17, 2020

Type Package

Title Package for sharing of the results of the OHDSI tools

Version 0.2.0

Date 2020-02-17

Author Martijn Schuemie [aut, cre],
Marc Suchard [aut],
Lee Evans [aut]

Maintainer Martijn Schuemie <schuemie@ohdsi.org>

Description Package for sharing of the results of the OHDSI tools, with
functions for encrypting results and sending results through SFTP to a central
site.

Imports rJava,
ParallelLogger

Suggests testthat

License Apache License

RoxygenNote 7.0.2

R topics documented:

compressAndEncryptFolder	2
compressFolder	3
decompressFolder	3
decryptAndDecompressFolder	4
decryptFile	5
encryptFile	5
generateKeyPair	6
sftpCd	7
sftpConnect	7
sftpDisconnect	7
sftpGetFile	8
sftpLs	8
sftpMkdir	9
sftpPutFile	9
sftpRename	10
sftpRm	10
sftpRmdir	10
sftpUploadFile	11
sftpPwd	11

Index**12**

`compressAndEncryptFolder`*Compress and encrypt a folder*

Description

Compress and encrypt a folder

Usage

```
compressAndEncryptFolder(sourceFolder, targetFileName, publicKeyFileName)
```

Arguments

`sourceFolder` Name of the folder that must be encrypted.

`targetFileName` Name of the file that will hold the encrypted data.

`publicKeyFileName`
 Name of the file where the public key is stored.

Details

Compresses all files in a folder and its subfolders, and encrypts using the provided public key.

Examples

```
## Not run:
generateKeyPair("public.key", "private.key")

# Create a folder with some data
dir.create("test")
data <- data.frame(x = runif(1000), y = 1:1000)
saveRDS(data, "test/data1.rds")
saveRDS(data, "test/data2.rds")

compressAndEncryptFolder("test", "data.zip.enc", "public.key")
decryptAndDecompressFolder("data.zip.enc", "test2", "private.key")

## End(Not run)
```

compressFolder	<i>Compress a folder</i>
----------------	--------------------------

Description

Compress a folder

Usage

```
compressFolder(sourceFolder, targetFileName)
```

Arguments

sourceFolder Name of the folder that must be compressed.
targetFileName Name of the file that will hold the compressed data.

Details

Compresses all files in a folder and its subfolders, and stores it in a single zip file.

Examples

```
## Not run:  
# Create a folder with some data  
dir.create("test")  
data <- data.frame(x = runif(1000), y = 1:1000)  
saveRDS(data, "test/data1.rds")  
saveRDS(data, "test/data2.rds")  
  
compressFolder("test", "data.zip")  
decompressFolder("data.zip", "test2")  
  
## End(Not run)
```

decompressFolder	<i>Decompress a folder</i>
------------------	----------------------------

Description

Decompress a folder

Usage

```
decompressFolder(sourceFileName, targetFolder)
```

Arguments

sourceFileName Name of the file that must be decompressed.
targetFolder Name of the folder that will hold the extracted data.

Details

Extracts all compressed files to a folder.

Examples

```
## Not run:
# Create a folder with some data
dir.create("test")
data <- data.frame(x = runif(1000), y = 1:1000)
saveRDS(data, "test/data1.rds")
saveRDS(data, "test/data2.rds")

compressFolder("test", "data.zip")
decompressFolder("data.zip", "test2")

## End(Not run)
```

decryptAndDecompressFolder

Decrypt and decompress a folder

Description

Decrypt and decompress a folder

Usage

```
decryptAndDecompressFolder(sourceFileName, targetFolder, privateKeyFileName)
```

Arguments

sourceFileName Name of the file that must be decrypted.
targetFolder Name of the folder that will hold the unencrypted data.
privateKeyFileName
 Name of the file where the private key is stored.

Details

Decrypts the data using the provided private key and extracts all files to a folder.

Examples

```
## Not run:
generateKeyPair("public.key", "private.key")

# Create a folder with some data
dir.create("test")
data <- data.frame(x = runif(1000), y = 1:1000)
saveRDS(data, "test/data1.rds")
saveRDS(data, "test/data2.rds")
```

```
compressAndEncryptFolder("test", "data.zip.enc", "public.key")
decryptAndDecompressFolder("data.zip.enc", "test2", "private.key")

## End(Not run)
```

decryptFile	<i>Decrypt a data file</i>
-------------	----------------------------

Description

Decrypt a data file

Usage

```
decryptFile(sourceFileName, targetFileName, privateKeyFileName)
```

Arguments

sourceFileName Name of the file that must be decrypted.
targetFileName Name of the file that will hold the unencrypted data.
privateKeyFileName
Name of the file where the private key is stored.

Details

Decrypts the data using the provided private key.

Examples

```
## Not run:
generateKeyPair("public.key", "private.key")
data <- data.frame(x = runif(1000), y = 1:1000)
saveRDS(data, "data.rds")
encryptFile("data.rds", "data.rds.enc", "public.key")
decryptFile("data.rds.enc", "data2.rds", "private.key")

## End(Not run)
```

encryptFile	<i>Encrypt a data file</i>
-------------	----------------------------

Description

Encrypt a data file

Usage

```
encryptFile(sourceFileName, targetFileName, publicKeyFileName)
```

Arguments

sourceFileName Name of the file that must be encrypted.
 targetFileName Name of the file that will hold the encrypted data.
 publicKeyFileName
 Name of the file where the public key is stored.

Details

Encrypts the data using the provided public key.

Examples

```
## Not run:
generateKeyPair("public.key", "private.key")
data <- data.frame(x = runif(1000), y = 1:1000)
saveRDS(data, "data.rds")
encryptFile("data.rds", "data.rds.enc", "public.key")

## End(Not run)
```

generateKeyPair	<i>Create a public-private key pair</i>
-----------------	---

Description

Create a public-private key pair

Usage

```
generateKeyPair(publicKeyFileName, privateKeyFileName)
```

Arguments

publicKeyFileName
 Name of the file where the public key should be stored.
 privateKeyFileName
 Name of the file where the private key should be stored.

Details

Creates an RSA 4096-bit public-private key pair. The public key can be used to encrypt data, and only with the private key can the data be decrypted.

Examples

```
## Not run:
generateKeyPair("public.key", "private.key")

## End(Not run)
```

sftpCd	<i>Change the current working director</i>
--------	--

Description

Change the current working director

Usage

```
sftpCd(sftpConnection, remoteFolder)
```

Arguments

sftpConnection	An SftpConnection object as created by the sftpConnect function.
remoteFolder	The folder on the server to change to.

sftpConnect	<i>Connect to the OHDSI SFTP server</i>
-------------	---

Description

Connect to the OHDSI SFTP server

Usage

```
sftpConnect(privateKeyFileName, userName)
```

Arguments

privateKeyFileName	
	A character string denoting the path to an RSA private key.
userName	
	A character string containing the user name.

Value

An SftpConnection object

sftpDisconnect	<i>Disconnect from the OHDSI SFTP server.</i>
----------------	---

Description

Disconnect from the OHDSI SFTP server.

Usage

```
sftpDisconnect(sftpConnection)
```

Arguments

sftpConnection	An SftpConnection object as created by the sftpConnect function.
----------------	--

sftpGetFile	<i>Get a file from the SFTP server</i>
-------------	--

Description

Get a file from the SFTP server

Usage

```
sftpGetFile(sftpConnection, remoteFileName, localFileName = remoteFileName)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.

remoteFileName The name the file on the server.

localFileName The name the file should have locally.

sftpLs	<i>List the files in folder on the server.</i>
--------	--

Description

List the files in folder on the server.

Usage

```
sftpLs(sftpConnection, remoteFolder = "./")
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.

remoteFolder The folder on the server. Defaults to the current folder.

Value

A data frame with two columns: the file names, and the file types (directory, link, or file).

sftpMkdir	<i>Make a directory</i>
-----------	-------------------------

Description

Make a directory

Usage

```
sftpMkdir(sftpConnection, remoteFolder)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.
remoteFolder The folder on the server to create.

sftpPutFile	<i>Put a file on the SFTP server</i>
-------------	--------------------------------------

Description

Put a file on the SFTP server

Usage

```
sftpPutFile(  
  sftpConnection,  
  localFileName,  
  remoteFileName = basename(localFileName)  
)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.
localFileName The path to the local file to upload.
remoteFileName The name the file should have on the server.

sftpRename	<i>Rename a file or folder</i>
------------	--------------------------------

Description

Rename a file or folder

Usage

```
sftpRename(sftpConnection, oldRemoteFilename, newRemoteFilename)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.

oldRemoteFilename

The file on the server to rename.

newRemoteFilename

The new file name.

sftpRm	<i>Remove a file</i>
--------	----------------------

Description

Remove a file

Usage

```
sftpRm(sftpConnection, remoteFile)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.

remoteFile The file on the server to remove.

sftpRmdir	<i>Remove a directory</i>
-----------	---------------------------

Description

Remove a directory

Usage

```
sftpRmdir(sftpConnection, remoteFolder)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.

remoteFolder The folder on the server to remove.

sftpUploadFile	<i>Upload a single file to the OHDSI SFTP server</i>
----------------	--

Description

This function combines calls to the [sftpConnect](#), [sftpPutFile](#), and [sftpDisconnect](#) functions. A random string will be prefixed to the file name to prevent overwriting existing files on the server.

Usage

```
sftpUploadFile(privateKeyFileName, userName, fileName)
```

Arguments

privateKeyFileName	A character string denoting the path to an RSA private key.
userName	A character string containing the user name.
fileName	A character string denoting the path to file to upload.

sftpPwd	<i>Get the present working directory</i>
---------	--

Description

Get the present working directory

Usage

```
sftpPwd(sftpConnection)
```

Arguments

sftpConnection An SftpConnection object as created by the [sftpConnect](#) function.

Value

A character string representing the current remote folder name.

Index

compressAndEncryptFolder, [2](#)
compressFolder, [3](#)

decompressFolder, [3](#)
decryptAndDecompressFolder, [4](#)
decryptFile, [5](#)

encryptFile, [5](#)

generateKeyPair, [6](#)

sftpCd, [7](#)
sftpConnect, [7](#), [7](#), [8–11](#)
sftpDisconnect, [7](#), [11](#)
sftpGetFile, [8](#)
sftpLs, [8](#)
sftpMkdir, [9](#)
sftpPutFile, [9](#), [11](#)
sftpRename, [10](#)
sftpRm, [10](#)
sftpRmdir, [10](#)
sftpUploadFile, [11](#)
sftpPwd, [11](#)