

# How to Use PhenotypeLibrary R Package

Gowtham A. Rao

2023-10-05

## Contents

1	Installation	1
2	Retrieval	1
3	Use	2

PhenotypeLibrary is part of HADES

## 1 Installation

- This is an installable R-package that may be installed as follows:

```
remotes::install_github("OHDSI/PhenotypeLibrary")
```

## 2 Retrieval

- The list of cohort definitions available may be retrieved as follows:

```
PhenotypeLibrary::getPhenotypeLog()
```

```
#> # A tibble: 550 x 80
#>   cohortId cohortName      cohortNameAtlas cohortNameFormatted cohortNameLong librarian status address
#>   <dbl> <chr>          <chr>          <chr>          <chr>          <chr>    <chr> <chr>
#> 1      3 Cough or Sputum [P] Cough or S~ Cough or Sputum Cough or Sput~ rao@ohds~ Pendi~ <NA>
#> 2      4 Diarrhea        [P] Diarrhea      Diarrhea        Diarrhea        rao@ohds~ Pendi~ <NA>
#> 3      5 Dyspnea         [P] Dyspnea       Dyspnea         Dyspnea         rao@ohds~ Pendi~ <NA>
#> 4      6 Fever           [P] Fever         Fever           Fever           rao@ohds~ Pendi~ <NA>
#> 5      7 Headache or He~ [P] Headache o~ Headache or Headac~ Headache or H~ rao@ohds~ Pendi~ <NA>
#> 6      8 Altered smell ~ [P] Altered sm~ Altered smell or t~ Altered smell~ rao@ohds~ Pendi~ <NA>
#> 7      9 Sore throat     [P] Sore throat   Sore throat     Sore throat     rao@ohds~ Pendi~ <NA>
#> 8     10 Nausea or Vomi~ [P] Nausea or ~ Nausea or Vomiting Nausea or Vom~ rao@ohds~ Pendi~ <NA>
#> 9     11 Malaise and or~ [P] Malaise an~ Malaise and or fat~ Malaise and o~ rao@ohds~ Pendi~ <NA>
#> 10    12 Rhinitis or co~ [P] Rhinitis o~ Rhinitis or common~ Rhinitis or c~ rao@ohds~ Pendi~ <NA>
#> # i 540 more rows
```

```
#> # i 69 more variables: contributors <chr>, contributorOrcIds <chr>, contributorOrganizations <chr>,
#> #   peerReviewerOrcIds <dbl>, recommendedReferentConceptIds <chr>, ohdsiForumPost <chr>, createdAt
#> #   lastModifiedBy <dbl>, replaces <dbl>, notes <chr>, isReferenceCohort <dbl>, censorWindowStartDate
#> #   collapseSettingsType <chr>, collapseEraPad <dbl>, exitStrategy <chr>, exitDateOffsetField <chr>,
#> #   numberOfInclusionRules <dbl>, initialEventLimit <chr>, initialEventRestrictionAdditionalCriteria
#> #   initialEventRestrictionAdditionalCriteriaLimit <chr>, inclusionRuleQualifyingEventLimit <chr>, n
```

- You can extract one or more cohort definitions into a cohortDefinitionSet object as

```
cohortDefinitionSet <- PhenotypeLibrary::getPlCohortDefinitionSet(cohortIds = c(1, 2, 3))

cohortDefinitionSet
```

```
#> # A tibble: 1 x 4
#>   cohortId cohortName      json
#>   <dbl> <chr>          <chr>
#> 1       3 Cough or Sputum "{\n\t\"cdmVersionRange\" : \">=5.0.0\", \n\t\"PrimaryCriteria\" : {\n\t\t
```

- cohortDefinitionSet is now a data.frame with specifications for the cohort ids 1, 2 and 3. For cohorts that conform to OHDSI Circe specifications, the field json is the cohort json specification that may be posted into your Atlas instance. The SQL is the SQL rendered from the JSON. For cohorts that do not conform to OHDSI Circe specification, only the SQL is provided and the json is left empty.

### 3 Use

- You can instantiate the cohorts in your environment as follows using (OHDSI/CohortGenerator)[<https://github.com/OHDSI/CohortGenerator>].

```
connectionDetails <-
  DatabaseConnector::createConnectionDetails(
    dbms = "postgresql",
    server = "some.server.com/ohdsi",
    user = "joe",
    password = "secret"
  )
cdmDatabaseSchema <- "cdm_synpuf"
cohortDatabaseSchema <- "scratch.dbo"
cohortTables <- CohortGenerator::getCohortTableNames()
CohortGenerator::generateCohortSet(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = cohortDatabaseSchema,
  cohortTableNames = cohortTables,
  cohortDefinitionSet = cohortDefinitionSet
)
```

- You can also run cohort diagnostics on this cohortDefinitionSet object as follows:

```

databaseId <- "synpuf"

databaseName <-
  "Medicare Claims Synthetic Public Use Files (SynPUFs)"

databaseDescription <-
  "Medicare Claims Synthetic Public Use Files (SynPUFs) were created to allow interested parties to gain

CohortDiagnostics::executeDiagnostics(
  cohortDefinitionSet = cohortDefinitionSet,
  exportFolder = outputFolder,
  databaseId = databaseId,
  databaseName = databaseName,
  databaseDescription = databaseDescription,
  cohortDatabaseSchema = cohortDatabaseSchema,
  cdmDatabaseSchema = cdmDatabaseSchema,
  connectionDetails = connectionDetails,
  cohortTableNames = cohortTableNames
)

```