

# How to Use PhenotypeLibrary R Package

Gowtham A. Rao

2025-04-02

## Contents

1	Installation	1
2	Retrieval	1
3	Use	2

PhenotypeLibrary is part of HADES

## 1 Installation

- This is an installable R-package that may be installed as follows:

```
remotes::install_github("OHDSI/PhenotypeLibrary")
```

## 2 Retrieval

- The list of cohort definitions available may be retrieved as follows:

```
PhenotypeLibrary::getPhenotypeLog()
```

```
#> # A tibble: 703 x 88
#>   cohortId cohortName      cohortNameAtlas cohortNameFormatted cohortNameLong librarian status add
#>   <dbl> <chr>          <chr>          <chr>          <chr>          <chr>    <chr> <chr>
#> 1      3 Cough or Sputum [P] Cough or S~ Cough or Sputum    Cough or Sput~ rao@ohds~ Pendi~ <NA>
#> 2      4 Diarrhea      [P] Diarrhea      Diarrhea          Diarrhea        rao@ohds~ Pendi~ <NA>
#> 3      5 Dyspnea      [P] Dyspnea      Dyspnea           Dyspnea          rao@ohds~ Pendi~ <NA>
#> 4      6 Fever        [P] Fever        Fever             Fever            rao@ohds~ Pendi~ <NA>
#> 5      7 Headache or Hea~ [P] Headache o~ Headache or Headac~ Headache or H~ rao@ohds~ Pendi~ <NA>
#> 6      8 Altered smell o~ [P] Altered sm~ Altered smell or t~ Altered smell~ rao@ohds~ Pendi~ <NA>
#> 7      9 Sore throat   [P] Sore throat   Sore throat       Sore throat      rao@ohds~ Pendi~ <NA>
#> 8     10 Nausea or Vomit~ [P] Nausea or ~ Nausea or Vomiting Nausea or Vom~ rao@ohds~ Pendi~ <NA>
#> 9     11 Malaise and or ~ [P] Malaise an~ Malaise and or fat~ Malaise and o~ rao@ohds~ Pendi~ <NA>
#> 10    12 Rhinitis or com~ [P] Rhinitis o~ Rhinitis or common~ Rhinitis or c~ rao@ohds~ Pendi~ <NA>
#> # i 693 more rows
```

```
#> # i 77 more variables: contributors <chr>, contributorOrcIds <chr>, contributorOrganizations <chr>,
#> #   peerReviewerOrcIds <dbl>, recommendedReferentConceptIds <chr>, ohdsiForumPost <chr>, createdAt
#> #   lastModifiedBy <dbl>, replaces <dbl>, notes <chr>, isReferenceCohort <dbl>, censorWindowStartDate
#> #   collapseSettingsType <chr>, collapseEraPad <dbl>, exitStrategy <chr>, exitDateOffsetField <chr>,
#> #   numberOfInclusionRules <dbl>, initialEventLimit <chr>, initialEventRestrictionAdditionalCriteria
#> #   initialEventRestrictionAdditionalCriteriaLimit <chr>, inclusionRuleQualifyingEventLimit <chr>, n
```

- You can extract one or more cohort definitions into a cohortDefinitionSet object as

```
cohortDefinitionSet <- PhenotypeLibrary::getPlCohortDefinitionSet(cohortIds = c(1, 2, 3))

cohortDefinitionSet
```

```
#> # A tibble: 2 x 4
#>   cohortId cohortName                                json
#>   <dbl> <chr>                                <chr>
#> 1       2 COVID-19 diagnosis or SARS-CoV-2 test (1pos) "{\n\t\"cdmVersionRange\" : \">=5.0.0\", \n\t
#> 2       3 Cough or Sputum                        "{\n\t\"cdmVersionRange\" : \">=5.0.0\", \n\t
```

- cohortDefinitionSet is now a data.frame with specifications for the cohort ids 1, 2 and 3. For cohorts that conform to OHDSI Circe specifications, the field json is the cohort json specification that may be posted into your Atlas instance. The SQL is the SQL rendered from the JSON. For cohorts that do not conform to OHDSI Circe specification, only the SQL is provided and the json is left empty.

### 3 Use

- You can instantiate the cohorts in your environment as follows using (OHDSI/CohortGenerator)[<https://github.com/OHDSI/CohortGenerator>].

```
connectionDetails <-
  DatabaseConnector::createConnectionDetails(
    dbms = "postgresql",
    server = "some.server.com/ohdsi",
    user = "joe",
    password = "secret"
  )
cdmDatabaseSchema <- "cdm_synpuf"
cohortDatabaseSchema <- "scratch.dbo"
cohortTables <- CohortGenerator::getCohortTableNames()
CohortGenerator::generateCohortSet(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = cohortDatabaseSchema,
  cohortTableNames = cohortTables,
  cohortDefinitionSet = cohortDefinitionSet
)
```

- You can also run cohort diagnostics on this cohortDefinitionSet object as follows:

```

databaseId <- "synpuf"

databaseName <-
  "Medicare Claims Synthetic Public Use Files (SynPUFs)"

databaseDescription <-
  "Medicare Claims Synthetic Public Use Files (SynPUFs) were created to allow interested parties to gain

CohortDiagnostics::executeDiagnostics(
  cohortDefinitionSet = cohortDefinitionSet,
  exportFolder = outputFolder,
  databaseId = databaseId,
  databaseName = databaseName,
  databaseDescription = databaseDescription,
  cohortDatabaseSchema = cohortDatabaseSchema,
  cdmDatabaseSchema = cdmDatabaseSchema,
  connectionDetails = connectionDetails,
  cohortTableNames = cohortTableNames
)

```