

Package ‘ResultModelManager’

March 25, 2023

Title Result Model Manager (RMM) for OHDSI packages

Version 0.3.1

Description Database data model management utilities for OHDSI packages.

License Apache License

Encoding UTF-8

VignetteBuilder knitr

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Depends R ($\geq 4.1.0$),
R6,
DatabaseConnector ($\geq 6.0.0$)

Imports SqlRender,
ParallelLogger,
checkmate,
DBI,
pool,
readr,
zip,
dplyr,
rlang,
lubridate

Suggests testthat ($\geq 3.0.0$),
RSQLite,
withr,
knitr,
rmarkdown,
keyring

Config/testthat/edition 3

Config/testthat/parallel true

R topics documented:

ConnectionHandler	2
DataMigrationManager	5
deleteAllRowsForDatabaseId	7
deleteAllRowsForPrimaryKey	8

generateSqlSchema	8
PooledConnectionHandler	9
unzipResults	10
uploadResults	11

ConnectionHandler	<i>ConnectionHandler</i>
-------------------	--------------------------

Description

Class for handling DatabaseConnector:connection objects with consistent R6 interfaces for pooled and non-pooled connections. Allows a connection to cleanly be opened and closed and stored within class/object variables

Value

DatabaseConnector Connection instance close Connection

boolean TRUE if connection is valid queryDb

boolean TRUE if connection is valid executeSql

Public fields

connectionDetails DatabaseConnector connectionDetails object

con DatabaseConnector connection object

isActive Is connection active or not #'

snakeCaseToCamelCase (Optional) Boolean. return the results columns in camel case (default)

Methods

Public methods:

- [ConnectionHandler\\$new\(\)](#)
- [ConnectionHandler\\$dbms\(\)](#)
- [ConnectionHandler\\$tbl\(\)](#)
- [ConnectionHandler\\$renderTranslateSql\(\)](#)
- [ConnectionHandler\\$initConnection\(\)](#)
- [ConnectionHandler\\$getConnection\(\)](#)
- [ConnectionHandler\\$closeConnection\(\)](#)
- [ConnectionHandler\\$finalize\(\)](#)
- [ConnectionHandler\\$dbIsValid\(\)](#)
- [ConnectionHandler\\$queryDb\(\)](#)
- [ConnectionHandler\\$executeSql\(\)](#)
- [ConnectionHandler\\$queryFunction\(\)](#)
- [ConnectionHandler\\$executeFunction\(\)](#)
- [ConnectionHandler\\$clone\(\)](#)

Method new():

Usage:

```

ConnectionHandler$new(
  connectionDetails,
  loadConnection = TRUE,
  snakeCaseToCamelCase = TRUE
)

```

Arguments:

`connectionDetails` DatabaseConnector::connectionDetails class

`loadConnection` Boolean option to load connection right away

`snakeCaseToCamelCase` (Optional) Boolean. return the results columns in camel case (default) get dbms

Method `dbms()`: Get the dbms type of the connection get table

Usage:

```
ConnectionHandler$dbms()
```

Method `tbl()`: get a dplyr table object (i.e. lazy loaded)

Usage:

```
ConnectionHandler$tbl(table, databaseSchema = NULL)
```

Arguments:

`table` table name

`databaseSchema` databaseSchema to which table belongs Render Translate Sql.

Method `renderTranslateSql()`: Masked call to SqlRender

Usage:

```
ConnectionHandler$renderTranslateSql(sql, ...)
```

Arguments:

`sql` Sql query string

`...` Elipsis initConnection

Method `initConnection()`: Load connection Get Connection

Usage:

```
ConnectionHandler$initConnection()
```

Method `getConnection()`: Returns connection for use with standard DatabaseConnector calls. Connects automatically if it isn't yet loaded

Usage:

```
ConnectionHandler$getConnection()
```

Method `closeConnection()`: Closes connection (if active) close Connection

Usage:

```
ConnectionHandler$closeConnection()
```

Method `finalize()`: Closes connection (if active) db Is Valid

Usage:

```
ConnectionHandler$finalize()
```

Method `dbIsValid()`: Masks call to DBI::dbIsValid. Returns False if connection is NULL

Usage:

```
ConnectionHandler$dbIsValid()
```

Method queryDb(): query database and return the resulting data.frame

If environment variable LIMIT_ROW_COUNT is set Returned rows are limited to this value (no default) Limit row count is intended for web applications that may cause a denial of service if they consume too many resources.

Usage:

```
ConnectionHandler$queryDb(
  sql,
  snakeCaseToCamelCase = self$snakeCaseToCamelCase,
  overrideRowLimit = FALSE,
  ...
)
```

Arguments:

sql sql query string

snakeCaseToCamelCase (Optional) Boolean. return the results columns in camel case (default)

overrideRowLimit (Optional) Boolean. In some cases, where row limit is enforced on the system You may wish to ignore it.

... Additional query parameters

Method executeSql(): execute set of database queries

Usage:

```
ConnectionHandler$executeSql(sql, ...)
```

Arguments:

sql sql query string

... Additional query parameters query Function

Method queryFunction(): queryFunction that can be overridden with subclasses (e.g. use different base function or intercept query) Does not translate or render sql.

Usage:

```
ConnectionHandler$queryFunction(
  sql,
  snakeCaseToCamelCase = self$snakeCaseToCamelCase
)
```

Arguments:

sql sql query string

snakeCaseToCamelCase (Optional) Boolean. return the results columns in camel case (default) execute Function

Method executeFunction(): exec query Function that can be overridden with subclasses (e.g. use different base function or intercept query) Does not translate or render sql.

Usage:

```
ConnectionHandler$executeFunction(sql)
```

Arguments:

sql sql query string

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
ConnectionHandler$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

DataMigrationManager *DataMigrationManager (DMM)*

Description

R6 class for management of database migration

Value

data frame all migrations, including file name, order and execution status
Get connection handler

Public fields

migrationPath Path migrations exist in
databaseSchema Path migrations exist in
packageName packageName, can be null
tablePrefix packageName, can be null

Methods

Public methods:

- [DataMigrationManager\\$new\(\)](#)
- [DataMigrationManager\\$migrationTableExists\(\)](#)
- [DataMigrationManager\\$getMigrationsPath\(\)](#)
- [DataMigrationManager\\$getStatus\(\)](#)
- [DataMigrationManager\\$getConnectionHandler\(\)](#)
- [DataMigrationManager\\$check\(\)](#)
- [DataMigrationManager\\$executeMigrations\(\)](#)
- [DataMigrationManager\\$isPackage\(\)](#)
- [DataMigrationManager\\$finalize\(\)](#)
- [DataMigrationManager\\$clone\(\)](#)

Method new():

Usage:

```
DataMigrationManager$new(
  connectionDetails,
  databaseSchema,
  tablePrefix = "",
  migrationPath,
  packageName = NULL,
  migrationRegexp = .defaultMigrationRegexp
)
```

Arguments:

connectionDetails DatabaseConnector connection details object
databaseSchema Database Schema to execute on
tablePrefix Optional table prefix for all tables (e.g. plp, cm, cd etc)
migrationPath Path to location of migration sql files. If in package mode, this should just be a folder (e.g. "migrations") that lives in the location "sql/sql_server" (and) other database platforms. If in folder model, the folder must include "sql_server" in the relative path, (e.g if migrationPath = 'migrations' then the folder 'migrations/sql_server' should exists)
packageName If in package mode, the name of the R package
migrationRegexp (Optional) regular expression pattern default is (Migration_([0-9]+))-(.+).sql
 Migration table exists

Method migrationTableExists(): Check if migration table is present in schema

Usage:

DataMigrationManager\$migrationTableExists()

Returns: boolean Get path of migrations

Method getMigrationsPath(): Get path to sql migration files

Usage:

DataMigrationManager\$getMigrationsPath(dbms = "sql server")

Arguments:

dbms Optionally specify the dbms that the migration fits under Get status of result model

Method getStatus(): Get status of all migrations (executed or not)

Usage:

DataMigrationManager\$getStatus()

Method getConnectionHandler(): Return connection handler instance

Usage:

DataMigrationManager\$getConnectionHandler()

Returns: ConnectionHandler instance Check migrations in folder

Method check(): Check if file names are valid for migrations Execute Migrations

Usage:

DataMigrationManager\$check()

Method executeMigrations(): Execute any unexecuted migrations

Usage:

DataMigrationManager\$executeMigrations(stopMigrationVersion = NULL)

Arguments:

stopMigrationVersion (Optional) Migrate to a specific migration number isPackage

Method isPackage(): is a package folder structure or not finalize

Usage:

DataMigrationManager\$isPackage()

Method finalize(): close database connection

Usage:

```
DataMigrationManager$finalize()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
DataMigrationManager$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

[ConnectionHandler](#) for information on returned class

deleteAllRowsForDatabaseId

Delete all rows for database id

Description

Delete all rows for database id

Usage

```
deleteAllRowsForDatabaseId(  
  connection,  
  schema,  
  tableName,  
  databaseId,  
  idIsInt = TRUE  
)
```

Arguments

connection	DatabaseConnector connection instance
schema	The schema on the postgres server where the results table exists
tableName	Database table name
databaseId	Results source database identifier
idIsInt	Identified is a numeric type? If not character is used

Details

Only PostgreSQL servers are supported.

```
deleteAllRowsForPrimaryKey
```

Delete results rows for primary key values from database server tables

Description

Delete results rows for primary key values from database server tables

Usage

```
deleteAllRowsForPrimaryKey(connection, schema, tableName, keyValues)
```

Arguments

connection	DatabaseConnector connection instance
schema	The schema on the postgres server where the results table exists
tableName	Database table name
keyValues	Key values of results rows to be deleted

Details

Only PostgreSQL servers are supported.

```
generateSqlSchema
```

Schema generator

Description

Take a csv schema definition and create a basic sql script with it.

Usage

```
generateSqlSchema(
  csvFilepath = NULL,
  schemaDefinition = NULL,
  sqlOutputPath = NULL,
  overwrite = FALSE
)
```

Arguments

csvFilepath	Path to schema file. Csv file must have the columns: "table_name", "column_name", "data_type", "is_required", "primary_key"
schemaDefinition	A schemaDefintion data.frame' with the columns: tableName, columnName, dataType, isRequired, primaryKey
sqlOutputPath	File to write sql to.
overwrite	Boolean - overwrite existing file?

Value

string containing the sql for the table

PooledConnectionHandler

Pooled Connection Handler

Description

Transparently works the same way as a standard connection handler but stores pooled connections. Useful for long running applications that serve multiple concurrent requests.

Super class

[ResultModelManager::ConnectionHandler](#) -> PooledConnectionHandler

Methods**Public methods:**

- [PooledConnectionHandler\\$new\(\)](#)
- [PooledConnectionHandler\\$initConnection\(\)](#)
- [PooledConnectionHandler\\$dbms\(\)](#)
- [PooledConnectionHandler\\$closeConnection\(\)](#)
- [PooledConnectionHandler\\$queryFunction\(\)](#)
- [PooledConnectionHandler\\$executeFunction\(\)](#)
- [PooledConnectionHandler\\$clone\(\)](#)

Method new():

Usage:

PooledConnectionHandler\$new(...)

Arguments:

... Elisis @seealso [ConnectionHandler](#) initialize pooled db connection

Method initConnection(): Overrides ConnectionHandler Call get dbms

Usage:

PooledConnectionHandler\$initConnection()

Method dbms(): Get the dbms type of the connection Close Connection

Usage:

PooledConnectionHandler\$dbms()

Method closeConnection(): Overrides ConnectionHandler Call query Function

Usage:

PooledConnectionHandler\$closeConnection()

Method queryFunction(): Overrides ConnectionHandler Call. Does not translate or render sql.

Usage:

```
PooledConnectionHandler$queryFunction(
  sql,
  snakeCaseToCamelCase = self$snakeCaseToCamelCase
)
```

Arguments:

sql sql query string

snakeCaseToCamelCase (Optional) Boolean. return the results columns in camel case (default) query Function

Method executeFunction(): Overrides ConnectionHandler Call. Does not translate or render sql.

Usage:

```
PooledConnectionHandler$executeFunction(sql)
```

Arguments:

sql sql query string

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PooledConnectionHandler$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

unzipResults	<i>Unzips a results.zip file and enforces standards required by uploadResults</i>
--------------	---

Description

This function will unzip the zipFile to the resultsFolder and assert that the file results-DataModelSpecification.csv exists in the resultsFolder to ensure that it will work with uploadResults

Usage

```
unzipResults(zipFile, resultsFolder)
```

Arguments

zipFile	The location of the .zip file that holds the results to upload
resultsFolder	The folder to use when unzipping the .zip file. If this folder does not exist, this function will attempt to create the folder.

uploadResults	<i>Upload results to the database server.</i>
---------------	---

Description

Requires the results data model tables have been created using the [createResultsDataModel](#) function.

Set the POSTGRES_PATH environmental variable to the path to the folder containing the psql executable to enable bulk upload (recommended).

Usage

```
uploadResults(
  connection = NULL,
  connectionDetails = NULL,
  schema,
  resultsFolder,
  tablePrefix = "",
  forceOverWriteOfSpecifications = FALSE,
  purgeSiteDataBeforeUploading = TRUE,
  databaseIdentifierFile = "cdm_source_info.csv",
  runCheckAndFixCommands = FALSE,
  warnOnMissingTable = TRUE,
  specifications
)
```

Arguments

connection	An object of type <code>connection</code> as created using the connect function in the DatabaseConnector package. Can be left NULL if <code>connectionDetails</code> is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
connectionDetails	An object of type <code>connectionDetails</code> as created using the createConnectionDetails function in the DatabaseConnector package.
schema	The schema on the postgres server where the tables have been created.
resultsFolder	The path to the folder containing the results to upload. See unzipResults for more information.
tablePrefix	String to prefix table names with - default is empty string
forceOverWriteOfSpecifications	If TRUE, specifications of the phenotypes, cohort definitions, and analysis will be overwritten if they already exist on the database. Only use this if these specifications have changed since the last upload.
purgeSiteDataBeforeUploading	If TRUE, before inserting data for a specific databaseId all the data for that site will be dropped. This assumes the results folder contains the full data for that data site.

databaseIdentifierFile

File contained that references databaseId field (used when purgeSiteDataBeforeUploading == TRUE). You may specify a relative path for the cdmsourceFile and the function will assume it resides in the resultsFolder. Alternatively, you can provide a path outside of the resultsFolder for this file.

runCheckAndFixCommands

If TRUE, the upload code will attempt to fix column names, data types and duplicate rows. This parameter is kept for legacy reasons - it is strongly recommended that you correct errors in your results where those results are assembled instead of relying on this option to try and fix it during upload.

warnOnMissingTable

Boolean, print a warning if a table file is missing.

specifications A tibble data frame object with specifications.