Results schema of the SelfControlledCaseSeries package

Martijn J. Schuemie

2022-12-14

Contents

1	\mathbf{Intr}	roduction	1
	1.1	Exposures, covariates of interest, and controls	1
	1.2	Exposures-outcome-sets, analysis IDs and models	2
	1.3	Fields with minimum values	2
2	Tab	les	2
	2.1	Table sccs_age_spanning	2
	2.2	Table sccs_analysis	2
	2.3	Table sccs_attrition	3
	2.4	Table sccs_calendar_time_spanning	3
	2.5	Table sccs_censor_model	3
	2.6	Table sccs_covariate	4
	2.7	Table sccs_covariate_analysis	4
	2.8	Table sccs_covariate_result	4
	2.9	Table sccs_diagnostics_summary	Į.
	2.10	Table sccs_era	Į.
		Table sccs_event_dep_observation	6
		Table sccs_exposure	6
		Table sccs_exposures_outcome_set	6
		Table sccs likelihood profile	7
		Table sccs_result	7
		Table sccs_spline	8
		Table sccs_time_to_event	8
		Table sccs_time_trend	C

1 Introduction

This document describes the data model of the output of the SelfControlledCaseSeries (SCCS) package, generated by the exportToCsv() function. This vignette assumes you are already familiar with the SelfControlledCaseSeries package, and have read all other vignettes.

1.1 Exposures, covariates of interest, and controls

As described in the 'Single studies using the SelfControlledCaseSeries package' vignette, eras are cohorts or drug eras extracted from the database. Covariates can either be splines, for example representing age or season, or era covariates, derived from eras. When defining covariates using the createEraCovariateSettings() function we can either use verbatim era IDs (e.g. cohort IDs), or we can reference a variable (typically called 'exposureId'). When defining exposures using the exposure() function, we can define different era IDs to be used for this variable, thereby using the same analysis settings for different exposures and outcomes. For each exposure we can set the trueEffectSize if known. Any exposure with known true effect size is considered a

control, and will be used for empirical calibration. Some of our covariates can be marked as covariates of interest by setting exposureOfInterest = TRUE when calling createEraCovariateSettings(). This is especially relevant for the results model, since these covariates will be reported in the sccs result table.

1.2 Exposures-outcome-sets, analysis IDs and models

Using the createExposuresOutcome() function we can define an outcome with one or more exposures, since an SCCS model can have multiple exposures (e.g. we could have separte exposures for the first and second dose of a vaccine). With the createSccsAnalysis() function we can create a set of settings for analysis describing which data to extract from the database, how to transform that data including which covariates to construct, and how to fit the SCCS model. Each analysis setting has a unique analysis ID. Each combination of an exposures-outcome-set and an analysis setting will correspond to one SCCS model. A model can have multiple covariates, and each covariates can be based on multiple eras.

1.3 Fields with minimum values

Some fields contain patient counts or fractions that can easily be converted to patient counts. To prevent identifiability, these fields are subject to a minimum value. When the value falls below this minimum, it is replaced with the negative value of the minimum. For example, if the minimum subject count is 5, and the actual count is 2, the value stored in the data model will be -5, which could be represented as '<5' to the user. Note that the value 0 is permissible, as it identifies no persons. These fields are identified below as having Min. count = 'Yes'.

2 Tables

In this section you will find the list of tables and their fields.

2.1 Table sccs age spanning

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set_	_iiht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
age_month	int	Yes	No	Age in months since birth.
cover_before_after_subj	int	No	Yes	Number of subjects whose observation period covers this month as well as the one before and after.

2.2 Table sccs_analysis

Field	Туре	Key	Min. count	Description
analysis_id	int	Yes	No	A unique identifier for an analysis.
description	varchar	No	No	A description for an analysis, e.g. 'Correcting for age and season'.

definition	varchar	No	No	A JSON object specifying the
				analysis.

2.3 Table sccs_attrition

Field	Type	Key	Min. count	Description
sequence_number	int	Yes	No	The place in the sequence of steps defining the final analysis cohort. 1 indicates the original exposed population without any inclusion criteria.
description	varchar	No	No	A description of the last restriction, e.g. "Removing persons with the outcome prior".
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set_	_i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
$covariate_id$	int	Yes	No	A foreign key referencing the sccs_covariate table. The identifier for the covariate of interest.
database_id	varchar	Yes	No	Foreign key referencing the database.
outcome_subjects	int	No	Yes	The number of subjects with at least one outcome.
outcome_events	int	No	Yes	The number of outcome events.
outcome_observation_pe	int	No	Yes	The number of observation periods containing at least one outcome.
observed_days	int	No	Yes	The number of days subjects were observed.

${\bf 2.4}\quad {\bf Table~sccs_calendar_time_spanning}$

Field	Type	Key	Min.	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_se	t_iiht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
calendar_year	$_{ m int}$	Yes	No	Calendar year (e.g. 2022)
calendar_month	int	Yes	No	Calendar month (e.g. 1 is January).
cover_before_after_su	bje ats t	No	Yes	Number of subjects whose observation period covers this month as well as the one before and after.

${\bf 2.5}\quad {\bf Table~sccs_censor_model}$

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set_	_i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
parameter_id	int	Yes	No	The parameter number in the censor model (starting at 1).
parameter_value	float	No	No	The fitted parameter value.
model_type	varchar	No	No	The type of censor model. Can be 'Weibull-Age'. 'Weibull-Interval', 'Gamma-Age', or 'Gamma-Interval'.

2.6 Table sccs_covariate

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set	_i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
covariate_id	int	Yes	No	A unique identifier for a covariate.
covariate_name	varchar	No	No	A description for the covariate.
era_id	int	No	No	A foreign key referencing the sccs_era table.
covariate_analysis_id	int	No	No	A foreign key referencing the sccs_covariate_analysis table.
database_id	varchar	Yes	No	Foreign key referencing the database.

${\bf 2.7}\quad {\bf Table~sccs_covariate_analysis}$

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
covariate_analysis_id	int	Yes	No	A unique identifier for a covariate analysis.
covariate_analysis_name	varchar	No	No	A name for a covariate analysis, e.g. 'Pre-exposure'.
$variable_of_interest$	int	No	No	Is the variable of interest $(1 = yes, 0 = no)$.

${\bf 2.8}\quad {\bf Table~sccs_covariate_result}$

Field	Type	Key	Min.	Description
			count	

analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set	_i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
covariate_id	int	Yes	No	The identifier for the covariate.
rr	float	No	No	The estimated relative risk (i.e. the incidence rate ratio).
ci_95_lb	float	No	No	The lower bound of the 95% confidence interval of the relative risk.
ci_95_ub	float	No	No	The upper bound of the 95% confidence interval of the relative risk.

2.9 Table sccs_diagnostics_summary

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set_	_iiht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
covariate_id	int	Yes	No	The identifier for the covariate of interest.
$database_id$	varchar	Yes	No	Foreign key referencing the database.
mdrr	float	No	No	The minimum detectable relative risk.
ease	float	No	No	The expected absolute systematic error.
time_trend_p	float	No	No	The family-wise p for whether the monthly outcome rate is equal to the mean.
pre_exposure_p	float	No	No	One-sided p-value for whether the rate before expore is higher than after, against the null of no difference.
mdrr_diagnostic	varchar(20)	No	No	Pass / warning / fail / not evaluated classification of the MDRR diagnostic.
ease_diagnostic	varchar(20)	No	No	Pass / warning / fail / not evaluated classification of the EASE diagnostic.
$time_trend_diagnostic$	varchar(20)	No	No	Pass / warning / fail / not evaluated classification of the time trend (unstalbe months) diagnostic.
pre_exposure_diagnostic	varchar(20)	No	No	Pass / warning / fail / not evaluated classification of the time trend (unstalbe months) diagnostic.
unblind	int	No	No	Is unblinding the result recommended? $(1 = yes, 0 = no)$

2.10 Table sccs_era

Field	Туре	Key	Min.	Description
exposures_outcome_set_	int	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
analysis_id	int	Yes	No	A unique identifier for an analysis.
era_type	varchar	Yes	No	The type of era (e.g. 'rx' for drugs).
era_id	int	Yes	No	A unique identifier, corresponding to the ID in the source table (e.g. cohort_definition_id in a cohort table, or the drug_concept_id in the drug_era table).
era_name	varchar	No	No	A name for the era. Is NULL for eras derived from cohorts.
database_id	varchar	Yes	No	Foreign key referencing the database.

2.11 Table sccs_event_dep_observation

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set_	_i t ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
months_to_end	int	Yes	No	Number of months until observation end.
censored	int	Yes	No	Whether the observation is censored (meaning, not equal to the end of database time). (1 = censored, 0 = not censored).
outcomes	int	No	Yes	Number of outcomes observed during the month.

$2.12 \quad \text{Table sccs_exposure}$

Field	Type	Key	Min.	Description
exposures_outcome_set_	int	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
era_id	int	Yes	No	A foreign key referencing the sccs_era table.
true_effect_size	float	No	No	If known, the true effect size. For negatitive controls this equals 1.

${\bf 2.13}\quad {\bf Table~sccs_exposures_outcome_set}$

Field	Type	Key	Min. count	Description
exposures_outcome_set_	int	Yes	No	A unique identifier for a set of exposures and an outcome.
outcome_id	int	No	No	A cohort ID.

${\bf 2.14 \quad Table \ sccs_likelihood_profile}$

Field	Туре	Key	Min. count	Description
log_rr	float	Yes	No	The log of the relative risk where the likelihood is sampled.
log_likelihood	float	No	No	The normalized log likelihood.
covariate_id	int	Yes	No	The identifier for the covariate of interest.
exposures_outcome_set	i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
database_id	varchar	Yes	No	Foreign key referencing the database.

${\bf 2.15}\quad {\bf Table~sccs_result}$

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_se	ti i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
covariate_id	int	Yes	No	A foreign key referencing the sccs_covariate table. The identifier for the covariate of interest.
rr	float	No	No	The estimated relative risk (i.e. the incidence rate ratio).
ci_95_lb	float	No	No	The lower bound of the 95% confidence interval of the relative risk.
ci_95_ub	float	No	No	The upper bound of the 95% confidence interval of the relative risk.
p	float	No	No	The two-sided p-value considering the null hypothesis of no effect.
$outcome_subjects$	$_{ m int}$	No	Yes	The number of subjects with at least one outcome.
outcome_events	int	No	Yes	The number of outcome events.
$outcome_observation_$	perionds	No	Yes	The number of observation periods containing at least one outcome.
covariate_subjects	int	No	Yes	The number of subjects having the covariate.

$covariate_days$	int	No	Yes	The total covariate time in days.
covariate_eras	int	No	Yes	The number of continuous eras of the covariate.
covariate_outcomes	int	No	Yes	The number of outcomes observed during the covariate time.
observed_days	int	No	Yes	The number of days subjects were observed.
log_rr	float	No	No	The log of the relative risk.
se_log_rr	float	No	No	The standard error of the log of the relative risk.
llr	float	No	No	The log of the likelihood ratio (of the MLE vs the null hypothesis of no effect).
calibratedrr	float	No	No	The calibrated relative risk.
calibrated_ci_95_lb	float	No	No	The lower bound of the calibrated 95% confidence interval of the relative risk.
calibrated_ci_95_ub	float	No	No	The upper bound of the calibrated 95% confidence interval of the relative risk.
calibrated_p	float	No	No	The calibrated two-sided p-value.
calibrated_log_rr	float	No	No	The log of the calibrated relative risk.
$calibrated_se_log_rr$	float	No	No	The standard error of the log of the calibrated relative risk.
database_id	varchar	Yes	No	Foreign key referencing the database.

${\bf 2.16}\quad {\bf Table~sccs_spline}$

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set	_i ċ ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
spline_type	varchar	Yes	No	Either 'age', 'season', or 'calendar time'.
knot_month	int	Yes	No	Location of the knot. For age, the month since birth. For season, the month of the year. For calendar time, the month since 1-1-1970.
rr	float	No	No	The estimated relative risk (i.e. the incidence rate ratio).

${\bf 2.17}\quad {\bf Table~sccs_time_to_event}$

Field	Туре	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.

exposures_outcome_set	_i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
era_id	int	Yes	No	A foreign key referencing the sccs_era table. The identifier for the era of interest.
week	int	Yes	No	The number of the week relative to exposure. Week 0 starts on the day of exposure initiation.
observed_subjects	int	No	Yes	The numer of people observed during the week.
outcomes	int	No	Yes	The number of outcomes observed durig the week.

${\bf 2.18}\quad {\bf Table~sccs_time_trend}$

Field	Type	Key	Min. count	Description
analysis_id	int	Yes	No	A foreign key referencing the sccs_analysis table.
exposures_outcome_set	_i i ht	Yes	No	A foreign key referencing the sccs_exposures_outcome_set table.
database_id	varchar	Yes	No	Foreign key referencing the database.
calendar_year	int	Yes	No	The calendar year (e.g. 2022).
calendar_month	int	Yes	No	The calendar month (e.g. 1 for January).
observed_subjects	int	No	Yes	Number of people observed during the month.
outcome_rate	float	No	Yes	Number of outcomes divided by the number of subjects.
$adjusted_rate$	float	No	Yes	The outcome rate, adjusted for age, season, or calendar time, as specified in the analysis.
stable	int	No	No	Does the adjusted rate not deviate significantly from the mean? $(1 = \text{stable}, 0 = \text{unstable})$
р	float	No	No	The two-sided p-value against the null hypothesis that the rate is equal to the mean.