

# Package ‘SelfControlledCaseSeries’

March 22, 2021

**Type** Package

**Title** Self-Controlled Case Series

**Version** 3.0.0

**Date** 2021-03-22

**Maintainer** Martijn Schuemie <schuemie@ohdsi.org>

**Description** SelfControlledCaseSeries is an R package for performing self-controlled case series (SCCS) analyses in an observational database in the OMOP Common Data Model. It extracts all necessary data from the database and transforms it to the format required for SCCS. Age and season can be modeled using splines assuming constant hazard within calendar months. Event-dependent censoring of the observation period can be corrected for. Many exposures can be included at once (MSCCS), with regularization on all coefficients except for the exposure of interest.

**VignetteBuilder** knitr

**URL** <https://github.com/OHDSI/SelfControlledCaseSeries>

**BugReports** <https://github.com/OHDSI/SelfControlledCaseSeries/issues>

**Depends** R (>= 3.2.2),  
Cyclops (>= 3.0.0),  
DatabaseConnector (>= 4.0.0),  
Andromeda

**Imports** SqlRender (>= 1.6.0),  
dplyr (>= 1.0.0),  
Rcpp (>= 0.11.2),  
ParallelLogger (>= 2.0.0),  
splines,  
ggplot2,  
methods,  
cli,  
pillar

**Suggests** testthat,  
knitr,  
rmarkdown,  
EmpiricalCalibration

**Remotes** ohdsi/EmpiricalCalibration

**License** Apache License 2.0

**LinkingTo** Rcpp

**NeedsCompilation** yes

**RoxygenNote** 7.1.1

**Roxygen** list(markdown = TRUE)

**Encoding** UTF-8

## R topics documented:

computeMdr	3
createAgeCovariateSettings	4
createControlIntervalSettings	4
createCreateSccsIntervalDataArgs	5
createCreateScriIntervalDataArgs	6
createCreateStudyPopulationArgs	7
createEraCovariateSettings	7
createExposureOutcome	9
createFitSccsModelArgs	9
createGetDbSccsDataArgs	10
createSccsAnalysis	11
createSccsIntervalData	12
createSccsSimulationSettings	13
createScriIntervalData	14
createSeasonalityCovariateSettings	15
createSimulationRiskWindow	16
createStudyPopulation	17
cyclicSplineDesign	18
fitSccsModel	18
getAttritionTable	19
getDbSccsData	19
getModel	22
isSccsData	23
isSccsIntervalData	23
loadExposureOutcomeList	24
loadSccsAnalysisList	24
loadSccsData	25
loadSccsIntervalData	25
plotAgeEffect	26
plotAgeSpans	26
plotEventObservationDependence	27
plotEventToCalendarTime	28
plotExposureCentered	28
plotSeasonality	29
runSccsAnalyses	29
saveExposureOutcomeList	32
saveSccsAnalysisList	32
saveSccsData	33
saveSccsIntervalData	33
SccsData-class	34
SccsIntervalData-class	34
simulateSccsData	35
summarizeSccsAnalyses	35

---

computeMdr*Compute the minimum detectable relative risk*

---

### Description

Compute the minimum detectable relative risk

### Usage

```
computeMdr(  
  sccsIntervalData,  
  exposureCovariateId,  
  alpha = 0.05,  
  power = 0.8,  
  twoSided = TRUE,  
  method = "binomial"  
)
```

### Arguments

sccsIntervalData	An object of type <a href="#">SccsIntervalData</a> as created using the <a href="#">createSccsIntervalData</a> function.
exposureCovariateId	Covariate Id for the health exposure of interest.
alpha	Type I error.
power	1 - beta, where beta is the type II error.
twoSided	Consider a two-sided test?
method	The type of sample size formula that will be used. Allowable values are "proportion", "binomial", "SRL1", "SRL2", or "ageEffects". Currently "ageEffects" is not supported.

### Details

Compute the minimum detectable relative risk (MDRR) for a given study population, using the observed time at risk and total time in days and number of events. Five sample size formulas are implemented: sampling proportion, binomial proportion, 2 signed root likelihood ratio methods, and likelihood extension for age effects. The expressions by Musonda (2006) are used.

### Value

A data frame with the MDRR, number of events, time at risk, and total time.

### References

Musonda P, Farrington CP, Whitaker HJ (2006) Samples sizes for self-controlled case series studies, *Statistics in Medicine*, 15;25(15):2618-31

---

```
createAgeCovariateSettings
```

*Create age covariate settings*

---

### Description

Create age covariate settings

### Usage

```
createAgeCovariateSettings(  
  ageKnots = 5,  
  allowRegularization = FALSE,  
  computeConfidenceIntervals = FALSE  
)
```

### Arguments

ageKnots	If a single number is provided this is assumed to indicate the number of knots to use for the spline, and the knots are automatically spaced according to equal percentiles of the data. If more than one number is provided these are assumed to be the exact location of the knots in age-days
allowRegularization	When fitting the model, should the covariates defined here be allowed to be regularized?
computeConfidenceIntervals	Should confidence intervals be computed for the covariates defined here? Setting this to FALSE might save computing time when fitting the model. Will be turned to FALSE automatically when allowRegularization = TRUE.

### Details

Create an object specifying whether and how age should be included in the model. Age can be included by splitting patient time into calendar months. During a month, the relative risk attributed to age is assumed to be constant, and the risk from month to month is modeled using a cubic spline.

### Value

An object of type AgeCovariateSettings.

---

```
createControlIntervalSettings
```

*Create control interval settings*

---

### Description

Create control interval settings

**Usage**

```
createControlIntervalSettings(
  includeEraIds = NULL,
  excludeEraIds = NULL,
  start = 0,
  startAnchor = "era start",
  end = 0,
  endAnchor = "era end",
  firstOccurrenceOnly = FALSE
)
```

**Arguments**

includeEraIds	One or more IDs of variables in the <a href="#">SccsData</a> object that should be used to construct this covariate. If no IDs are specified, all variables will be used.
excludeEraIds	One or more IDs of variables in the [SccsData] object that should not be used to construct this covariate.
start	The start of the control interval (in days) relative to the startAnchor.
startAnchor	The anchor point for the start of the control interval. Can be "era start" or "era end".
end	The end of the control interval (in days) relative to the endAnchor.
endAnchor	The anchor point for the end of the control interval. Can be "era start" or "era end".
firstOccurrenceOnly	Should only the first occurrence of the exposure be used?

**Details**

Create an object specifying how to create a control interval for the self-controlled risk interval (SCRI) design.

**Value**

An object of type ControlSettings.

---

```
createCreateSccsIntervalDataArgs
```

*Create a parameter object for the function createSccsIntervalData*

---

**Description**

Create a parameter object for the function createSccsIntervalData

**Usage**

```
createCreateSccsIntervalDataArgs(
  eraCovariateSettings,
  ageCovariateSettings = NULL,
  seasonalityCovariateSettings = NULL,
  minCasesForAgeSeason = 10000,
  eventDependentObservation = FALSE
)
```

**Arguments****eraCovariateSettings**

Either an object of type EraCovariateSettings as created using the createEraCovariateSettings() function, or a list of such objects.

**ageCovariateSettings**

An object of type ageCovariateSettings as created using the createAgeCovariateSettings() function.

**seasonalityCovariateSettings**

An object of type seasonalityCovariateSettings as created using the createSeasonalityCovariateSettings() function.

**minCasesForAgeSeason**

Minimum number of cases to use to fit age and season splines. If needed (and available), cases that are not exposed will be included.

**eventDependentObservation**

Should the extension proposed by Farrington et al. be used to adjust for event-dependent observation time?

**Details**

Create an object defining the parameter values.

---

**createCreateScriIntervalDataArgs**

*Create a parameter object for the function createScriIntervalData*

---

**Description**

Create a parameter object for the function createScriIntervalData

**Usage**

```
createCreateScriIntervalDataArgs(eraCovariateSettings, controlIntervalSettings)
```

**Arguments****eraCovariateSettings**

Either an object of type EraCovariateSettings as created using the createEraCovariateSettings() function, or a list of such objects.

**controlIntervalSettings**

An object of type ControlIntervalSettings as created using the createControlIntervalSettings() function.

**Details**

Create an object defining the parameter values.

---

```
createCreateStudyPopulationArgs
```

*Create a parameter object for the function createStudyPopulation*

---

## Description

Create a parameter object for the function createStudyPopulation

## Usage

```
createCreateStudyPopulationArgs(  
  firstOutcomeOnly = FALSE,  
  naivePeriod = 0,  
  minAge = NULL,  
  maxAge = NULL  
)
```

## Arguments

firstOutcomeOnly	Whether only the first occurrence of an outcome should be considered.
naivePeriod	The number of days at the start of a patient's observation period that should not be included in the risk calculations. Note that the naive period can be used to determine current covariate status right after the naive period, and whether an outcome is the first one.
minAge	Minimum age at which patient time will be included in the analysis. Note that information prior to the min age is still used to determine exposure status after the minimum age (e.g. when a prescription was started just prior to reaching the minimum age). Also, outcomes occurring before the minimum age is reached will be considered as prior outcomes when using first outcomes only. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.
maxAge	Maximum age at which patient time will be included in the analysis. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.

## Details

Create an object defining the parameter values.

---

```
createEraCovariateSettings
```

*Create era covariate settings*

---

## Description

Create era covariate settings

**Usage**

```
createEraCovariateSettings(
  includeEraIds = NULL,
  excludeEraIds = NULL,
  label = "Covariates",
  stratifyById = TRUE,
  start = 0,
  startAnchor = "era start",
  end = 0,
  endAnchor = "era end",
  firstOccurrenceOnly = FALSE,
  splitPoints = c(),
  allowRegularization = FALSE
)
```

**Arguments**

includeEraIds	One or more IDs of variables in the <a href="#">SccsData</a> object that should be used to construct this covariate. If no IDs are specified, all variables will be used.
excludeEraIds	One or more IDs of variables in the [SccsData] object that should not be used to construct this covariate.
label	A label used to identify the covariates created using these settings.
stratifyById	Should a single covariate be created for every ID in the <a href="#">SccsData</a> object, or should a single covariate be constructed? For example, if the IDs identify exposures to different drugs, should a covariate be constructed for every drug, or a single covariate for exposure to any of these drugs. Note that overlap will be considered a single exposure.
start	The start of the risk window (in days) relative to the startAnchor.
startAnchor	The anchor point for the start of the risk window. Can be "era start" or "era end".
end	The end of the risk window (in days) relative to the endAnchor.
endAnchor	The anchor point for the end of the risk window. Can be "era start" or "era end".
firstOccurrenceOnly	Should only the first occurrence of the exposure be used?
splitPoints	To split the risk window into several smaller windows, specify the end of each sub-window relative to the start of the main risk window. If add Exposed-DaysToStart is TRUE, the split points will be considered to be relative to the end of the main risk window instead.
allowRegularization	When fitting the model, should the covariates defined here be allowed to be regularized?

**Details**

Create an object specifying how to create a (set of) era-based covariates.

**Value**

An object of type EraCovariateSettings.



---

createExposureOutcome *Create a exposure-outcome combination.*

---

### Description

Create a exposure-outcome combination.

### Usage

```
createExposureOutcome(exposureId, outcomeId, ...)
```

### Arguments

exposureId	A concept ID identifying the target drug in the exposure table. If multiple strategies for picking the exposure will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the exposureType parameter in the <a href="#">createSccsAnalysis</a> function.
outcomeId	A concept ID identifying the outcome in the outcome table.
...	Custom variables, to be used in the analyses.

### Details

Create a set of hypotheses of interest, to be used with the [runSccsAnalyses](#) function.

---

createFitSccsModelArgs  
*Create a parameter object for the function fitSccsModel*

---

### Description

Create a parameter object for the function fitSccsModel

### Usage

```
createFitSccsModelArgs(
  prior = createPrior("laplace", useCrossValidation = TRUE),
  control = createControl(cvType = "auto", selectorType = "byPid", startingVariance =
    0.1, noiseLevel = "quiet")
)
```

### Arguments

prior	The prior used to fit the model. See Cyclops::createPrior for details.
control	The control object used to control the cross-validation used to determine the hyperparameters of the prior (if applicable). See Cyclops::createControl for details.

### Details

Create an object defining the parameter values.

---

```
createGetDbSccsDataArgs
```

*Create a parameter object for the function getDbSccsData*

---

## Description

Create a parameter object for the function getDbSccsData

## Usage

```
createGetDbSccsDataArgs(
  useCustomCovariates = FALSE,
  useNestingCohort = FALSE,
  nestingCohortId = NULL,
  deleteCovariatesSmallCount = 100,
  studyStartDate = "",
  studyEndDate = "",
  maxCasesPerOutcome = 0,
  exposureIds = "exposureId",
  customCovariateIds = ""
)
```

## Arguments

useCustomCovariates	Create covariates from a custom table?
useNestingCohort	Should the study be nested in a cohort (e.g. people with a specific indication)? If not, the study will be nested in the general population.
nestingCohortId	A cohort definition ID identifying the records in the nestingCohortTable to use as nesting cohort.
deleteCovariatesSmallCount	The minimum count for a covariate to appear in the data to be kept.
studyStartDate	A calendar date specifying the minimum date where data is used. Date format is 'yyyymmdd'.
studyEndDate	A calendar date specifying the maximum date where data is used. Date format is 'yyyymmdd'.
maxCasesPerOutcome	If there are more than this number of cases for a single outcome cases will be sampled to this size. maxCasesPerOutcome = 0 indicates no maximum size.
exposureIds	A list of identifiers to define the exposures of interest. If exposureTable = DRUG_ERA, exposureIds should be CONCEPT_ID. If exposureTable <> DRUG_ERA, exposureIds is used to select the cohort_concept_id in the cohort-like table. If no exposureIds are provided, all drugs or cohorts in the exposureTable are included as exposures.
customCovariateIds	A list of cohort definition IDS identifying the records in the customCovariateTable to use for building custom covariates.

## Details

Create an object defining the parameter values.

---

createSccsAnalysis	<i>Create a SelfControlledCaseSeries analysis specification</i>
--------------------	---

---

## Description

Create a SelfControlledCaseSeries analysis specification

## Usage

```
createSccsAnalysis(
  analysisId = 1,
  description = "",
  exposureType = NULL,
  outcomeType = NULL,
  getDbSccsDataArgs,
  createStudyPopulationArgs,
  design = "SCCS",
  createSccsIntervalDataArgs = NULL,
  createScriIntervalDataArgs = NULL,
  fitSccsModelArgs
)
```

## Arguments

analysisId	An integer that will be used later to refer to this specific set of analysis choices.
description	A short description of the analysis.
exposureType	If more than one exposure is provided for each exposureOutcome, this field should be used to select the specific exposure to use in this analysis.
outcomeType	If more than one outcome is provided for each exposureOutcome, this field should be used to select the specific outcome to use in this analysis.
getDbSccsDataArgs	An object representing the arguments to be used when calling the <a href="#">getDbSccsData</a> function.
createStudyPopulationArgs	An object representing the arguments to be used when calling the <a href="#">getDbSccsData</a> function.
design	Either "SCCS" for the general self-controlled case series design, or "SCRI" for the self-controlled risk interval design.
createSccsIntervalDataArgs	An object representing the arguments to be used when calling the <a href="#">createSccsIntervalData</a> function. Ignored when design = "SCRI".
createScriIntervalDataArgs	An object representing the arguments to be used when calling the <a href="#">createScriIntervalData</a> function. Ignored when design = "SCCS".
fitSccsModelArgs	An object representing the arguments to be used when calling the <a href="#">fitSccsModel</a> function.

## Details

Create a set of analysis choices, to be used with the [runSccsAnalyses](#) function.

---

```
createSccsIntervalData
```

*Create SCCS era data*

---

## Description

Create SCCS era data

## Usage

```
createSccsIntervalData(
  studyPopulation,
  sccsData,
  eraCovariateSettings,
  ageCovariateSettings = NULL,
  seasonalityCovariateSettings = NULL,
  minCasesForAgeSeason = 10000,
  eventDependentObservation = FALSE
)
```

## Arguments

**studyPopulation**

An object created using the [createStudyPopulation\(\)](#) function.

**sccsData**

An object of type [SccsData](#) as created using the [getDbSccsData](#) function.

**eraCovariateSettings**

Either an object of type [EraCovariateSettings](#) as created using the [createEraCovariateSettings](#) function, or a list of such objects.

**ageCovariateSettings**

An object of type [ageCovariateSettings](#) as created using the [createAgeCovariateSettings\(\)](#) function.

**seasonalityCovariateSettings**

An object of type [seasonalityCovariateSettings](#) as created using the [createSeasonalityCovariateSettings](#) function.

**minCasesForAgeSeason**

Minimum number of cases to use to fit age and season splines. If needed (and available), cases that are not exposed will be included.

**eventDependentObservation**

Should the extension proposed by Farrington et al. be used to adjust for event-dependent observation time?

## Details

This function creates covariates based on the data in the `sccsData` argument, according to the provided settings. It chops patient time into periods during which all covariates remain constant. The output details these periods, their durations, and a sparse representation of the covariate values.

**Value**

An object of type [SccsIntervalData](#).

**References**

Farrington, C. P., Anaya-Izquierdo, A., Whitaker, H. J., Hocine, M.N., Douglas, I., and Smeeth, L. (2011). Self-Controlled case series analysis with event-dependent observation periods. *Journal of the American Statistical Association* 106 (494), 417-426

---

```
createSccsSimulationSettings
```

*Create SCCS simulation settings*

---

**Description**

Create SCCS simulation settings

**Usage**

```
createSccsSimulationSettings(
  meanPatientTime = 4 * 365,
  sdPatientTime = 2 * 365,
  minAge = 18 * 365,
  maxAge = 65 * 365,
  minBaselineRate = 0.001,
  maxBaselineRate = 0.01,
  eraIds = c(1, 2),
  patientUsages = c(0.2, 0.1),
  usageRate = c(0.01, 0.01),
  meanPrescriptionDurations = c(14, 30),
  sdPrescriptionDurations = c(7, 14),
  simulationRiskWindows = list(createSimulationRiskWindow(relativeRisks = 1),
    createSimulationRiskWindow(relativeRisks = 1.5)),
  includeAgeEffect = TRUE,
  ageKnots = 5,
  includeSeasonality = TRUE,
  seasonKnots = 5,
  outcomeId = 10
)
```

**Arguments**

meanPatientTime	Mean number of observation days per patient.
sdPatientTime	Standard deviation of the observation days per patient.
minAge	The minimum age in days.
maxAge	The maximum age in days.
minBaselineRate	The minimum baseline rate (per day).

maxBaselineRate	The maximum baseline rate (per day).
eraIds	The IDs for the covariates to be generated.
patientUsages	The fraction of patients that use the drugs.
usageRate	The rate of prescriptions per person that uses the drug.
meanPrescriptionDurations	The mean duration of a prescription, per drug.
sdPrescriptionDurations	The standard deviation of the duration of a prescription, per drug.
simulationRiskWindows	One or a list of objects of type <code>simulationRiskWindow</code> as created using the <a href="#">createSimulationRiskWindow</a> function.
includeAgeEffect	Include an age effect for the outcome?
ageKnots	Number of knots in the age spline.
includeSeasonality	Include seasonality for the outcome?
seasonKnots	Number of knots in the seasonality spline.
outcomeId	The ID to be used for the outcome.

### Details

Create an object of settings for an SCCS simulation.

### Value

An object of type `sccsSimulationSettings`.

---

`createScriIntervalData`

*Create Self-Controlled Risk Interval (SCRI) era data*

---

### Description

Create Self-Controlled Risk Interval (SCRI) era data

### Usage

```
createScriIntervalData(
  studyPopulation,
  sccsData,
  eraCovariateSettings,
  controlIntervalSettings
)
```

**Arguments**

studyPopulation

An object created using the [createStudyPopulation\(\)](#) function.

sccsData

An object of type [SccsData](#) as created using the [getDbSccsData](#) function.

eraCovariateSettings

Either an object of type EraCovariateSettings as created using the [createEraCovariateSettings](#) function, or a list of such objects.

controlIntervalSettings

An object of type ControlIntervalSettings as created using the [createControlIntervalSettings](#) function.**Details**

This function creates interval data according to the elf-Controlled Risk Interval (SCRI) design. Unlike the generic SCCS design, where all patient time is used to establish a background rate, in the SCRI design a specific control interval (relative to the exposure) needs to be defined. The final model will only include time that is either part of the risk interval (defined using the eraCovariateSettings argument, or the control interval (defined using controlIntervalSettings).

**Value**An object of type [SccsIntervalData](#).**References**

Greene SK, Kulldorff M, Lewis EM, Li R, Yin R, Weintraub ES, Fireman BH, Lieu TA, Nordin JD, Glanz JM, Baxter R, Jacobsen SJ, Broder KR, Lee GM. Near real-time surveillance for influenza vaccine safety: proof-of-concept in the Vaccine Safety Datalink Project. Am J Epidemiol. 2010 Jan 15;171(2):177-88. doi: 10.1093/aje/kwp345.

---

createSeasonalityCovariateSettings

*Create seasonality settings*


---

**Description**

Create seasonality settings

**Usage**

```
createSeasonalityCovariateSettings(
  seasonKnots = 5,
  allowRegularization = FALSE,
  computeConfidenceIntervals = FALSE
)
```

**Arguments**

- seasonKnots** If a single number is provided this is assumed to indicate the number of knots to use for the spline, and the knots are automatically equally spaced across the year. If more than one number is provided these are assumed to be the exact location of the knots in days relative to the start of the year.
- allowRegularization** When fitting the model, should the covariates defined here be allowed to be regularized?
- computeConfidenceIntervals** Should confidence intervals be computed for the covariates defined here? Setting this to FALSE might save computing time when fitting the model. Will be turned to FALSE automatically when allowRegularization = TRUE.

**Details**

Create an object specifying whether and how seasonality should be included in the model. Seasonality can be included by splitting patient time into calendar months. During a month, the relative risk attributed to season is assumed to be constant, and the risk from month to month is modeled using a cyclic cubic spline.

**Value**

An object of type `seasonalitySettings`.

---

`createSimulationRiskWindow`

*Create a risk window definition for simulation*

---

**Description**

Create a risk window definition for simulation

**Usage**

```
createSimulationRiskWindow(
  start = 0,
  end = 0,
  endAnchor = "era end",
  splitPoints = c(),
  relativeRisks = c(0)
)
```

**Arguments**

- start** Start of the risk window relative to exposure start.
- end** The end of the risk window (in days) relative to the endAnchor.
- endAnchor** The anchor point for the end of the risk window. Can be "era start" or "era end".
- splitPoints** Subdivision of the risk window in to smaller sub-windows.
- relativeRisks** Either a single number representing the relative risk in the risk window, or when splitPoints have been defined a vector of relative risks, one for each sub-window.



**Value**

An object of type `simulationRiskWindow`.

---

`createStudyPopulation`    *Create a study population*

---

**Description**

Create a study population

**Usage**

```
createStudyPopulation(
  sccsData,
  outcomeId = NULL,
  firstOutcomeOnly = FALSE,
  naivePeriod = 0,
  minAge = NULL,
  maxAge = NULL
)
```

**Arguments**

<code>sccsData</code>	An object of type <a href="#">SccsData</a> as created using the <a href="#">getDbSccsData</a> function.
<code>outcomeId</code>	The outcome to create the era data for. If not specified it is assumed to be the one outcome for which the data was loaded from the database.
<code>firstOutcomeOnly</code>	Whether only the first occurrence of an outcome should be considered.
<code>naivePeriod</code>	The number of days at the start of a patient's observation period that should not be included in the risk calculations. Note that the naive period can be used to determine current covariate status right after the naive period, and whether an outcome is the first one.
<code>minAge</code>	Minimum age at which patient time will be included in the analysis. Note that information prior to the min age is still used to determine exposure status after the minimum age (e.g. when a prescription was started just prior to reaching the minimum age). Also, outcomes occurring before the minimum age is reached will be considered as prior outcomes when using first outcomes only. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.
<code>maxAge</code>	Maximum age at which patient time will be included in the analysis. Age should be specified in years, but non-integer values are allowed. If not specified, no age restriction will be applied.

---

cyclicSplineDesign	<i>Create a design matrix for a cyclic spline</i>
--------------------	---

---

**Description**

Create a design matrix for a cyclic spline

**Usage**

```
cyclicSplineDesign(x, knots, ord = 4)
```

**Arguments**

x	Vector of coordinates of the points to be interpolated.
knots	Location of the knots.
ord	Order of the spline function.

**Details**

This function is used by other functions in this package.

---

fitScCsModel	<i>Fit the SCCS model</i>
--------------	---------------------------

---

**Description**

Fit the SCCS model

**Usage**

```
fitScCsModel(
  scCsIntervalData,
  prior = createPrior("laplace", useCrossValidation = TRUE),
  control = createControl(cvType = "auto", selectorType = "byPid", startingVariance =
    0.1, noiseLevel = "quiet")
)
```

**Arguments**

scCsIntervalData	An object of type <a href="#">ScCsIntervalData</a> as created using the <a href="#">createScCsIntervalData</a> function.
prior	The prior used to fit the model. See <a href="#">Cyclops::createPrior</a> for details.
control	The control object used to control the cross-validation used to determine the hyperparameters of the prior (if applicable). See <a href="#">Cyclops::createControl</a> for details.

**Details**

Fits the SCCS model as a conditional Poisson regression. When allowed, coefficients for some or all covariates can be regularized.

**Value**

An object of type `SccsModel`. Generic functions `print`, `coef`, and `confint` are available.

**References**

Suchard, M.A., Simpson, S.E., Zorych, I., Ryan, P., and Madigan, D. (2013). Massive parallelization of serial inference algorithms for complex generalized linear models. *ACM Transactions on Modeling and Computer Simulation* 23, 10

---

getAttritionTable	<i>Get the attrition table for a population</i>
-------------------	---

---

**Description**

Get the attrition table for a population

**Usage**

```
getAttritionTable(object)
```

**Arguments**

object	Either an object of type <code>SccsData</code> , a population object generated by functions like <code>createStudyPopulation</code> , or an object of type <code>outcomeModel</code> .
--------	--

**Value**

A tibble specifying the number of people and exposures in the population after specific steps of filtering.

---

getDbSccsData	<i>Load data for SCCS from the database</i>
---------------	---

---

**Description**

Load all data needed to perform an SCCS analysis from the database.

## Usage

```
getDbScCsData(
  connectionDetails,
  cdmDatabaseSchema,
  oracleTempSchema = cdmDatabaseSchema,
  outcomeDatabaseSchema = cdmDatabaseSchema,
  outcomeTable = "condition_era",
  outcomeIds,
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  exposureIds = c(),
  useCustomCovariates = FALSE,
  customCovariateDatabaseSchema = cdmDatabaseSchema,
  customCovariateTable = "cohort",
  customCovariateIds = c(),
  useNestingCohort = FALSE,
  nestingCohortDatabaseSchema = cdmDatabaseSchema,
  nestingCohortTable = "cohort",
  nestingCohortId = NULL,
  deleteCovariatesSmallCount = 100,
  studyStartDate = "",
  studyEndDate = "",
  cdmVersion = "5",
  maxCasesPerOutcome = 0
)
```

## Arguments

connectionDetails

An R object of type ConnectionDetails created using the function `DatabaseConnector::createConnectionDetails` function.

cdmDatabaseSchema

The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm\_instance.dbo'.

oracleTempSchema

A schema where temp tables can be created in Oracle.

outcomeDatabaseSchema

The name of the database schema that is the location where the data used to define the outcome cohorts is available. If outcomeTable = CONDITION\_ERA, outcomeDatabaseSchema is not used. Requires read permissions to this database.

outcomeTable

The tablename that contains the outcome cohorts. If outcomeTable is not CONDITION\_OCCURRENCE or CONDITION\_ERA, then expectation is outcomeTable has format of COHORT table: COHORT\_DEFINITION\_ID, SUBJECT\_ID, COHORT\_START\_DATE, COHORT\_END\_DATE.

outcomeIds

A list of ids used to define outcomes. If outcomeTable = CONDITION\_OCCURRENCE, the list is a set of ancestor CONCEPT\_IDs, and all occurrences of all descendant concepts will be selected. If outcomeTable <> CONDITION\_OCCURRENCE, the list contains records found in COHORT\_DEFINITION\_ID field.

exposureDatabaseSchema

The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG\_ERA,

	exposureDatabaseSchema is not used but assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
exposureIds	A list of identifiers to define the exposures of interest. If exposureTable = DRUG_ERA, exposureIds should be CONCEPT_ID. If exposureTable <> DRUG_ERA, exposureIds is used to select the cohort_concept_id in the cohort-like table. If no exposureIds are provided, all drugs or cohorts in the exposureTable are included as exposures.
useCustomCovariates	Create covariates from a custom table?
customCovariateDatabaseSchema	The name of the database schema that is the location where the custom covariate data is available.
customCovariateTable	Name of the table holding the custom covariates. This table should have the same structure as the cohort table.
customCovariateIds	A list of cohort definition IDS identifying the records in the customCovariateTable to use for building custom covariates.
useNestingCohort	Should the study be nested in a cohort (e.g. people with a specific indication)? If not, the study will be nested in the general population.
nestingCohortDatabaseSchema	The name of the database schema that is the location where the nesting cohort is defined.
nestingCohortTable	Name of the table holding the nesting cohort. This table should have the same structure as the cohort table.
nestingCohortId	A cohort definition ID identifying the records in the nestingCohortTable to use as nesting cohort.
deleteCovariatesSmallCount	The minimum count for a covariate to appear in the data to be kept.
studyStartDate	A calendar date specifying the minimum date where data is used. Date format is 'yyyymmdd'.
studyEndDate	A calendar date specifying the maximum date where data is used. Date format is 'yyyymmdd'.
cdmVersion	Define the OMOP CDM version used: currently support "4" and "5".
maxCasesPerOutcome	If there are more than this number of cases for a single outcome cases will be sampled to this size. maxCasesPerOutcome = 0 indicates no maximum size.

## Details

This function downloads several types of information:

- Information on the occurrences of the outcome(s) of interest. Note that information for multiple outcomes can be fetched in one go, and later the specific outcome can be specified for which we want to build a model.

- Information on the observation time and age for the people with the outcomes.
- Information on exposures of interest which we want to include in the model.

Five different database schemas can be specified, for five different types of information: The

- **cdmDatabaseSchema** is used to extract patient age and observation period. The
- **outcomeDatabaseSchema** is used to extract information about the outcomes, the
- **exposureDatabaseSchema** is used to retrieve information on exposures, and the
- **customCovariateDatabaseSchema** is optionally used to find additional, user-defined covariates. All four locations could point to the same database schema.
- **nestingCohortDatabaseSchema** is optionally used to define a cohort in which the analysis is nested, for example a cohort of diabetics patients.

All five locations could point to the same database schema.

### Value

An [SccsData](#) object.

---

getModel	<i>Output the full model</i>
----------	------------------------------

---

### Description

Output the full model

### Usage

```
getModel(sccsModel)
```

### Arguments

sccsModel      An object of type sccsModel as created using the [fitSccsModel](#) function.

### Value

A data frame with the coefficients and confidence intervals (when not-regularized) for all covariates in the model.

---

isSccsData	<i>Check whether an object is a SccsData object</i>
------------	---

---

**Description**

Check whether an object is a SccsData object

**Usage**

```
isSccsData(x)
```

**Arguments**

x	The object to check.
---	----------------------

**Value**

A logical value.

---

isSccsIntervalData	<i>Check whether an object is a SccsIntervalData object</i>
--------------------	---

---

**Description**

Check whether an object is a SccsIntervalData object

**Usage**

```
isSccsIntervalData(x)
```

**Arguments**

x	The object to check.
---	----------------------

**Value**

A logical value.

---

`loadExposureOutcomeList`*Load a list of exposureOutcome from file*

---

**Description**

Load a list of objects of type exposureOutcome from file. The file is in JSON format.

**Usage**

```
loadExposureOutcomeList(file)
```

**Arguments**

<code>file</code>	The name of the file
-------------------	----------------------

**Value**

A list of objects of type exposureOutcome.

---

`loadSccsAnalysisList` *Load a list of sccsAnalysis from file*

---

**Description**

Load a list of objects of type sccsAnalysis from file. The file is in JSON format.

**Usage**

```
loadSccsAnalysisList(file)
```

**Arguments**

<code>file</code>	The name of the file
-------------------	----------------------

**Value**

A list of objects of type sccsAnalysis.



---

loadSccsData	<i>Load the cohort method data from a file</i>
--------------	--

---

**Description**

Loads an object of type [SccsData](#) from a file in the file system.

**Usage**

```
loadSccsData(file)
```

**Arguments**

file	The name of the file containing the data.
------	---

**Value**

An object of class [SccsData](#).

---

loadSccsIntervalData	<i>Load the cohort method data from a file</i>
----------------------	--

---

**Description**

Loads an object of type [SccsIntervalData](#) from a file in the file system.

**Usage**

```
loadSccsIntervalData(file)
```

**Arguments**

file	The name of the file containing the data.
------	---

**Value**

An object of class [SccsIntervalData](#).

---

plotAgeEffect	<i>Plot the age effect</i>
---------------	----------------------------

---

**Description**

Plot the age effect

**Usage**

```
plotAgeEffect(sccsModel, rrLim = c(0.1, 10), fileName = NULL)
```

**Arguments**

sccsModel	An object of type sccsModel as created using the <a href="#">fitSccsModel</a> function.
rrLim	The limits on the incidence rate ratio scale in the plot.
fileName	Name of the file where the plot should be saved, for example 'plot.png'. See the function ggsave in the ggplot2 package for supported file formats.

**Details**

Plot the spline curve of the age effect.

**Value**

A Ggplot object. Use the ggsave function to save to file.

---

plotAgeSpans	<i>Plot the age ranges spanned by each observation period.</i>
--------------	--

---

**Description**

Plot the age ranges spanned by each observation period.

**Usage**

```
plotAgeSpans(studyPopulation, maxPersons = 10000, fileName = NULL)
```

**Arguments**

studyPopulation	An object created using the <a href="#">createStudyPopulation()</a> function.
maxPersons	The maximum number of persons to plot. If there are more than this number of persons a random sample will be taken to avoid visual clutter.
fileName	Name of the file where the plot should be saved, for example 'plot.png'. See the function <a href="#">ggplot2::ggsave()</a> for supported file formats.

**Details**

Plots a line per patient from their age at observation start to their age at observation end.

**Value**

A ggplot object. Use the `ggplot2::ggsave()` function to save to file in a different format.

---

plotEventObservationDependence

*Plot time from event to observation end for censored and uncensored time.*

---

**Description**

Plot time from event to observation end for censored and uncensored time.

**Usage**

```
plotEventObservationDependence(studyPopulation, fileName = NULL)
```

**Arguments**

studyPopulation

An object created using the `createStudyPopulation()` function.

fileName

Name of the file where the plot should be saved, for example 'plot.png'. See the function `ggplot2::ggsave()` for supported file formats.

**Details**

This plot shows whether there is a difference in time between (first) event and the observation period end for periods that are 'censored' and those that are 'uncensored'. By 'censored' we mean periods that end before we would normally expect. Here, we define periods to be uncensored if they end at either the study end date (if specified), database end date (i.e. the date after which no data is captured in the database), or maximum age (if specified). All other periods are assumed to be censored.

As proposed by Farrington et al., by comparing the two plots, we can gain some insight into whether the censoring is dependent on the occurrence of the event.

**Value**

A ggplot object. Use the `ggplot2::ggsave()` function to save to file in a different format.

**References**

Farrington P, Whitaker H, Ghebremichael Weldeselassie Y (2018), Self-controlled case series studies: A modelling guide with R, Taylor & Francis

---

plotEventToCalendarTime

*Plot the count of events over calendar time.*


---

### Description

Plot the count of events over calendar time.

### Usage

```
plotEventToCalendarTime(studyPopulation, fileName = NULL)
```

### Arguments

studyPopulation

An object created using the [createStudyPopulation\(\)](#) function.

fileName

Name of the file where the plot should be saved, for example 'plot.png'. See the function [ggplot2::ggsave\(\)](#) for supported file formats.

### Value

A ggplot object. Use the [ggplot2::ggsave\(\)](#) function to save to file in a different format.

---

plotExposureCentered    *Plot information centered around the start of exposure*


---

### Description

Plot information centered around the start of exposure

### Usage

```
plotExposureCentered(
  studyPopulation,
  sccsData,
  exposureEraId = NULL,
  fileName = NULL
)
```

### Arguments

studyPopulation

An object created using the [createStudyPopulation\(\)](#) function.

sccsData

An object of type [SccsData](#) as created using the [getDbSccsData](#) function.

exposureEraId

The exposure to create the era data for. If not specified it is assumed to be the one exposure for which the data was loaded from the database.

fileName

Name of the file where the plot should be saved, for example 'plot.png'. See the function [ggplot2::ggsave\(\)](#) for supported file formats.

**Details**

This plot shows the number of events and the number of subjects under observation in week-sized intervals relative to the start of the first exposure.

**Value**

A ggplot object. Use the `ggplot2::ggsave()` function to save to file in a different format.

---

plotSeasonality	<i>Plot the seasonality effect</i>
-----------------	------------------------------------

---

**Description**

Plot the seasonality effect

**Usage**

```
plotSeasonality(sccsModel, rrLim = c(0.1, 10), fileName = NULL)
```

**Arguments**

sccsModel	An object of type <code>sccsModel</code> as created using the <code>fitSccsModel</code> function.
rrLim	The limits on the incidence rate ratio scale in the plot.
fileName	Name of the file where the plot should be saved, for example 'plot.png'. See the function <code>ggsave</code> in the <code>ggplot2</code> package for supported file formats.

**Details**

Plot the spline curve of the seasonality effect.

**Value**

A Ggplot object. Use the `ggsave` function to save to file.

---

runSccsAnalyses	<i>Run a list of analyses</i>
-----------------	-------------------------------

---

**Description**

Run a list of analyses

## Usage

```
runSccsAnalyses(
  connectionDetails,
  cdmDatabaseSchema,
  oracleTempSchema = cdmDatabaseSchema,
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema,
  outcomeTable = "condition_era",
  customCovariateDatabaseSchema = cdmDatabaseSchema,
  customCovariateTable = "cohort",
  nestingCohortDatabaseSchema = cdmDatabaseSchema,
  nestingCohortTable = "cohort",
  cdmVersion = 5,
  outputFolder = "../SccsOutput",
  sccsAnalysisList,
  exposureOutcomeList,
  combineDataFetchAcrossOutcomes = TRUE,
  getDbSccsDataThreads = 1,
  createStudyPopulationThreads = 1,
  createSccsIntervalDataThreads = 1,
  fitSccsModelThreads = 1,
  cvThreads = 1
)
```

## Arguments

**connectionDetails**

An R object of type `ConnectionDetails` created using the function `DatabaseConnector::createC`

**cdmDatabaseSchema**

The name of the database schema that contains the OMOP CDM instance. Requires read permissions to this database. On SQL Server, this should specify both the database and the schema, so for example 'cdm\_instance.dbo'.

**oracleTempSchema**

A schema where temp tables can be created in Oracle.

**exposureDatabaseSchema**

The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If `exposureTable = "DRUG_ERA"`, `exposureDatabaseSchema` is not used but assumed to be `cdmDatabaseSchema`. Requires read permissions to this database.

**exposureTable** The table name that contains the exposure cohorts. If `exposureTable <> "DRUG_ERA"`, then expectation is `exposureTable` has format of COHORT table: `cohort_concept_id`, `SUBJECT_ID`, `COHORT_START_DATE`, `COHORT_END_DATE`.

**outcomeDatabaseSchema**

The name of the database schema that is the location where the data used to define the outcome cohorts is available. If `outcomeTable = "CONDITION_ERA"`, `outcomeDatabaseSchema` is not used. Requires read permissions to this database.

**outcomeTable** The table name that contains the outcome cohorts. If `outcomeTable` is not `CONDITION_OCCURRENCE` or `CONDITION_ERA`, then expectation is `outcomeTable` has format of COHORT table: `COHORT_DEFINITION_ID`, `SUBJECT_ID`, `COHORT_START_DATE`, `COHORT_END_DATE`.

customCovariateDatabaseSchema	The name of the database schema that is the location where the custom covariate data is available.
customCovariateTable	Name of the table holding the custom covariates. This table should have the same structure as the cohort table.
nestingCohortDatabaseSchema	The name of the database schema that is the location where the nesting cohort is defined.
nestingCohortTable	Name of the table holding the nesting cohort. This table should have the same structure as the cohort table.
cdmVersion	Define the OMOP CDM version used: currently support "4" and "5".
outputFolder	Name of the folder where all the outputs will written to.
sccsAnalysisList	A list of objects of sccsAnalysis as created using the <a href="#">createSccsAnalysis()</a> function.
exposureOutcomeList	A list of objects of type exposureOutcome as created using the <a href="#">createExposureOutcome()</a> function.
combineDataFetchAcrossOutcomes	Should fetching data from the database be done one outcome at a time, or for all outcomes in one fetch? Combining fetches will be more efficient if there is large overlap in the subjects that have the different outcomes.
getDbSccsDataThreads	The number of parallel threads to use for building the SccsData objects.
createStudyPopulationThreads	The number of parallel threads to use for building the studyPopulation objects.
createSccsIntervalDataThreads	The number of parallel threads to use for building the SccsIntervalData objects.
fitSccsModelThreads	The number of parallel threads to use for fitting the models.
cvThreads	The number of parallel threads to use for the cross- validation when estimating the hyperparameter for the outcome model. Note that the total number of CV threads at one time could be <code>fitSccsModelThreads * cvThreads</code> .

## Details

Run a list of analyses for the drug-comparator-outcomes of interest. This function will run all specified analyses against all hypotheses of interest, meaning that the total number of outcome models is `length(cmAnalysisList) * length(drugComparatorOutcomesList)` (if all analyses specify an outcome model should be fitted). When you provide several analyses it will determine whether any of the analyses have anything in common, and will take advantage of this fact. For example, if we specify several analyses that only differ in the way the outcome model is fitted, then this function will extract the data and fit the propensity model only once, and re-use this in all the analysis.

**Value**

A tibble describing for each exposure-outcome-analysisId combination where the intermediary and outcome model files can be found, relative to the outputFolder.

---

`saveExposureOutcomeList`

*Save a list of exposureOutcome to file*

---

**Description**

Write a list of objects of type exposureOutcome to file. The file is in JSON format.

**Usage**

```
saveExposureOutcomeList(exposureOutcomeList, file)
```

**Arguments**

exposureOutcomeList

The exposureOutcome list to be written to file

file

The name of the file where the results will be written

---

`saveSccsAnalysisList` *Save a list of sccsAnalysis to file*

---

**Description**

Write a list of objects of type sccsAnalysis to file. The file is in JSON format.

**Usage**

```
saveSccsAnalysisList(sccsAnalysisList, file)
```

**Arguments**

sccsAnalysisList

The sccsAnalysis list to be written to file

file

The name of the file where the results will be written



---

saveSccsData	<i>Save the cohort method data to file</i>
--------------	--

---

**Description**

Saves an object of type [SccsData](#) to a file.

**Usage**

```
saveSccsData(SccsData, file)
```

**Arguments**

SccsData	An object of type <a href="#">SccsData</a> as generated using <a href="#">getDbSccsData()</a> .
file	The name of the file where the data will be written. If the file already exists it will be overwritten.

**Value**

Returns no output.

---

saveSccsIntervalData	<i>Save the cohort method data to file</i>
----------------------	--

---

**Description**

Saves an object of type [SccsIntervalData](#) to a file.

**Usage**

```
saveSccsIntervalData(SccsIntervalData, file)
```

**Arguments**

SccsIntervalData	An object of type <a href="#">SccsIntervalData</a> as generated using <a href="#">createSccsIntervalData()</a> .
file	The name of the file where the data will be written. If the file already exists it will be overwritten.

**Value**

Returns no output.

---

SccsData-class	<i>SCCS Data</i>
----------------	------------------

---

### Description

SccsData is an S4 class that inherits from [Andromeda](#). It contains information on the cases and their covariates.

A SccsData is typically created using [getDbSccsData\(\)](#), can only be saved using [saveSccsData\(\)](#), and loaded using [loadSccsData\(\)](#).

### Usage

```
## S4 method for signature 'SccsData'
show(object)
```

```
## S4 method for signature 'SccsData'
summary(object)
```

### Arguments

object            An object of type SccsData.

---

SccsIntervalData-class	<i>SCCS Interval Data</i>
------------------------	---------------------------

---

### Description

SccsIntervalData is an S4 class that inherits from [Andromeda](#). It contains information on the cases and their covariates, divided in non-overlapping time intervals.

A SccsIntervalData is typically created using [createSccsIntervalData\(\)](#), can only be saved using [saveSccsIntervalData\(\)](#), and loaded using [loadSccsIntervalData\(\)](#).

### Usage

```
## S4 method for signature 'SccsIntervalData'
show(object)
```

```
## S4 method for signature 'SccsIntervalData'
summary(object)
```

### Arguments

object            An object of type SccsIntervalData.

---

simulateSccsData	<i>Simulate SCCS data</i>
------------------	---------------------------

---

**Description**

Simulate SCCS data

**Usage**

```
simulateSccsData(nCases, settings)
```

**Arguments**

nCases            The number of cases to simulate.

settings          An object of type `sccsSimulationSettings` as created using the [createSccsSimulationSettings](#)

**Value**

An object of type `sccsData`.

---

summarizeSccsAnalyses	<i>Create a summary report of the analyses</i>
-----------------------	--

---

**Description**

Create a summary report of the analyses

**Usage**

```
summarizeSccsAnalyses(referenceTable, outputFolder)
```

**Arguments**

referenceTable    A tibble as created by the [runSccsAnalyses](#) function.

outputFolder     Name of the folder where all the outputs have been written to.

**Value**

A tibble containing summary statistics for each exposure-outcome-analysis combination.

# Index

Andromeda, [34](#)

computeMdr, [3](#)

createAgeCovariateSettings, [4](#)

createAgeCovariateSettings(), [12](#)

createControlIntervalSettings, [4](#)

createControlIntervalSettings(), [15](#)

createCreateSccsIntervalDataArgs, [5](#)

createCreateScriIntervalDataArgs, [6](#)

createCreateStudyPopulationArgs, [7](#)

createEraCovariateSettings, [7](#)

createEraCovariateSettings(), [12](#), [15](#)

createExposureOutcome, [9](#)

createExposureOutcome(), [31](#)

createFitSccsModelArgs, [9](#)

createGetDbSccsDataArgs, [10](#)

createSccsAnalysis, [9](#), [11](#)

createSccsAnalysis(), [31](#)

createSccsIntervalData, [3](#), [11](#), [12](#), [18](#)

createSccsIntervalData(), [33](#), [34](#)

createSccsSimulationSettings, [13](#), [35](#)

createScriIntervalData, [11](#), [14](#)

createSeasonalityCovariateSettings, [15](#)

createSeasonalityCovariateSettings(), [12](#)

createSimulationRiskWindow, [14](#), [16](#)

createStudyPopulation, [17](#), [19](#)

createStudyPopulation(), [12](#), [15](#), [26–28](#)

cyclicSplineDesign, [18](#)

Cyclops::createControl, [18](#)

Cyclops::createPrior, [18](#)

DatabaseConnector::createConnectionDetails(), [20](#), [30](#)

fitSccsModel, [11](#), [18](#), [22](#), [26](#), [29](#)

getAttritionTable, [19](#)

getDbSccsData, [11](#), [12](#), [15](#), [17](#), [19](#), [28](#)

getDbSccsData(), [33](#), [34](#)

getModel, [22](#)

ggplot2::ggsave(), [26–29](#)

isSccsData, [23](#)

isSccsIntervalData, [23](#)

loadExposureOutcomeList, [24](#)

loadSccsAnalysisList, [24](#)

loadSccsData, [25](#)

loadSccsData(), [34](#)

loadSccsIntervalData, [25](#)

loadSccsIntervalData(), [34](#)

plotAgeEffect, [26](#)

plotAgeSpans, [26](#)

plotEventObservationDependence, [27](#)

plotEventToCalendarTime, [28](#)

plotExposureCentered, [28](#)

plotSeasonality, [29](#)

runSccsAnalyses, [9](#), [12](#), [29](#), [35](#)

saveExposureOutcomeList, [32](#)

saveSccsAnalysisList, [32](#)

saveSccsData, [33](#)

saveSccsData(), [34](#)

saveSccsIntervalData, [33](#)

saveSccsIntervalData(), [34](#)

SccsData, [5](#), [8](#), [12](#), [15](#), [17](#), [19](#), [22](#), [25](#), [28](#), [33](#)

SccsData (SccsData-class), [34](#)

SccsData-class, [34](#)

SccsIntervalData, [3](#), [13](#), [15](#), [18](#), [25](#), [33](#)

SccsIntervalData (SccsIntervalData-class), [34](#)

SccsIntervalData-class, [34](#)

show, SccsData-method (SccsData-class), [34](#)

show, SccsIntervalData-method (SccsIntervalData-class), [34](#)

simulateSccsData, [35](#)

summarizeSccsAnalyses, [35](#)

summary, SccsData-method (SccsData-class), [34](#)

summary, SccsIntervalData-method (SccsIntervalData-class), [34](#)